

## Aluminum Capacitors SMD (Chip), High Temperature, Low Impedance




Fig. 1

| QUICK REFERENCE DATA                        |                                     |
|---------------------------------------------|-------------------------------------|
| DESCRIPTION                                 | VALUE                               |
| Nominal case sizes<br>(L x W x H in mm)     | 12.5 x 12.5 x 13<br>to 18 x 18 x 21 |
| Rated capacitance range, $C_R$              | 47 $\mu$ F to 3300 $\mu$ F          |
| Tolerance on $C_R$                          | $\pm 20 \%$                         |
| Rated voltage range, $U_R$                  | 16 V to 63 V                        |
| Category temperature range                  | -55 °C to +150 °C                   |
| Endurance test at 150 °C                    | 1000 h to 1500 h                    |
| Useful life at 150 °C                       | 1000 h to 2000 h                    |
| Useful life at 40 °C<br>1.8 x $I_R$ applied | 300 000 h to 400 000 h              |
| Shelf life at 0 V, 150 °C                   | 1000 h                              |
| Based on sectional<br>specification         | IEC 60384-18/CECC 32300             |
| Climatic category IEC 60068                 | 55/150/56                           |

### FEATURES

- Useful life: Up to 2000 h at 150 °C
- High reliability
- Low ESR
- Polarized aluminum electrolytic capacitors, non-solid electrolyte, self healing
- SMD-version with base plate, lead (Pb)-free reflow solderable
- Charge and discharge proof, no peak current limitation
- High temperature reflow soldering according to JEDEC® J-STD-020
- High temperature proof
- Vibration proof, 4-pin version and 6-pin version
- AEC-Q200 qualified
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

AUTOMOTIVE  
GRADE

RoHS  
COMPLIANT

### APPLICATIONS

- SMD technology, for high temperature reflow soldering
- High temperature environment, high peak load
- Automotive, industrial
- Smoothing, filtering, buffering

### MARKING

- Rated capacitance (in  $\mu$ F)
- Rated voltage (in V)
- Date code, in accordance with IEC 60062
- Black mark or “-” sign indicating the cathode (the anode is identified by bevelled edges)
- Code indicating group number (A)

### PACKAGING

Supplied in blister tape on reel

**SELECTION CHART FOR  $C_R$ ,  $U_R$ , AND RELEVANT NOMINAL CASE SIZES (L x W x H in mm)**

| $C_R$<br>( $\mu F$ ) | $U_R$ (V)        |                  |                  |                  |                  |
|----------------------|------------------|------------------|------------------|------------------|------------------|
|                      | 16               | 25               | 35               | 50               | 63               |
| 47                   | -                | -                | -                | -                | 12.5 x 12.5 x 13 |
| 68                   | -                | -                | -                | -                | 12.5 x 12.5 x 13 |
| 100                  | →                | →                | →                | 12.5 x 12.5 x 13 | 12.5 x 12.5 x 13 |
| 150                  | →                | →                | →                | 12.5 x 12.5 x 13 | 12.5 x 12.5 x 16 |
| 220                  | →                | →                | 12.5 x 12.5 x 13 | 12.5 x 12.5 x 16 | 16 x 16 x 16     |
| 330                  | →                | 12.5 x 12.5 x 13 | 12.5 x 12.5 x 13 | 16 x 16 x 16     | 18 x 18 x 16     |
| 470                  | 12.5 x 12.5 x 13 | 12.5 x 12.5 x 13 | 16 x 16 x 16     | 18 x 18 x 16     | 16 x 16 x 21     |
| 680                  | 12.5 x 12.5 x 13 | 16 x 16 x 16     | 18 x 18 x 16     | 16 x 16 x 21     | 18 x 18 x 21     |
| 1000                 | 16 x 16 x 16     | 18 x 18 x 16     | 16 x 16 x 21     | 18 x 18 x 21     | -                |
| 1500                 | 18 x 18 x 16     | 16 x 16 x 21     | 18 x 18 x 21     | -                | -                |
| 2200                 | 16 x 16 x 21     | 18 x 18 x 21     | -                | -                | -                |
| 2700                 | 18 x 18 x 21     | -                | -                | -                | -                |
| 3300                 | 18 x 18 x 21     | -                | -                | -                | -                |




Fig. 2 - Dimensional outline

Table 1

| <b>DIMENSIONS in millimeters AND MASS</b> |           |                   |                   |                   |      |                   |     |                    |          |
|-------------------------------------------|-----------|-------------------|-------------------|-------------------|------|-------------------|-----|--------------------|----------|
| NOMINAL CASE SIZE<br>L x W x H            | CASE CODE | L <sub>MAX.</sub> | W <sub>MAX.</sub> | H <sub>MAX.</sub> | Ø D  | B <sub>MAX.</sub> | S   | L1 <sub>MAX.</sub> | MASS (g) |
| 12.5 x 12.5 x 13                          | 1213      | 12.9              | 12.9              | 14.0              | 12.5 | 1.3               | 3.6 | 14.9               | ≈ 2.9    |
| 12.5 x 12.5 x 16                          | 1216      | 12.9              | 12.9              | 16.5              | 12.5 | 1.3               | 3.6 | 14.9               | ≈ 3.2    |
| 16 x 16 x 16                              | 1616      | 16.6              | 16.6              | 17.5              | 16.0 | 1.3               | 6.5 | 18.6               | ≈ 5.8    |
| 16 x 16 x 21                              | 1621      | 16.6              | 16.6              | 22.0              | 16.0 | 1.3               | 6.5 | 18.6               | ≈ 7.1    |
| 18 x 18 x 16                              | 1816      | 19.0              | 19.0              | 17.5              | 18.0 | 1.3               | 6.5 | 21.0               | ≈ 8.0    |
| 18 x 18 x 21                              | 1821      | 19.0              | 19.0              | 22.0              | 18.0 | 1.3               | 6.5 | 21.0               | ≈ 9.3    |

**Table 2**

| TAPE AND REEL DIMENSIONS in millimeters, <b>PACKAGING QUANTITIES</b> |           |                         |                 |                                  |               |                             |
|----------------------------------------------------------------------|-----------|-------------------------|-----------------|----------------------------------|---------------|-----------------------------|
| NOMINAL CASE SIZE<br>L x W x H                                       | CASE CODE | PITCH<br>P <sub>1</sub> | TAPE WIDTH<br>W | TAPE THICKNESS<br>T <sub>2</sub> | REEL DIAMETER | PACKAGING QUANTITY PER REEL |
| 12.5 x 12.5 x 13                                                     | 1213      | 20                      | 24              | 16.2                             | 380           | 250                         |
| 12.5 x 12.5 x 16                                                     | 1216      | 24                      | 32              | 18.5                             | 380           | 200                         |
| 16 x 16 x 16                                                         | 1616      | 28                      | 44              | 18.9                             | 380           | 150                         |
| 16 x 16 x 21                                                         | 1621      | 28                      | 44              | 23.4                             | 380           | 100                         |
| 18 x 18 x 16                                                         | 1816      | 32                      | 44              | 18.9                             | 380           | 125                         |
| 18 x 18 x 21                                                         | 1821      | 32                      | 44              | 23.4                             | 380           | 100                         |

**Note**

- Detailed tape dimensions see section “PACKAGING”

**MOUNTING**

The capacitors are designed for automatic placement on to printed-circuit boards.

Optimum dimensions of soldering pads depend amongst others on soldering method, mounting accuracy, print layout and/or adjacent components.

For recommended soldering pad dimensions, refer to Fig. 3 and Table 3.


**SOLDERING**

Soldering conditions are defined by the curve, temperature versus time, where the temperature is that measured on the component during processing.

For maximum conditions refer to Fig. 4.

Any temperature versus time curve which does not exceed the specified maximum curves may be applied.

As a general principle, temperature and duration shall be the **minimum** necessary required to ensure good soldering connections. However, the specified maximum curves should never be exceeded.


**Fig. 3 - Recommended soldering pad dimensions**
**Table 3**

| RECOMMENDED SOLDERING PAD DIMENSIONS in millimeters |     |     |     |     |     |     |
|-----------------------------------------------------|-----|-----|-----|-----|-----|-----|
| CASE CODE                                           | a   | b   | c   | d   | e   | f   |
| 1213                                                | 6.3 | 2.5 | 4.0 | 4.2 | 5.0 | 5.6 |
| 1216                                                | 6.3 | 2.5 | 4.0 | 4.2 | 5.0 | 5.6 |
| 1616                                                | 7.8 | 9.6 | 4.7 | -   | -   | -   |
| 1621                                                | 7.8 | 9.6 | 4.7 | -   | -   | -   |
| 1816                                                | 8.8 | 9.6 | 4.7 | -   | -   | -   |
| 1821                                                | 8.8 | 9.6 | 4.7 | -   | -   | -   |

# **ADVANCED SOLDERING PROFILE FOR LEAD (Pb)-FREE REFLOW PROCESS ACCORDING TO JEDEC J-STD-020**




Fig. 4 - Maximum temperature load during reflow soldering

Table 4

| REFLOW SOLDERING CONDITIONS for MAL216099xxxE3    |                           |                           |
|---------------------------------------------------|---------------------------|---------------------------|
| PROFILE FEATURES                                  | CASE CODE<br>1213 TO 1216 | CASE CODE<br>1616 TO 1821 |
| Max. time from 25 °C to $T_{Peak}$                | 300 s                     | 300 s                     |
| Max. ramp-up rate to 150 °C                       | 3 K/s                     | 3 K/s                     |
| Max. time from 150 °C to 200 °C ( $t_1$ )         | 150 s                     | 150 s                     |
| Max. time from 190 °C to 200 °C ( $t_2$ )         | 110 s                     | 110 s                     |
| Ramp up rate from 200 °C to $T_{Peak}$            | 0.5 K/s to 3 K/s          | 0.5 K/s to 3 K/s          |
| Max. time above $T_{Liquidus}$ (217 °C) ( $t_3$ ) | 90 s                      | 90 s                      |
| Max. time above 230 °C ( $t_4$ )                  | 65 s                      | 60 s                      |
| Peak temperature $T_{Peak}$                       | 250 °C                    | 245 °C                    |
| Max. time above $T_{Peak}$ minus 5 °C             | 30 s                      | 30 s                      |
| Ramp-down rate from $T_{Liquidus}$                | 3 K/s to 6 K/s            | 3 K/s to 6 K/s            |

## **Notes**

- Temperature measuring point on top of the case and on terminals.
- Max. 2 runs with pause of min. 30 min in between.



| ELECTRICAL DATA |                                                   |
|-----------------|---------------------------------------------------|
| SYMBOL          | DESCRIPTION                                       |
| $C_R$           | Rated capacitance at 100 Hz, tolerance $\pm 20\%$ |
| $I_R$           | Rated RMS ripple current at 100 kHz, 150 °C       |
| $I_{L2}$        | Max. leakage current after 2 min at $U_R$         |
| $\tan \delta$   | Max. dissipation factor at 100 Hz                 |
| $Z$             | Max. impedance at 100 kHz                         |

**Note**

- Unless otherwise specified, all electrical values in Table 5 apply at  $T_{amb} = 20\text{ °C}$ ,  $P = 86\text{ kPa}$  to  $106\text{ kPa}$ ,  $RH = 45\%$  to  $75\%$

Table 5

| ELECTRICAL DATA AND ORDERING INFORMATION |                            |                                           |                                    |                                        |                         |                                         |                                          |                                |
|------------------------------------------|----------------------------|-------------------------------------------|------------------------------------|----------------------------------------|-------------------------|-----------------------------------------|------------------------------------------|--------------------------------|
| $U_R$<br>(V)                             | $C_R$<br>( $\mu\text{F}$ ) | NOMINAL<br>CASE SIZE<br>L x W x H<br>(mm) | $I_R$<br>150 °C<br>100 kHz<br>(mA) | $I_{L2}$<br>2 min<br>( $\mu\text{A}$ ) | $\tan \delta$<br>100 Hz | $Z$<br>100 kHz<br>20 °C<br>( $\Omega$ ) | $Z$<br>100 kHz<br>-40 °C<br>( $\Omega$ ) | ORDERING<br>CODE<br>MAL2160... |
| 16                                       | 470                        | 12.5 x 12.5 x 13                          | 750                                | 75                                     | 0.16                    | 0.080                                   | 0.70                                     | 99501E3                        |
|                                          | 680                        | 12.5 x 12.5 x 13                          | 800                                | 109                                    | 0.16                    | 0.080                                   | 0.70                                     | 99502E3                        |
|                                          | 1000                       | 16 x 16 x 16                              | 850                                | 160                                    | 0.16                    | 0.050                                   | 0.45                                     | 99503E3                        |
|                                          | 1500                       | 18 x 18 x 16                              | 900                                | 240                                    | 0.16                    | 0.050                                   | 0.45                                     | 99504E3                        |
|                                          | 2200                       | 16 x 16 x 21                              | 1100                               | 352                                    | 0.18                    | 0.035                                   | 0.32                                     | 99505E3                        |
|                                          | 2700                       | 18 x 18 x 21                              | 1350                               | 432                                    | 0.18                    | 0.035                                   | 0.32                                     | 99506E3                        |
|                                          | 3300                       | 18 x 18 x 21                              | 1400                               | 528                                    | 0.20                    | 0.035                                   | 0.32                                     | 99507E3                        |
| 25                                       | 330                        | 12.5 x 12.5 x 13                          | 650                                | 83                                     | 0.14                    | 0.080                                   | 0.70                                     | 99601E3                        |
|                                          | 470                        | 12.5 x 12.5 x 13                          | 700                                | 118                                    | 0.14                    | 0.080                                   | 0.70                                     | 99602E3                        |
|                                          | 680                        | 16 x 16 x 16                              | 800                                | 170                                    | 0.14                    | 0.050                                   | 0.45                                     | 99603E3                        |
|                                          | 1000                       | 18 x 18 x 16                              | 830                                | 250                                    | 0.14                    | 0.050                                   | 0.45                                     | 99604E3                        |
|                                          | 1500                       | 16 x 16 x 21                              | 1050                               | 375                                    | 0.14                    | 0.035                                   | 0.32                                     | 99605E3                        |
|                                          | 2200                       | 18 x 18 x 21                              | 1350                               | 550                                    | 0.16                    | 0.035                                   | 0.32                                     | 99606E3                        |
| 35                                       | 220                        | 12.5 x 12.5 x 13                          | 550                                | 77                                     | 0.12                    | 0.080                                   | 0.70                                     | 99001E3                        |
|                                          | 330                        | 12.5 x 12.5 x 13                          | 650                                | 116                                    | 0.12                    | 0.080                                   | 0.70                                     | 99002E3                        |
|                                          | 470                        | 16 x 16 x 16                              | 800                                | 165                                    | 0.12                    | 0.050                                   | 0.45                                     | 99003E3                        |
|                                          | 680                        | 18 x 18 x 16                              | 830                                | 238                                    | 0.12                    | 0.050                                   | 0.45                                     | 99004E3                        |
|                                          | 1000                       | 16 x 16 x 21                              | 1000                               | 350                                    | 0.12                    | 0.035                                   | 0.32                                     | 99005E3                        |
|                                          | 1500                       | 18 x 18 x 21                              | 1350                               | 525                                    | 0.12                    | 0.035                                   | 0.32                                     | 99006E3                        |
| 50                                       | 100                        | 12.5 x 12.5 x 13                          | 420                                | 50                                     | 0.10                    | 0.130                                   | 1.20                                     | 99101E3                        |
|                                          | 150                        | 12.5 x 12.5 x 13                          | 450                                | 75                                     | 0.10                    | 0.120                                   | 1.10                                     | 99102E3                        |
|                                          | 220                        | 12.5 x 12.5 x 16                          | 550                                | 110                                    | 0.10                    | 0.085                                   | 0.76                                     | 99103E3                        |
|                                          | 330                        | 16 x 16 x 16                              | 700                                | 165                                    | 0.10                    | 0.072                                   | 0.65                                     | 99104E3                        |
|                                          | 470                        | 18 x 18 x 16                              | 720                                | 235                                    | 0.10                    | 0.070                                   | 0.63                                     | 99105E3                        |
|                                          | 680                        | 16 x 16 x 21                              | 800                                | 340                                    | 0.10                    | 0.052                                   | 0.47                                     | 99106E3                        |
|                                          | 1000                       | 18 x 18 x 21                              | 1100                               | 500                                    | 0.10                    | 0.049                                   | 0.44                                     | 99107E3                        |
| 63                                       | 47                         | 12.5 x 12.5 x 13                          | 300                                | 30                                     | 0.10                    | 0.240                                   | 2.16                                     | 99801E3                        |
|                                          | 68                         | 12.5 x 12.5 x 13                          | 320                                | 43                                     | 0.10                    | 0.240                                   | 2.16                                     | 99802E3                        |
|                                          | 100                        | 12.5 x 12.5 x 13                          | 320                                | 63                                     | 0.10                    | 0.240                                   | 2.16                                     | 99803E3                        |
|                                          | 150                        | 12.5 x 12.5 x 16                          | 400                                | 95                                     | 0.10                    | 0.160                                   | 1.44                                     | 99804E3                        |
|                                          | 220                        | 16 x 16 x 16                              | 500                                | 139                                    | 0.10                    | 0.100                                   | 0.90                                     | 99805E3                        |
|                                          | 330                        | 18 x 18 x 16                              | 520                                | 208                                    | 0.10                    | 0.095                                   | 0.86                                     | 99806E3                        |
|                                          | 470                        | 16 x 16 x 21                              | 600                                | 296                                    | 0.10                    | 0.075                                   | 0.68                                     | 99807E3                        |
|                                          | 680                        | 18 x 18 x 21                              | 700                                | 428                                    | 0.10                    | 0.072                                   | 0.65                                     | 99808E3                        |

**ORDERING EXAMPLE**

Electrolytic capacitor 160 CLA series

220  $\mu\text{F}$ /50 V;  $\pm 20\%$ Nominal case size: 12.5 mm x 12.5 mm x 16 mm;  
taped on reel

Ordering code: MAL216099103E3

Table 6

| ADDITIONAL ELECTRICAL DATA                   |                                                             |                                          |
|----------------------------------------------|-------------------------------------------------------------|------------------------------------------|
| PARAMETER                                    | CONDITIONS                                                  | VALUE                                    |
| <b>Voltage</b>                               |                                                             |                                          |
| Surge voltage for short periods              | IEC 60384-18, subclause 4.14                                | $U_S \leq 1.15 \times U_R$               |
| Reverse voltage for short periods            | IEC 60384-18, subclause 4.16; $T_A \leq 150^\circ\text{C}$  | $U_{rev} \leq 1\text{ V}$                |
| <b>Current</b>                               |                                                             |                                          |
| Leakage current                              | After 2 min at $U_R$                                        | $I_{L2} \leq 0.01 \times C_R \times U_R$ |
| <b>Inductance</b>                            |                                                             |                                          |
| Equivalent series inductance (ESL)           | $\varnothing D \geq 12.5\text{ mm}$                         | Typ. 11 nH                               |
| <b>Resistance</b>                            |                                                             |                                          |
| Equivalent series resistance (ESR) at 100 Hz | Calculated from $\tan \delta_{max}$ and $C_R$ (see Table 5) | $ESR = \tan \delta / 2\pi f C_R$         |

## CAPACITANCE (C)




Fig. 5 - Typical multiplier of capacitance as a function of ambient temperature






Fig. 6 - Typical multiplier of capacitance as a function of frequency

## DISSIPATION FACTOR ( $\tan \delta$ )


Fig. 7 - Typical multiplier of dissipation factor ( $\tan \delta$ ) as a function of ambient temperature

Fig. 8 - Typical multiplier of dissipation factor ( $\tan \delta$ ) as a function of frequency

## EQUIVALENT SERIES RESISTANCE (ESR)




Fig. 9 - Typical multiplier of ESR as a function of frequency

## IMPEDANCE (Z)




Fig. 10 - Typical multiplier of impedance as a function of temperature




Fig. 11 - Typical impedance as a function of frequency




Fig. 12 - Typical impedance as a function of frequency

## RIPPLE CURRENT AND USEFUL LIFE

Table 7

| ENDURANCE TEST DURATION AND USEFUL LIFE AS A FUNCTION OF CASE SIZE |           |                               |                                 |                                                             |
|--------------------------------------------------------------------|-----------|-------------------------------|---------------------------------|-------------------------------------------------------------|
| NOMINAL CASE SIZE<br>Ø D x L<br>(mm)                               | CASE CODE | ENDURANCE<br>AT 150 °C<br>(h) | USEFUL LIFE<br>AT 150 °C<br>(h) | USEFUL LIFE AT 40 °C<br>1.8 x I <sub>R</sub> APPLIED<br>(h) |
| 12.5 x 12.5 x 13                                                   | 1213      | 1000                          | 1250 <sup>(1)</sup>             | 300 000                                                     |
| 12.5 x 12.5 x 16                                                   | 1216      | 1000                          | 1250                            | 325 000                                                     |
| 16 x 16 x 16                                                       | 1616      | 1000                          | 1500                            | 350 000                                                     |
| 16 x 16 x 21                                                       | 1621      | 1500                          | 2000                            | 400 000                                                     |
| 18 x 18 x 16                                                       | 1816      | 1000                          | 1500                            | 350 000                                                     |
| 18 x 18 x 21                                                       | 1821      | 1500                          | 2000                            | 400 000                                                     |

**Note**
<sup>(1)</sup> 12.5 x 12.5 x 13 at 63 V only useful life of 1000 h.

## RIPPLE CURRENT AND USEFUL LIFE




Fig. 13 - Multiplier of useful life as a function of ambient temperature and ripple current load

Table 8

| <b>MULTIPLIER OF RIPPLE CURRENT (<math>I_R</math>) AS A FUNCTION OF FREQUENCY</b> |                                                         |
|-----------------------------------------------------------------------------------|---------------------------------------------------------|
| <b>FREQUENCY<br/>(Hz)</b>                                                         | <b><math>I_R</math> MULTIPLIER</b>                      |
|                                                                                   | <b><math>U_R = 16 \text{ V TO } 63 \text{ V}</math></b> |
| 50                                                                                | 0.40                                                    |
| 100                                                                               | 0.60                                                    |
| 300                                                                               | 0.75                                                    |
| 1000                                                                              | 0.80                                                    |
| 3000                                                                              | 0.90                                                    |
| 10 000                                                                            | 0.95                                                    |
| 30 000                                                                            | 0.97                                                    |
| 100 000                                                                           | 1.00                                                    |

Table 9

| <b>TEST PROCEDURES AND REQUIREMENTS</b>        |                                                |                                                                                                                                                                 |                                                                                                                                                                                    |
|------------------------------------------------|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>TEST</b>                                    |                                                | <b>PROCEDURE<br/>(quick reference)</b>                                                                                                                          | <b>REQUIREMENTS</b>                                                                                                                                                                |
| <b>NAME OF TEST</b>                            | <b>REFERENCE</b>                               |                                                                                                                                                                 |                                                                                                                                                                                    |
| Mounting                                       | IEC 60384-18,<br>subclause 4.3                 | Shall be performed prior to tests mentioned below;<br>reflow soldering;<br>for maximum temperature load<br>refer to chapter "Mounting"                          | $\Delta C/C: \pm 5 \%$<br>$\tan \delta \leq \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$                                                                                |
| Endurance                                      | IEC 60384-18/<br>CECC 32300,<br>subclause 4.15 | $T_{\text{amb}} = 150 \text{ }^\circ\text{C}$ ; $U_R$ applied;<br>for test duration see Table 7                                                                 | $\Delta C/C: \pm 20 \%$<br>$\tan \delta \leq 2 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$                                                                      |
| Useful life                                    | CECC 30301,<br>subclause 1.8.1                 | $T_{\text{amb}} = 150 \text{ }^\circ\text{C}$ ; $U_R$ and $I_R$ applied;<br>for test duration see Table 7                                                       | $\Delta C/C: \pm 30 \%$<br>$\tan \delta \leq 3 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$<br>no short or open circuit<br>total failure percentage: $\leq 1 \%$ |
| Shelf life<br>(storage at high<br>temperature) | IEC 60384-18/<br>CECC 32300,<br>subclause 4.17 | $T_{\text{amb}} = 150 \text{ }^\circ\text{C}$ ; no voltage applied;<br>1000 h<br>After test: $U_R$ to be applied for 30 min,<br>24 h to 48 h before measurement | For requirements<br>see "Endurance test" above                                                                                                                                     |
| Reverse voltage                                | IEC 60384-18/<br>CECC 32300,<br>subclause 4.16 | $T_{\text{amb}} = 150 \text{ }^\circ\text{C}$ :<br>125 h at $U = -0.5 \text{ V}$ ,<br>followed by 125 h at $U_R$                                                | $\Delta C/C: \pm 15 \%$<br>$\tan \delta \leq 1.5 \times \text{spec. limit}$<br>$I_{L2} \leq \text{spec. limit}$                                                                    |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331