

www.vishay.com


Vishay Mills

Wirewound Resistor, Ultra Precision, Epoxy Molded, Axial Lead



FEATURES

- Resistance values up to 6 $M\Omega$
- Resistance tolerances down to ± 0.005 %
- Tighter tolerances and lower resistance values available, please contact factory
- Temperature coefficients down to ± 2 ppm/°C, and up to 6000 ppm/°C
- Matched resistance sets available in tolerances down to ± 0.001 %, and in temperature coefficients down to ± 0.5 ppm/°C, please contact factory









ROHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

STANDARD ELECTRICAL SPECIFICATIONS								
GLOBAL MODEL	POWER RATING W ⁽¹⁾	RESISTANCE RANGE $Ω$ ± 0.1 %, ± 0.25 %, ± 0.5 %, ± 1 %	$\begin{array}{c} \text{RESISTANCE RANGE} \\ \Omega \\ \pm 0.05~\%, \pm 0.1~\%, \\ \pm 0.25~\%, \pm 0.5~\%, \pm 1~\% \end{array}$	RESISTANCE RANGE Ω ± 0.01 %, ± 0.05 %, ± 0.1 %, ± 0.25 %, ± 0.5 %, ± 1 %	$\begin{array}{c} \textbf{RESISTANCE RANGE} \\ \Omega \\ \pm 0.005~\%, \pm 0.01~\%, \\ \pm 0.05~\%, \pm 0.1~\%, \\ \pm 0.25~\%, \pm 0.5~\%, \pm 1~\% \end{array}$	MAXIMUM WORKING VOLTAGE V (2)		
MR101	0.120	1 to 400K	5 to 400K	50 to 400K	1K to 400K	150		
MR102	0.175	1 to 750K	5 to 750K	50 to 750K	1K to 750K	200		
MR103	0.200	1 to 750K	5 to 750K	50 to 750K	1K to 750K	200		
MR104	0.150	1 to 500K	5 to 500K	50 to 500K	1K to 500K	100		
MR105	0.200	1 to 1.0M	5 to 1.0M	50 to 1.0M	1K to 1.0M	200		
MR106	0.250	1 to 1.2M	5 to 1.2M	50 to 1.2M	1K to 1.2M	300		
MR107	0.330	1 to 2.5M	5 to 2.5M	50 to 2.5M	1K to 2.5M	400		
MR108	0.400	1 to 3.8M	5 to 3.8M	50 to 3.8M	1K to 3.8M	300		
MR110	0.500	1 to 3.8M	5 to 3.8M	50 to 3.8M	1K to 3.8M	400		
MR111	0.500	1 to 3.8M	5 to 3.8M	50 to 3.8M	1K to 3.8M	400		
MR112	0.750	1 to 6.0M	5 to 6.0M	50 to 6.0M	1K to 6.0M	600		
MR114	1.000	1 to 6.0M	5 to 6.0M	50 to 6.0M	1K to 6.0M	800		
MR115	1.500	1 to 6.0M	5 to 6.0M	50 to 6.0M	1K to 6.0M	900		
MR116	2.000	1 to 6.0M	5 to 6.0M	50 to 6.0M	1K to 6.0M	1000		

Notes


(1) Power rating is based on tolerance, please see derating chart.

⁽²⁾ The maximum working voltage is the highest voltage that can be applied to the resistor. Below this value, the maximum voltage that can continuously be applied is given by $(P \times R)^{1/2}$.

continuously be applied is given by $(P \times R)^{1/2}$.									
GLOBAL PART NUMBER INFORMATION									
Global Part Numbering examp	ole: MR106250R00TAE66 (visit <u>www.vi</u>	shay.net SAP parts manual for all op	otions)						
GLOBAL MODEL	VALUE TOLERANCE	TC PACKAGI							
(5 digits)	(6 digits) (1 digit)	(1 digit) (3 di							
(see Standard Electrical Specifications Global Model column for options) Historical Part Number examp	R = decimal K = thousand M = million 1R5000 = 1.5 Ω 1K5000 = 1.5 kΩ 1M0000 = 1 MΩ	10 to 30 (W) bulk	(dash number) From 1 to 99 as applicable S = 0.025" terminal						
MR106	W = STANDARD	250 Ω	0.01 %						
HISTORICAL MODEL	TC	RESISTANCE VALUE	TOLERANCE						



DIMENSIONS in inches [millimeters]



GLOBAL MODEL	DIMENSIONS in inches [millimeters]				
GLOBAL MODEL	L ± 0.025 [0.635]	D ± 0.005 [0.127]	LD ± 0.002 [0.051]		
MR101	0.250 [6.35]	0.187 [4.75]	0.025 [0.635]		
MR102	0.375 [9.52]	0.187 [4.75]	0.025 [0.635]		
MR103	0.450 [11.43]	0.187 [4.75]	0.025 [0.635]		
MR104	0.250 [6.35]	0.250 [6.35]	0.025 [0.635]		
MR105	0.375 [9.52]	0.250 [6.35]	0.032 [0.813] (1)		
MR106	0.500 [12.70]	0.250 [6.35]	0.032 [0.813] ⁽¹⁾		
MR107	0.750 [19.05]	0.250 [6.35]	0.032 [0.813] (1)		
MR108	0.500 [12.70]	0.375 [9.52]	0.032 [0.813]		
MR110	0.750 [19.05]	0.375 [9.52]	0.032 [0.813]		
MR111	0.750 [19.05]	0.375 [9.52]	0.032 [0.813]		
MR112	1.000 [25.40]	0.375 [9.52]	0.032 [0.813]		
MR114	1.000 [25.40]	0.500 [12.70]	0.032 [0.813]		
MR115	1.500 [38.10]	0.500 [12.70]	0.032 [0.813]		
MR116	2.000 [50.80]	0.500 [12.70]	0.032 [0.813]		

Note

MATERIAL SPECIFICATIONS

Element: nickel-chrome alloy, other materials available

depending on TC requirements


Core: molded epoxy **Encapsulant:** epoxy

Standard Terminals: 100 % matte tinned copper **Part Marking:** Mills, model, value, tolerance, date code

Note

 Due to resistor size limitations some resistors will have minimal information marked on parts

DERATING



TECHNICAL SPECIFICATIONS					
PARAMETER	UNIT	MR100 RESISTOR CHARACTERISTICS			
Temperature Coefficient	ppm/°C	\pm 10 for > 100 $\Omega;$ \pm 20 for 10 Ω to 100 $\Omega;$ \pm 30 for < 10 Ω			
Terminal Strength	lb	4.5			
Dielectric Withstanding Voltage	V_{AC}	750			
Operating Temperature Range	°C	-55 to +145 (see derating chart)			

^{(1) 0.025&}quot; [0.635] available, this is called out by putting an "S" in the SPECIAL section of the part number.



Legal Disclaimer Notice

Vishay

Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.

Revision: 02-Oct-12 Document Number: 91000



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331