



TABLE OF CONTENTS	
SHEET NO.	SHEET DESCRIPTION
1	NOTES
2, 3	CONFIGURATIONS
4	RECEPTACLE CONNECTOR ASSEMBLY
5	MOLEX INTERFACE

NOTES: VALID UNLESS OTHERWISE SPECIFIED


1. GENERAL:
 - a. APPLICATION SPECIFICATION SEE: AS-34062-000
-CONTAINS: PRODUCT INTRODUCTION, PRODUCT SUMMARY, CONNECTOR ASSEMBLY, PACKAGING INFORMATION, CONNECTOR MATING, SERVICE INSTRUCTIONS, ELECTRICAL CONTINUITY CHECKING, CRIMPING, AND TROUBLESHOOTING.
 2. PRODUCT SPECIFICATION SEE: PS-34062-000
CONTAINS: SCOPE, PRODUCT DESCRIPTION, INTEGRAL COMPONENTS AND ACCESSORIES, APPLICABLE DOCUMENTS AND SPECIFICATIONS, RATINGS, PERFORMANCE, PACKAGING, GAUGE AND FIXTURES, AND OTHER INFORMATION.
 - a. PACKAGING SPECIFICATION PER MOLEX DRAWING: PK-30907-879
 - b. PARTS MUST BE IN COMPLIANCE TO MOLEX CHEMICAL SUBSTANCES FOR PRODUCTS AND PACKAGING SPECIFICATION: ES-40000-5016
 - c. DATA MUST BE SUBMITTED UNDER THE MOLEX PART NUMBER TO IMDS (COMPANY ID#13255)
 - d. DESIGNED TO MATE WITH DEVICE CONNECTION AS SPECIFIED IN DRAWING EWCAP 150-S-002-1-Z01. AVAILABLE AT <http://ewcap.uscarteams.org/>.
2. DESIGN - MATERIALS:
 - a. SEE BOM TABLE IN SD-34062-004
3. DESIGN - GEOMETRY:
 - a. THIS IS A 100% CAD GENERATED PART. THE CAD MATHEMATICAL DATA IS THE MASTER FOR THIS PART. FOR DIMENSIONAL OR ANY INFORMATION NOT SHOWN ON THIS DRAWING, ANALYZE THE CAD MODEL.
 - b. GEOMETRIC DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994
 - c. EDGES AND UNDIMENSIONED DETAILS PER ISO13715
 - d. CORNERS SHOWN AS SHARP TO BE R 0.2 MAX.
 - e. LETTERING SHALL BE 0.15 MAX RAISED IN 0.25 MAX RECESS PAD. THIS INCLUDES RECYCLING CODE, CAVITY ID, VENDOR IDENTIFICATION, AND CUSTOMER MATERIAL NUMBER.
 - f. VISUAL DEFECTS SHALL MEET COSMETIC STANDARD PS-45499-002 (Class B)
 - g. LASER MARKING: TBD



INSPECTION NUMBER LOG
LAST NUMBER USED:
ADDED:
REMOVED:

J11	MOVED BOM TO MOLEX DRAWING E-34062-004
J10	P/N 34062-0048 THRU 0055 & 0056 SALEABLE
J9	UPDATED VIEWS
J8	UPDATE 34062-0057
J7	ADDED P/N 34062-0057
J6	P/N 34062-0041, 0043, 0044, & 0046 SALEABLE
J5	ADDED P/N 34062-0056
J4	ADDED P/N 34062-4003 & 34062-4004
J3	34062-0042 & 34062-0045 SALEABLE
J2	UPDATED VIEWS
REV	DESCRIPTION


ENTER DESCRIPTION IEC NO: UAU2016-0110 DRAWN: BORUSZSKI 1/2015/07/23 CHKD: APPR: WOSHY	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED) mm INCH 4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.10 ± --- 1 PLACE ± 0.3 ± --- 0 PLACE ± ± ANGULAR ± 3 ° DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION STYLE MM ONLY DRAWN BY DATE CHECKED BY DATE APPROVED BY DATE	SCALE 4:1 DESIGN UNITS METRIC THIRD ANGLE PROJECTION	TITLE MX150 2 WAY CABLE SEAL RECEPTACLE CONN. SYSTEM (5.0MM PITCH) molex	MATERIAL NO. SEE NOTE 2a.	DOCUMENT NO. SD-34062-002	SHEET NO. 1 OF 5




SHEET DESCRIPTION
CONFIGURATIONS




OPTION A




OPTION B




OPTION C




OPTION D






OPTION E




OPTION F



OPTION G




REAR VIEW



REAR VIEW

Ø 23.40
MINIMUM PASS-THRU WITH
NO CLEARANCE
APPLIES TO NON CLIP-SLOT
OPTIONS A, C, D, & G



Ø 26.00
MINIMUM PASS-THRU WITH
NO CLEARANCE
APPLIES TO NON CLIP-SLOT
OPTIONS B, E, & F





NON CLIP-SLOT OPTION
SCALE 4:1

ENTER DESCRIPTION IEC NO: UAU2016-0110 DRAWN: BORUSZENSKI 1/2015/07/23 CHKD: APPR: WOSHY J12	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION			
				mm	INCH	DRAWN BY KCUNNINGHAM	DATE 2011/11/08	TITLE MX150 2 WAY CABLE SEAL RECEPTACLE CONN. SYSTEM (5.0MM PITCH)				
			4 PLACES ± --- ± ---		CHECKED BY MYANSLAMBROU	DATE 1/26/2012	molex					
			3 PLACES ± --- ± ---		APPROVED BY	DATE						
			2 PLACES ± 0.10 ± ---		MATERIAL NO.	DOCUMENT NO.						
			1 PLACE ± 0.3 ± ---		SIZE D	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION						
			0 PLACE ± ±		ANGULAR ± 3 °		SD-34062-002			SHEET NO. 2 OF 5		
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS									



SHEET DESCRIPTION
CONFIGURATIONS




OPTION A W/CLIP-SLOT





Ø25.50
MINIMUM PASS-THRU WITH
NO CLEARANCE
APPLIES TO CLIP-SLOT
OPTIONS A, C AND D





OPTION B W/CLIP-SLOT





Ø26.00
MINIMUM PASS-THRU WITH
NO CLEARANCE
APPLIES TO CLIP-SLOT
OPTIONS B




OPTION C W/CLIP-SLOT



CLIP-SLOT OPTION
SCALE 4:1



OPTION D W/CLIP-SLOT







ENTER DESCRIPTION LEC NO: UAU2016-0110 DRAWN BY: DRWN:KBRUSZESKI 2015/07/23 CHKD: CHYD: APPR:WKOSHY 2015/07/27 REV J12	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	DESIGNATION	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	TITLE MX150 2 WAY CABLE SEAL RECEPTACLE CONN. SYSTEM (5.0MM PITCH) molex	SHEET NO. SD-34062-002 3 OF 5
			4 PLACES ±.000 ±.000		DRAWN BY KCUNNINGHAM		DATE 2011/11/08				
			3 PLACES ±.000 ±.000		CHECKED BY		DATE				
			2 PLACES ±.010 ±.000		MVANSLAMBROU		1/26/2012				
			1 PLACE ±.03 ±.000		APPROVED BY		DATE				
			0 PLACE ±.0 ±.000								
			ANGULAR ± 3 °		MATERIAL NO.		DOCUMENT NO.				
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		SEE NOTE 2a.		SD-34062-002				
					SIZE D		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				



SHEET DESCRIPTION

RECEPTACLE CONNECTOR ASSEMBLY


OPTIONAL LASER MARKING SURFACE
SEE NOTE h.



OPTIONAL LASER MARKING SURFACE
SEE NOTE h.



TPA SHOWN IN THE
PRE-STAGED POSITION
SECTION A-A




SECTION B-B

TPA SHOWN IN
FINAL-LOCK POSITION


ENTER DESCRIPTION EC NO: UAU2016-0110 DRAWN BY: BORUSZENSKI 2015/07/23 CHKD: WOSHY APPR: WOSHY J12	QUALITY SYMBOLS ▽=0 ▽=0 ▽=0	DESCRIPTION DRAWING	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE 4:1	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION
					DRAWN BY KCUNNINGHAM	DATE 2011/11/08	TITLE MX150 2 WAY CABLE SEAL RECEPTACLE CONN. SYSTEM (5.0MM PITCH)		
					CHECKED BY MYANSLAMBROU	DATE 1/26/2012	DOCUMENT NO. SD-34062-002		
					APPROVED BY	DATE	SHEET NO. 4 OF 5		
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE NOTE 2a.		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		

Figure 1 is a technical drawing of a connector shroud. It shows a cross-section of the shroud with several dimensions and callouts. The dimensions are: 13.90 MIN. (CD 1), 11.80 MIN. (CD 2), and CD 3 (5.65 MIN. MIN ALL AROUND). The callouts are: DATUM A (top surface), DATUM B (bottom surface), and FOR MATING CONNECTOR SHROUD CLEARANCE. The drawing is labeled Figure 1: Connector Shroud Dimensions.




A technical line drawing of a U-shaped metal profile. The profile has a semi-circular end on the left side. It features a central channel and two side flanges. The drawing is a perspective view, showing the top, front, and side surfaces.


OPTION E




OPTION G
SAME AS OPTION F
EXCEPT AS SHOWN




DETAIL 2
SCALE 10:1




SECTION W-W




OPTION F



OPTION F




OPTION E
SAME AS OPTION F
EXCEPT AS SHOWN



SECTION X-X

1. ALL DIMENSIONS SHOWN IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994
3. 0.25 RADII ON ALL CORNERS SHOWN SHARP.
4. UNSPECIFIED RADII: 0.25 EXCEPT AS NOTED.
5. STANDARD COLORS FOR POLARIZATION (SEE CHART).
DEVIATION REQUIRES APPROVAL OF AUTHORIZED PERSON.
6. REFER TO SAE/USCAR 12 CONNECTOR GUIDELINES
FOR ADDITIONAL REQUIREMENTS.
7. EXCEPT WHERE NOTED, DRAFT ON OUTSIDE SURFACES IS PERMISSIBLE
WITHIN TOLERANCE.
8.  SYMBOL INDICATES DRAFT DIRECTION.
9. FOR TERMINAL MATERIAL, DIMENSIONAL, AND COATING REQUIREMENTS
AND ANY BLADE TERMINAL DESIGN INFORMATION NOT SHOWN ON THIS
DRAWING SEE EWCAP DWG. NO. EWCAP-001
10. A FULL SHROUD ON THE MATING CONNECTOR IS REQUIRED
TO INSURE THAT THE CONNECTOR-HEADER POLARIZATION
FEATURES (OPTIONS A THRU D) WILL FUNCTION. THE FULL
SHROUD ALSO PREVENTS SCOOP DAMAGE TO THE HEADER
PINS. REFER TO SAE/USCAR-12 CONNECTOR DESIGN
GUIDE LINES FOR ADDITIONAL INFORMATION.
11. REFER TO SAE/USCAR PART LIST AS FOUND ON WEBSITE
<http://www.uscarteams.org>
12. THIS IS A 100% CAD GENERATED PART. THE CAT MATHEMATICAL DATA
IS THE MASTER FOR THIS PART. FOR DIMENSIONAL OR ANY INFORMATION
NOT SHOWN ON THIS DRAWING, ANALYZE THE CAD MODEL.

[illegible]



BOM/ APPLICABLE COMPONENTS TABLE			
ABBREVIATION	DESCRIPTION	COLOR	MATERIAL
A-BLK	HOUSING KEYING OPTION A	BLACK	PA6 GF30
B-LG	HOUSING KEYING OPTION B	LIGHT GRAY	PA6 GF30
C-BLK	HOUSING KEYING OPTION C	BLACK	PA6 GF30
D-BLK	HOUSING KEYING OPTION D	BLACK	PA6 GF30
D-LG	HOUSING KEYING OPTION D	LIGHT GRAY	PA6 GF30
E-BLK	HOUSING KEYING OPTION E	BLACK	PA6 GF30
F-LG	HOUSING KEYING OPTION F	LIGHT GRAY	PA6 GF30
G-BLK	HOUSING KEYING OPTION G	BLACK	PA6 GF30
A-BLK-CLIP	HOUSING KEYING OPTION A WITH CLIPSLOT	BLACK	PA6 GF30
B-LG-CLIP	HOUSING KEYING OPTION B WITH CLIPSLOT	LIGHT GRAY	PA6 GF30
C-BLK-CLIP	HOUSING KEYING OPTION C WITH CLIPSLOT	BLACK	PA6 GF30
D-BLK-CLIP	HOUSING KEYING OPTION D WITH CLIPSLOT	BLACK	PA6 GF30
D-LG-CLIP	HOUSING KEYING OPTION D WITH CLIPSLOT	LIGHT GRAY	PA6 GF30
C-BLK-SV	HOUSING KEYING OPTION C - SEVERE VIBRATION	BLACK	PA6 GF30
D-BLK-SV	HOUSING KEYING OPTION D - SEVERE VIBRATION	BLACK	PA6 GF30
R3	RING SEAL TEMP. CLASS 3	MEDIUM BLUE	INHERENTLY LUBRICATED SILICONE
R4	RING SEAL TEMP. CLASS 4	GREEN	INHERENTLY LUBRICATED SILICONE
CPA	CPA	RED	PBT GF30
TPA	INSERT, TPA	NATURAL	PBT GF30

FOR ADDITIONAL INFORMATION SEE SD-34062-002

ASSEMBLY DESCRIPTION	ASSEMBLY PART NUMBER	COMPONENT				ASSEMBLY OPERATING TEMPERATURE	RECOMMENDED MATING DEVICE			PRODUCTION TOOL STATUS	COMMENTS	
		THE PRESENCE OF AN ABBREVIATION INDICATES THE PRESENCE OF THAT COMPONENT.					1	2	3			
		HOUSING KEY/COLOR	TPA	CPA	RING SEAL							
KEY A, BLACK, W/O CPA	34062-0021	A-BLK	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY B, LIGHT GRAY, W/O CPA	34062-0022	B-LG	TPA		R3	-40°C TO 125°C	1			SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, W/O CPA	34062-0023	C-BLK	TPA		R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, W/O CPA	34062-0024	D-BLK	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY D, LIGHT GRAY, W/O CPA	34062-0029	D-LG	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY A, BLACK, W/ CPA	34062-0025	A-BLK	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY B, LIGHT GRAY, W/ CPA	34062-0026	B-LG	TPA	CPA	R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, W/ CPA	34062-0027	C-BLK	TPA	CPA	R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, W/ CPA	34062-0028	D-BLK	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY D, LIGHT GRAY, W/ CPA	34062-0030	D-LG	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY A, BLACK, WITH CLIPSLOT, W/O CPA	34062-0031	A-BLK-CLIP	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY B, LIGHT GRAY, WITH CLIPSLOT, W/O CPA	34062-0032	B-LG-CLIP	TPA		R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, WITH CLIPSLOT, W/O CPA	34062-0033	C-BLK-CLIP	TPA		R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, WITH CLIPSLOT, W/O CPA	34062-0034	D-BLK-CLIP	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY D, LIGHT GRAY, WITH CLIPSLOT, W/O CPA	34062-0035	D-LG-CLIP	TPA		R3	-40°C TO 125°C	1			SALEABLE		
KEY A, BLACK, WITH CLIPSLOT, W/ CPA	34062-0036	A-BLK-CLIP	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY B, LIGHT GRAY, WITH CLIPSLOT, W/ CPA	34062-0037	B-LG-CLIP	TPA	CPA	R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, WITH CLIPSLOT, W/ CPA	34062-0038	C-BLK-CLIP	TPA	CPA	R3	-40°C TO 125°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, WITH CLIPSLOT, W/ CPA	34062-0039	D-BLK-CLIP	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY D, LIGHT GRAY, WITH CLIPSLOT, W/ CPA	34062-0040	D-LG-CLIP	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY C, BLACK, SEVERE VIBRATION, W/ CPA	34062-4008	C-BLK-SV	TPA	CPA	R4	-40°C TO 155°C	1			SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, SEVERE VIBRATION, W/ CPA	34062-4009	D-BLK-SV	TPA	CPA	R4	-40°C TO 155°C	1			SALEABLE		
KEY E, BLACK, W/O CPA	34062-0041	E-BLK	TPA		R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY F, LIGHT GRAY, W/O CPA	34062-0042	F-LG	TPA		R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY G, BLACK, W/O CPA	34062-0043	G-BLK	TPA		R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY E, BLACK, W/ CPA	34062-0044	E-BLK	TPA	CPA	R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY F, LIGHT GRAY, W/ CPA	34062-0045	F-LG	TPA	CPA	R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY G, BLACK, W/ CPA	34062-0046	G-BLK	TPA	CPA	R4	-40°C TO 155°C		2		SALEABLE	PREFERRED, FULLY SHROUDED	
KEY A, BLACK, W/ CPA	34062-0047	A-BLK	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
KEY B, LIGHT GRAY, W/O CPA	34062-0048	B-LG	TPA		R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, W/O CPA	34062-0049	C-BLK	TPA		R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY B, LIGHT GRAY, W/ CPA	34062-0050	B-LG	TPA	CPA	R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, W/ CPA	34062-0051	C-BLK	TPA	CPA	R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY B, LIGHT GRAY, WITH CLIPSLOT, W/O CPA	34062-0052	B-LG-CLIP	TPA		R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, WITH CLIPSLOT, W/O CPA	34062-0053	C-BLK-CLIP	TPA		R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY B, LIGHT GRAY, WITH CLIPSLOT, W/ CPA	34062-0054	B-LG-CLIP	TPA	CPA	R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, WITH CLIPSLOT, W/ CPA	34062-0055	C-BLK-CLIP	TPA	CPA	R4	-40°C TO 155°C	1		3	SALEABLE	PREFERRED, FULLY SHROUDED	
KEY C, BLACK, SEVERE VIBRATION, W/O CPA	34062-4003	C-BLK-SV	TPA		R4	-40°C TO 155°C	1			SALEABLE	PREFERRED, FULLY SHROUDED	
KEY D, BLACK, SEVERE VIBRATION, W/O CPA	34062-4004	D-BLK-SV	TPA		R4	-40°C TO 155°C	1			SALEABLE		
KEY D, BLACK, WITH CLIPSLOT, W/ CPA	34062-0056	D-BLK-CLIP	TPA	CPA	R4	-40°C TO 155°C	1			SALEABLE		
KEY A, BLACK, WITH CLIPSLOT, W/ CPA	34062-0057	A-BLK-CLIP	TPA	CPA	R3	-40°C TO 125°C	1			SALEABLE		
					</							



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331