

NB3N551

3.3 V / 5.0 V Ultra-Low Skew 1:4 Clock Fanout Buffer

Description

The NB3N551 is a low skew 1-to 4 clock fanout buffer, designed for clock distribution in mind. The NB3N551 specifically guarantees low output-to-output skew. Optimal design, layout and processing minimize skew within a device and from device to device.

The output enable (OE) pin three-states the outputs when low.

Features

- Input/Output Clock Frequency up to 180 MHz
- Low Skew Outputs (50 ps typical)
- Output goes to Three-State Mode via OE
- Operating Range: $V_{DD} = 3.0\text{ V to }5.5\text{ V}$
- Ideal for Networking Clocks
- Packaged in 8-pin SOIC
- Industrial Temperature Range
- These are Pb-Free Devices




Figure 1. Block Diagram




ON Semiconductor®

<http://onsemi.com>


MARKING DIAGRAMS*




**SOIC-8
D SUFFIX
CASE 751**



3N551 = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb-Free Package



**DFN8
MN SUFFIX
CASE 506AA**




6K = Specific Device Code
M = Date Code
▪ = Pb-Free Package

(Note: Microdot may be in either location)

*For additional marking information, refer to Application Note AND8002/D.

PIN CONNECTIONS



ORDERING INFORMATION

| Device | Package | Shipping† |
|--------------|---------------------|------------------|
| NB3N551DG | SOIC-8 (Pb-Free) | 98 Units/Rail |
| NB3N551DR2G | SOIC-8 (Pb-Free) | 2500/Tape & Reel |
| NB3N551MNR4G | DFN-8 (Pb-Free) | 1000/Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specification Brochure, BRD8011/D.

NB3N551

| OE | Function |
|----|----------|
| 0 | Disable |
| 1 | Enable |

Table 1. OE, Output Enable Function

PIN DESCRIPTION

| Pin # | Name | Type | Description |
|-------|------------------|-------------------------|--|
| 1 | I _{CLK} | (LV)CMOS/(LV)TTL Input | Clock Input. Internal pull-up resistor. |
| 2 | Q1 | (LV)CMOS/(LV)TTL Output | Clock Output 1 |
| 3 | Q2 | (LV)CMOS/(LV)TTL Output | Clock Output 2 |
| 4 | Q3 | (LV)CMOS/(LV)TTL Output | Clock Output 3 |
| 5 | Q4 | (LV)CMOS/(LV)TTL Output | Clock Output 4 |
| 6 | GND | Power | Negative supply voltage; Connect to ground, 0 V |
| 7 | V _{DD} | Power | Positive supply voltage (3.0 V to 5.5 V) |
| 8 | OE | (LV)CMOS/(LV)TTL Input | Output Enable for the clock outputs. Outputs are enabled when HIGH or when left open; OE pin has internal pull-up resistor. Three-states outputs when LOW. |

MAXIMUM RATINGS

| Symbol | Parameter | Condition 1 | Condition 2 | Rating | Units |
|--------------------------------|--|--------------------|----------------|---|--------------|
| V _{DD} | Positive Power Supply | GND = 0 V | - | 7.0 | V |
| V _I /V _O | Input/Output Voltage | t ≤ 1.5 ns | - | GND-1.5 ≤ V _I /V _O ≤ V _{DD} +1.5 | V |
| T _A | Operating Temperature Range, Industrial | - | - | ≥ -40 to ≤ +85 | °C |
| T _{stg} | Storage Temperature Range | - | - | -65 to +150 | °C |
| θ _{JA} | Thermal Resistance (Junction-to-Ambient) | 0 LFPM 500 LFPM | SOIC-8 | 190 130 | °C/W °C/W |
| θ _{JC} | Thermal Resistance (Junction-to-Case) | (Note 1) | SOIC-8 | 41 to 44 | °C/W |
| θ _{JA} | Thermal Resistance (Junction-to-Ambient) | 0 LFPM 500 LFPM | DFN-8 DFN-8 | 129 84 | °C/W |

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. JEDEC standard multilayer board – 2S2P (2 signal, 2 power)

ATTRIBUTES

| Characteristic | Value |
|---|--|
| ESD Protection | Human Body Model Machine Model > 4 kV > 200 V |
| Moisture Sensitivity, Indefinite Time Out of Drypack (Note 2) | Level 1 |
| Flammability Rating | Oxygen Index: 28 to 34 UL-94 code V-0 @ 0.125 in |
| Transistor Count | 531 Devices |
| Meets or Exceeds JEDEC Standard EIA/JESD78 IC Latchup Test | |

2. For additional Moisture Sensitivity information, refer to Application Note AND8003/D.

NB3N551

DC CHARACTERISTICS ($V_{DD} = 3.0\text{ V to }3.6\text{ V}$, $GND = 0\text{ V}$, $T_A = -40^\circ\text{C to }+85^\circ\text{C}$) (Note 3)

| Symbol | Characteristic | Min | Typ | Max | Unit |
|----------------------|--|------------------|----------|------------------|------------|
| I_{DD} | Power Supply Current @ 135 MHz, No Load, $V_{DD} = 3.3\text{ V}$ | – | 20 | 40 | mA |
| V_{OH} | Output HIGH Voltage – $I_{OH} = -25\text{ mA}$, $V_{DD} = 3.3\text{ V}$ | 2.4 | – | – | V |
| V_{OL} | Output LOW Voltage – $I_{OL} = 25\text{ mA}$ | – | – | 0.4 | V |
| V_{OH} | Output HIGH Voltage – $I_{OH} = -12\text{ mA}$ (CMOS level) | $V_{DD} - 0.4$ | – | – | V |
| V_{IH} , I_{CLK} | Input HIGH Voltage, I_{CLK} | $(V_{DD}/2)+0.7$ | – | 3.8 | V |
| V_{IL} , I_{CLK} | Input LOW Voltage, I_{CLK} | – | – | $(V_{DD}/2)-0.7$ | V |
| V_{IH} , OE | Input HIGH Voltage, OE | 2.0 | – | V_{DD} | V |
| V_{IL} , OE | Input LOW Voltage, OE | 0 | – | 0.8 | V |
| ZO | Nominal Output Impedance | – | 20 | – | Ω |
| RPU | Input Pull-up Resistor, OE | – | 220 | – | k Ω |
| CIN | Input Capacitance, OE | – | 5.0 | – | pF |
| IOS | Short Circuit Current | – | ± 50 | – | mA |

DC CHARACTERISTICS ($V_{DD} = 4.5\text{ V to }5.5\text{ V}$, $GND = 0\text{ V}$, $T_A = -40^\circ\text{C to }+85^\circ\text{C}$) (Note 3)

| Symbol | Characteristic | Min | Typ | Max | Unit |
|----------------------|--|------------------|----------|------------------|------------|
| I_{DD} | Power Supply Current @ 135 MHz, No Load, $V_{DD} = 5.0\text{ V}$ | – | 50 | 95 | mA |
| V_{OH} | Output HIGH Voltage – $I_{OH} = -35\text{ mA}$ | 2.4 | – | – | V |
| V_{OL} | Output LOW Voltage – $I_{OL} = 35\text{ mA}$ | – | – | 0.4 | V |
| V_{OH} | Output HIGH Voltage – $I_{OH} = -12\text{ mA}$ (CMOS level) | $V_{DD} - 0.4$ | – | – | V |
| V_{IH} , I_{CLK} | Input HIGH Voltage, I_{CLK} | $(V_{DD}/2) + 1$ | – | 5.5 | V |
| V_{IL} , I_{CLK} | Input LOW Voltage, I_{CLK} | – | – | $(V_{DD}/2) - 1$ | V |
| V_{IH} , OE | Input HIGH Voltage, OE | 2.0 | – | V_{DD} | V |
| V_{IL} , OE | Input LOW Voltage, OE | 0 | – | 0.8 | V |
| ZO | Nominal Output Impedance | – | 20 | – | Ω |
| RPU | Input Pull-up Resistor, OE | – | 220 | – | k Ω |
| CIN | Input Capacitance, OE | – | 5.0 | – | pF |
| IOS | Short Circuit Current | – | ± 80 | – | mA |

AC CHARACTERISTICS ($V_{DD} = 3.0\text{ V to }5.5\text{ V}$, $GND = 0\text{ V}$, $T_A = -40^\circ\text{C to }+85^\circ\text{C}$) (Note 3)

| Symbol | Characteristic | Min | Typ | Max | Unit |
|-------------------|---|-----|-----|-----|------|
| f_{in} | Input Frequency | – | – | 180 | MHz |
| t_{jitter} (pd) | Period Jitter (RMS, 1σ) | – | 2.0 | – | ps |
| t_r/t_f | Output rise and fall times; 0.8 V to 2.0 V | – | 0.5 | 1.0 | ns |
| t_{pd} | Propagation Delay, CLK to Qn, 0 – 180 MHz, (Note 4) | 1.5 | 3.0 | 6.0 | ns |
| t_{skew} | Output-to-output skew; (Note 5) | – | 50 | 160 | ps |

3. Outputs loaded with external $R_L = 33\text{-}\Omega$ series resistor and $C_L = 15\text{ pF}$ to GND for proper operation. Duty cycle out = duty in. A $0.01\text{ }\mu\text{F}$ decoupling capacitor should be connected between V_{DD} and GND. A $33\text{ }\Omega$ series terminating resistor may be used on each clock output if the trace is longer than 1 inch.


4. Measured with rail-to-rail input clock.

5. Measured on rising edges at $V_{DD} \div 2$.

NB3N551

PACKAGE DIMENSIONS

SOIC-8 NB
CASE 751-07
ISSUE AG




NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETER.
3. DIMENSION A AND B DO NOT INCLUDE MOLD PROTRUSION.
4. MAXIMUM MOLD PROTRUSION 0.15 (0.006) PER SIDE.
5. DIMENSION D DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.127 (0.005) TOTAL IN EXCESS OF THE D DIMENSION AT MAXIMUM MATERIAL CONDITION.
6. 751-01 THRU 751-06 ARE OBSOLETE. NEW STANDARD IS 751-07.

| DIM | MILLIMETERS | | INCHES | |
|-----|-------------|------|-----------|-------|
| | MIN | MAX | MIN | MAX |
| A | 4.80 | 5.00 | 0.189 | 0.197 |
| B | 3.80 | 4.00 | 0.150 | 0.157 |
| C | 1.35 | 1.75 | 0.053 | 0.069 |
| D | 0.33 | 0.51 | 0.013 | 0.020 |
| G | 1.27 BSC | | 0.050 BSC | |
| H | 0.10 | 0.25 | 0.004 | 0.010 |
| J | 0.19 | 0.25 | 0.007 | 0.010 |
| K | 0.40 | 1.27 | 0.016 | 0.050 |
| M | 0° | 8° | 0° | 8° |
| N | 0.25 | 0.50 | 0.010 | 0.020 |
| S | 5.80 | 6.20 | 0.228 | 0.244 |

SOLDERING FOOTPRINT*






SCALE 6:1 (mm / inches)

*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

NB3N551

PACKAGE DIMENSIONS


DFN8
CASE 506AA-01
ISSUE D



NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994 .
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.25 AND 0.30 MM FROM TERMINAL.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| MILLIMETERS | | |
|-------------|----------|------|
| DIM | MIN | MAX |
| A | 0.80 | 1.00 |
| A1 | 0.00 | 0.05 |
| A3 | 0.20 REF | |
| b | 0.20 | 0.30 |
| D | 2.00 BSC | |
| D2 | 1.10 | 1.30 |
| E | 2.00 BSC | |
| E2 | 0.70 | 0.90 |
| e | 0.50 BSC | |
| K | 0.20 | --- |
| L | 0.25 | 0.35 |

ON Semiconductor and  are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
P.O. Box 5163, Denver, Colorado 80217 USA
Phone: 303-675-2175 or 800-344-3860 Toll Free USA/Canada
Fax: 303-675-2176 or 800-344-3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free
USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81-3-5773-3850

ON Semiconductor Website: www.onsemi.com
Order Literature: <http://www.onsemi.com/orderlit>
For additional information, please contact your local Sales Representative



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331