






spec ref		---		dr	Mark Gray		2012/01/28		projection		MM	size	A2	scale	10:1																					
tolerance std		ASME Y14.5M		eng	Art Lin		2016/11/16																													
TOLERANCES UNLESS OTHERWISE SPECIFIED				chr	Heaven Cen		2016/11/17																													
				appr	Pei-Ming Zheng		2016/11/18																													
									product family		-		ecn no		ELX-DG-25255-1																					
													rel level		Released																					
surface	linear	0.X		±.3		Amphenol FCi	title					AirMax VSE R.A. HEADER					dwg no					10119886					rev					F				
		0.XX		±.15																																
		0.XXX		±.050																																
		angular		0°																																
							cat. no.		-		Product - Customer Drw							sheet 1 of 3																		




RECOMMENDED PCB LAYOUT
FOR DIFFERENTIAL APPLICATIONS
COMPONENT SIDE
(TWO ADJACENT FOOTPRINTS SHOWN)
NOTES 8 & 12

SCALE 10:1


spec ref ---				dr Mark Gray		2012/01/28		projection		MM		size A2		scale 10:1	
tolerance std				eng Art Lin		2016/11/16						ecn no		ELX-DG-25255-1	
ASME Y14.5M				chr Heaven Cen		2016/11/17						rel level		Released	
				appr Pei-Ming Zheng		2016/11/18						product family		-	
surface		linear		Amphenol FCI		title AirMax VSE R.A. HEADER Ass'y, 3 Pair, 54 pos, 6 IMLA		dwg no 10119886		rev F					
		0.X ±.3													
		0.XX ±.15													
		0.XXX ±.050													
		angular 0° ±2°				cat. no. -		Product - Customer Drw				sheet 2 of 3			

PRODUCT NUMBER	PRESS-FIT TAIL PLATING TYPE	SHORT DETECTION CONTACT
10119886-101LF	TIN OVER NICKEL (LEAD FREE)	NO
10119886-111LF	TIN OVER NICKEL (LEAD FREE)	YES (SEE NOTE 14)


- 1 - CONNECTOR MATERIALS:
HOUSING: HIGH TEMP THERMOPLASTIC, NATURAL, UL94-V0
IMLA PLASTIC: HIGH TEMP THERMOPLASTIC, BLACK, UL94-V0
CONTACT: COPPER ALLOY
ORGANIZER: HIGH TEMP THERMOPLASTIC, NATURAL, UL94-V0
- 2 - CONTACT PLATING:
SEPARABLE INTERFACE:
PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12-0956 INCLUDING TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE TEST SEQUENCE
- PRESS-FIT TAILS: SEE TABLE
- 3 - PRODUCT SPECIFICATION: GS-12-0956
- 4 - APPLICATION SPECIFICATION: GS-20-0305
- 5 - PRODUCT MARKING, (PROTOTYPE, PART NUMBER & LOT CODE), ON THIS SURFACE.
- 6 - POSITIONS "F" OF ODD NUMBERED COLUMNS AND POSITIONS "G" OF EVEN NUMBERED COLUMNS CORRESPOND TO EARLY MATE HEADER PINS.
- 7 - CONNECTOR OUTLINE MAY BE SCREEN PRINTED ONTO CUSTOMER PCB TO BE USED AS A GUIDE FOR CONNECTOR PLACEMENT.
- 8 - REFER TO CUSTOMER DRAWING 10104444 FOR INFORMATION ON PCB HOLE DIAMETERS AND PLATING OPTIONS
- 9 - LEAD FREE PRODUCT MEETS THE EUROPEAN UNION DIRECTIVES & OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008
- 10 - A  SYMBOL WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE WHICH HAS BEEN MODIFIED WITH THE CURRENT DRAWING REVISION.
- 11 - PACKAGING MEETS GS-14-920 LEAD FREE LABELING SPECIFICATION.
- 12 - GROUND CONTACTS (C, F, & I IN ODD COLUMNS AND A, D, & G IN EVEN COLUMNS) REQUIRE (Ø0.50) FINISHED HOLES. SIGNAL LOCATIONS REQUIRE (Ø0.40) FINISHED HOLES
- 13 - HESE OUTER VIAS (J) ARE OPTIONAL. WHILE NO CONNECTOR EONS ARE PRESSED INTO THESE HOLES WE RECCOMEND (Ø0.500) FINISHED HOLES AT THESE LOCATIONS TO PROVIDE GROUND SYMMETRY THROUGH THE PCB.
- 14 - MATING PIN E4 HAS 0.5mm LESS NOMINAL WIPE THAN THE SHORTEST PIN



10119886-101LF



DETAIL A
SCALE 15:1

spec ref ---				dr Mark Gray		2012/01/28		projection		MM		size A2		scale 10:1	
tolerance std				eng Art Lin		2016/11/16						ecn no ELX-DG-25255-1			
ASME Y14.5M				chr Heaven Cen		2016/11/17						rel level Released			
				appr Pei-Ming Zheng		2016/11/18						product family -			
surface		linear		Amphenol FCi		title AirMax VSE R.A. HEADER Ass'y, 3 Pair, 54 pos, 6 IMLA		dwg no 10119886		rev F					
		0.X ±.3													
		0.XX ±.15													
		0.XXX ±.050													
		angular 0° ±2°													
						cat. no. -		Product - Customer Drw				sheet 3 of 3			



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331