



**Product:** <u>83515</u> ☑

Electronic, 15 C #24 Str TC, FEP Ins, OS+TC Brd, FEP Jkt, CMP

# Request Sample

# **Product Description**

High Temperature Electronic, 15 Conductor 24AWG (7x32) Tinned Copper, FEP Insulation, Overall Beldfoil®+Tinned Copper Braid(85%) Shield, FEP Outer Jacket, CMP

## **Technical Specifications**

#### **Product Overview**

Suitable Applications: extreme high/low temperature environments; chemical resistant; outdoor and burial applications; low voltage analog signals (4-20ma, 0-10v, ...); low voltage control (24v, ...); line level audio; voice communications; panel wiring

#### **Construction Details**

#### Conductor

Element	Number of Element	AWG	Stranding	Material
Conductor(s)	15	24	7x32	TC - Tinned Copper

#### Insulation

Element	Material	Thickness [in]	Color Code	
Conductor(s) FEP - Fluorinated Ethylene Propylene 0.006 Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe Black/White Stripe, Red/White Stripe, Green/White Stripe, Blue/White Stripe		Black, White, Red, Green, Orange, Blue, White/Black Stripe, Red/Black Stripe, Green/Black Stripe, Orange/Black Stripe, Blue/Black Stripe, Blue/White Stripe, Blue/White Stripe, Blue/White Stripe		

## Outer Shield Material

Туре	Material	Coverage
Tape + Braid	Alum / Poly + Tinned Copper (TC)	100% + 85%

#### **Outer Jacket Material**

Material	Thickness	Diameter
FEP - Fluorinated Ethylene Propylene	0.014 in	0.227 in

## **Electrical Characteristics**

#### Electricals

Element	Nom. Conductor DCR	Nom. Capacitance Cond-to-Cond	Nom. Capacitance Cond-to-Other (Conds + Shield)	Max. Current
Conductor(s)	24 Ohm/1000ft	20 pF/ft	36 pF/ft	1.4 Amps per Conductor at 25°C

### Voltage

UL Voltage Rating 300 V (CMP)

## **Mechanical Characteristics**

# Temperature

UL Rating	Operating
150°C	-70°C to +200°C

## Bend Radius

Stationary Min.

2.5 in

Max. Pull Tension:	93 lbs
Bulk Cable Weight:	50 lbs/1000ft

#### **Standards and Compliance**

Environmental Suitability:	Outdoor, Oil Resistance
Sustainability:	CA Prop 65
Flammability / Fire Resistance:	NFPA 262, FT6
NEC / UL Compliance:	Article 800, CMP
CEC / C(UL) Compliance:	CMP
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU, EU Directive 2011/65/EU (ROHS II), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### **Product Notes**

#### **History**

Update and Revision:	Revision Number: 0.315 Revision Date: 06-18-2020

#### © 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

#### Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331