



## N-channel 30 V, 1.1 mΩ typ., 260 A, STripFET™ H6 Power MOSFET in a PowerFLAT 5x6 package

### Features



PowerFLAT™ 5x6



NGD5678S123

Order code	V <sub>DS</sub>	R <sub>DS(on)</sub> max.	I <sub>D</sub>	Package
STL260N3LLH6	30 V	1.3 mΩ	260 A	PowerFLAT™ 5x6

- Very low on-resistance
- Very low gate charge
- High avalanche ruggedness
- Low gate drive power loss

### Applications

- Switching applications

### Description

This device is an N-channel Power MOSFET developed using the STripFET™ H6 technology with a new trench gate structure. The resulting Power MOSFET exhibits very low R<sub>DS(on)</sub> in all packages.



#### Product status link

[STL260N3LLH6](#)

#### Product summary

Order code	STL260N3LLH6
Marking	260N3LH6
Package	PowerFLAT™ 5x6
Packing	Tape and reel

## 1

## Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
$V_{DS}$	Drain-source voltage	30	V
$V_{GS}$	Gate-source voltage	$\pm 20$	V
$I_D$ <sup>(1)</sup>	Drain current (continuous) at $T_C = 25^\circ C$	260	A
	Drain current (continuous) at $T_C = 100^\circ C$	190	
$I_{DM}$ <sup>(1) (2)</sup>	Drain current (pulsed)	1040	A
$I_D$ <sup>(3)</sup>	Drain current (continuous) at $T_{pcb} = 25^\circ C$	45	A
	Drain current (continuous) at $T_{pcb} = 100^\circ C$	32	A
$I_{DM}$ <sup>(2) (3)</sup>	Drain current (pulsed)	180	A
$P_{TOT}$ <sup>(1)</sup>	Total power dissipation at $T_C = 25^\circ C$	166	W
$P_{TOT}$ <sup>(3)</sup>	Total power dissipation at $T_{pcb} = 25^\circ C$	4.8	W
$E_{AS}$ <sup>(4)</sup>	Single pulse avalanche energy	900	mJ
$T_{stg}$ $T_j$	Storage temperature range Operating junction temperature range	-55 to 175	°C

1. The value is rated according to  $R_{thj-c}$ .
2. Pulse width limited by safe operating area.
3. The value is rated according to  $R_{thj-pcb}$ .
4. Starting  $T_J = 25^\circ C$ ,  $I_D = 35 A$ .

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj-case}$	Thermal resistance junction-case	0.9	°C/W
$R_{thj-pcb}$ <sup>(1)</sup>	Thermal resistance junction-pcb	31.3	

1. When mounted on an 1-inch<sup>2</sup> FR-4, 2 Oz copper board,  $t < 10 s$ .

## 2 Electrical characteristics

( $T_{case} = 25^\circ\text{C}$  unless otherwise specified)

**Table 3. Static**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{(BR)DSS}$	Drain-source breakdown voltage	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	30			V
$I_{DSS}$	Zero gate voltage drain current	$V_{GS} = 0 \text{ V}, V_{DS} = 30 \text{ V}$			1	$\mu\text{A}$
		$V_{GS} = 0 \text{ V}, V_{DS} = 30 \text{ V}, T_C = 125^\circ\text{C}$ (1)			10	$\mu\text{A}$
$I_{GSS}$	Gate-body leakage current	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$			$\pm 100$	nA
$V_{GS(th)}$	Gate threshold voltage	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	1			V
$R_{DS(on)}$	Static drain-source on-resistance	$V_{GS} = 10 \text{ V}, I_D = 22.5 \text{ A}$		1.1	1.3	$\text{m}\Omega$
		$V_{GS} = 4.5 \text{ V}, I_D = 22.5 \text{ A}$		1.6	2.0	

1. Defined by design, not subject to production test.

**Table 4. Dynamic**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$C_{iss}$	Input capacitance	$V_{DS} = 25 \text{ V}, f = 1 \text{ MHz}, V_{GS} = 0 \text{ V}$	-	6375	-	$\text{pF}$
$C_{oss}$	Output capacitance		-	1230	-	
$C_{rss}$	Reverse transfer capacitance		-	675	-	
$Q_g$	Total gate charge	$V_{DD} = 15 \text{ V}, I_D = 45 \text{ A}, V_{GS} = 0 \text{ to } 4.5 \text{ V}$ (see Figure 13. Test circuit for gate charge behavior)	-	61.5	-	$\text{nC}$
$Q_{gs}$	Gate-source charge		-	20	-	
$Q_{gd}$	Gate-drain charge		-	24	-	
$R_g$	Gate input resistance	$f = 1 \text{ MHz}, I_D = 0 \text{ A}$	-	1.4	-	$\Omega$

**Table 5. Switching times**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 15 \text{ V}, I_D = 22.5 \text{ A}, R_G = 4.7 \Omega, V_{GS} = 10 \text{ V}$ (see Figure 12. Test circuit for resistive load switching times and Figure 17. Switching time waveform)	-	22.5	-	$\text{ns}$
$t_r$	Rise time		-	32	-	
$t_{d(off)}$	Turn-off delay time		-	107.5	-	
$t_f$	Fall time		-	54	-	


**Table 6. Source-drain diode**

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$I_{SD}$	Source-drain current		-		45	A
$I_{SDM}^{(1)}$	Source-drain current (pulsed)		-		180	A
$V_{SD}^{(2)}$	Forward on voltage	$V_{GS} = 0 \text{ V}$ , $I_{SD} = 45 \text{ A}$	-		1.1	V
$t_{rr}$	Reverse recovery time	$I_{SD} = 45 \text{ A}$ , $dI/dt = 100 \text{ A}/\mu\text{s}$ ,	-	37.2		ns
$Q_{rr}$	Reverse recovery charge	$V_{DD} = 25 \text{ V}$ (see <a href="#">Figure 14. Test circuit for inductive load switching and diode recovery times</a> )	-	36		nC
$I_{RRM}$	Reverse recovery current		-	1.9		A


1. Pulse width is limited by safe operating area.
2. Pulse test: pulse duration = 300  $\mu\text{s}$ , duty cycle 1.5%.

## 2.1 Electrical characteristics (curves)


**Figure 1. Safe operating area**




**Figure 2. Thermal impedance**




**Figure 3. Output characteristics**




**Figure 4. Transfer characteristics**








**Figure 5. Normalized  $V_{(BR)DSS}$  vs temperature**




**Figure 6. Static drain-source on-resistance**



**Figure 7. Gate charge vs gate-source voltage**

**Figure 8. Capacitance variations**

**Figure 9. Normalized gate threshold voltage vs temperature**

**Figure 10. Normalized on-resistance vs temperature**

**Figure 11. Source-drain diode forward characteristics**



### 3 Test circuits

**Figure 12.** Test circuit for resistive load switching times




AM01468v1

**Figure 13.** Test circuit for gate charge behavior




AM01469v1

**Figure 14.** Test circuit for inductive load switching and diode recovery times




AM01470v1

**Figure 15.** Unclamped inductive load test circuit




AM01471v1

**Figure 16.** Unclamped inductive waveform



AM01472v1

**Figure 17.** Switching time waveform



AM01473v1

**4**


## Package information

---

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

## 4.1 PowerFLAT™ 5x6 type C package information

Figure 18. PowerFLAT™ 5x6 type C package outline




8231817\_typeC\_Rev18

**Table 7. PowerFLAT™ 5x6 type C package mechanical data**

Dim.	mm		
	Min.	Typ.	Max.
A	0.80		1.00
A1	0.02		0.05
A2		0.25	
b	0.30		0.50
C	5.80	6.00	6.20
D	5.00	5.20	5.40
D2	4.15		4.45
D3	4.05	4.20	4.35
D4	4.80	5.00	5.20
D5	0.25	0.40	0.55
D6	0.15	0.30	0.45
e		1.27	
E	5.95	6.15	6.35
E2	3.50		3.70
E3	2.35		2.55
E4	0.40		0.60
E5	0.08		0.28
E6	0.20	0.325	0.45
E7	0.75	0.90	1.05
K	1.05		1.35
L	0.725		1.025
L1	0.05	0.15	0.25
θ	0°		12°


**Figure 19.** PowerFLAT™ 5x6 recommended footprint (dimensions are in mm)



8231817\_FOOTPRINT\_simp\_Rev\_18

## 4.2 PowerFLAT™ 5x6 packing information

**Figure 20.** PowerFLAT™ 5x6 tape (dimensions are in mm)



**Figure 21.** PowerFLAT™ 5x6 package orientation in carrier tape





Figure 22. PowerFLAT™ 5x6 reel



All dimensions are in millimeters

8234350\_Reel\_rev\_C

## Revision history

**Table 8. Document revision history**

Date	Version	Changes
03-Aug-2014	1	First release.
03-Nov-2014	2	Updated value Table 2: Electrical characteristics Minor text changes
06-Feb-2019	3	Removed maturity status indication from cover page. The document status is production data. Updated marking information in Product summary table in cover page. Updated <a href="#">Section 4 Package information</a> . Minor text changes.

## Contents

<b>1</b>	<b>Electrical ratings .....</b>	<b>2</b>
<b>2</b>	<b>Electrical characteristics.....</b>	<b>3</b>
<b>2.1</b>	Electrical characteristics (curves) .....	5
<b>3</b>	<b>Test circuits .....</b>	<b>7</b>
<b>4</b>	<b>Package information.....</b>	<b>8</b>
<b>4.1</b>	PowerFLAT™ 5x6 type C package information.....	8
<b>4.2</b>	PowerFLAT™ 5x6 packing information .....	11
	<b>Revision history .....</b>	<b>14</b>

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литер Н,  
помещение 100-Н Офис 331