


# Optocoupler, Phototransistor Output, AC Input, Low Input Current



## DESCRIPTION

The SFH628A (DIP) and SFH6286 (SMD) feature a high current transfer ratio, low coupling capacitance and high isolation voltage. These couplers have a GaAs infrared emitting diode, which is optically coupled to a silicon planar phototransistor detector, and is incorporated in a plastic DIP-4 or SMD package.

The coupling devices are designed for signal transmission between two electrically separated circuits.

The couplers are end-stackable with 2.54 mm lead spacing. Creepage and clearance distances of > 8 mm are achieved with option 6. This version complies with IEC 60950 (DIN VDE 0805) for reinforced insulation to an operation voltage of 400 V<sub>RMS</sub> or DC.

## FEATURES

- High common mode interference immunity
- Isolation test voltage, 5300 V<sub>RMS</sub>
- Low coupling capacitance
- Good CTR linearity depending on forward current
- Low CTR degradation
- High collector emitter voltage, V<sub>CEO</sub> = 55 V
- Compliant to RoHS Directive to 2002/95/EC and in accordance WEEE 2002/96/EC



**RoHS**  
COMPLIANT

## APPLICATIONS


- Telecom
- Industrial controls
- Battery powered equipment
- Office machines

## AGENCY APPROVALS

- UL1577, file no. E52744 system code H
- DIN EN 60747-5-2 (VDE0884)/DIN EN 60747-5-5 (pending), available with option 1
- BSI IEC 60950; IEC 60065

## ORDERING INFORMATION

|             |   |   |   |   |   |   |   |         |                |   |   |   |               |
|-------------|---|---|---|---|---|---|---|---------|----------------|---|---|---|---------------|
| S           | F | H | 6 | 2 | 8 | x | - | #       | X              | 0 | # | # | T             |
| PART NUMBER |   |   |   |   |   |   |   | CTR BIN | PACKAGE OPTION |   |   |   | TAPE AND REEL |



| AGENCY CERTIFIED/PACKAGE | CTR (%)                   |                   |                   |                           |                           |                           |
|--------------------------|---------------------------|-------------------|-------------------|---------------------------|---------------------------|---------------------------|
|                          | SFH628A                   |                   |                   | SFH6286                   |                           |                           |
| <b>UL, BSI</b>           | <b>63 to 200</b>          | <b>100 to 320</b> | <b>160 to 500</b> | <b>63 to 200</b>          | <b>100 to 320</b>         | <b>160 to 500</b>         |
| DIP-4                    | SFH628A-2T <sup>(1)</sup> | SFH628A-3         | SFH628A-4         | -                         | -                         | -                         |
| SMD-4, option 9          | -                         | -                 | -                 | SFH6286-2T <sup>(1)</sup> | SFH6286-3T <sup>(1)</sup> | SFH6286-4T <sup>(1)</sup> |
| <b>VDE, UL, BSI</b>      | <b>63 to 200</b>          | <b>100 to 320</b> | <b>160 to 500</b> | <b>63 to 200</b>          | <b>100 to 320</b>         | <b>160 to 500</b>         |
| DIP-4                    | -                         | SFH628A-3X001     | -                 | -                         | -                         | -                         |
| DIP-4, 400 mil, option 6 | SFH628A-2X016             | SFH628A-3X016     | SFH628A-4X016     | -                         | -                         | -                         |
| SMD-4, option 7          | -                         | SFH628A-3X017T    | -                 | -                         | -                         | -                         |
| SMD-4, option 8          | SFH628A-2X018             | -                 | -                 | -                         | -                         | -                         |
| SMD-4, option 9          | -                         | -                 | -                 | SFH6286-2X001T            | SFH6286-3X001T            | SFH6286-4X001             |

## Note

- Additional options may be possible, please contact sales office.
- <sup>(1)</sup> Also available in tubes; do not add T to end.

Vishay Semiconductors Optocoupler, Phototransistor Output,  
AC Input, Low Input Current

| <b>ABSOLUTE MAXIMUM RATINGS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                |            |                |                    |
|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|------------|----------------|--------------------|
| PARAMETER                                                                                              | TEST CONDITION                                                 | SYMBOL     | VALUE          | UNIT               |
| <b>INPUT</b>                                                                                           |                                                                |            |                |                    |
| DC forward current                                                                                     |                                                                | $I_F$      | $\pm 50$       | mA                 |
| Surge forward current                                                                                  | $t \leq 10\text{ }\mu\text{s}$                                 | $I_{FSM}$  | $\pm 2.5$      | A                  |
| Power dissipation                                                                                      |                                                                | $P_{diss}$ | 76             | mW                 |
| <b>OUTPUT</b>                                                                                          |                                                                |            |                |                    |
| Collector emitter voltage                                                                              |                                                                | $V_{CE}$   | 55             | V                  |
| Emitter collector voltage                                                                              |                                                                | $V_{EC}$   | 7              | V                  |
| Collector current                                                                                      |                                                                | $I_C$      | 50             | mA                 |
|                                                                                                        | $t_p \leq 1\text{ ms}$                                         | $I_C$      | 100            | mA                 |
| Power dissipation                                                                                      |                                                                | $P_{diss}$ | 150            | mW                 |
| <b>COUPLER</b>                                                                                         |                                                                |            |                |                    |
| Isolation test voltage                                                                                 |                                                                | $V_{ISO}$  | 5300           | $V_{RMS}$          |
| Creepage distance                                                                                      |                                                                |            | $\geq 7$       | mm                 |
| Clearance distance                                                                                     |                                                                |            | $\geq 7$       | mm                 |
| Insulation thickness between                                                                           |                                                                |            | $\geq 0.4$     | mm                 |
| Comparative tracking index per DIN IEC112/                                                             |                                                                |            | 175            |                    |
| Isolation resistance                                                                                   | $V_{IO} = 500\text{ V}, T_{amb} = 25\text{ }^{\circ}\text{C}$  | $R_{IO}$   | $\geq 10^{12}$ | $\Omega$           |
|                                                                                                        | $V_{IO} = 500\text{ V}, T_{amb} = 100\text{ }^{\circ}\text{C}$ | $R_{IO}$   | $\geq 10^{11}$ | $\Omega$           |
| Storage temperature range                                                                              |                                                                | $T_{stg}$  | - 55 to + 150  | $^{\circ}\text{C}$ |
| Ambient temperature range                                                                              |                                                                | $T_{amb}$  | - 55 to +100   | $^{\circ}\text{C}$ |
| Soldering temperature <sup>(1)</sup>                                                                   | max. 10 s, dip soldering distance                              | $T_{sld}$  | 260            | $^{\circ}\text{C}$ |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

<sup>(1)</sup> Refer to reflow profile for soldering conditions for surface mounted devices (SMD). Refer to wave profile for soldering conditions for through hole devices (DIP).


| <b>ELECTRICAL CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                               |           |             |      |      |      |      |
|----------------------------------------------------------------------------------------------------------|-----------------------------------------------|-----------|-------------|------|------|------|------|
| PARAMETER                                                                                                | TEST CONDITION                                | PART      | SYMBOL      | MIN. | TYP. | MAX. | UNIT |
| <b>INPUT</b>                                                                                             |                                               |           |             |      |      |      |      |
| Forward voltage                                                                                          | $I_F = \pm 5\text{ mA}$                       |           | $V_F$       |      | 1.1  | 1.5  | V    |
| Capacitance                                                                                              | $V_R = 0\text{ V}, f = 1\text{ MHz}$          |           | $C_O$       |      | 45   |      | pF   |
| Thermal resistance                                                                                       |                                               |           | $R_{thja}$  |      | 1070 |      | K/W  |
| <b>OUTPUT</b>                                                                                            |                                               |           |             |      |      |      |      |
| Collector emitter leakage current                                                                        | $V_{CE} = 10\text{ V}$                        |           | $I_{CEO}$   |      | 10   | 200  | nA   |
| Collector emitter capacitance                                                                            | $V_{CE} = 5\text{ V}, f = 1\text{ MHz}$       |           | $C_{CE}$    |      | 7    |      | pF   |
| Thermal resistance                                                                                       |                                               |           | $R_{thja}$  |      | 500  |      | K/W  |
| <b>COUPLER</b>                                                                                           |                                               |           |             |      |      |      |      |
| Collector emitter saturation voltage                                                                     | $I_F = \pm 1\text{ mA}, I_C = 0.5\text{ mA}$  | SFH628A-2 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |
|                                                                                                          |                                               | SFH6286-2 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |
|                                                                                                          | $I_F = \pm 1\text{ mA}, I_C = 0.8\text{ mA}$  | SFH628A-3 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |
|                                                                                                          |                                               | SFH6286-3 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |
|                                                                                                          | $I_F = \pm 1\text{ mA}, I_C = 1.25\text{ mA}$ | SFH628A-4 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |
|                                                                                                          |                                               | SFH6286-4 | $V_{CEsat}$ |      | 0.25 | 0.4  | V    |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.


| <b>CURRENT TRANSFER RATIO</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                     |           |        |      |      |      |      |
|------------------------------------------------------------------------------------------------------|-----------------------------------------------------|-----------|--------|------|------|------|------|
| PARAMETER                                                                                            | TEST CONDITION                                      | PART      | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| $I_C/I_F$                                                                                            | $I_F = \pm 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH628A-2 | CTR    | 63   |      | 200  | %    |
|                                                                                                      |                                                     | SFH6286-2 | CTR    | 63   |      | 200  | %    |
|                                                                                                      | $I_F = \pm 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH628A-2 | CTR    | 32   | 100  |      | %    |
|                                                                                                      |                                                     | SFH6286-2 | CTR    | 32   | 100  |      | %    |
|                                                                                                      | $I_F = \pm 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH628A-3 | CTR    | 100  |      | 320  | %    |
|                                                                                                      |                                                     | SFH6286-3 | CTR    | 100  |      | 320  | %    |
|                                                                                                      | $I_F = \pm 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH628A-3 | CTR    | 50   | 160  |      | %    |
|                                                                                                      |                                                     | SFH6286-3 | CTR    | 50   | 160  |      | %    |
|                                                                                                      | $I_F = \pm 1\text{ mA}$ , $V_{CE} = 0.5\text{ V}$   | SFH628A-4 | CTR    | 160  |      | 500  | %    |
|                                                                                                      |                                                     | SFH6286-4 | CTR    | 160  |      | 500  | %    |
|                                                                                                      | $I_F = \pm 0.5\text{ mA}$ , $V_{CE} = 1.5\text{ V}$ | SFH628A-4 | CTR    | 80   | 250  |      | %    |
|                                                                                                      |                                                     | SFH6286-4 | CTR    | 80   | 250  |      | %    |

| <b>SWITCHING CHARACTERISTICS</b> ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                                                         |           |      |      |      |               |
|---------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|-----------|------|------|------|---------------|
| PARAMETER                                                                                               | TEST CONDITION                                                          | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
| Turn-on time                                                                                            | $V_{CC} = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ | $t_{on}$  |      |      | 6    | $\mu\text{s}$ |
| Rise time                                                                                               | $V_{CC} = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ | $t_r$     |      |      | 3.5  | $\mu\text{s}$ |
| Turn-off time                                                                                           | $V_{CC} = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ | $t_{off}$ |      |      | 5.5  | $\mu\text{s}$ |
| Fall time                                                                                               | $V_{CC} = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ | $t_f$     |      |      | 5    | $\mu\text{s}$ |



isfh618a\_11

Fig. 1 - Test Circuit



isfh618a\_12

Fig. 2 - Test Circuit and Waveforms

| <b>SAFETY AND INSULATION RATINGS</b>                 |                        |        |       |           |      |                    |
|------------------------------------------------------|------------------------|--------|-------|-----------|------|--------------------|
| PARAMETER                                            | TEST CONDITION         | SYMBOL | MIN.  | TYP.      | MAX. | UNIT               |
| Climatic classification (according to IEC 68 part 1) |                        |        |       | 55/100/21 |      |                    |
| Comparative tracking index                           |                        | CTI    | 175   |           | 399  |                    |
| $V_{IOTM}$                                           |                        |        | 10000 |           |      | V                  |
| $V_{IORM}$                                           |                        |        | 890   |           |      | V                  |
| $P_{SO}$                                             |                        |        |       |           | 400  | mW                 |
| $I_{SI}$                                             |                        |        |       |           | 275  | mA                 |
| $T_{SI}$                                             |                        |        |       |           | 175  | $^{\circ}\text{C}$ |
| Creepage distance                                    | Standard DIP-8         |        | 7     |           |      | mm                 |
| Clearance distance                                   | Standard DIP-8         |        | 7     |           |      | mm                 |
| Creepage distance                                    | 400 mil DIP-8          |        | 8     |           |      | mm                 |
| Clearance distance                                   | 400 mil DIP-8          |        | 8     |           |      | mm                 |
| Insulation thickness, reinforced rated               | per IEC 60950 2.10.5.1 |        | 0.4   |           |      | mm                 |

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.1, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

## TYPICAL CHARACTERISTICS ( $T_{amb} = 25^\circ\text{C}$ , unless otherwise specified)




Fig. 3 - Current Transfer Ratio (typ.)




Fig. 6 - Diode Forward Voltage (typ.)




Fig. 4 - Current Transfer Ratio (typ.)




Fig. 7 - Transistor Capacitance




Fig. 5 - Diode Forward Voltage (typ.)




Fig. 8 - Output Characteristics




Fig. 9 - Permissible Forward Current Diode




Fig. 11 - Switching Times (Typ.)






Fig. 10 - Permissible Power Dissipation

### PACKAGE DIMENSIONS in millimeters




# SFH628A, SFH6286

Vishay Semiconductors Optocoupler, Phototransistor Output,  
AC Input, Low Input Current



## PACKAGE MARKING



## Notes

- Only options 1, 7 and 8 are reflected in the package marking.
- The VDE Logo is only marked on option1 parts.
- Tape and reel suffix (T) is not part of the package marking.



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331