

		REVISIONS			
REV	DESCRIPTION		DATE	APPROVED	
--	REVISED PER ECN 99-0001		5/13/99	S. Moody	

NOTES

1. CONNECTOR CENTERLINES SHALL BE 180° ± 30° APART AS SHOWN.

<u>ELECTRICAL</u> Frequency DC - 6 GHz Nominal Impedance 50 ohms Voltage Rating 250 Volts (VRMS Max.) @ Sea Level VSWR 1.20:1 Max. @ 2GHz 1.40:1 Max. @ 6GHz Insulation Resistance 1000 Megohms Minimum Dielectric Withstanding Voltage 500 Volts (VRMS Minimum) @ Sea Level <u>MECHANICAL</u> Connector Durability 100 mating cycles <u>ENVIRONMENTAL</u> Temperature Rating -40°C (-40°F) To +105°C (221°F)		<table><tr><td>OUTER CONTACT</td><td>BERYLLIUM COPPER</td><td>GOLD PLATE OVER NICKEL PLATE</td></tr><tr><td>CENTER CONTACT</td><td>BERYLLIUM COPPER</td><td>GOLD PLATE OVER NICKEL PLATE</td></tr><tr><td>DIELECTRIC</td><td>POLYPROPYLENE, GF</td><td>N/A</td></tr><tr><td>CABLE JACKET</td><td>POLYVINYLCHLORIDE</td><td>N/A</td></tr><tr><td>SHIELD</td><td>TINNED COPPER WIRE, 38 AWG</td><td>N/A</td></tr><tr><td>DIELECTRIC</td><td>FLUORINATED ETHYLENE PROPYLENE (FEP)</td><td>N/A</td></tr><tr><td>CENTER CONDUCTOR</td><td>TINNED COPPER CLAD STEEL</td><td>N/A</td></tr><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON</td></tr><tr><td>FRAC</td><td>DEC</td><td>ANGLES</td></tr><tr><td>± 1/64</td><td>± 0.13</td><td>± 1°</td></tr><tr><td colspan="3">These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td></tr><tr><td colspan="3">DRAWN BY <i>BB</i> DATE 08/10/92</td></tr><tr><td colspan="3">CHECKED BY</td></tr><tr><td colspan="3">APPROVED BY <i>PR</i> DATE 08/14/92</td></tr><tr><td colspan="3">USE ASSY PROCEDURE</td></tr><tr><td colspan="3">NO. A.P. <u>N/A</u></td></tr><tr><td colspan="3">TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td>9950-3100-23</td></tr><tr><td>SCALE 10:1</td><td colspan="2">REV 018</td></tr><tr><td colspan="3">SHEET 1 OF 1</td></tr></table>	OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE	CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE	DIELECTRIC	POLYPROPYLENE, GF	N/A	CABLE JACKET	POLYVINYLCHLORIDE	N/A	SHIELD	TINNED COPPER WIRE, 38 AWG	N/A	DIELECTRIC	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A	CENTER CONDUCTOR	TINNED COPPER CLAD STEEL	N/A	COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON			FRAC	DEC	ANGLES	± 1/64	± 0.13	± 1°	These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			DRAWN BY <i>BB</i> DATE 08/10/92			CHECKED BY			APPROVED BY <i>PR</i> DATE 08/14/92			USE ASSY PROCEDURE			NO. A.P. <u>N/A</u>			TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)			SIZE B	CODE IDENT NO. 26805	9950-3100-23	SCALE 10:1	REV 018		SHEET 1 OF 1		
OUTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE																																																															
CENTER CONTACT	BERYLLIUM COPPER	GOLD PLATE OVER NICKEL PLATE																																																															
DIELECTRIC	POLYPROPYLENE, GF	N/A																																																															
CABLE JACKET	POLYVINYLCHLORIDE	N/A																																																															
SHIELD	TINNED COPPER WIRE, 38 AWG	N/A																																																															
DIELECTRIC	FLUORINATED ETHYLENE PROPYLENE (FEP)	N/A																																																															
CENTER CONDUCTOR	TINNED COPPER CLAD STEEL	N/A																																																															
COMPONENT	MATERIAL	FINISH																																																															
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM TOLERANCE ON																																																																	
FRAC	DEC	ANGLES																																																															
± 1/64	± 0.13	± 1°																																																															
These drawings and specifications are the property of AMP Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.																																																																	
DRAWN BY <i>BB</i> DATE 08/10/92																																																																	
CHECKED BY																																																																	
APPROVED BY <i>PR</i> DATE 08/14/92																																																																	
USE ASSY PROCEDURE																																																																	
NO. A.P. <u>N/A</u>																																																																	
TITLE OSMT RIGHT ANGLE JACK TO JACK CABLE ASSEMBLY (180° OFFSET)																																																																	
SIZE B	CODE IDENT NO. 26805	9950-3100-23																																																															
SCALE 10:1	REV 018																																																																
SHEET 1 OF 1																																																																	



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331