

10119191 - X0E - XXXLF

8-COLUMN
DIFFERENTIAL
SIGNAL

LEAD-FREE DESIGNATION
ONLY WITH APPLICABLE
PLATING CODES

LETTER	PERFORMANCE-BASED PLATING (SEE NOTE 2)	
	TARGET APPLICATION	LEAD-FREE (LF)
B	TELCORDIA CO	NO
C	TELCORDIA UE	NO
D	TELCORDIA CO	YES
E	TELCORDIA UE	YES

NUMBER	GUIDE PIN STYLE, HEIGHT
0	STANDARD GUIDE PIN MACHINED, 31.6mm
4	STANDARD GUIDE PIN MACHINED, 25.7mm

MODULE DESCRIPTION	LETTER DESIGNATION REPRESENTED IN DASH NUMBER										BASE MODULE
LEFT POLARIZING GUIDANCE MODULE (SEE SHEET 3)	J	A	B	C	D	E	F	G	H		
RIGHT POLARIZING GUIDANCE MODULE (SEE SHEET 4)	Y	P	Q	R	S	T	U	V	W		
OPEN MODULE (TWO WALL) (SEE SHEET 2)	0 (ZERO)										
LEFT WALL MODULE (SEE SHEET 5)	L										
RIGHT WALL MODULE (SEE SHEET 6)	M										
FOUR WALL MODULE (SEE SHEET 7)	I (ONE)										

NUMBER	CONTACT MATING WIPE LENGTH		COMPLIANT PIN DRILL SIZE
	SIGNAL	GROUND	
1	2	4	Ø0.55 [0.0217"]
2	3	4	Ø0.55 [0.0217"]
3	2	4	Ø0.45 [0.0177"]
4	3	4	Ø0.45 [0.0177"]
5	2	3	Ø0.55 [0.0217"]
6	3	3	Ø0.55 [0.0217"]
7	2	3	Ø0.45 [0.0177"]
8	3	3	Ø0.45 [0.0177"]

TABLE 1: OPTIONAL PCB HOLE SIZE (SEE NOTE 11)







	GROUNDED	UNGROUNDED
FINISHED	Ø2.35-2.55	Ø2.35-2.55
PAD	Ø5.50	N/A
PLATED	YES	NO
DRILL (mm/in)	2.58/.1015	2.44/.096

TABLE 2: OPTIONAL SCREW TYPE (SEE NOTE 10)

SCREW P/N	DESCRIPTION	BOARD THICKNESS
10091790-002LF	#2.56 X .375" PHILIPS PANHEAD W/SQ CONICAL WASHER	1.60 - 5.00
10091790-003LF	#2.56 X .500" PHILIPS PANHEAD W/SQ CONICAL WASHER	5.00 - 10.00







spec ref		-		dr		Roger Ng		2011/11/22		projection		MM		size		A2		scale		4:1	
tolerance std		-		eng		Michael Song		2016/06/01						ecn no		ELX-DG-24191-1					
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Heaven Cen		2016/06/08						rel level		Released					
				appr		Pei-Ming Zheng		2016/06/15						product family		XCEDE					
surface		linear		0.X		±0.2		Amphenol FCI		title		MODULE ASSEMBLY		dwg no		10119191		rev		C	
		0.XX		±0.10																	
		0.XXX		±0.050																	
ASME Y14.5		angular		0°		±2°				cat. no.		-		Product - Customer Drw		sheet 1 of 8					

OPEN (2- WALL) MODULE







spec ref		-		dr		Roger Ng		2011/11/22		projection				MM		size		A2		scale		4:1	
tolerance std		-		eng		Michael Song		2016/06/01						ecn no		ELX-DG-24191-1		rel level		Released			
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Heaven Cen		2016/06/08								product family				XCED			
				appr		Pei-Ming Zheng		2016/06/15															
surface		linear		0.X		±0.2		Amphenol FCi		title		MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR		dwg no		10119191		rev		C			
		0.XX		±0.10																			
		0.XXX		±0.050																			
ASME Y14.5		angular		0°		±2°		cat. no.		-		Product - Customer Drw		sheet 2 of 8									

LEFT POLARIZING/GUIDE MODULE



ASSEMBLY BASE CONFIGURATION END DASH NO.	GUIDE PIN	POLARIZING KEY
	DIM 'R'	DIM 'S'
-X0X	31.6mm	22.8mm
-X4X	25.7mm	20.0mm

spec ref		-		dr		Roger Ng		2011/11/22		projection		MM		size		A2		scale		5:1	
tolerance std		-		eng		Michael Song		2016/06/01						ecn no		ELX-DG-24191-1		rel level		Released	
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Heaven Cen		2016/06/08													
				appr		Pei-Ming Zheng		2016/06/15		product family		XCED									
surface		linear		0.X		±0.2		Amphenol FCI		title		MODULE ASSEMBLY		dwg no		10119191		rev		C	
				0.XX		±0.10															
				0.XXX		±0.050															
ASME Y14.5		angular		0°		±2°				cat. no.		-		Product - Customer Drw						sheet 3 of 8	





```

5.2 (3MM SMALL END GROUNDS) -
5.2 (3MM WIPE SIGNALS)
4.2 (2MM WIPE SIGNALS)
SEE P/N TREE

```

6.2 (4MM WIPE WIDE GROUNDS)
5.2 (3MM WIPE WIDE GROUNDS)




PCB HOLE PATTERN
COMPONENT SIDE
SCALE 6:1

ASSEMBLY BASE CONFIGURATION END DASH NO.	GUIDE PIN	POLARIZING KEY
	DIM 'R'	DIM 'S'
-X0X	31.6mm	22.8mm
-X4X	25.7mm	20.0mm






TAIL LENGTH
SEE NOTE 12

spec ref		-		dr		Roger Ng		2011/11/22		projection		MM		size		A2		scale		4:1	
tolerance std		-		eng		Michael Song		2016/06/01						ecn no		ELX-DG-24191-1					
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Heaven Cen		2016/06/08								rel level		Released			
				appr		Pei-Ming Zheng		2016/06/15		product family		XCEDE									
surface		linear		0.X		±0.2		Amphenol FCI		title		MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR		dwg no		10119191		rev		C	
				0.XXX		±0.10															
ASME Y14.5		angular		0°		±0.050															
										cat. no.		-		Product - Customer Drw				sheet 4 of 8			

RIGHT WALL MODULE



SEE NOTE 8









spec ref		-		dr		Roger Ng		2011/11/22		projection						size		A2		scale		4:1	
tolerance std		-		eng		Michael Song		2016/06/01						ecn no		ELX-DG-24191-1							
ASME Y14.5		TOLERANCES UNLESS OTHERWISE SPECIFIED		chr		Heaven Cen		2016/06/08						rel level		Released							
				appr		Pei-Ming Zheng		2016/06/15						product family		XCEDE							
surface		linear		0.X		±0.2				title		MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR		dwg no		10119191		rev		C			
		0.XX		±0.10																			
		0.XXX		±0.050																			
ASME Y14.5		angular		0°		±2°		cat. no.		-		Product - Customer Drw		sheet 6 of 8									

PDS: Rev :C

STATUS:Released

Printed: Jun 15, 2016

FOUR WALL MODULE



5.2 (3MM SMALL END GROUNDS)
5.2 (3MM WIPE SIGNALS)
4.2 (2MM WIPE SIGNALS)
SEE P/N TREE
6.2 (4MM WIPE WIDE GROUNDS)
5.2 (3MM WIPE WIDE GROUNDS)

spec ref	-	dr	Roger Ng	2011/11/22	projection	MM	size	A2	scale	4:1
tolerance std	-	eng	Michael Song	2016/06/01		←	ecn no	ELX-DG-24191-1	rel level	Released
ASME Y14.5	TOLERANCES UNLESS OTHERWISE SPECIFIED	chr	Heaven Cen	2016/06/08						
		appr	Pei-Ming Zheng	2016/06/15						
surface	linear	0.X	±0.2	Amphenol FCI	title	MODULE ASSEMBLY	cat. no.	Product - Customer Drw	sheet 7 of 8	rev
		0.XX	±0.10							
		0.XXX	±0.050							
ASME Y14.5	angular	0°	±2°							

PDS: Rev :C

STATUS:Released

Printed: Jun 15, 2016

NOTES:

- CONNECTOR MATERIALS
SHROUD: HIGH-TEMP THERMOPLASTIC, GRAY, UL94V-0
CONTACTS: HIGH PERFORMANCE COPPER ALLOY
- CONTACT PLATING:

SEPARABLE INTERFACE: PERFORMANCE-BASED PLATING, QUALIFIED TO MEET THE REQUIREMENTS OF FCI PRODUCT SPECIFICATION GS-12 588, INCLUDING THE TELCORDIA GR-1217-CORE (NOVEMBER 1995) CENTRAL OFFICE (CO) OR UNCONTROLLED ENVIRONMENT (UE) TEST SEQUENCE AS NOTED IN P/N TREE.


PRESS-FIT TAILS: TIN OVER NICKEL (LF), OR TIN-LEAD ALLOY OVER NICKEL (NON-LF). SEE P/N TREE.
- PRODUCT SPECIFICATION: GS-12-588
- APPLCATION SPECIFICATION: GS-20-121
- PRODUCT MARKING (PART NUMBER AND LOT CODE) ON THESE SURFACES.
- HOUSING MUST WITHSAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 40 SECONDS IN A CONVECTION, INFRA-RED, OR VAPOR-PHASE REFLOW OVEN.
- PACKAGING MEETS GS-14-920 LEAD-FREE LABELING SPECIFICATION.
- NOTCH INDICATES "ROW A" SIDE OF CONNECTOR.
- SEE APPLICATION SPECIFICATION FOR ROUTING GUIDELINES, ADDITIONAL PTH GUIDELINES, MATED DIMENSIONS, GUIDE PN SELECTION, ETC.
- SCREW IS OPTIONAL AND ENGAGES WITH BOTTOM OF GUIDE-PIN FROM BENEATH THE PCB FOR ADDITIONAL GUIDE-PIN SUPPORT.
- OPTINAL HOLE LOCATION FOR GROUNDED PIN OR ADDITIONAL GUIDE-PIN SUPPORT. SEE TABLE 1 ON SHEET 1 FOR ADDITIONAL DETAILS.
- TAIL LENGTH=1.3mm FOR $\varnothing 0.55[0.0217"]$ COMPLIANT PIN DRILL
TAIL LENGTH=1.5mm FOR $\varnothing 0.45[0.0177"]$ COMPLIANT PIN DRILL

TABLE 3: PTH AND PAD SIZES WITH REFERENCE TO COMPLIANT PIN DRILL

COMPLIANT PIN DRILL	PTH	PAD
$\varnothing 0.55 [0.0217"]$	$\varnothing 0.45\pm 0.05$	$\varnothing 0.85$
$\varnothing 0.45 [0.0177"]$	$\varnothing 0.36\pm 0.05$	$\varnothing 0.75$

REFER TO TABLE 3
FOR PTH, DRILL & PAD SIZES

$\varnothing$	$\varnothing 0.10$	X_BP	Y_BP
---------------	--------------------	------	------



spec ref -				dr Roger Ng		2011/11/22		projection		MM		size A2		scale 3:1	
tolerance std -				eng Michael Song		2016/06/01						ecn no ELX-DG-24191-1		rel level Released	
ASME Y14.5				chr Heaven Cen		2016/06/08									
				appr Pei-Ming Zheng		2016/06/15									
								product family							
surface -				Amphenol FCI		title MODULE ASSEMBLY VERTICAL HEADER, 8-COLUMN, 3-PAIR		dwg no 10119191		rev C					
linear		0.X ±0.2													
		0.XX ±0.10													
ASME Y14.5		0.XXX ±0.050													
		angular 0° ±2°		cat. no. -		Product - Customer Drw						sheet 8 of 8			



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331