Series 803 Mighty Mouse ¼ Turn Bayonet Plug



803-001 and 803-002 Ordering Information



Series 803 compact size and rugged design make them suitable for light-to-medium duty applications where water immersion is not a consideration. Splashproof design withstands exposure to rain and condensation. Bayonet coupling mechanism uses a rotating coupling nut on the plug and three integral bayonet pins on the receptacle. Push to mate, then rotate the coupling nut 90º to lock. Connector shells are machined aluminum or stainless steel. Supplied with crimp contacts, packaged separately. Terminate contacts with standard M22520 tools. Metal clips inside the connector body lock contact into place. Contacts are removable. Fluorosilicone seals and rear grommet protect connector from water ingress. Terminate cable shield directly to connector body with Band-Master™ ATS strap, or choose rear accessory thread to attach optional cable clamp or backshell. Available in shell sizes 5 through 14 in 46 contact arrangements.

How To Order						
Sample Part Number	**803-001**	**-06**	**NF**	**9-19**	**P**	**N**
Series (See Table I)	**803-001** = Plug with Banding Platform **803-002** = Plug with Accessory Thread					
Shell Style	**-06** = Plug					
Shell Material and Finish	**C** = Aluminum / Black Anodize (Non-Conductive); RoHS Compliant **M** = Aluminum / Electroless Nickel; RoHS Compliant **MT** = Aluminum / Nickel-PTFE RoHS Compliant **NF** = Aluminum / Cadmium with Olive Drab Chromate **ZN** = Aluminum / Zinc-Nickel with Olive Drab Chromate **ZNU** = Aluminum / Zinc-Nickel with Black Chromate **Z1** = Stainless Steel / Passivated; RoHS Compliant **UCR** = Aluminum / Zinc-Cobalt with Black Chromate; RoHS Compliant					
Shell Size - Insert Arrangement	See Contact Arrangements Page F-2					
Contact Type	Connector supplied with contacts **P** = Pin **S** = Socket	Connector supplied without contacts **A** = Pin Connector, less contacts **B** = Socket Connector, less contacts				
	Connectors with contacts are supplied with signal and/or power crimp contacts. These contacts are not installed.					
	Coaxial contacts and non-standard signal contacts are ordered separately.					
Shell Key Positions (See Table II)	**N** = Normal **X** = Pos. X **Y** = Pos. y **Z** = Pos. Z					

Table I: Series

	
803-001 Plug with Banding Platform	**803-002** Plug with Accessory Thread

Dimensions in Inches (millimeters) are subject to change without notice.

© 2014 Glenair, Inc.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331