

WHITE-RODGERS DC PRODUCTS

Type 70 and 71 contactors

FEATURES

- High current capacity control
- Isolated or grounded coils
- Enclosed in dust-resistant case
- Longer steel encasement permits lower heat rise and more sensitive operation on Type 71

ENGINEERING DATA

Contacts

- Pole form— SPNO, SPDT
- Material— SPNO-copper or silver
SPDT-copper and silver or all silver
- Termination— $\frac{5}{16}$ "-24 UNF-2A thread

RATINGS					
Type	Volts DC	NO		NC	
		Cont.	Inrush	Cont.	Inrush
70	6	80A	300 A	60A	100 A
	12	80 A	150 A	60 A	60 A
	24 & 36	50 A	50 A	30 A	30 A
71	6	80A	300 A	60A	100 A
	12	80 A	150 A	60 A	60 A
	24 & 36	50 A	50 A	30 A	30 A

Coils

- Voltage—6 VDC through 36 VDC
- Termination—#10-32 UNF-2A thread
- Power (approximate)
 - Type 70 intermittent 23 watts
 - Type 70 continuous 9 watts
 - Type 71 intermittent 25 watts
 - Type 71 continuous 10 watts
- Connections
 1. Two coil terminals isolated from case
 2. One coil terminal with ground wire, one coil terminal isolated from case
 3. One coil lead common to NO terminal marked "BAT" (one terminal)
- Operate (77°F/25°C)
 - 75% of nominal coil voltage; 110% max. safe of nominal coil voltage



GENERAL DATA

Dielectric Strength

- 500 Volts

Temperature Range

- -40°F/-40°C to 122°F/50°C

Mechanical Life (no load)

- 250,000 operations

Electrical Life (rated load)

- 100,000 operations

Mounting Position

- Recommended mounting with cap down

Vibration

- 5 g's vertical and horizontal planes

Weight (approximate)

- Type 70—14.0 oz.
- Type 71—17.0 oz.

Duty Cycle

- Continuous
- Intermittent—10 seconds "on" maximum and minimum 60 seconds "off". One minute "on" maximum and minimum 6 minutes "off".

Hardware Torque Specification

- Contact Terminal: 45-55 inch-lbs.
- Coil Terminal: 12-18 inch-lbs.
- Mounting Bracket: 100 inch-lbs. max (a backup wrench must be used to hold the bottom nut stationary during installation)

COIL DATA					
TYPE 70			TYPE 71		
Volts DC	Resistance (Ohms)		Volts DC	Resistance (Ohms)	
	Int.	Cont.		Int.	Cont.
6	1.5	4.0	6	1.4	3.5
12	6.2	16.0	12	4.9	13.5
18	16.0	37.4	18	13.46	36.0
24	23.9	60.4	24	20.1	57.1
36	60.4	114.0	36	57.1	131.0

TYPE 70/71 PART NUMBERING SYSTEM

7x - x xx x x x - x

Basic Part Number Series
Type 71 case is approx. 0.29" longer than Type 70

Contact Form
1 – SPNO
3 – SPDT

Coil Voltage/Duty
08 – 6 Volt continuous
09 – 6 Volt intermittent
11 – 12 Volt continuous
12 – 12 Volt intermittent
14 – 18 Volt continuous
15 – 18 Volt intermittent
17 – 24 Volt continuous
18 – 24 Volt intermittent
20 – 36 Volt continuous
21 – 36 Volt intermittent

**Coil Termination
(15 in-lb torque spec.)**
221 – Isolated coil, all Ag contacts
222 – Coil terminal with ground wire, all Ag contacts
224 – Isolated coil, Cu NO and Ag NC contacts
225 – Coil terminal with ground wire, Cu NO and Ag NC contacts
226 – Coil common to NO (stud marked "BAT"), Cu NO and Ag NC contacts


**Factory Assigned Specials
(where undefined, contact factory)**
2 – Hardware loosely assembled
2B – Customer requested markings
2C – Customer requested markings
3 – Customer requested markings
4 – Customer requested markings
5 – Hardware bulk packed
5C – Customer requested markings
5F – Customer requested markings
7 – No hardware included

Not all part number combinations are released. Please contact your Sales Representative for a list of active part numbers.


APPLICATION NOTES

- A back-up wrench **MUST** be used to hold the bottom nut stationary during installation.
- Solenoids applied in battery charging circuits should be protected from higher than rated voltage during charging. The service life may be affected by this condition and the solenoid may or may not operate the circuit as intended.
- Circuits should be designed to provide safe operation should the solenoid fail in either the open or closed position.
- Special construction options, including a curved bracket, may be available under other part numbers, including 111-xxxD (short can), 111-xxxE (long can), 5608-x and 878x-x.


SPNO – Isolated Coil




Coil Terminal to Ground



Coil Common to Load



SPDT – Isolated Coil





**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331