# multimec®

## Cap solution for navigating

navimec™ 5G + 1ZB/1ZCS

- Round solution
- Designed for navigating a display or controlling a unit
- 90° R=17.5 mm; Ø14.3 mm (Ø34.25 mm)
- h =12.2 mm; 11.7 mm
- Material: ABS/polycarbonate
- Temp. Range:
  - Solid cap: -40/+65°C
  - Transparent cap: -40/+85°C
- Panel cut-out: 1ZB-$R_1$ 7,1 $R_2$ 17,5 – 17,75 90° 1ZCS-Ø14.7
- navimec™ panel cut-out: Ø35,0 - 35,5 Depending on application

*All dimensions in mm* *Tolerances -/+0.2mm*



### DIMENSIONS

TH + 1ZB




SMD w/LED + 1ZCS




PCB layout for Navimec solution




We recommend using through-hole terminals for precise placing.

### ILLUMINATED – HOW TO ORDER

**Switch** [5][G]

**Mounting** [ ][ ][ ]

**TH9** through-hole
(**SH9** surface mount)

**Actuation force** [ ][ ]

**20**
**35**
**65**
**Q***

**LED** [ ][ ][ ][ ] +

**02** blue
**22** green
**42** yellow
**61** white
**82** red
**2242** green/yellow
**8222** red/green
**8242** red/yellow

**Cap** [1][Z][B][1][6]

Frosted white with black hard paint and laser marking

[1][Z][C][S][1][6]

**Legend code** [ ][ ][ ]

**DLMH136** ▲

[ ][ ][ ]

**LMH118** OK
**LMH123** ⏻

*For an illuminated quiet 2.0N switch add Q to the end of the switch part number.

### NON-ILLUMINATED– HOW TO ORDER

**Switch** [5][G]

**Mounting** [ ][ ][ ]

**TH9** through-hole
(**SH9** surface mount)

**Actuation force** [ ][ ][ ] +

**20**
**20Q**
**35**
**65**

**Cap** [1][Z][B]



[1][Z][C][S]

**Colour code** [ ][ ]

**03** grey
**06** white
**09** *black*
**30** ultra blue
**40** dusty blue
**42** aqua blue
**50** metal dark blue
**53** metal light grey
**57** metal dark grey
**58** metal bordeaux

**Legend code**** [ ][ ][ ]

**D136** ▲

pad printed legends

[ ][ ][ ]

**038** RESET
**105** ENTER
**118** OK
**119** SET
**120** MENU
**121** FUNC
**122** HOME
**123** ⏻

** White legends on black caps are standard, other options are available but considered custom products. See pages 34-35 or www.mec.dk

Ordering example: 4x 5GTH93561+1ZB16DLMH13609 + 1x 5GTH93561+1ZCS16LMH12309 (with illumination) OR 4x 5GSH920+1ZB09 + 1x 5GSH920+1ZCS09 (without illumination) OR *5GTH92002Q (Illuminated quiet version)

*Please see colour codes, updates of products and changes of specifications on www.mec.dk*

# Legends

Avaliable for Multimec caps



| LEGEND | 1B09U_ 1B09D_ | 1DS09_ | 1FS096R_ | 1ZB09D_ 1ZB16DLMH_ | 1ZCS_ | 10R_ & 10RF_ 10RM16_ | 10Q_ 10QM16_ |
|---|---|---|---|---|---|---|---|
| **0** | 000 | 000 | 000 | | | | |
| **1** | 001 | 001 | 001 | | | | |
| **2** | 002 | 002 | 002 | | | | |
| **3** | 003 | 003 | 003 | | | | |
| **4** | 004 | 004 | 004 | | | | |
| **5** | 005 | 005 | 005 | | | | |
| **6** | 006 | 006 | 006 | | | | |
| **7** | 007 | 007 | 007 | | | | |
| **8** | 008 | 008 | 008 | | | | |
| **9** | 009 | 009 | 009 | | | | |
| # | | 107 | 107 | | | | |
| ✱ | | 019 | 019 | | | | |
| → | | 033 | | | | | |
| ← | | 133 | | | | | |
| ↑ | | 034 | | | | | |
| ↓ | | 134 | | | | | |
| ↵ | | 135 | 135 | | | | |
| + | | | | | | 054 | 054 |
| - | | | | | | 059 | 059 |
| ▲ | | | | 136* | | | |
| ⏻ | | 123 | 123 | | 123* | 123 | 123 |
| **ON/OFF** | | | | | | 017 | 017 |
| **STOP** | | | | | | 018 | 018 |
| **START** | | | | | | 031 | 031 |
| **RESET** | | | | | 038 | 038 | 038 |
| **CANCEL** | | | | | | 048 | 048 |
| **ENTER** | | | | | 105 | 105 | 105 |
| **ESC** | | | | | 051 | | |
| **OK** | | | | | 118* | 118 | 118 |
| **SET** | | | | | 119 | | |
| **MENU** | | | | | 120 | | |
| **FUNC** | | | | | 121 | | |
| **HOME** | | | | | 122 | | |

STANDARD OPTIONS

1B
pad printed

1DS
pad printed

1FS
reverse printed

1ZB
pad printed
*laser marked

1ZCS
pad printed
*reverse printed
*laser marked

10R(F) & 10Q_
pad printed
reverse printed

10RM & 10QM
metal symbol

Ordering example: 1FS096R12309; 1ZB09D13606; 1ZCS16LMH11809
Please see colour codes, updates of products and changes of specifications on www.mec.dk

# Legends

Avaliable for Multimec caps






UP
1A09U01706




UP
1B09U01706

DOWN
1A09D01706




DOWN
1B09D01706



DOWN
1ZB09D13606

POSITIONING OF LEGENDS ON ROCKER-ACTION CAPS

When ordering legends for caps with hinge-type cap retention system, it is important to note the position of the cap. An extra letter (U or D) needs to be added to the part number to refer to the position of the hinges in relation to the legend. See samples to the left.

Rocker-action caps without a lens: 1A, 1B, 1M, 1ZA and 1ZB

Orientation of the switch:




## LEGEND ILLUMINATION

Option 1:LASER MARKED
In case of laser marked legends an "LM" is added after the cap colour, before the legend code. We recommend using hard paint (additional "H" ) for increased lifetime of the paint. E.g. 1ZB16DLMH13609

Option 2: REVERSE PRINTED
In case of reverse printed caps an "R" is added after the cap colour, before the legend code. Especially relevant when standard legends has both negative and positive print option. E.g. 1FS096R00009

Option 3: METAL SYMBOL
Only available for 10RM and 10QM (therefore the "M"). E.g. 10RM16059

## STANDARD AND CUSTOM LEGENDS - HOW TO ORDER

### STANDARD LEGENDS

- Standard are only certain legends on certain caps. See the table on the previous page.
- All standard pad-printed legends are white on black caps.
- All standard reverse-printed and laser marked legends are black on frosted white cap.

| Cap | Cap colour | Direction* | Type* | Legend | Legend colour* |
|---|---|---|---|---|---|
| **1B**<br>**1DS**<br>... etc | **00** blue<br>**02** green<br>**03** grey<br>**04** yellow<br>**06** white<br>**08** red<br>**09** black<br>**16** frosted white<br>... etc | **D** down<br>**U** up<br><br>*only for hinge-type caps | **LM** laser marked on soft paint<br>**LMH** laser marked on hard paint<br>**R** reverse printed<br><br>*in case of illumination | **001** 1<br>**002** 2<br>**003** 3<br>... etc | **00** blue<br>**02** green<br>**03** grey<br>**04** yellow<br>**06** white<br>**08** red<br>**09** black<br>... etc<br><br>*in case of laser marked legends the colour of the soft or hard paint |

## NOTE:

- The size of the legends listed may not correspond to the actual size.
- If you decide to use one of the standard legends without any adjustments (without a new cliché) on another cap than designated in the table, then there is no start-up cost, for this to apply the cap has to be black and the print white.
- Standard legend colours are white paint on a black cap and black paint on a frosted white cap. Other colour combinations are handled as custom.
- For further information on legends please contact your local distributor or MEC.

PLEASE FIND THE FULL LIST OF AVAILABLE LEGENDS ON MEC WEBSITE www.mec.dk

Ordering example: 1ZW0913611806; 1B06U13508; 10R16R10509
Please see colour codes, updates of products and changes of specifications on www.mec.dk

# multimec®

## Solid colours

| No. | 00 | 02 | 03 | 04 | 06 | 08 | 09 |
|---|---|---|---|---|---|---|---|
| Colour | blue | green | grey | yellow | white | red | black |
| RAL Code | 5012 | 6018 | 7004 | 1023 | 9010 | 3000 | 9004 |

| No. | 30 | 32 | 33 | 34 | 38 | 40 | 42 |
|---|---|---|---|---|---|---|---|
| Colour | ultra blue | mint green | tele grey | melon | noble red | dusty blue | aqua blue |
| RAL Code | 5002 | 6029 | 7046 | 1028 | 3002 | 5014 | 5021 |

## Metallic Colours

| No. | 50 | 53 | 57 | 58 |
|---|---|---|---|---|
| Colour | dark blue | light grey | dark grey | bordeaux |
| RAL Code | No Ral Code | No Ral Code | No Ral Code | No Ral Code |

| CAP \ CODE | | 00 | 02 | 03 | 04 | 06 | 08 | 09 | 30 | 32 | 33 | 34 | 38 | 40 | 42 | 50 | 53 | 57 | 58 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1A | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1B | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1C | | | | • | | | • | • | | | | | | | | | | | |
| 1DS | | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • | • |
| 1ES/1FS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1GAS/1GCS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1H | | | | • | | | | • | | | | | | | | | | | |
| 1JS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1KS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1M | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1NS | | | | • | | | | • | | | | | | | | | | | |
| 1PS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1QS/1RS | | • | | • | | | | • | | | | | | | | | | | |
| 1SS/1LS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1TS/1US/1VS | | • | | • | | | • | • | | | | | | | | | | | |
| 1WAS/1WDS/1WPS | | • | | • | | | • | • | • | | | | | • | • | | • | • | |
| 1XS | | • | • | • | • | • | • | • | | | | | | | | | | | |
| 1ZA | | | | • | | • | | • | • | | | | | • | • | • | • | • | • |
| 1ZB | | | | • | | • | | • | • | | | | | • | • | • | • | • | • |
| 1ZCS | | | | • | | • | • | • | • | | | | | • | • | • | • | • | • |
| 1Z/1ZW | | • | | • | | • | • | • | | | | | | | | | | | |
| 10R/10RF + 10Q | | • | • | • | • | • | • | • | | | | | | | | | | | |

The RAL Codes mentioned are the codes nearest to the solid colors in the multimec® range.

*For product updates and/or changes of specifications please see www.mec.dk*

- Module should be attached to the front plate with bolts (bolts not supplied by MEC)
- Round solution
- Ø34.25 mm
- h =11.7 mm; 12.2 mm
- Temp. Range:
  - Solid cap: -40/+65°C
  - Transparent cap: -40/+85°C
- Recommended panel cut-out: Ø35,0 - 35,5 Depending on application

*All dimensions in mm* *Tolerances -/+0.2mm*

## DIMENSIONS

Navimec Module










When the 1ZB is activated the diameter changes from 34,25 mm to 35,0 mm





## HOW TO ORDER

navimec™ Module ordering options:
- navimec™ Module excl. keycaps
- navimec™ Module incl. keycaps
- navimec™ Module incl. keycaps with legends
- Illuminated navimec™ Module excl. keycaps
- Illuminated navimec™ Module incl. keycaps with legends

Part no. for a module:
navimec™ Module has many customisation options regarding actuation force, cap and LED colours and legends. Because of that "How to order" has been placed on page 43.

See previous page for information on switch and cap options.

SEE THE "HOW TO ORDER" GRAPH AS WELL AS CIRCUIT DIAGRAM AND CONNECTOR INFO ON PAGE 43

Ordering example:
95NA200913611806 (without illumination)
95NB350116LMH13612309 (with illumination)
*Please see colour codes, updates of products and changes of specifications on www.mec.dk*

**Circuit diagram for switches**




**Circuit diagram for additional LEDs for controlmec™**




Connectors on the module are Molex picoflex series 90816-0320 for switches and 90816-0316 for additional LEDs.

We recommend using:

Cable socket: 90327-0320 for switches and 90327-0316 for additional LEDs

## HOW TO ORDER - MODULES

**Module**

**9 5**

**+**

**Cap**

**C** controlmec module
**N** navimec module
**Q** 10Q module
**R** 10R module

**+**

**Type**

**A** non-illuminated
**B** illuminated

Sealed controlmec module:

**C** non-illuminated
**D** illuminated

**+**

**Actuation force**

**20** 2.0N**
**35** 3.5N
**65** 6.5N

**+**

**LED***

**02** blue
**22** green
**42** yellow
**61** white
**82** red
**2242** green/yellow
**8222** red/green
**8242** red/yellow

**+**

**Cap colour**

**09** black
**16** frosted white

**+**

**Legend type***

**(nothing)** pad printed
**LMH** hard paint laser marked
**M** Metal

**+**

**Legend on the edges***

**136** ▲

**+**

**Legend in the centre***

**118** OK
**123** ⏻
****Find more options on mec.dk*

**+**

**Legend colour***

**06** white
**09** black

*optional, ** 2.0N actuation force not recommended for controlmec*

Ordering example:
95CB358216LMH13611809 - illuminated non-sealed controlmec
95CC650913612306 - non-illuminated panel sealed controlmec
95NB358216LMH13611809 - illuminated Navimec module
95QB200116M118 - illuminated 10Q module
95RA350912306 - non-illuminated 10R module
*Please see colour codes, updates of products and changes of specifications on www.mec.dk*

- Through-hole (TH) or surface mount (SMD)
- 50mA/24VDC
- Single pole/momentary
- 10,000,000 operations lifetime (NO function)
- Temperature range:
  - Switch: -40/+160°C
  - LED: -40/+85°C
- IP 67 sealing
- Actuation force: 2.0N, 3.5N, 6.5N
- NO or NC/NO

*All dimensions in mm* *Tolerances -/+0.2mm*

## THROUGH-HOLE (TH)

5G




5G illuminated




5E




## PCB LAYOUT

Non-illuminated




1 LED




2 LED




## SURFACE MOUNT (SMD)

5G




5G illuminated




5E




## PCB LAYOUT

Non-illuminated




1 LED




2 LED




## NORMALLY CLOSED/NORMALLY OPEN FUNCTION

**NOT FOR SALE IN JAPAN**

- Available for 5E and non-illuminated 5G in 3.5N actuation force.
- Same PCB layout as the NO 5E and 5G
- Housing colour is **grey**

## CIRCUIT DIAGRAM



## RIGHT ANGLE SWITCHES

5E




5G




5G + 1SS




5G + 1DS




## PCB LAYOUT




multimec® 5 series has only normally open (NO) non-illuminated right angle switch.

## ILLUMINATED – HOW TO ORDER

| Switch | Mounting | Actuation force | LED | | Quiet (optional) |
|---|---|---|---|---|---|
| 5 G | | | | | |
| | **TH9** through-hole | **20** | **02** blue | **82** red | **Q** |
| | **SH9** surface mount | **35** | **22** green | **2242** green/yellow | only for 2.0N |
| | | **65** | **42** yellow | **8222** red/green | |
| | | | **61** white | **8242** red/yellow | |

## NON-ILLUMINATED– HOW TO ORDER

| Switch | Mounting | Actuation force | RAS (optional) | | NC/NO (only for 3.5N) |
|---|---|---|---|---|---|
| 5 E | | | | **or** | |
| | **TH9** through-hole | **20** | **RAS** right angle switch | | **NCNO** normally closed/ normally open function |
| | **SH9** surface mount | **20Q** | | | |
| | | **35** | | | |
| | | **65** | | | |

| Switch | Mounting | Actuation force | RAS (optional) | | NC/NO (only for 3.5N) |
|---|---|---|---|---|---|
| 5 G | | | | **or** | |
| | **TH9** through-hole | **20** | **RAS** right angle switch | | **NCNO** normally closed/ normally open function |
| | **SH9** surface mount | **20Q** | | | |
| | | **35** | | | |
| | | **65** | | | |

Ordering example: 5ESH935 (non-illuminated), 5GTH9658222 (illuminated), 5GSH935NCNO (normally closed/normally open); 5ETH920RAS (right angle) 5ETH920Q or 5GSH92061Q (quiet versions)
*Please see colour codes, updates of products and changes of specifications on www.mec.dk*

### Basic switch spacing

through-hole (TH)




surface mount (SMD)




### Recommended switch/cap spacing

Switch spacing




Cap dimensions




Panel cut-out




### Panel cut-out

1NS 1VS




1TS




### Spacing examples

**multimec**
5GT+1B/C+2C/D




**multimec**
5GS+1B/C+2C/D




**multimec**
5GT + 1A/H




**multimec**
5GT + 1M




**multimec**
1NS + 1NS + 1NS




**multimec**
1VS + 1TS+ 1VS




| Cap series | Recommended min. switch spacing AxB | Nominal cap dimension WxH | Recommended min. panel cut-out |
|---|---|---|---|
| 1A/1H | 12.7x10.16 | 12.6x10.1 | 13.0x10.5 |
| 1B/1C+2C/2D | 15.24x15.24 | 15.1x15.1 | 15.5x15.5 |
| 1DS/1ES/1FS | 12.7x12.7 | ø9.6 | ø10.0 |
| 1GAS | 12.7x11.14 | ø11 | ø11.4 |
| 1GCS | 15.14x15.14 | ø15 | ø15.4 |
| 1JS | 12.7x12.7 | ø9.6 | ø10.4 |
| 1KS/1KBS/1KCS | 15.24x15.24 | 14.3x14.3 | 14.7x14.7 |
| 1M | 25.4x10.16 | 25.0x10. | 25.7x10.5 |
| 1NS | 12.7x12.7 | ø9.8/□4.9 | ø10.2/□5.1 |
| 1PS/1QS/1RS | 15.24x10.16 | 6.5x12.5 | 7.0x13.0, R max. 1.0 |
| 1SS/1IS/1LS | 12.7x12.7 | ø6.5 | ø7.0 |
| 1TS | 12.7x12.7 | 10.6x10.6 | 11.0x11.0 |
| 1US | 12.7x12.7 | ø10.6 | ø11.0 |
| 1VS | 12.7x12.7 | 10.6x13.25 | 11.0x13.65 |
| 1WAS/1WPS | 12.7x10.3 | 12.5x6.5 | 12.9x6.9 |
| 1WDS | 15.34x10.3 | 15.2x8.0 | 15.6x8.4 |
| 1XS | 12.7x12.7 | 9.4x7.4 | 9.8x7.9 |
| 1YS | 17x17 | 15x15 | 16x16 |
| 1ZA | 18.84x10.3 | 18.7x10.1 | 19.4x10.5 |
| 1ZB | 24.34x12.1 | R1=7.4; R2=17.5 90° | R1=7.1; R2=17.5-17.75 90° |
| 1ZCS | 14.44x14.44 | ø14.3 | ø14.7 |
| 1Z/1ZW | 35.5x35.5; 41.6x41.6 | ø29.5 | ø30.3 |
| 10R/10RF/10RM | 40.5x40.5 | ø30.0 | ø30.6 |
| 10Q/10QM | 32.5x32.5 | 22x22 | 22.5x22.5 |

## Tape & Reel

Tape and reel is available for the parts listed and has the following specifications:

| | | | |
|---|---|---|---|
| Reel diameter: | Ø330mm | Tape and reel material: | antistatic or better |
| Tape width: | 24mm | | |
| Pitch: | see list | Quantity per reel: | see list |

### 3C/3E/5E/5G multimec®tape & reel

| Part No. | Ordering Code | Pitch | Quantity per reel |
|---|---|---|---|
| 3CSH9 | 3CSH9R | 16 | 500 |
| 3ESH9 | 3ESH9R | 16 | 500 |
| 5ESH9XX | 5ESH9XXR | 16 | 500 |
| 5GSH9XX | 5GSH9XXR | 16 | 500 |
| 5XSH9XX1SSXX-08.0 | 5XSH9XXR1SSXX-08.0 | 20 | 250 |
| 5XSH9XX1SSXX-09.5 | 5XSH9XXR1SSXX-09.5 | 20 | 250 |
| 5XSH9XX1SSXX-10.4 | 5XSH9XXR1SSXX-10.4 | 20 | 250 |
| 5XSH9XX1SSXX-11.0 | 5XSH9XXR1SSXX-11.0 | 20 | 250 |
| 5XSH9XX1SSXX-12.0 | 5XSH9XXR1SSXX-12.0 | 20 | 250 |
| All varimec h <12.5; add R after part no. | | 20 | 250 |

### illuminated 5G multimec®tape & reel

| Part No. | Ordering Code | Pitch | Quantity per reel |
|---|---|---|---|
| 5GSH9XX02 | 5GSH9XX02R | 20 | 250 |
| 5GSH9XX22 | 5GSH9XX22R | 20 | 250 |
| 5GSH9XX42 | 5GSH9XX42R | 20 | 250 |
| 5GSH9XX61 | 5GSH9XX61R | 20 | 250 |
| 5GSH9XX82 | 5GSH9XX82R | 20 | 250 |
| 5GSH9XX2242 | 5GSH9XX2242R | 20 | 250 |
| 5GSH9XX8222 | 5GSH9XX8222R | 20 | 250 |
| 5GSH9XX8242 | 5GSH9XX8242R | 20 | 250 |

## How to assemble

**multimec®**
5GS+1A/H



**multimec®**
5GS+1B/C+2C/D



## Operating force

(typical example)




## Mounting tool for multimec® through-hole switches




Part No. 9861000

## RoHS Compatible

| | HIGH TEMPERATURE VERSIONS | | |
|---|---|---|---|
| | SILVER | GOLD | NC/NO |
| **ELECTRICAL SPECIFICATIONS** | | | |
| Contact resistance | <30m Ω - typ. 10m Ω | | |
| Insulation resistance | >10M Ω | | |
| Recommended load | 0.5-50mA 24VDC | 0.5µ-50mA 24VDC | |
| Contact bounce | <2mS - typically 0.5mS | | |
| **MECHANICAL SPECIFICATIONS** | | | |
| Standard actuation force (switch) | 2.0N, 3.5N, 6.5 N | | 3.5N |
| Max. Actuation force without cap | 115N for 60 sec (according to MIL-PRF-22885H) | | 100N for 10 sec |
| Key travel (switch) | 1 mm | | |
| Life time (switch) | >10,000,000 cycles | | >1,000,000 cycles |
| **TEMPERATURE RANGE** | | | |
| Working temperature | Min -40°C Max +160°C | | |
| Storage temperature | Min -40°C Max +160°C | | |
| 5G with LED (working & storage temp) | Min -30°C Max +85°C | | |
| Soldering (through-hole switch) | IEC 68-2-20 8: | | |
| | Infrared, vapour phase, wave - max 240°C for | | |
| | max 40 sec or max 260°C for max 30 sec. | | |
| | Soldering iron - max 350°C for max 3 sec. | | |
| | Flux tight. | | |
| **SOLDERING (SMD)** | JEDEC J-STD-020C | | |
| **ENVIRONMETAL ENDURANCE IEC 68-2-3** | | | |
| Temperature | +40°C | | |
| Humidity | 93% RH | | |
| Duration | 56 Days | | |
| **TEMPERATURE CYCLING IEC 68-2-14** | | | |
| Temperature limit | Min -55°C - Max +85°C | | |
| Number of cycles | 200 | | |
| Exposure time at each temperature | 10 min | | |
| Recovery time before measurements | 16 hrs | | |
| Sealing IEC 529 | IP-67 | | |
| Cleaning | Standard methods - see usage guidelines | | |
| **MATERIAL SPECIFICATIONS - SWITCHES** | | | |
| Housing | PPS UL94V0 | | |
| Actuator | PPS UL94V0 | | |
| Sealing + spring | Silicone rubber | | |
| Contact spring | Stainless steel | Stainless steel | |
| | + 3µAg | + 1µAu | |
| Fixed contacts | SnCu + 2µNI + 3µAg | SnCu + 2µNI + 1µAu | |
| Terminals | SnCu + 2µNI + 3µSn100 | | |

## Caps, Bezels & Legends – Material Specifications

| MATERIAL | PARTS | TEMP. LIMIT | UL RATING |
|---|---|---|---|
| ABS | 1A, 1B, 1C, 1DS, 1ES, 1FS, 1H, 1JS, 1KS, 1LS, 1M, 1NS, 1PS, 1QS, 1RS, 1TS, 1US, 1VS, 1WAS, 1WDS, 1WPS, 1XS, 1Z, 1ZA, 1ZB, 1ZCS, 1ZW, 2C, 2D, 2K, reflectors for 1KBS/1KCS and 1YS | Max. 65°C | UL94HB |
| Polycarbonate | All lenses and transparent colour caps, lids for 1KBS/1KCS | Max. 85°C | UL94HB |
| Polyamide | 1GAS/1GCS, 1SS, 2SS | Max. 160°C | UL94V2 |
| Legends Adhesion | DS/EN ISO 2409 Class 1 & ASTM D3359 Class 4B | | |

## LEDs specifications

**5G switches**

| Colour | | Blue | Green | Yellow | White | Red | High Intensity Green |
|---|---|---|---|---|---|---|---|
| **Colour Codes** | | 02 | 22 | 42 | 61 | 82 | 29 |
| **ABSOLUTE MAXIMUM RATINGS** (Ta=25°C) | | | | | | | |
| Power | mW | 95 | 75 | 60 | 48 | 65 | 102.5 |
| Current forward | mA | 25 | 30 | 25 | 15 | 25 | 25 |
| Forward peak current | mA | 100 | 80 | 60 | 100 | 100 | 150 |
| Voltage reverse | V | 5 | 5 | 5 | NA | 12 | 5 |
| Operating temperature | °C | -40/+85 | -55/+85 | -40/+85 | -40/+85 | -30/+85 | -40/+85 |
| Storage temperature | °C | -40/+90 | -55/+85 | -40/+90 | -40/+85 | -40/+85 | -40/+85 |
| Soldering temperature | °C | 245 for max. 10 sec | | | | | |
| **ELECTRICAL-OPTICAL CHARACTERISTICS** (Ta=25°C) | | | | | | | |
| Voltage forward | Typ. V | 3.3 | 2 | 1.75** | 2.85 | 2 | 3.3 |
| | Max. V | 3.7 | 2.4 | 2.35 | 3.1 | 2.5 | 4.1 |
| Current reverse (VR=5V) | Max. µA | 50 | 100 | 10 | NA | 100 | 50 |
| Wave length | nm | 470 | 571 | 591 | NA | 633 | 525 |
| Spread | Δnm | 25 | NA | 15 | NA | 16 | 30 |
| Spread angle | degree | 120 | 130 | 120 | 150 | 160 | 60 |
| **Luminous Intensity** | Min. mcd | 45 | 18 | 28.5 | 71 | 28 | 500 |
| | Typ. mcd | 112* | 35 | 72* | 224* | 180* | 1000 |
| Optical intensity | Lm/w | NA | NA | NA | 36 | 7 | NA |

*Max.mcd **Min. V

| **3F switches** | | **3FXXX (for 1E-1F-1N-1Q-1R-1S-1X)** | | | | | | | | **3FXXX (for 1K-1T-1U-1V-1W-1WD)** | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **Colour** | | **B** | **G** | **Y** | **W** | **R** | **G/Y** | **R/G** | **R/Y** | **G** | **Y** | **R** |
| **Colour Codes** | | 00 | 20 | 40 | 65 | 80 | 2040 | 8020 | 8040 | 24 | 46 | 87 |
| **Absolute Maximum Ratings** | (Ta=25°C) | | | | | | | | | | | |
| Power | mW | 105 | 70 | 60 | 120 | 60 | 120 | 100 | 120 | 60 | 60 | 120 |
| Current forward | mA | 30 | 20 | 20 | 25 | 20 | 25 | 30 | 25 | 25 | 25 | 50 |
| Forward peak current | mA | 150 | 60** | 60** | 100 | 60** | 150 | 120 | 150 | 60 | 60 | 200 |
| Voltage reverse | V | 5 | 3 | 3 | 5 | 3 | 5 | 5 | 5 | 5 | 5 | 5 |
| Operating temperature | °C | -40/+85 | | | -40/+85 | -25/+85 | -40/+85 | -55/+100 | -40/+85 | -40/+85 | -40/+85 | -40/+85 |
| Storage temperature | °C | -40/+85 | | | -40/+100 | -30/+100 | -40/+85 | -55/+100 | -40/+85 | -40/+85 | -40/+100 | -40/+100 |
| Soldering temperature | °C | 260 for max 5 sec | | | | | 260 for max 2 sec | | | 300 for max 3 sec | 260 for max 5 sec | |
| **Electrical-Optical Characteristics (Ta=25°C)** | | | | | | | | | | | | |
| Voltage forward | Typ. V | 3.8 | 2.1 | 2.1 | 3.8 | 2.0 | 2.1 | 2.0 | 2.1 | 2.0* | 2.0 | 2.0*** |
| | Max. V | 4.5 | 3.0 | 3.0 | 4.3 | 3.0 | 2.8 | 2.6 | 2.8 | 2.4* | 2.4 | 2.4*** |
| Current reverse (VR=5V) | µA | 10 | 10 | 10 | 50 | 10 | 2 | 2 | 2 | 10 | 10 | 10 |
| Wave length | nm | 466 | 563 | 585 | NA | 650 | 565/590 | 630/565 | 625/590 | 570 | 589 | 624/632 |
| Spread | Δnm | 60 | 40 | 40 | NA | 40 | 35 | 35 | 35 | 10 | NA | 20 |
| Spread angle | degree | 60 | 45 | 45 | 25 | 45 | 60 | 200 | 60 | 100 | 40 | 40 |
| **Luminous Intensity** | Min. mcd | 18 | 9.0 | 5.6 | 630 | 5.6 | 8 | 2.2 | 8 | 70**** | 630 | 400**** |
| | Typ. mcd | 50 | 25 | 16 | 1000 | 16 | 25 | 4.8 | 25 | 20**** | 1250 | 800**** |
| Orientation | The longer pin is the anode, the shorter is the cathode. For bicolour LEDs the anode for the first colour (ex. 2080) is the longer pin. | | | | | | | | | | | |

**Pulse width 1ms Duty cycle 1:5, ***/F =50mA, **** Luminous Flux mlm
B=Blue, G=Green, Y=Yellow, R=Red, W=White
Specifications are subject to change without notice.

# Usage guidelines

**How to get the best results with MEC Switches?**
These guidelines are offered to users of MEC Switches as an aid to ensure successful and reliable switch operation.

**Temperature**
Both unimec™ and multimec® switches are produced in low and high temperature versions. Please see the technical specifications for details on operating and storage temperatures and soldering guidelines to make sure you select the best switch for your application. When wave soldering is taking place, MEC strongly recommend that the temperature profile is analysed and compared with the temperature rating of the switch. In case of doubt always select the high temperature versions unimec™ 154XX, and multimec® 5XXH9XX. It is also important to monitor the accumulated heat build up from both the pre-heat zones and the solder zone.

Most standard accessories for both unimec™ and multimec® switches are made from ABS plastic with a maximum operating temperature of 65°C. It is strongly recommended that accessories are mounted after soldering of the switch. If this is not possible care must be taken not to overheat the accessories during the soldering process. The 1SS, 1GAS/1GCS and Varimec™ caps are, however, made of high temperature materials and will meet the same temperature specifications as the high temperature switches.

For accessories made from other plastic materials please see multimec® and unimec™ technical specifications.

LEDs have their own temperature specifications. When fitted in a high temperature switch the LED will determine the max. operating temperature, i.e. 5GTH93524 has an upper temperature limit of 85°C! This also applies with 3F switches.

**Mounting and Dismounting**
If switches are to be mounted in rows it is essential that the recommendations regarding spacing are followed. PC board thickness should be 1.4±0.2 mm and terminal hole diameter should be 0.9mm.

All unimec™ and multimec® caps and bezels are easily snapped onto the switch modules and can be changed at a later time with the exception of the unimec 16.700 cap. The same applies to the 3E caps. Once these caps are installed they are not designed to be removed. To do so may cause damage to the switch and the PC board if not done very carefully. If the 16.300 or 16.700 cap must be removed from a unimec™ alternate action switch, make sure that the switch actuator is in the released, upper position before attempting to remove the cap. This will prevent possible damage to the internal latching pin.

Care must be taken when inserting the 3FT switch and LED assembly into the PC board. Do not press direct on the LED. This will force the LED down into the actuator and risks to cause the switch contacts to remain in the closed position. To correct the fault, the LED must be raised slightly and centered in the actuator to assure unrestricted movement of the actuator. A mounting tool is available for multimec® switches.

**Soldering and Cleaning unimec™**
Most assembly and field problems experienced by users of unsealed switches are caused by the contamination of the contacts during soldering and cleaning.

Contact contamination may be recognised by an increase in contact resistance and possible intermittent operation of the switch, especially in low power applications. Care must be taken not to submerge the switch in cleaning agents or spray the switch during cleaning. The switch must be protected at all times to prevent contamination by flux or cleaning liquids.

For unimec™ alternate versions we recommend to leave the actuator in the released upper position during soldering. This makes the switch more resistent to overheating.

**Soldering and Cleaning multimec®**
multimec® switches are fully sealed to IP67 specifications to prevent solder flux and aqueous based cleaning solutions from entering the switch and contaminating the contacts. The switches can be placed on the PC board with other components and wave soldered. multimec® offers a high level of sealing, however, with aqueous solvent solutions care must be taken to avoid the worst case situation with water jets, complete immersion into a liquid with a temperature below the board or surface tension reducing additives.

Recommended cleaning methods are demineralized water. Any surface tension reducing agents, such as soap, must not be used as they risk causing a potential leakage of the switch.

**Soldering - Through Hole Versions**
Hand soldering: Max. 350°C for max. 3 sec., this applies for both low temperature and high temperature versions.

Wave soldering: heat built up in the switch during pre-heating and soldering must not exceed the maximum operating temperature of the switch. If, for some reason, a high pre-heating temperature is required, MEC recommend the high temperature switches. In any case peak temperature must not exceed 260°C, and soldering time is max 10 sec.

**Soldering - Surface Mount Versions**
For all methods - infrared, convection and vapour phase. The upper limit 260°C/30 sec must be observed. The soldering temperature profile must have moderate temperature gradients.

**RoHS Compliance**
As of 1 July 2006 MEC has completed the conversion to RoHS compliance. For more info please see our homepage www.mec.dk

**Temperature Limits:**

| | |
|---|---|
| Low temperature switch | 115°C |
| High temperature switch | 160°C |
| LEDs | 85/100°C |
| Accessories | 65/85/160°C |

**Packaging**
unimec™ and multimec® switches are packed in rigid tubes of 50 pieces each.

A box contains 1.000 pcs.

The surface mount versions of multimec®switches with a height up to 12.5mm can also be delivered on tape/reel. Each reel contains 250/500 pcs.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** sales@st-electron.ru

**Адрес:** 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331