

16/32-Bit

Architecture

**XC2263N, XC2264N,
XC2265N, XC2268N**

16/32-Bit Single-Chip Microcontroller with
32-Bit Performance

XC2000 Family Derivatives / Value Line

Addendum to Data Sheet V2.0

V1.0 2011-03

Microcontrollers

Edition 2011-03

**Published by
Infineon Technologies AG
81726 Munich, Germany**

**© 2011 Infineon Technologies AG
All Rights Reserved.**

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

16/32-Bit

Architecture

XC2263N, XC2264N, XC2265N, XC2268N

16/32-Bit Single-Chip Microcontroller with
32-Bit Performance

XC2000 Family Derivatives / Value Line

Addendum to Data Sheet V2.0

V1.0 2011-03

Microcontrollers

XC226xN

Revision History: V1.0, 2011-03

Previous Version(s):

None

| Page | Subjects (major changes since last revisions) |
|------|---|
| | |
| | |
| | |

Trademarks

C166™, TriCore™, and DAVE™ are trademarks of Infineon Technologies AG.

We Listen to Your Comments

Is there any information in this document that you feel is wrong, unclear or missing?

Your feedback will help us to continuously improve the quality of this document.

Please send your proposal (including a reference to this document) to:

mcdocu.comments@infineon.com



Table of Contents

| | | |
|----------|-------------------------------|----------|
| 1 | Additional Information | 6 |
| 1.1 | Additional Basic Device Type | 6 |
| 1.2 | Product Type Reference | 7 |

**16/32-Bit Single-Chip Microcontroller with 32-Bit Performance
XC226xN (XC2000 Family)**

1 Additional Information

Orders of the various product types described in the Data Sheet can be fulfilled with an alternate marking version (additional basic device type).

Additional information can be obtained from the corresponding Info Note 064/10.

This addendum defines the marking version that can be shipped in response to orders of the original devices listed in the referenced standard Data Sheet for the XC226xN:

1.1 Additional Basic Device Type

This table defines the additional basic device type.

This basic device type provides all features of the respective covered product types as listed in [Table 2](#).

Table 1 Additional XC226xN Basic Device Type

| Derivative | Flash Memory¹⁾ | PSRAM DSRAM²⁾ | Capt./Comp. Modules | ADC³⁾ Chan. | Interfaces³⁾ |
|--------------------|----------------------------------|---------------------------------|----------------------------|-------------------------------|--------------------------------|
| SAK-XC2060N-40F80L | 320 Kbytes Flash | 16 Kbytes 16 Kbytes | CC2 CCU60/1 | 11 + 5 | 3 CAN Nodes, 6 Serial Chan. |

1) Specific information about the on-chip Flash memory in the referenced Data Sheet.

2) All derivatives additionally provide 8 Kbytes SBRAM and 2 Kbytes DPRAM.

3) Specific information about the available channels in the referenced Data Sheet.

Analog input channels are listed for each Analog/Digital Converter module separately (ADC0 + ADC1).

1.2 Product Type Reference

All orders of product types described in the referenced Data Sheet can be fulfilled with devices with this marking:

SAK-XC2060N-40F80L.

For easy reference these product types are listed in the table below.

Table 2 Covered Product Types

| Derivative | Device Type |
|-------------------|--------------------|
| XC2263N-24F40L | Basic |
| XC2263N-40F80L | Basic |
| XC2265N-40F80L | Basic |
| XC2268N-40F80L | Basic |
| XC2261N-24FxL | Special |
| XC2263N-16FxL | Special |
| XC2263N-24FxL | Special |
| XC2263N-40FxL | Special |
| XC2264N-16FxL | Special |
| XC2264N-24FxL | Special |
| XC2264N-40FxL | Special |
| XC2265N-16FxL | Special |
| XC2265N-24FxL | Special |
| XC2265N-40FxL | Special |

Note: You may continue to order your known product type(s).

The replacement will be done automatically during the delivery process.

www.infineon.com



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331