

M81714 SERIES I

Amphenol Pcd

Designed and qualified to MIL-T-81714, Amphenol PCD's Series I Terminal Junction Modules are robust, reliable, and always perform to highest standards. Amphenol PCD offerings cover the full SAE-AS81714 range of configurations—Feedback/Feedthrough, Electronic, In-Line Splice, Electronic Splice, and Ground. They use standard M39029/1 pin contacts and accommodate 12-26 AWG wires. Mounting rail and installation/termination accessories are available, and customization is always an option.



Feedback, Feedthrough & Bussing Modules

Electronic Modules

Ground Modules

*Single In-Line Splices
Dual In-Line Splices
Electronic Splices*

Mounting Tracks

Feedback, Feedthrough & Bussing Modules

TJM and TJHD modules offer a lightweight junction system with a full range of bussing arrangements and contact sizes. TJM and TJHD modules meet M81714 requirements, and are QPL approved.

Electronic Modules

TJE electronic modules offer a wide variety of diodes, resistors, capacitors and fuses in a Series I form factor. TJE modules perform to M81714 specifications. Many variations are available, and custom options are always available.

In-Line Splices

Single and Dual Splices and Electronic Splices are designed to provide a quick and efficient solution to customer wiring requirements. Single and Dual Wire Splices meet MIL-T-81714/11 & /12 requirements and are highly resistant to temperature and fluids.

Grounding Modules

Multi-contact grounding/bus connection modules are provided with an integral threaded grounding stud or flange. The stud and flange is electrically and mechanically common to all internal contacts of the module. The modules are dimensional identical to the equivalent MIL-T-81714/27 grounding stud modules.

Electronic Splices

TJSE electronic splices can be supplied with a wide variety of diodes, resistors, capacitors, and fuses within the splice itself. TJSE electronic splices meet the electrical parameters of MIL-T-81714/21 /23 /24 and allow customers to incorporate system modifications into a wire bundle, avoiding expensive changes in panels and wire harnesses themselves.

Module Mounting Tracks & Brackets

One track holds all module sizes with STD, lightweight & feed through types available. Each track unit consists of an aluminum alloy track and anodized black locking clamp. The stainless steel clamp screw is self locking to meet vibration, shock and temperature variation requirements. /29 mounting brackets also available.

Features & Benefits

SAE-AS81714 & MIL-T-81714

Approved Meets high quality standards

AS39029/1 Type Contacts

Meets military specification AS39029

Integral Bus Bar

Assures electrical and mechanical integrity over long product life
Fewer solder joints for more reliable and repeatable electrical operation

Integral Contacts

High conductivity allows for optimum electrical performance

Split Socket Design

Provides peripheral surface wipe and contact
Maximizes mating surfaces of pin and contact

Class D Module System

Combines max high temperature and high fluid resistance performance parameters previously divided among three module classes: A, B, C

Electronic Systems

Modules can be supplied with a variety of diode, resistors, capacitors, and fuses Meets electronic parameters of MIL-T-81714 /24 /25 /26

Class 3B Silicone Sealant

Tear and flex resistant silicone

Ultrasonic Bonding + Proprietary Epoxy

No bond lines and ultrasonic fusing means few voids, long field life

Product Availability

Largest QPL availability in the industry
Non-QPL variants and custom modules

Technical Specifications

Materials

Insulator Body: Polyetherimide, color: black

Grommet: Silicone elastomer, color: blue

Contacts: Copper alloy, gold plated

Contact Retainers: Stainless steel

Performance

Temperature Range: -65°C to 200°C

Insulation Resistance:

>5000 megohms

AS81714, para 3.5.1

Dielectric Withstanding Voltage:

1500Vrms @ sea level

200Vrms @ 100,000 ft altitude

AS81714-para 3.5.6

Current Ratings (By Contact Size):

Size 22/22: 5 Amps

Size 20/20: 7.5 Amps Size 16/16: 13 Amps

Size 12/12: 23 Amps

Vibration: Per AS81714, para. 3.5.8

Mechanical Shock: Per AS81714, para. 3.5.9

QPL & Non-QPL Coverage

| | | |
|------|------------------------|--------------------------------------|
| TJM | Sz 12/16/20 | M81714/1, /2, /3, /4, /6, /7, /8, /9 |
| TJE | Sz 12/16/20 Electronic | performs to M81714/26, /25 (non-QPL) |
| TJHD | Sz 22 Electronic | M81714/17 |
| TJT | Tracks | M81714/5, /10, /16 (light weight) |
| TJF | Flange Ground | performs to M81714/28 (non-QPL) |
| TJG | Stud Ground | performs to M81714/27 (non-QPL) |
| TJS | Splices- Single & Dbl | M81714/11, /12 |
| TJSE | Electronic Splices | M81714/21, /23, /24 (/24 non-QPL) |

AVAILABLE IMMEDIATELY

NEW

Series I Electronic Splice

M81714/21 Inline Diodes

M81714/23 Inline Fuses



Class D, QPL certified to SAE-AS81714 Use MilStd Pin Contacts

M39029/1-100 size 22

M39029/1-101 size 20

Reliable & Proven Tried & True – Technology you can trust



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331