

# Surface mount type

# TPU Series

RoHS compliance, Halogen free  
Small size, Low profile: L2.0xW1.25xH0.9mm (S09)  
Face down terminal type

## Specifications

Items	Condition	Specifications			
		2.5	4.0	6.3	10
Rated voltage (V)	—	2.5	4.0	6.3	10
Surge voltage (V)	—	2.9	4.6	7.2	12
Category temperature range (°C)	—	-55 to +85			
Capacitance tolerance (%)	120Hz/20°C	M: ±20			
Rated capacitance range (μF)	120Hz/20°C	4.7 to 150			
Dissipation Factor (DF)	120Hz/20°C	Please see the attached characteristics list			
Leakage current	Rated voltage applied, after 5 minutes	Please see the attached characteristics list			
Equivalent series resistance (ESR)	100kHz/20°C	Please see the attached characteristics list			
Characteristics of impedance ratio at high temp. and low temp.	100kHz/+20°C	-55°C	Z/Z <sub>20°C</sub>	0.6 to 2.0	
		+85°C	Z/Z <sub>20°C</sub>	0.6 to 2.0	
Endurance	85°C, 1,000h, rated voltage applied	ΔC/C	Within±20% of the initial value		
		DF	≤ 1.5 times of the initial limit		
		LC	Within the initial limit		
Damp heat (Steady State)	60°C, 90 to 95%RH, 500h, No-applied voltage	ΔC/C	Within+40%, -20% of the initial value		
		DF	≤ 1.5 times of the initial limit		
		LC	≤ 3 times of the initial limit		
Surge	85°C, 1,000 cycles, 1kΩ discharge resistance, surge voltage applied	ΔC/C	Within±5% of the initial value		
		DF	Within the initial limit		
		LC	≤ 3 times of the initial limit		

## Marking and dimensions

S09size

B09size

Rated capacitance\*3

R.V.	2.5	4.0	6.3	10
Mark	e	g	j	A

Rated voltage\*1

Capacitance(μF)	150
Mark	E8

※1 The rated voltage is as follows.

※2 Lot.No.shows roughly manufacturing date.

※3 The rated capacitance is as follows.(B09)

※4 The rated capacitance is as follows.(S09)

Size code	L ±0.1※1	W ±0.1※1	H ±0.1	S ±0.1※1	W1 ±0.1
S09	2.0	1.25	0.9	0.5	0.9
B09	3.5	2.8	0.9	0.8	2.2

unit : mm

※1 ±0.2:B09

## Recommended land pattern dimension of PWB

Size code	a	b	c
S09	1	0.9	0.6
B09	1.6	2.7	1.4

unit : mm

## Size list

RV:Rated voltage

RV	2.5	4.0	6.3	10
4.7				S09
10			S09	
22			S09	
47	S09		S09	
68		S09		
100	S09			
150			B09	

## TPU series characteristics list

Size code	Part number	Rated voltage (V)	Rated temperature (°C)	Rated capacitance (μF)	Category voltage (V)	Category temperature (°C)	DF (% max)	LC (μA) max/5min.	ESR (mΩmax) 100kHz/20°C	Maximum allowable ripple current (mA rms) 100kHz※1	MSL	
											Reflow temp. ≤ 260°C	Reflow temp. ≤ 250°C
S09	10TPU4R7MSI	10	85	4.7	10	85	10	4.7	300	360	3	3
	6TPU47MSI	6.3	85	47	6.3	85	10	59.2	150	510	—	3
	6TPU22MSI	6.3	85	22	6.3	85	10	27.7	150	510	—	3
	6TPU10MSI	6.3	85	10	6.3	85	10	6.3	250	400	—	3
	4TPU68MSI	4.0	85	68	4.0	85	10	54.4	150	510	—	3
	ETPU100MSI	2.5	85	100	2.5	85	10	50.0	150	510	—	3
	2R5TPU47MSI	2.5	85	47	2.5	85	10	23.5	150	510	—	3
	6TPU150MBI	6.3	85	150	6.3	85	10	94.5	100	670	3	3

※1 100k to 500kHz,45°C



## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331