

## Knife disconnect terminal block - PT 1,5/S-TWIN-MT - 3210311

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Knife disconnect terminal block, Connection type: Push-in connection, Cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 14, Nominal current: 10 A, Nominal voltage: 400 V, Length: 67.8 mm, Width: 3.5 mm, Color: gray, Assembly: NS 35/7,5, NS 35/15

### Product Features

- ✓ The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- ✓ The compact design and front connection enable wiring in a confined space
- ✓ In addition to the testing facility in the double function shaft, all terminal blocks provide an additional test connection
- ✓ Convenient separation of circuits, thanks to lever-type disconnect knife



### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 5.2 g    |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                                        |                     |
|----------------------------------------|---------------------|
| Number of levels                       | 1                   |
| Number of connections                  | 3                   |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Color                                  | gray                |
| Insulating material                    | PA                  |
| Flammability rating according to UL 94 | V0                  |
| Rated surge voltage                    | 6 kV                |
| Pollution degree                       | 3                   |
| Overvoltage category                   | III                 |

# Knife disconnect terminal block - PT 1,5/S-TWIN-MT - 3210311

## Technical data

### General

|                                                                                 |                                     |
|---------------------------------------------------------------------------------|-------------------------------------|
| Insulating material group                                                       | I                                   |
| Connection in acc. with standard                                                | IEC 60947-7-1                       |
| Maximum load current                                                            | 10 A                                |
| Nominal current $I_N$                                                           | 10 A                                |
| Nominal voltage $U_N$                                                           | 400 V                               |
| Open side panel                                                                 | ja                                  |
| Shock protection test specification                                             | DIN EN 50274 (VDE 0660-514):2002-11 |
| Back of the hand protection                                                     | guaranteed                          |
| Finger protection                                                               | guaranteed                          |
| Surge voltage test setpoint                                                     | 7.3 kV                              |
| Result of surge voltage test                                                    | Test passed                         |
| Power frequency withstand voltage setpoint                                      | 1.89 kV                             |
| Result of power-frequency withstand voltage test                                | Test passed                         |
| Checking the mechanical stability of terminal points (5 x conductor connection) | Test passed                         |
| Bending test rotation speed                                                     | 10 rpm                              |
| Bending test turns                                                              | 135                                 |
| Bending test conductor cross section/weight                                     | 0.14 mm <sup>2</sup> / 0.2 kg       |
|                                                                                 | 1.5 mm <sup>2</sup> / 0.4 kg        |
| Result of bending test                                                          | Test passed                         |
| Conductor cross section tensile test                                            | 0.14 mm <sup>2</sup>                |
| Tractive force setpoint                                                         | 10 N                                |
| Conductor cross section tensile test                                            | 1.5 mm <sup>2</sup>                 |
| Tractive force setpoint                                                         | 40 N                                |
| Tensile test result                                                             | Test passed                         |
| Tight fit on carrier                                                            | NS 35                               |
| Setpoint                                                                        | 1 N                                 |
| Result of tight fit test                                                        | Test passed                         |
| Requirements, voltage drop                                                      | ≤ 6,4 mV                            |
| Result of voltage drop test                                                     | Test passed                         |
| Temperature-rise test                                                           | Test passed                         |
| Conductor cross section short circuit testing                                   | 1.5 mm <sup>2</sup>                 |
| Short-time current                                                              | 0.18 kA                             |
| Short circuit stability result                                                  | Test passed                         |
| Ageing test for screwless modular terminal block temperature cycles             | 192                                 |
| Result of aging test                                                            | Test passed                         |
| Proof of thermal characteristics (needle flame) effective duration              | 30 s                                |

# Knife disconnect terminal block - PT 1,5/S-TWIN-MT - 3210311

## Technical data

### General

|                                                                       |                                                |
|-----------------------------------------------------------------------|------------------------------------------------|
| Result of thermal test                                                | Test passed                                    |
| Test specification, oscillation, broadband noise                      | DIN EN 50155 (VDE 0115-200):2008-03            |
| Test spectrum                                                         | Service life test category 2, bogie mounted    |
| Test frequency                                                        | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level                                                             | $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$      |
| Acceleration                                                          | 3.12 g                                         |
| Test duration per axis                                                | 5 h                                            |
| Test directions                                                       | X-, Y- and Z-axis                              |
| Oscillation, broadband noise test result                              | Test passed                                    |
| Test specification, shock test                                        | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                                            | Half-sine                                      |
| Acceleration                                                          | 30g                                            |
| Shock duration                                                        | 18 ms                                          |
| Number of shocks per direction                                        | 3                                              |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.)              |
| Shock test result                                                     | Test passed                                    |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C                                         |
| Static insulating material application in cold                        | -60 °C                                         |

### Dimensions

|                  |          |
|------------------|----------|
| Width            | 3.5 mm   |
| End cover width  | 0.8 mm   |
| Length           | 67.8 mm  |
| Height           | 30.50 mm |
| Height NS 35/7,5 | 32 mm    |
| Height NS 35/15  | 39.5 mm  |

### Connection data

|                                            |                      |
|--------------------------------------------|----------------------|
| Connection method                          | Push-in connection   |
| Connection in acc. with standard           | IEC 60947-7-1        |
| Conductor cross section solid min.         | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.         | 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.           | 26                   |
| Conductor cross section AWG max.           | 14                   |
| Conductor cross section flexible min.      | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.      | 1.5 mm <sup>2</sup>  |
| Min. AWG conductor cross section, flexible | 26                   |
| Max. AWG conductor cross section, flexible | 14                   |

## Knife disconnect terminal block - PT 1,5/S-TWIN-MT - 3210311

### Technical data

#### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 1 mm <sup>2</sup>    |
| Stripping length                                                           | 8 mm ... 10 mm       |
| Internal cylindrical gage                                                  | A1 / B1              |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27141120 |
| eCl@ss 6.0 | 27141120 |
| eCl@ss 8.0 | 27141126 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000902 |
| ETIM 5.0 | EC000902 |

### Approvals

#### Approvals

#### Approvals

UL Recognized / cUL Recognized / CSA / cULus Recognized

#### Ex Approvals

#### Approvals submitted

### Approval details

|                                                                                                   |       |       |
|---------------------------------------------------------------------------------------------------|-------|-------|
| UL Recognized  |       |       |
|                                                                                                   | B     | C     |
| mm <sup>2</sup> /AWG/kcmil                                                                        | 26-16 | 26-16 |

## Knife disconnect terminal block - PT 1,5/S-TWIN-MT - 3210311

### Approvals

|                                | B     | C     |
|--------------------------------|-------|-------|
| Nominal current I <sub>N</sub> | 10 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

cUL Recognized 

|                                | B     | C     |
|--------------------------------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-16 | 26-16 |
| Nominal current I <sub>N</sub> | 10 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

CSA 

|                                | B     | C     |
|--------------------------------|-------|-------|
| mm <sup>2</sup> /AWG/kcmil     | 26-16 | 26-16 |
| Nominal current I <sub>N</sub> | 10 A  | 10 A  |
| Nominal voltage U <sub>N</sub> | 300 V | 300 V |

cULus Recognized 

### Drawings

Circuit diagram





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331