


## 3M™ Static Shielding Bag 1000

This transparent metal-in static shielding bag is designed to provide a static safe environment for sensitive electronic devices. Bags are printed with an ESD warning symbol and a lot code for traceability. Open top and ZipTop styles are available. The bags are heat sealable.

3M Static Shielding Bags 1000 are manufactured from a polyester, metal, polyethylene laminate. The polyester dielectric in concert with the metal layer is intended to provide shielding of Electrostatic Discharge (ESD) and to help minimize the penetration of electric field.


These bags are tested to meet or exceed certain electrical and physical requirements of Static Shielding Bags, ANSI/ESD S541, and to be ANSI/ESD S20.20 program compliant. Bags are RoHS Compliant\* and lead-free\*\*.



3M™ Static Shielding Bag 1000,  
Open Top



3M™ Static Shielding Bag 1000,  
ZipTop



| Physical                      | Typical Value                | Testing Method            |
|-------------------------------|------------------------------|---------------------------|
| Tensile Strength              | 4600 PSI, 32 MPa             | ASTM D882                 |
| Puncture Resistance           | 12 lbs, 53 N                 | MIL-STD-3010C Method 2065 |
| Seal Strength                 | 11 lbs, 48 N                 | ASTM D882                 |
| Thickness                     | 2.8 mils, .071 mm +/-15%     | MIL-STD-3010C Method 1003 |
| Marking Adhesion              | Pass                         | IPC-TM-650 2.4.1          |
| Transparency                  | 40%                          | Tobias                    |
| Electrical                    | Typical Value                | Testing Method            |
| ESD Shielding                 | <10 nJ                       | ANSI/ESD STM11.31         |
| Surface Resistance - Interior | <1x10 <sup>11</sup> ohms     | ANSI/ESD STM11.11         |
| Surface Resistance - Exterior | <1x10 <sup>11</sup> ohms     | ANSI/ESD STM11.11         |
| Static Decay                  | < 2 seconds                  | ETS 406D                  |
| Cleanliness                   | Typical Value                | Testing Method            |
| Silicone                      | Not Detected                 | FTIR                      |
| Heat Sealing Conditions       | Typical Value                |                           |
| Temperature                   | 300°F – 375°F, 149°C – 190°C |                           |
| Time                          | 0.5 – 3.5 seconds            |                           |
| Pressure                      | 30 – 70 PSI, 206 – 482 KPa   |                           |

This product is intended for commercial use only. This product is not on the Qualified Product Listing under the Defense Standardization Program.

# Product Data Sheet

## 3M™ Static Shielding Bag 1000

| Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. |
|---------------------------|----------|---------------------------|----------|---------------------------|----------|
| 2 x 3                     | 10023    | 6 x 30                    | 100630   | 12 x 12                   | 1001212  |
| 2 x 4                     | 10024    | 6.5 x 10                  | 1006.51  | 12 x 14                   | 1001214  |
| 2 x 6                     | 10026    | 6.5 x 16                  | 1006.516 | 12 x 16                   | 1001216  |
| 3 x 3                     | 10033    | 7 x 10                    | 100710   | 12 x 18                   | 1001218  |
| 3 x 5                     | 10035    | 7 x 11                    | 100711   | 12 x 24                   | 1001224  |
| 4 x 4                     | 10044    | 7 x 15                    | 100715   | 12 x 25                   | 1001225  |
| 4 x 6                     | 10046    | 7 x 16                    | 100716   | 12 x 30                   | 1001230  |
| 4 x 8                     | 10048    | 8 x 8                     | 10088    | 14 x 18                   | 1001418  |
| 4 x 24                    | 100424   | 8 x 10                    | 100810   | 14 x 20                   | 1001420  |
| 4 x 26                    | 100426   | 8 x 12                    | 100812   | 14 x 30                   | 1001430  |
| 4 x 30                    | 100430   | 8 x 18                    | 100818   | 15 x 18                   | 1001518  |
| 5 x 6                     | 10056    | 8 x 24                    | 100824   | 16 x 18                   | 1001618  |
| 5 x 7                     | 10057    | 8 x 30                    | 100830   | 16 x 20                   | 1001620  |
| 5 x 8                     | 10058    | 9 x 12                    | 100912   | 16 x 24                   | 1001624  |
| 5 x 10                    | 100510   | 10 x 12                   | 1001012  | 18 x 18                   | 1001818  |
| 6 x 8                     | 10068    | 10 x 14                   | 1001014  | 18 x 20                   | 1001820  |
| 6 x 9                     | 10069    | 10 x 16                   | 1001016  | 18 x 24                   | 1001824  |
| 6 x 10                    | 100610   | 10 x 18                   | 1001018  | 18 x 30                   | 1001830  |
| 6 x 12                    | 100612   | 10 x 24                   | 1001024  | 20 x 20                   | 1002020  |
| 6 x 14                    | 100614   | 10 x 26                   | 1001026  | 20 x 24                   | 1002024  |
| 6 x 16                    | 100616   | 10 x 30                   | 1001030  | 22 x 24                   | 1002224  |
| 6 x 18                    | 100618   | 11 x 14                   | 1001114  | 24 x 24                   | 1002424  |
| 6 x 24                    | 100624   | 11 x 15                   | 1001115  | 24 x 30                   | 1002430  |
| 6 x 26                    | 100626   |                           |          | 30 x 24                   | 1003024  |


Custom Sizes and Printing Available.

| Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. | Dimensions<br>(W x L in.) | Part No. |
|---------------------------|----------|---------------------------|----------|---------------------------|----------|
| 2 x 3                     | 30023    | 6 x 10                    | 300610   | 10 x 30                   | 3001030  |
| 3 x 3                     | 30033    | 6 x 24                    | 300624   | 11 x 15                   | 3001115  |
| 3 x 4                     | 30034    | 6 x 30                    | 300630   | 12 x 12                   | 3001212  |
| 3 x 5                     | 30035    | 7 x 15                    | 300715   | 12 x 16                   | 3001216  |
| 4 x 4                     | 30044    | 8 x 8                     | 30088    | 12 x 18                   | 3001218  |
| 4 x 6                     | 30046    | 8 x 10                    | 300810   | 14 x 18                   | 3001418  |
| 4 x 8                     | 30048    | 8 x 12                    | 300812   | 15 x 18                   | 3001518  |
| 4 x 24                    | 300424   | 9 x 12                    | 300912   | 16 x 24                   | 3001624  |
| 4 x 30                    | 300430   | 10 x 10                   | 3001010  | 18 x 18                   | 3001818  |
| 5 x 8                     | 30058    | 10 x 12                   | 3001012  | 18 x 24                   | 3001824  |
| 5 x 10                    | 300510   | 10 x 14                   | 3001014  | 20 x 24                   | 3002024  |
| 6 x 8                     | 30068    | 10 x 24                   | 3001024  | 24 x 24                   | 3002424  |

Custom Sizes and Printing Available.

- Standard sizes stocked for prompt shipment (usually same day).
- Width is measured from inside seam to inside seam.
- Length is measured from the top edge to the bottom fold.
- Opening is in the "width" dimension.
- Custom bag sizes, custom printing, and custom hot stamping are available.
- Most sizes are packed 100 per case.
- Small sizes are packed 500 or 1,000 per case.

## 3M™ Static Shielding Bag 1000



Tolerance (inches): Width -0, +0.250  
Length +/- 0.125 Offset 0 to 0.250  
Seal width +/- 0.125

3M is a trademark of 3M Company. All other trademarks are owned by their respective companies.

\* **RoHS 2011/65/EU Compliant** means that the product or part does not contain any of the substances in excess of the maximum concentration values ("MCVs") in EU RoHS Directive 2011/65/EU. The MCVs are by weight in homogeneous materials. This information represents 3M's knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

In the event any product is proven not to conform with 3M's Regulatory Information, then 3M's entire liability and Buyer's exclusive remedy will be in accordance with the Warranty section.

\*\*Lead-free means that the product has less than 2 ppm of lead when tested by ICP-AES, with reference to EPA method 3051A/3052.



### Electronic Solutions Division Static Control Products

926 JR Industrial Drive  
Sanford, NC 27332-9733  
Toll-Free: 866-722-3736  
International: 919-718-0000  
Email: 3mstaticinfo@mmm.com  
www.3mstatic.com

### Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

### Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for one year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331