


## High efficiency ultrafast diode

### Features

- Very low conduction losses
- Negligible switching losses
- Low forward and reverse recovery times
- High junction temperature

### Description

The STTH2R06 uses ST Turbo 2 600 V planar Pt doping technology. It is specially suited for switching mode base drive and transistor circuits. Packaged in axial, SMA, SMB and SMC, this device is intended for use in high frequency inverters, free wheeling and polarity protection.



**Table 1. Device summary**

| Symbol               | Value  |
|----------------------|--------|
| $I_{F(AV)}$          | 2 A    |
| $V_{RRM}$            | 600 V  |
| $T_j$                | 175 °C |
| $V_F(\text{typ})$    | 1.0 V  |
| $t_{rr}(\text{typ})$ | 35 ns  |

# 1 Characteristics

**Table 2. Absolute ratings (limiting values)**

| Symbol              | Parameter                            |                    |                                     | Value        | Unit |
|---------------------|--------------------------------------|--------------------|-------------------------------------|--------------|------|
| V <sub>RRM</sub>    | Repetitive peak reverse voltage      |                    |                                     | 600          | V    |
| I <sub>F(RMS)</sub> | Forward rms current                  |                    |                                     | 7            | A    |
| I <sub>F(AV)</sub>  | Average forward current δ = 0.5      | DO-41              | T <sub>L</sub> = 70 °C              | 2            | A    |
|                     |                                      | SMA                | T <sub>L</sub> = 85 °C              |              |      |
|                     |                                      | SMB                | T <sub>L</sub> = 100 °C             |              |      |
|                     |                                      | SMC                | T <sub>L</sub> = 115 °C             |              |      |
| I <sub>FSM</sub>    | Surge non repetitive forward current | DO-41              | t <sub>p</sub> = 10ms<br>sinusoidal | 40           | A    |
|                     |                                      | SMA / SMB /<br>SMC |                                     | 30           |      |
| T <sub>stg</sub>    | Storage temperature range            |                    |                                     | -65 to + 175 | °C   |
| T <sub>j</sub>      | Operating junction temperature range |                    |                                     | -40 to + 175 | °C   |

**Table 3. Thermal resistance**

| Symbol        | Parameter        |       |                   | Maximum | Unit                 |
|---------------|------------------|-------|-------------------|---------|----------------------|
| $R_{th(j-l)}$ | Junction to lead | DO-41 | $L = 5\text{ mm}$ | 35      | $^{\circ}\text{C/W}$ |
|               |                  | SMA   |                   | 30      |                      |
|               |                  | SMB   |                   | 25      |                      |
|               |                  | SMC   |                   | 20      |                      |

**Table 4. Static electrical characteristics**

| Symbol      | Parameter               | Test conditions                     |                    | Min. | Typ. | Max. | Unit          |
|-------------|-------------------------|-------------------------------------|--------------------|------|------|------|---------------|
| $I_R^{(1)}$ | Reverse leakage current | $T_j = 25\text{ }^{\circ}\text{C}$  | $V_R = V_{RRM}$    | -    | -    | 2    | $\mu\text{A}$ |
|             |                         | $T_j = 150\text{ }^{\circ}\text{C}$ |                    | -    | 12   | 85   |               |
| $V_F^{(2)}$ | Forward voltage drop    | $T_j = 25\text{ }^{\circ}\text{C}$  | $I_F = 2\text{ A}$ | -    | -    | 1.7  | V             |
|             |                         | $T_j = 150\text{ }^{\circ}\text{C}$ |                    | -    | 1.0  | 1.25 |               |

1. Pulse test:  $t_p = 5\text{ ms}$ ,  $\delta < 2\%$

2. Pulse test:  $t_p = 380\text{ }\mu\text{s}$ ,  $\delta < 2\%$

To evaluate the maximum conduction losses use the following equation:

$$P = 1 \times I_{F(AV)} + 0.125 I_{F(RMS)}^2$$

Table 5. Dynamic electrical characteristics

| Symbol   | Parameter                | Test conditions                    |                                                                                                | Min. | Typ. | Max. | Unit |
|----------|--------------------------|------------------------------------|------------------------------------------------------------------------------------------------|------|------|------|------|
| $t_{rr}$ | Reverse recovery time    | $T_j = 25\text{ }^{\circ}\text{C}$ | $I_F = 0.5\text{ A}$ , $I_{rr} = 0.25\text{ A}$ ,<br>$I_R = 1\text{ A}$                        | -    | -    | 30   | ns   |
|          |                          |                                    | $I_F = 1\text{ A}$ ,<br>$di_F/dt = -50\text{ A}/\mu\text{s}$<br>$V_R = 30\text{ V}$            | -    | 35   | 50   |      |
| $t_{fr}$ | Forward recovery time    | $T_j = 25\text{ }^{\circ}\text{C}$ | $I_F = 2\text{ A}$ ,<br>$di_F/dt = 100\text{ A}/\mu\text{s}$<br>$V_{FR} = 1.1 \times V_{Fmax}$ | -    | -    | 100  | ns   |
| $V_{FP}$ | Forward recovery voltage |                                    |                                                                                                | -    | -    | 10   | V    |

Figure 1. Conduction losses versus average forward current




Figure 2. Forward voltage drop versus forward current




Figure 3. Relative variation of thermal impedance junction to case versus pulse duration




Figure 4. Peak reverse recovery current versus  $di_F/dt$  (typical values)




Figure 5. Reverse recovery time versus  $di_F/dt$  (typical values)




Figure 6. Reverse recovery charges versus  $di_F/dt$  (typical values)




Figure 7. Relative variations of dynamic parameters versus junction temperature




Figure 8. Transient peak forward voltage versus  $di_F/dt$  (typical values)




Figure 9. Forward recovery time versus  $di_F/dt$  (typical values)




Figure 10. Junction capacitance versus reverse voltage applied (typical values)




Figure 11. Thermal resistance junction to ambient versus copper surface under each lead





Figure 12. Thermal resistance versus lead length (DO-41)



## 2 Package information

- Epoxy meets UL 94, V0
- Band indicates cathode
- Bending method (DO-41): see Application note AN1471

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK® is an ST trademark.

**Table 6. DO-41 (plastic) dimensions**

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A    | 4.07        | 5.20 | 0.160  | 0.205 |
| B    | 2.04        | 2.71 | 0.080  | 0.107 |
| C    | 25.4        |      | 1      |       |
| D    | 0.71        | 0.86 | 0.028  | 0.034 |

**Table 7. SMA dimensions**

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A1   | 1.90        | 2.45 | 0.075  | 0.094 |
| A2   | 0.05        | 0.20 | 0.002  | 0.008 |
| b    | 1.25        | 1.65 | 0.049  | 0.065 |
| c    | 0.15        | 0.40 | 0.006  | 0.016 |
| D    | 2.25        | 2.90 | 0.089  | 0.114 |
| E    | 4.80        | 5.35 | 0.189  | 0.211 |
| E1   | 3.95        | 4.60 | 0.156  | 0.181 |
| L    | 0.75        | 1.50 | 0.030  | 0.059 |

Figure 13. Footprint (dimensions in mm)



Table 8. SMB dimensions

| Ref. | Dimensions  |      |        |       |
|------|-------------|------|--------|-------|
|      | Millimeters |      | Inches |       |
|      | Min.        | Max. | Min.   | Max.  |
| A1   | 1.90        | 2.45 | 0.075  | 0.096 |
| A2   | 0.05        | 0.20 | 0.002  | 0.008 |
| b    | 1.95        | 2.20 | 0.077  | 0.087 |
| c    | 0.15        | 0.40 | 0.006  | 0.016 |
| D    | 3.30        | 3.95 | 0.130  | 0.156 |
| E    | 5.10        | 5.60 | 0.201  | 0.220 |
| E1   | 4.05        | 4.60 | 0.159  | 0.181 |
| L    | 0.75        | 1.50 | 0.030  | 0.059 |

Figure 14. Footprint (dimensions in mm)




Table 9. SMC dimensions

| Ref.             | Dimensions  |      |        |       |
|------------------|-------------|------|--------|-------|
|                  | Millimeters |      | Inches |       |
|                  | Min.        | Max. | Min.   | Max.  |
| A1               | 1.90        | 2.45 | 0.075  | 0.096 |
| A2               | 0.05        | 0.20 | 0.002  | 0.008 |
| b <sup>(1)</sup> | 2.90        | 3.20 | 0.114  | 0.126 |
| c <sup>(1)</sup> | 0.15        | 0.40 | 0.006  | 0.016 |
| D                | 5.55        | 6.25 | 0.218  | 0.246 |
| E                | 7.75        | 8.15 | 0.305  | 0.321 |
| E1               | 6.60        | 7.15 | 0.260  | 0.281 |
| E2               | 4.40        | 4.70 | 0.173  | 0.185 |
| L                | 0.75        | 1.50 | 0.030  | 0.059 |

1. Dimensions b and c apply to plated leads

Figure 15. Footprint, dimensions in mm (inches)



### 3 Ordering information

**Table 10. Ordering information**

| Order code | Marking  | Package | Weight  | Base qty | Delivery mode |
|------------|----------|---------|---------|----------|---------------|
| STTH2R06   | STTH2R06 | DO-41   | 0.34 g  | 2000     | Ammopack      |
| STTH2R06RL | STTH2R06 | DO-41   | 0.34 g  | 5000     | Tape and reel |
| STTH2R06A  | R6A      | SMA     | 0.068 g | 5000     | Tape and reel |
| STTH2R06U  | R6U      | SMB     | 0.11 g  | 2500     | Tape and reel |
| STTH2R06S  | R62      | SMC     | 0.243 g | 2500     | Tape and reel |

### 4 Revision history

**Table 11. Document revision history**

| Date        | Revision | Changes                                             |
|-------------|----------|-----------------------------------------------------|
| 07-Sep-2004 | 1        | First issue                                         |
| 1-Jun-2005  | 2        | SMC package addition.                               |
| 30-Sep-2009 | 3        | Updated <a href="#">Table 6</a> package dimensions. |
| 04-Dec-2009 | 4        | Updated <a href="#">Table 9</a> package dimensions. |

**Please Read Carefully:**

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

**UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.**

**UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.**

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

[www.st.com](http://www.st.com)



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331