

12mm Insulated Shaft Rotary Encoder

Application

- ✓ Audio, Home appliance, Precision apparatus,
Automotive, Communication, Industrial control, etc.

Feature

- ✓ Incremental Output Signal Encoder



■Specification

Rotation Angle	360° endless
Rating	5V DC 0.5mA
Operating Temperature	-10 °C~70 °C
Rotational Torque	30 ~ 150 gf.cm
Rotational Life	15,000 cycles
Switch Circuit	S.P.S.T. (Push on)
Switch Stroke	0.5 mm
Switch Rating	5V DC 1mA
Switch Operating Force	200 ~ 460 gf.cm
Switch Operating Life	20,000 cycles

■How to order

RE130F – 40 – 20F – 12P

[Model](#)

[Resolution](#)

Code	Model	Pulses	Detents
12P	RE130	12	12
24P	RE120	24	24

Shaft

Terminal Type

Code	Terminal type	Push Switch
40	Vertical	Without switch
41	Vertical	With switch




Code	Bushing Type (D)		Bushing Thread
None	Ø6.8mm	5mm	Without thread
E3	Ø9mm	7mm	With thread

E3 Just for Terminal code '40'

12mm Insulated Shaft Rotary Encoder

Model Description




Model	Terminal Type	Push Switch	Bushing Type (D)		Bushing Thread
RE130F-40	Vertical	Without switch	Ø6.8mm	5mm	Without thread
RE120F-40	Vertical	Without switch	Ø6.8mm	5mm	Without thread
RE130F-41	Vertical	With switch	Ø6.8mm	5mm	Without thread
RE12CF-41	Vertical	With switch	Ø6.8mm	5mm	Without thread
RE130F-40E3	Vertical	Without switch	Ø9mm	7mm	With thread
RE120F-40E3	Vertical	Without switch	Ø9mm	7mm	With thread

Order Code	Outline Drawing																										
RE130F-40-(L)F-12P RE120F-40-(L)F-24P	  RE130F <table><tr><td>L</td><td>17.5</td><td>20</td><td>25</td></tr><tr><td>F</td><td>5</td><td>7</td><td>12</td></tr></table> RE120F <table><tr><td>L</td><td>17.5</td><td>20</td><td>22.5</td><td>25</td><td>30</td></tr><tr><td>F</td><td>5</td><td>7</td><td>7</td><td>12</td><td>12</td></tr></table>					L	17.5	20	25	F	5	7	12	L	17.5	20	22.5	25	30	F	5	7	7	12	12		
L	17.5	20	25																								
F	5	7	12																								
L	17.5	20	22.5	25	30																						
F	5	7	7	12	12																						
RE130F-41-(L)F-12P RE12CF-41-(L)F-24P	  RE130F <table><tr><td>L</td><td>17.5</td><td>20</td><td>25</td><td>30</td></tr><tr><td>F</td><td>5</td><td>7</td><td>12</td><td>12</td></tr></table> RE120F <table><tr><td>L</td><td>17.5</td><td>20</td><td>22.5</td><td>25</td><td>30</td></tr><tr><td>F</td><td>5</td><td>7</td><td>7</td><td>12</td><td>12</td></tr></table>					L	17.5	20	25	30	F	5	7	12	12	L	17.5	20	22.5	25	30	F	5	7	7	12	12
L	17.5	20	25	30																							
F	5	7	12	12																							
L	17.5	20	22.5	25	30																						
F	5	7	7	12	12																						
RE130F-40E3-(L)F-12P RE120F-40E3-(L)F-24P	  RE130F <table><tr><td>L</td><td>15</td><td>17.5</td><td>20</td><td>25</td></tr><tr><td>F</td><td>7</td><td>7</td><td>12</td><td>12</td></tr></table> RE120F <table><tr><td>L</td><td>15</td><td>17.5</td><td>20</td><td>25</td></tr><tr><td>F</td><td>7</td><td>7</td><td>12</td><td>12</td></tr></table>					L	15	17.5	20	25	F	7	7	12	12	L	15	17.5	20	25	F	7	7	12	12		
L	15	17.5	20	25																							
F	7	7	12	12																							
L	15	17.5	20	25																							
F	7	7	12	12																							

[Back to top](#)

12mm Insulated Shaft Rotary Encoder

■Resolution and Output Signal

Model	Resolution (Pulses/Rotation)	Detent Number	Output Signal Format		
			Shaft Rotational Direction	Signal	Output
RE130	12/360°	12	C.W.	A (Terminal A-C)	OFF ON 
				B (Terminal B-C)	OFF ON 
RE120	24/360°	24	C.W.	A (Terminal A-C)	OFF ON 
				B (Terminal B-C)	OFF ON 

Design and specifications presented here are for the standard parts only. Please kindly contact us for your special requests and ask for the current technical specifications before purchase and/or use.

[Back to top](#)

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Alpha \(Taiwan\):](#)

[RE130F-41-175F-12P](#) [RE130F-40-20F-12P](#) [RE130F-40E3-15F-12P-037](#) [RE12CF-41-20F-24P](#)



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331