
Data Sheet

AKU240 Family
Top port, Digital Silicon MEMS Microphones

AKUSTICA
Bosch Group



Data Sheet


Part number(s)	AKU240, AKU241, AKU242
Package type	8-pin LGA top port
Data sheet revision	1.01
Release date	23 December 2014
Document number	DS45-1.01 AKU240 Family Data Sheet
Notes	Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

AKU240 Family
Digital, HD Voice Silicon MEMS Microphones

General Description

AKU240 family consists of HD Voice quality, top port, digital output silicon MEMS IC microphones. They are microphones consisting of a MEMS acoustic sensor, and an integrated circuit (IC) with a pre-amplifier, analog-to-digital converter, charge pump and supporting circuitry in a small 4.0 x 3.0 x 1.0 mm^3 package.
The robust digital output stream from the



AKU240 family is virtually immune to all forms of Radio Frequency Interference (RFI) and Electromagnetic Interference (EMI), allowing designers the flexibility to integrate the component anywhere on the platform and obtain consistent SNR regardless of proximity to displays, Wi-Fi antennae, or other sources of interference that would degrade the signal of conventional analog microphones.
The devices in this family provide a pulse density modulated (PDM), single-bit digital stream designed to enable the multiplexing of stereo microphone data onto a single wire. With a user selectable L/R channel option, it is ideal for use in multiple microphone applications.

Key Features

- Digital PDM output
- Omni-directional audio sensor
- Excellent acoustic performance: 63dB SNR
- Sensitivity: -26dBFS
- Tightly controlled sensitivity tolerances:
    - AKU240: ± 2dB
    - AKU241: ± 1dB
    - AKU242: ± 1.5dB
- Compatible with Microsoft® Windows®, LYNC® & Skype® logo certifications, Intel® Ultrabook™ and Google® Chromebook™ requirements for digital microphones
- Robust digital-output & Faraday-cage constructed package immune to RF/EM interference
- Matched microphones in frequency and phase response for array applications
- Output supports dual-microphone, single-wire multiplexing
- Industry standard microphone interface compatible with multiple codecs
- Low current power-down mode
- Lead-free surface-mountable and RoHS2 compliant
- Halogen-free compliance, IEC61249-2-21
- Thin profile, SMT packaging
- Industry std. package: 4.00x3.00x1.00mm^3

Typical Applications

- Ultrabooks
- Mobile phones
- Media tablets
- eReaders
- Microphone arrays
- Webcams and camera modules

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

Index of Contents

1. ABSOLUTE MAXIMUM RATINGS....4

2. STANDARD OPERATING CONDITIONS....4

3. ELECTRICAL AND ELECTRO-ACOUSTIC SPECIFICATIONS....4

3.1 Timing Characteristics
3.2 Digital Logic Characteristics
3.3 Sleep Mode, and Active Mode
3.4 Radio Frequency Interference (RFI) Immunity

4. DEVICE CHARACTERISTICS....7-8

4.1 Typical Frequency Response
4.2 I_{DD} vs. V_{DD}
4.3 Sensitivity vs. V_{DD}
4.4 I_{DD} vs. Clock Frequency
4.5 Sensitivity vs. Temperature
4.6 PSR vs. Frequency

6. PIN-OUT AND CONNECTION DIAGRAMS....9

6.1 Pin Out
6.2 Schematic

7. MANUFACTURING NOTES....10-12

7.1 Solder Reflow
7.2 Part Handling
7.3 PCB Land Pattern & Stencil Pattern

8. RELIABILITY SPECIFICATIONS....13

9. PART MARKING INFORMATION....13

10. PACKAGING INFORMATION....14

11. ORDERING INFORMATION....15

12. DOCUMENT REVISIONS....15

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

1. ABSOLUTE MAXIMUM RATINGS

Supply Voltage, V_{DD} to GND	5.5V
ESD Tolerance	
Human Body Model	2000V
Machine Model	200V
Storage Temperature Range	-40°C to 105°C

2. STANDARD OPERATING CONDITIONS

Operating Temperature Range	-40°C to 85°C
Supply Voltage (V_{DD})	1.62V to 3.6V
Clock Frequency	1.00MHz to 3.25MHz

3. ELECTRICAL AND ELECTRO-ACOUSTIC SPECIFICATIONS

Unless otherwise noted, test conditions are:
V_{DD} = 1.8V Ta = 25°C RH = 50% CLK = 2.4MHz

Parameter		Test Conditions	Min.	Typ.	Max.	Unit
Directivity			Omni-directional			
Signal to Noise Ratio (SNR)		f_{in} = 1kHz, A-weighted, 20Hz-10kHz		63		dB
Low Frequency Corner[1]		-3dB from 1kHz sensitivity value		50	100	Hz
High Frequency Corner		+3dB from 1kHz sensitivity value		11		kHz
Sensitivity[1]	AKU240	1kHz, 94dB SPL, full-scale = 100% 1's density at PDM output of microphone	-28	-26	-24	dBFS
	AKU241		-27	-26	-25	
	AKU242		-27.5	-26	-24.5	
Total Harmonic Distortion[1] (THD)		@ 100dB SPL, f_{in} = 1kHz			1	%
		@ 110dB SPL, f_{in} = 1kHz			5	
Acoustic Overload Point (AOP)		< 10% THD, f_{in} = 1 kHz		116		dBSPL
Power Supply Rejection (PSR)		Signal on V_{DD} = 217Hz, 100mV_{pp}		-73		dBFS
Part-to-part phase matching from nominal		f_{in} = 1kHz			± 10	°
Current Consumption[1] (with no load)	AKU240/242	Clock on (CLK = 2.8MHz)		800	930	µA
	AKU241			865	1020	µA
		Clock off		5	7	µA
Power-up initialization		Data invalid time from clock on			28	ms
Polarity		Increasing sound pressure	Increasing 1's density			


Note 1: Max. value of parameter 100% tested

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

3.1 Timing Characteristics

(Typical performance with load capacitance <20pF and a clock frequency of 2.4MHz)

	Typical Mode	Data Valid	Data Sampled	L/R SELECT Connected to
$DATA_L$	Left	Falling clock	Rising clock	GND
$DATA_R$	Right	Rising clock	Falling clock	V_{DD}



Output	Parameter	Typical Value	Description
$DATA_R$	**t_1**	6ns	Time from falling edge of clock until data becomes high impedance
$DATA_L$	**t_2**	61ns	Time from falling edge of clock until data becomes valid
$DATA_L$	**t_3**	6ns	Time from rising edge of clock until data becomes high impedance
$DATA_R$	**t_4**	53ns	Time from rising edge of clock until data becomes valid

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

3.2 Digital Logic Characteristics

(Typical performance with load capacitance <20pF and a clock frequency of 2.4MHz)

Symbol	Parameter	Min	Max	Units
$V_{IL\ MAX}$	Maximum level considered a logic 0		$0.4*V_{DD}$	V
$V_{IH\ MIN}$	Minimum level considered a logic 1	$0.5*V_{DD}$		V
$V_{OL\ MAX}$	Maximum level a driven output logic 0 can be		$0.05*V_{DD}$	V
$V_{OH\ MIN}$	Minimum level a driven output logic 1 can be	$0.95*V_{DD}$		V

3.3 Sleep Mode, and Active Mode

The AKU24X enters Sleep Mode within 5µS of the clock signal becoming inactive (i.e. clock frequency = 0Hz).


In Sleep Mode the microphone PDM Data output pin is in high impedance state.

The microphone returns from Sleep Mode to Active Mode 65,536 cycles after the clock becomes active (i.e. clock frequency ≥ 1.0MHz). With a 3.072MHz clock, the microphone start-up time is 21.4ms; for a 2.4MHz clock the microphone start-up time is 27.4ms.

3.4 Radio Frequency Interference (RFI) Immunity

The AKU240 family is virtually immune to all forms of Radio Frequency Interference (RFI) and Electromagnetic Interference (EMI). Select devices in the family have additional built-in RF filter(s), as shown in the microphone block diagram below.

Please refer to the ordering information table in section 11, for available device options.




© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

4. DEVICE CHARACTERISTICS


4.1 Frequency Response

(Measured frequency response normalized to 1kHz)




4.2 I_{DD} vs. V_{DD}

(Measured current consumption relative to supply voltage)




4.3 Sensitivity vs. VDD

(Measured sensitivity changes relative to supply voltage)




4.4 I_{DD} vs. Clock Frequency

(Measured current consumption relative to clock frequency)




4.5 Sensitivity vs. Temperature

(Typical sensitivity changes relative to temperature)



4.6 PSR vs. Frequency


(Typical PSR relative to frequency)



© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

5. MECHANICAL SPECIFICATIONS

Bottom View | Top View | Side View




Item	Dimension	Tolerance	Units
Length (L)	4.00	± 0.10	mm
Width (W)	3.00	± 0.10	mm
Height (H)	1.00	± 0.10	mm
Acoustic Port (AP)	0.400	± 0.10	mm
Solder Mask (SRO)	0.700	± 0.05	mm
Planarity	Top/Bottom	± 0.10	mm
All dimensions in mm Tolerance ± 0.05mm unless otherwise specified			

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

6. PIN-OUT AND CONNECTION DIAGRAMS

6.1 Pin-Out


(As viewed from **bottom** of package)



Pin	Name	Function
1	V_{DD}	Power
2	L/R*	Left / Right Select
3	CLK	Clock
4	DATA	PDM Data output
5, 6, 7, 8	GND	Ground

*Must be electrically connected to either ground or V_{DD}.

6.2 Typical Application Schematic



Value of termination resistor (R_T) is dependent on system design and location of resistor (near codec or near mic).


Contact support@akustica.com for more information.

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

7. MANUFACTURING NOTES

7.1 Solder Reflow

Typical solder reflow profile



Average ramp-up rate	max. 3°C/s
Time t_s between Ts_{min} (150°C) and Ts_{max} (200°C)	60s – 120s
Time t_L above liquidous temperature T_L (217°C)	60s – 90s
Peak temperature T_P	max. 260°C
Time t_P at T_P	max. 20s
Average ramp-down rate	max. 6°C/s

Note: It is recommended to fine-tune the reflow process to optimize for variations in materials, environment, handling, PCB board size and thickness, etc.

Please refer to AN60-Handling, Soldering, and Mounting Instructions for more detailed information and precautions.

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

7.2. Microphone Handling

Although the microphone may not appear damaged immediately due to inappropriate handling, there can be long term effects that affect the lifetime of the component.

Rule of thumb: The microphone is an artificial ear so treat it like your own ear.

- Do not blow air into the acoustic port of the microphone for any reason. Do not subject it to pressurized air
  - e.g. when cleaning the board or other components on the same board
- Do not apply vacuum to acoustic port of the microphone
  - See section 5.0 for pick & place location
- Do not insert liquids
  - If populated circuit boards are washed, the microphone must be protected
- Do not insert dust
  - The production facilities must be clean
  - e.g. if PCB routing/sawing is done close to the microphone after SMT assembly and reflow
- Do not insert any objects
  - If assembly or rework is done manually, care must be taken that the tools cannot enter the microphone sound port
  - It is best to choose tool size so that it does not fit through the sound port of the microphone
- Do not cover the acoustic port with tape when heating during assembly or reflow
- Do not apply extreme mechanical stresses on the microphone, including mechanical shocks above 10kG or compression of the microphone package.
- After a bottom port microphone has been assembled on a circuit board, protect the sound port (now on the other side of the board) from dust, liquids, and other foreign materials as well as any tools and pressurized air.

ESD Handling Procedures




Follow CMOS handling procedures with Akustica MEMS microphones. Handle the microphone with proper workplace grounding to include wrist straps and ionized airflow over open trays and reels of microphones. Do not hot-swap/hot-plug during testing. Device pins have ESD ratings of 2kV/200V for HBM/MM respectively.


© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

7.3 PCB Land Pattern & Stencil Pattern

PCB Land Pattern Layout



Suggested Solder Paste Stencil Pattern Layout



Note: Stencil printer settings will likely require minor optimizations when transferring this stencil pattern to a high volume production printer.

Please refer to AN60-Handling, Soldering, and Mounting Instructions for more detailed information and precautions.

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

8. RELIABILITY SPECIFICATIONS

The microphone sensitivity after stress must deviate by no more than 3dB from the initial value.

	Test	Test Condition
1	Cold Temp Operation	Temperature = -40°C, 1000 hours (with bias)
2	Hot Temp Operation	Temperature = 105°C, 1000 hours (with bias)
3	Humidity Operation	Temperature = 85°C, RH = 85%, 1000 hours (with bias)
4	Cold Temp Storage	Temperature = -40°C, 1000 hours (without bias)
5	Hot Temp Storage	Temperature = 105°C, 1000 hours (without bias)
6	Humidity Storage	Temperature = 85°C, RH = 85%, 1000 hours (without bias)
7	Thermal Cycle	100 Cycles, -40°C to +125°C, 15min soaks, <30sec ramps
8	Vibration	Sinusoidal Vibration, 20Hz-2000Hz, 4min sweeps, 16min along each of 3 axis, amplitude 3 limits of 20G and 0.06”
9	Mechanical Shock	10,000G shocks, 5 impacts along each of 6 axes
10	Drop Test	Using 150gm aluminum fixture, 3 drops along each of 6 axes (total 18 drops) from 1.5m height onto concrete drop surface.
11	ESD (HBM)	+/- 2000V, 1 discharge for each polarity, 11 pin combinations, 22 total discharges per microphone
12	ESD (MM)	+/- 200V, 1 discharge for each polarity, 11 pin combinations, 22 total discharges per microphone
13	ESD	+/- 8kV, contact discharge to lid with DUT grounded
14	Moisture Sensitivity Level	24 hour bake at 125°C, followed by 168 hours at 85°C, 85%RH, followed by 3 passes solder reflow (MSL Level 1)

9. PART MARKING INFORMATION




Line 1: A24XF (A = Akustica | 24X = Part Num | X = 0, 1, 2 | F = Assembly Facility)
Line 2: WWYLL (WW = Work Week | Y = Year | LL = Lot Number Processed During Work Week)

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

10. PACKAGING INFORMATION


10.1 Tape Specification



Ao = 4.30
Bo = 3.20
Ko = 1.30

Notes:
1. 10 sprocket hole pitch cumulative tolerance +/- 0.2
2. Camber in compliance with EIA-481
3. Pocket position relative to sprocket hole measured as true position of pocket, not pocket hole

10.2 Component Orientation



© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

11. ORDERING INFORMATION

Order Number	Sensitivity Tolerance (dB)	RF Filter	Part Marking	Package	Shipping Method	Standard Quantity
02730A0006* 02730A0007*	+/- 2	No	A240	8-Pad LGA	13” Reel	5,700
02730A0029	+/- 1	Yes	A241			
02730A0019	+/- 1.5	No	A242			

*Not recommended for new designs

12. DOCUMENT REVISIONS

Rev. No	Description of modification/changes	Date
0.75	Released 0.75.	26-Aug-14
0.76	Updated first page description	25-Sep-14
0.77	Updated sensitivity tolerance	06-Oct-14
0.78	Updated current consumption	20-Oct-14
1.0	Released 1.0	06-Nov-14
1.01	Updated section 4	23-Dec-14

Akustica, Inc.
2835 E Carson St. Suite 301
Pittsburgh, PA / USA 15203

sales@akustica.com
www.akustica.com

Modifications reserved | Printed in USA
Specifications subject to change without notice

© Akustica, Inc. reserves all rights even in the event of industrial property rights. We reserve all rights of disposal such as copying and passing on to third parties. Bosch Group and the symbol are registered trademarks of Robert Bosch GmbH, Germany. Note: Specifications within this document are subject to change without notice.

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331