REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	04/20/07	A.D.M.
B	ECO #6647	04/25/07	D.N.

PROPRIETARY INFORMATION
NOT TO BE RELEASED
WITHOUT WRITTEN PERMISSION
FROM AN AUTHORIZED
REPRESENTATIVE OF
APPLIED ENGINEERING PRODUCTS





NOTES:

MATERIALS:

1. BODY = STAINLESS STEEL PER ASTM A582, ALLOY 303, CONDITION "A".
2. INSULATORS = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
3. CONTACT = BERYLLIUM COPPER PER ASTM B196, ALLOY C17300, TEMPER TD04.
4. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:

1. BODY = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .000050 TO .00010 STRESS FREE NICKEL PER QQ-N-290.
2. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.
3. ALL OTHER METAL PARTS = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .00010 TO .00020 COPPER STRIKE PER MIL-C-14550.

ELECTRICAL:

INSERTION LOSS = $.03 \times \sqrt{F(GHz)}$ MAX TEST FREQUENCY 6 GHz.
VSWR = 1.15+(.020xF[GHz]), DC-12.4 GHz.
IMPEDANCE = 50 ohms.
FREQUENCY RANGE = DC TO 18GHz, DEPENDENT ON CABLE TYPE & CONFIGURATION.

ENVIRONMENTAL:

VIBRATION: METHOD 204, TEST CONDITION D.
MECHANICAL SHOCK = METHOD 213, CONDITION I.
THERMAL SHOCK = METHOD 107, CONDITION B.
CORROSION = METHOD 101, CONDITION B, 5% SALT SOLUTION.
MOISTURE RESISTANCE = METHOD 106.
CORONA LEVEL = CORONA FREE @ 70,000 FEET, VOLTAGE DEPENDENT ON CABLE SIZE.
TEMPERATURE RATING = -65°C TO +165°C.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON	DWN: A.D.M.	DATE 04/20/07	APPLIED ENGINEERING PRODUCTS, a RADIALL company, 104 John W. Murphy Dr. New Haven, CT 06513
DECIMAL / ANGLE	CHKD: D.N.	DATE 04/20/07	SMA STRAIGHT JACK CLAMP TYPE FOR RG-55 & SIMILAR CABLES
	APVD: J.M.	DATE 04/20/07	

REFERENCE: ORIGINATED: A.D.M. DATE: 04/20/07	MATERIALS & FINISHES: SEE NOTES	SIZE A	FSCM NO. 19505	DWG NO. 9202-1553-001	REV B
		SCALE 5:1	THIRD ANGLE PROJECTION	SHEET 1 OF 1	

9202-1553-001

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331