



TSM4NB65

650V N-Channel Power MOSFET

TO-220



ITO-220




Pin Definition:

1. Gate
2. Drain
3. Source


Key Parameter Performance

Parameter	Value	Unit
V_{DS}	650	V
$R_{DS(on)}$ (max)	3.37	Ω
Q_g	13.46	nC

TO-251
(IPAK)



TO-252
(DPAK)



Application


- Power Supply.
- Lighting

Ordering Information

Part No.	Package	Packing
TSM4NB65CZ C0G	TO-220	50pcs / Tube
TSM4NB65CI C0G	ITO-220	50pcs / Tube
TSM4NB65CH C5G	TO-251	75pcs / Tube
TSM4NB65CP ROG	TO-252	2.5kpcs / 13" Reel

Note: "G" denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

Block Diagram



N-Channel MOSFET

Absolute Maximum Ratings ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Parameter	Symbol	Limit			Unit
		IPAK/DPAK	ITO-220	TO-220	
Drain-Source Voltage	V_{DS}	650			V
Gate-Source Voltage	V_{GS}	± 30			V
Continuous Drain Current ^(Note 1)	I_D	4			A
		2.4			A
Pulsed Drain Current ^(Note 2)	I_{DM}	16			A
Single Pulse Avalanche Energy ^(Note 3)	E_{AS}	31.2			mJ
Total Power Dissipation @ $T_C = 25^\circ\text{C}$	P_{TOT}	50	25	70	W
Operating Junction Temperature	T_J	-55 to +150			$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-55 to +150			$^\circ\text{C}$

Thermal Performance

Parameter	Symbol	Limit			Unit
		IPAK/DPAK	ITO-220	TO-220	
Thermal Resistance - Junction to Case	$R_{\theta JC}$	2.5	5	1.78	$^{\circ}\text{C/W}$
Thermal Resistance - Junction to Ambient	$R_{\theta JA}$	83	62.5	62.5	$^{\circ}\text{C/W}$

Electrical Specifications ($T_A=25^{\circ}\text{C}$ unless otherwise noted)


Parameter	Conditions	Symbol	Min	Typ	Max	Unit
Static ^(Note 4)						
Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	BV _{DSS}	650	--	--	V
Drain-Source On-State Resistance	V _{GS} = 10V, I _D = 2A	R _{DS(ON)}	--	2.7	3.37	Ω
Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	V _{GS(TH)}	2.5	3.6	4.5	V
Zero Gate Voltage Drain Current	V _{DS} = 650V, V _{GS} = 0V	I _{DSS}	--	--	1	μA
Gate Body Leakage	V _{GS} = ±30V, V _{DS} = 0V	I _{GSS}	--	--	±100	nA
Forward Transfer Conductance	V _{DS} = 40V, I _D = 2A	g _{fs}	--	2.6	--	S
Dynamic ^(Note 5)						
Total Gate Charge	V _{DS} = 480V, I _D = 4A, V _{GS} = 10V	Q _g	--	13.46	--	nC
Gate-Source Charge		Q _{gs}	--	2.98	--	
Gate-Drain Charge		Q _{gd}	--	6.66	--	
Input Capacitance	V _{DS} = 25V, V _{GS} = 0V, f = 1.0MHz	C _{iss}	--	549	--	pF
Output Capacitance		C _{oss}	--	75	--	
Reverse Transfer Capacitance		C _{rss}	--	18	--	
Switching ^(Note 6)						
Turn-On Delay Time	V _{GS} = 10V, I _D = 4A, V _{DD} = 300V, R _G = 25Ω	t _{d(on)}	--	11	--	ns
Turn-On Rise Time		t _r	--	20	--	
Turn-Off Delay Time		t _{d(off)}	--	30	--	
Turn-Off Fall Time		t _f	--	19	--	
Source-Drain Diode Ratings and Characteristic ^(Note 4)						
Source Current	Integral reverse diode in the MOSFET	I _S	--	--	4	A
Source Current (Pulse)		I _{SM}	--	--	16	A
Diode Forward Voltage	I _S = 4A, V _{GS} = 0V	V _{SD}	--	--	1.13	V

Notes:


- Current limited by package
- Pulse width limited by the maximum junction temperature
- $L = 10\text{mH}, I_{AS} = 2.4\text{A}, V_{DD} = 50\text{V}, R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$
- Pulse test: $PW \leq 300\mu\text{s}$, duty cycle $\leq 2\%$
- For DESIGN AID ONLY, not subject to production testing.
- Switching time is essentially independent of operating temperature.

Electrical Characteristics Curves


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature



Source-Drain Diode Forward Current vs. Voltage




TSM4NB65


650V N-Channel Power MOSFET

Electrical Characteristics Curves


Capacitance vs. Drain-Source Voltage




BV_{DSS} vs. Junction Temperature




Maximum Safe Operating Area (TO-220)



Maximum Safe Operating Area (ITO-220)




Maximum Safe Operating Area (DPAK/IPAK)




Electrical Characteristics Curves


Normalized Thermal Transient Impedance, Junction-to-Case (TO-220)




Normalized Thermal Transient Impedance, Junction-to-Case (ITO-220)



Normalized Thermal Transient Impedance, Junction-to-Case (DPAK/IPAK)




TO-220 Mechanical Drawing



Unit: Millimeters

Marking Diagram



Y = Year Code

M = Month Code for Halogen Free Product


O =Jan **P** =Feb **Q** =Mar **R** =Apr

S =May **T** =Jun **U** =Jul **V** =Aug

W =Sep **X** =Oct **Y** =Nov **Z** =Dec


L = Lot Code

ITO-220 Mechanical Drawing




Unit: Millimeters

Marking Diagram




G = Halogen Free
Y = Year Code
WW = Week Code (01~52)
F = Factory Code

TO-252 (DPAK) Mechanical Drawing




Unit: Millimeters

Marking Diagram




Y = Year Code
M = Month Code for Halogen Free Product
O =Jan P =Feb Q =Mar R =Apr
S =May T =Jun U =Jul V =Aug
W =Sep X =Oct Y =Nov Z =Dec
L = Lot Code

TO-251 (IPAK) Mechanical Drawing



Unit: Millimeters

Marking Diagram



Y = Year Code
M = Month Code for Halogen Free Product
O = Jan P = Feb Q = Mar R = Apr
S = May T = Jun U = Jul V = Aug
W = Sep X = Oct Y = Nov Z = Dec
L = Lot Code

TSM4NB65

650V N-Channel Power MOSFET

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331