


Precise SMD Temperature Compensated Crystal Oscillators

7.0 x 5.0 x 2.0 mm 7N Series (10 pad)

Features

- High Stability Over Temperature: $\pm 0.14\text{ppm} \sim \pm 0.28\text{ppm}$
- Operating Temperature Range: $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
- Holdover 24Hr: $\pm 0.40\text{ppb}$ (Option)
- Free Run Stability for 20 years: $\pm 4.6\text{ppm}$ (Option)
- Frequency: 10 ~ 52MHz
- Supply Voltage: 2.7V ~ 5.5V
- Voltage Control Function Available
- Output Enable/Disable Function Available
- Support Clipped Sinewave and CMOS Output Waveform
- Application: Small Cell, Base Station, Networking Infrastructure
- ROHS Compliant / Pb Free





Electrical Specifications

Item / Type		7N	
Output Type		Clipped Sinewave	CMOS
Output Load		10K Ω //10pF	15pF
Output Voltage		0.8 Vp-p Min.	Output Low (VOL) 0.1 * Vcc Max. Output High (VOH) 0.9 * Vcc Min.
Supply Current		5 mA Max.	10 mA Max.
Oscillation Mode			Fundamental
Supply Voltage			2.7 ~ 5.5 V
Frequency Range			10 ~ 52 MHz
Initial Frequency Tolerance at 25°C after 2 Reflows			± 2.0 ppm
Frequency Tolerance	Vs. Temperature (- 40 ~ + 85 °C)		$\pm 0.14 / \pm 0.28$ ppm
	Vs. Load (± 5 %)		± 0.1 ppm Max.
	Vs. Supply Voltage (± 5 %)		± 0.1 ppm Max.
Storage Temperature Range			$-55 \sim +125$ °C
Auto Frequency Control Range (Option)			$\pm 5 \sim \pm 16$ ppm (1.5 \pm 1 V)
Start-up Time			2.5 ms Max.
Harmonics			-5 dBc Max.
Phase Noise at 1KHz Offset			-130 dBc/Hz
Aging			± 1 ppm / year Max.
24 Hr Holdover Stability (Option) [#1]			± 40 ppb
Free Run Stability for 20 Years (Option) [#2]			± 4.6 ppm

[#1] 24 hours at constant temperature after 48 hours operation.

[#2] Inclusive of initial tolerance at 25°C , temperature, supply voltage $\pm 5\%$, load $\pm 5\%$, reflow soldering and ageing 20 years.


Dimensions



Pin Connection

Name	Function
Pin 1	NC
Pin 2	NC
Pin 3	NC
Pin 4	GND
Pin 5	Output
Pin 6	NC
Pin 7	NC
Pin 8	Tri-State
Pin 9	VCC
Pin 10	AFC or GND

Recommended Land Pattern



Units: mm



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331