Chip Varistors

Countermeasure for surge voltage and static electricity

AVR series

Type: **AVR-M**
AVRL

Issue date: September 2011

- All specifications are subject to change without notice.
- Conformity to RoHS Directive: This means that, in conformity with EU Directive 2002/95/EC, lead, cadmium, mercury, hexavalent chromium, and specific bromine-based flame retardants, PBB and PBDE, have not been used, except for exempted applications.

Varistors(SMD)


Conformity to RoHS Directive

Countermeasure for Surge Voltage and Static Electricity


AVR Series AVR-M, AVRL Types

Varistors are voltage dependent nonlinear resistive elements with a resistance that decreases rapidly when the voltage is over the constant value.
Varistor is equivalent with Zener diode of two series connection. Therefore, do not have polarity.

CURRENT vs. VOLTAGE CHARACTERISTICS




EQUIVALENT CIRCUIT



THE EFFECT OF THE VARISTOR


WITHOUT VARISTOR

A malfunction and failure of electronic equipment



WITH VARISTOR

Suppress abnormal voltage by inserting varistor in a circuit



FEATURES

- No polarity, due to symmetrical current-voltage characteristics.
  Equivalent to anode common type Zener diode.
- Excellent electrostatic absorption capability.
  Response is as good or better than Zener diode.
  Keeps symmetrical current-voltage characteristics even after electrostatic absorption.
- Adopted the inner electrodes lamination structure.
  Wide range of varistor voltages are available in series (6.8 to 39V).
  Low capacitance items are available in series (1.1pF to).
  World's smallest 0603-, 1005-, 1608-, 2012-chip types and 1410-array type are available in series.
- Excellent mount reliability. Good for Pb-free soldering.
  Adopted (Ni/Sn) electroplating.
  Achieved good solderability and solder heat resistance.
- Can replace a Zener diode + capacitor combination.
  Reduced footprint and total mounting cost.

APPLICATIONS


- Electrostatic absorption
- Pulse noise absorption

TEMPERATURE RANGES


Type	AVR-M1005/1608/2012	AVR-M14A2/0603/AVRL
Operating	–40 to +125°C	–40 to +85°C
Storage	–40 to +125°C	–40 to +85°C

APPLICATION EXAMPLES

Consumer product	Application
Mobile phone	Data terminal
Digital video camera	LCD panel
Digital camera	Touch panel
PDA	Button and switch unit
Note PC	Battery terminal
DVD-ROM, CD-ROM	Audio-Video input-output terminal
CD/MD/MP3 player	Microphone/receiver unit
Game machine	Controller unit
In-car equipment	CAN-BUS
	ECU
	Connector
	Air conditioner panel
	Car audio
	Car navigation




INTERNAL STRUCTURE




CIRCUITS


SINGLE TYPE




ARRAY TYPE



OPERATIONAL VOLTAGE RANGES



RECOMMENDED REFLOW SOLDERING CONDITIONS



AVR-M TYPE

PRODUCT IDENTIFICATION

AVR-M	1005	C	270	M	T	AAB
(1)	(2)	(3)	(4)	(5)	(6)	(7)

(1) Series name

(2) Dimensions L×W

0603	0.6×0.3mm
1005	1.0×0.5mm
1608	1.6×0.8mm
2012	2.0×1.2mm
14A2	1.4×1.0mm (2-element)

(3) Structure code

(4) Varistor voltage

270	27×10^{0}V

(5) Varistor voltage tolerance

K	±10%
M	±20%


(6) Packaging style


T	Taping
B	Bulk

(7) Capacitance and TDK internal code

SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN


0603/1005/1608/2012 TYPES





Dimensions in mm


Type	L	W	T	B min.	Weight (mg)typ.
0603	0.6±0.03	0.3±0.03	0.3±0.03	0.1	0.2
1005	1.0±0.05	0.5±0.05	0.5±0.05	0.1	1.2
1608	1.6±0.1	0.8±0.1	0.8±0.1	0.2	5
2012	2.0±0.2	1.25±0.2	1.0±0.2	0.2	15



Dimensions in mm

Type	a	b	c
0603	0.25 to 0.35	0.2 to 0.3	0.25 to 0.35
1005	0.3 to 0.5	0.35 to 0.45	0.4 to 0.6
1608	0.6 to 0.8	0.6 to 0.8	0.6 to 0.8
2012	0.9 to 1.2	0.7 to 0.9	0.9 to 1.2


1410 TYPE





Weight: 4mg typ.

Dimensions in mm



Dimensions in mm

ELECTRICAL CHARACTERISTICS


Part No.	Varistor voltage (Breakdown voltage) V_{1mA}(V)[DC1mA]		Maximum continuous voltage (Rated voltage) Vdc(V)	Clamping voltage Vcl(V) [8/20μs]	Maximum energy E(Joule) [10/1000μs]	Maximum peak current Ip(A) [8/20μs]	Capacitance C(pF) [1kHz, 1Vrms]	Packaging quantities (Taping) (pieces/reel)
0603 type								
AVRM0603C6R8N□*101N	6.8	(4.76 to 8.84)	3.5 max.	14[1A]	0.01 max.	10 max.	100 typ.	15,000
AVRM0603C080M□101N	8	(6.4 to 9.6)	5.5 max.	17[1A]	0.01 max.	4 max.	100 typ.	
AVRM0603C120M□101N	12.8	(10 to 15.6)	5.5 max.	20[1A]	0.01 max.	5 max.	100 typ.	
AVR-M0603C120M□AAB	12	(9.6 to 14.4)	7.5 max.	23[1A]	0.01 max.	1 max.	33 typ.	
1005 type								
AVRM1005C6R8N□101N	6.8	(4.76 to 8.84)	3.5 max.	14[1A]	0.02 max.	10 max.	100 typ.	10,000
AVR-M1005C080M□AAB	8	(6.4 to 9.6)	5.5 max.	14[1A]	0.04 max.	25 max.	650 typ.	
AVR-M1005C080M□ADB	8	(6.4 to 9.6)	5.5 max.	14[1A]	0.04 max.	25 max.	480 typ.	
AVR-M1005C080M□ABB	8	(6.4 to 9.6)	5.5 max.	15[1A]	0.02 max.	3 max.	100 typ.	
AVR-M1005C080M□ACB	8	(6.4 to 9.6)	5.5 max.	19[1A]	0.01 max.	1 max.	33 typ.	
AVR-M1005C120M□AAB	12	(9.6 to 14.4)	7.5 max.	20[1A]	0.05 max.	10 max.	130 typ.	
AVRM1005C270K□101N	27	(24 to 30)	19 max.	55[1A]	0.06 max.	4 max.	100 typ.	
AVR-M1005C270M□AAB	27	(21.6 to 32.4)	15 max.	50[1A]	0.06 max.	4 max.	40 typ.	
AVR-M1005C270M□ABB	27	(21.6 to 32.4)	15 max.	50[1A]	0.05 max.	1 max.	15 typ.	
1608 type								
AVR-M1608C080M□AAB	8	(6.4 to 9.6)	5.5 max.	15[2A]	0.09 max.	30 max.	650 typ.	4,000
AVR-M1608C120M□6AB	12	(9.6 to 14.4)	7.5 max.	20[2A]	0.09 max.	50 max.	1050 typ.	
AVR-M1608C120M□2AB	12	(9.6 to 14.4)	7.5 max.	20[2A]	0.06 max.	15 max.	400 typ.	
AVR-M1608C180M□6AB	18	(14.4 to 21.6)	11 max.	30[2A]	0.1 max.	30 max.	600 typ.	
AVR-M1608C220K□6AB	22	(19.8 to 24.2)	16 max.	34[2A]	0.1 max.	30 max.	560 typ.	
AVR-M1608C220K□2AB	22	(19.8 to 24.2)	16 max.	37[2A]	0.03 max.	10 max.	210 typ.	
AVR-M1608C270K□6AB	27	(24 to 30)	19 max.	42[2A]	0.1 max.	48 max.	430 typ.	
AVR-M1608C270K□2AB	27	(24 to 30)	19 max.	42[2A]	0.1 max.	20 max.	160 typ.	
AVR-M1608C270K□ACB	27	(24 to 30)	19 max.	54[2A]	0.05 max.	10 max.	60 typ.	
AVR-M1608C270M□AAB	27	(21.6 to 32.4)	17 max.	52[2A]	0.05 max.	2 max.	30 typ.	
AVR-M1608C270M□ABB	27	(21.6 to 32.4)	17 max.	52[2A]	0.05 max.	2 max.	15 typ.	
AVRM1608C390K□271N	39	(35 to 43)	28 max.	69[2A]	0.1 max.	78 max.	270 typ.	
2012 type								
AVR-M2012C120M□6AB	12	(9.6 to 14.4)	7.5 max.	20[5A]	0.2 max.	60 max.	1000 typ.	2,000
AVR-M2012C220K□6AB	22	(19.8 to 24.2)	16 max.	38[5A]	0.3 max.	100 max.	800 typ.	
AVR-M2012C390K□6AB	39	(35 to 43)	28 max.	62[5A]	0.3 max.	100 max.	430 typ.	
1410 type								
AVR-M14A2C240M□600N	24	(20 to 27)	16 max.	50[1A]	0.01 max.	5 max.	60 typ.[1MHz]	4,000
AVR-M14A2C270M□470N	27	(21.6 to 32.4)	15 max.	54[1A]	0.007 max.	5 max.	47 typ.[1MHz]	
AVRM14A2C270M□150N	27	(21.6 to 32.4)	15 max.	55[1A]	0.02 max.	3 max.	15 typ.[1MHz]	
AVRM14A2C270M□3R3F	27	(21.6 to 32.4)	10 max.	45[0.2A]	0.002 max.	0.2 max.	3.3 typ.[1MHz]	

* □: Packaging style(T: Taping/B: Bulk)


TERMINOLOGY

Item	Unit	Terminology
Varistor voltage (Breakdown voltage)	V_{1mA} (V)	Voltage measured across the varistor when DC1mA is applied.
Maximum continuous voltage (Rated voltage)	Vdc (V)	Maximum DC voltage that can be applied continuously. Varistor leakage current: 50μA max. (Within the range of maximum allowable circuit voltage)
Clamping voltage	Vcl (V)	Voltage appearing across the varistor when a pulse current (8/20μs*1) of specified peak value is applied.
Maximum energy	E (Joule)	Maximum energy that can be absorbed without deteriorating varistor characteristics when an impulse (10/1000μs*2) is applied once.
Maximum peak current	Ip (A)	Maximum current that can be withstood without deteriorating varistor characteristics when an impulse current (8/20μs*1) is applied once.
Capacitance	C (pF)	Capacitance measured at 1kHz (or 1MHz) of oscillator frequency and 1Vrms of oscillator voltage.

*1 8/20μs test waveform



*2 10/1000μs test waveform



• All specifications are subject to change without notice.

AVRL TYPE

PRODUCT IDENTIFICATION

AVRL	10	1A	3R3	F	T	A
(1)	(2)	(3)	(4)	(5)	(6)	(7)

(1) Series name

(2) Dimensions L×W

10	1.0×0.5mm
16	1.6×0.8mm

(3) Maximum continuous voltage

1A	10Vdc

(4) Capacitance

1R1	1.1pF
3R3	3.3pF
6R8	6.8pF

(5) Capacitance tolerance


N	±0.3pF
F	±1pF
G	±2pF

(6) Packaging style

T	Taping
B	Bulk

(7) Varistor voltage and TDK internal code


SHAPES AND DIMENSIONS/RECOMMENDED PC BOARD PATTERN





Dimensions in mm

Type	L	W	T	B min.	Weight (mg)typ.
1005	1.0±0.05	0.5±0.05	0.5±0.05	0.1	1.2
1608	1.6±0.1	0.8±0.1	0.8±0.1	0.2	5



Dimensions in mm

Type	a	b	c
1005	0.3 to 0.5	0.35 to 0.45	0.4 to 0.6
1608	0.6 to 0.8	0.6 to 0.8	0.6 to 0.8

ELECTRICAL CHARACTERISTICS

Part No.	Capacitance C(pF) [1MHz, 1Vrms]	Maximum continuous voltage (Rated voltage) Vdc(V)	Insulation resistance Rdc(MΩ) [3Vrms]	Varistor voltage V_{1mA}(V)[DC1mA]	Packaging quantities (Taping) (pieces/reel)
1005 type					
AVRL101A1R1N□*A	1.1[0.8 to 1.4]	10 max.	10 min.	90 typ.	10,000
AVRL101A1R1N□B	1.1[0.8 to 1.4]	10 max.	10 min.	39 typ.	
AVRL101C2R2D□A	2.2[1.7 to 2.7]	16 max.	10 min.	90 typ.	
AVRL101A3R3F□A	3.3[2.3 to 4.3]	10 max.	10 min.	27 typ.	
AVRL101A6R8G□A	6.8[4.8 to 8.8]	10 max.	10 min.	27 typ.	
1608 type					
AVRL161A1R1N□A	1.1[0.8 to 1.4]	10 max.	10 min.	90 typ.	4,000
AVRL161A1R1N□B	1.1[0.8 to 1.4]	10 max.	10 min.	39 typ.	
AVRL161A3R3F□A	3.3[2.3 to 4.3]	10 max.	10 min.	27 typ.	
AVRL161A6R8G□A	6.8[4.8 to 8.8]	10 max.	10 min.	27 typ.	


* □: Packaging style(T: Taping/B: Bulk)

TERMINOLOGY


Item	Unit	Terminology
Capacitance	C (pF)	Capacitance measured at 1MHz of oscillator frequency and 1Vrms of oscillator voltage.
Maximum continuous voltage (Rated voltage)	Vdc (V)	Maximum DC voltage that can be applied continuously. Varistor leakage current: 50μA max. (Within the range of maximum allowable circuit voltage)
Insulation resistance	Rdc (MΩ)	Insulation resistance appearing across the varistor when specified voltage is applied.
Varistor voltage (Breakdown voltage)	V_{1mA} (V)	Voltage measured across the varistor when DC1mA is applied.

TYPICAL ELECTRICAL CHARACTERISTICS


CURRENT vs. VOLTAGE CHARACTERISTICS




IMPEDANCE vs. FREQUENCY CHARACTERISTICS



TRANSMISSION CHARACTERISTICS



CAPACITANCE vs. FREQUENCY CHARACTERISTICS




ELECTROSTATIC DISCHARGE TESTS

TEST CONDITIONS


150pF, 330Ω contact discharge

Charged voltage /8kV, 0.1s interval


MEASURING CIRCUIT




AVR-M0603 TYPE




AVR-M1005 TYPE



AVR-M1608 TYPE




AVRL101A3R3F




ELECTROSTATIC ABSORPTION CHARACTERISTICS

DISCHARGE CURRENT WAVEFORM




DISCHARGE VOLTAGE WAVEFORM



WAVEFORM PARAMETERS [IEC61000-4-2]


Test level	ESD Charge voltage (kV)	First peak current of discharge (A)	Rise time (ns)
1	2	7.5	0.7 to 1.0
2	4	15	0.7 to 1.0
3	6	22.5	0.7 to 1.0
4	8	30	0.7 to 1.0

MEASURING CIRCUIT




ESD ABSORPTION CHARACTERISTICS

COMPARISON OF VARIOUS ELEMENTS



	Open waveform	AVR-M1005C080MTAAB	AVR-M1005C120MTAAB	Zener diode/Vz:6.2V
■Peak	316	45	58	47
■Average	117	16	24	21



Peak voltage:Peak voltage of standing up part
Average voltage : Average voltage of 30 to 100ns

ESD (Electro Static Discharge) absorption characteristics of V1mA-8V is superior to Vz-6.2V Zener diode.


MERITS OF REPLACEMENT FROM ZENER DIODE

(1) Reduction in the number of parts


(2) Reduction in mounting cost

COMPARISON OF FOOTPRINT

Zener diode




Chip varistor




Save a mount area 65% down

EXAMPLE OF REPLACEMENT AT AUDIO TERMINAL



(3) Improved electrostatic absorption capability


COMPARE DATA OF CHIP VARISTOR AND ZENER DIODE ABOUT IC PROTECTION




CMOS: D74HC04C
ESD generator : Noise Laboratory Co.,Ltd., ESS -630A
200pF-0Ω method model equipment
Contact type discharge
ESD applied point: Vcc-ground

APPLICATION EXAMPLES

CELLULAR PHONE




AUDIO/VIDEO




APPLICATION EXAMPLES


USB 2.0



MEASURING CIRCUIT




WITHOUT VARISTOR




WITH VARISTOR

AVRL101A3R3FT(3.3pF)



AVRL101A6R8GT(6.8pF)



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331