Reflective Object Sensor

OPB706A, OPB706B, OPB706C
OPB707A, OPB707B, OPB707C

Features:

- Choice of Phototransistor (OPB706) or Photodarlington (OPB707) output
- Unfocused for sensing diffuse surface
- Low cost plastic housing
- Designed for use with PCBoards or connectors

Description:

The **OPB706** consists of an infrared Light Emitting Diode (LED) and an NPN silicon Phototransistor mounted "side-by-side" on parallel axes in a black plastic housing. The **OPB707** consists of an infrared LED and an NPN silicon Photodarlington mounted "side-by-side" on parallel axes in a black plastic housing.

On both **OPB706** and **OPB707**, the LED and Phototransistor / Photodarlington are molded using dark infrared transmissive plastic to reduce ambient light noise. The Phototransistor / Photodarlington responds to light from the emitter when a reflective object passes within its field of view of the device.

Custom electrical, wire and cabling and connectors are available. Contact your local representative or OPTEK for more information.

Applications:

- Non-contact reflective object sensor
- Assembly line automation
- Machine automation
- Machine safety
- End of travel sensor
- Door sensor

Part Number	LED Peak Wavelength	Sensor	Reflection Distance	Lead Length / Spacing
OPB706A	935 nm	Transistor	0.050" (1.27mm)	0.45" / 0.087", 0.100"
OPB706B				
OPB706C				
OPB707A		Darlington		
OPB707B				
OPB707C				



DIMENSIONS ARE IN: **[MILLIMETERS]**
INCHES

OPB706



OPB707



Pin #	LED	Pin #	Transistor
3	Anode	1	Collector
4	Cathode	2	Emitter

RoHS

General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

© TT electronics plc

OPTEK Technology, Inc.
1645 Wallace Drive, Carrollton, TX 75006|Ph: +1 972 323 2200
www.optekinc.com | www.ttelectronics.com

Absolute Maximum Ratings (T_A = 25° C unless otherwise noted)	
Storage and Operating Temperature Range	-40° C to +85° C
Lead Soldering Temperature [1/16 inch (1.6mm) from the case for 5 sec. with soldering iron](1)	260° C
Input Diode	
Forward DC Current	50 mA
Peak Forward Current (1 µs pulse width, 300 pps)	3 A
Reverse DC Voltage	2 V
Power Dissipation(2)	75 mW
Output Phototransistor (OPB706) | Output Photodarlington (OPB707)	
Collector-Emitter Voltage OPB706 OPB707	 24 V 15 V
Emitter-Collector Voltage	5 V
Collector DC Current OPB706 OPB707	 25 mA 125 mA
Power Dissipation OPB706(2) OPB707(3)	 75 mW 100 mW

Notes:

(1) RMA flux is recommended. Duration can be extended to 10 seconds maximum when flow soldering.

(2) Derate linearly 1.25 mW/°C above 25 ° C.

(3) Derate linearly 1.67 mW/°C above 25 ° C.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

OPTEK Technology, Inc.

1645 Wallace Drive, Carrollton, TX 75006|Ph: +1 972 323 2200

www.optekinc.com | www.ttelectronics.com

© TT electronics plc

Electrical Characteristics (T_A = 25° C unless otherwise noted)						
SYMBOL	PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
Input Diode (see OP165W for additional information)						
V_F	Forward Voltage	-	-	1.7	V	I_F = 20 mA
I_R	Reverse Current	-	-	100	µA	V_R = 2 V
Output Phototransistor (see OP505W for additional information) | **Photodarlington** (see OP535 for additional information)						
$V_{(BR)CEO}$	Collector-Emitter Breakdown Voltage OPB706 OPB707	 24 15	 - -	 - -	V	I_C = 100 µA
$V_{(BR)ECO}$	Emitter-Collector Breakdown Voltage	5	-	-	V	I_E = 100 µA
I_{CEO}	Collector Dark Current OPB706 OPB707	 - -	 - -	 100 250	nA	V_{CE} = 5 V, I_F = 0, $E_E \leq 0.1$ µW/cm^2
Combined						
I_{CX}	Crosstalk OPB706 OPB707	 - -	 - -	 200 10	 nA µA	I_F = 20 mA, V_{CE} = 5 V, No reflecting surface(1)
$I_{C(ON)}$	On-State Collector Current OPB706A OPB706B OPB706C	 500 350 250	 - - -	 - - -	µA	I_F = 20 mA, V_{CE} = 5V , d = 0.05" (1.27 mm)(2) (3)
	OPB707A OPB707B OPB707C	25 17 10	- - -	- - -	mA	
$V_{CE(SAT)}$	Collector-Emitter Saturation Voltage OPB706 OPB707	 0.4 1.1	 - -	 - -	V	I_F = 20 mA, d = 0.05" (1.27 mm)(2) (3) $I_{C(ON)}$ = 100µA $I_{C(ON)}$ = 2 mA

Notes:

(1) Crosstalk (I_{CX}) is the collector current measured with the indicated current in the input diode and with no reflecting surface.

(2) The distance from the assembly face to the reflective surface is "d".

(3) Measured using Eastman Kodak neutral white test card with 90% diffuse reflectance as a reflecting surface. Reference: Eastman Kodak, Catalog #E 152 7795.

(4) Lower curve is a calculated worst case condition rather than the conventional -2 Ω limit.

(5) All parameters tested using pulse techniques.

General Note

TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

OPTEK Technology, Inc.

1645 Wallace Drive, Carrollton, TX 75006|Ph: +1 972 323 2200

www.optekinc.com | www.ttelectronics.com

© TT electronics plc

OPB706 - Normalized Collector Current vs. Object Distance



OPB706 - Output Current vs Forward Current vs Temperature



OPB707 - Normalized Collector Current vs. Object Distance



OPB707 - Output Current vs Forward Current vs Temperature



General Note
TT Electronics reserves the right to make changes in product specification without notice or liability. All information is subject to TT Electronics' own data and is considered accurate at time of going to print.

OPTEK Technology, Inc.
1645 Wallace Drive, Carrollton, TX 75006|Ph: +1 972 323 2200
www.optekinc.com | www.ttelectronics.com

© TT electronics plc

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331