

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
© COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.

LOC	DIST
FT	69


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H	REV PER 0G3C-0156-03	130CT04	JR	MZ





1. FINISH: SOLDERTAILS TIN PLATE 0.0051 [.000200] MIN. THICK. CONTACT AREA 0.00076[.000030] MIN. HARD GOLD OVER 0.00127-0.00254 [.000050-.000100] LOW STRESS NICKEL.
2. CHARACTERS 2.5 [.10] HIGH, COLOR BLACK.
3. BLANK HOLE FOR MECHANICAL STABILITY OF SWITCH.



P.C. BOARD HOLE LAYOUT
SWITCH SIDE

		SWITCH POSITION							
		0	1	2	3	4	5	6	7
COMMON TO	1		●		●		●		●
	2			●	●			●	●
	4					●	●	●	●

435174-1
PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±0.5 [.02]
3 PLC ±-
4 PLC ±-
ANGLES ±0°30′

MATERIAL
CASE: THERMOPLASTIC, COLOR NATURAL
CONTACT: BERYLLIUM COPPER

FINISH 1

DWN R. TALLEY	8-7-91
CHK R. MILLER	8-7-91
APVD D. HUFFMAN	8-9-91
PRODUCT SPEC 108-7514	
APPLICATION SPEC 114-7005	
WEIGHT –	

AMP Incorporated
Harrisburg, PA 17105-3608

NAME ROTARY SWITCH ASSY, 8 POSN, 6000 SERIES BCO

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C- 435174	–

CUSTOMER DRAWING

SCALE	SHEET	REV
2:1	1 OF 3	H


THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
© COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


LOC	DIST
FT	69

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H	SEE SHEET 1	-	-	-

1. FINISH: SOLDERTAILS TIN PLATE 0.0051 [.000200] MIN. THICK. CONTACT AREA 0.00076[.000030] MIN. HARD GOLD OVER 0.00127-0.00254 [.000050-.000100] LOW STRESS NICKEL.
2. CHARACTERS 2.5 [.10] HIGH, COLOR BLACK.
3. BLANK HOLE FOR MECHANICAL STABILITY OF SWITCH.





P.C. BOARD HOLE LAYOUT
SWITCH SIDE

		SWITCH POSITION							
		0	1	2	3	4	5	6	7
COMMON TO	1		●		●		●		●
	2			●	●			●	●
	4					●	●	●	●

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±0.5 [.02]
3 PLC ±-
4 PLC ±-
ANGLES ±0°30′

MATERIAL
CASE: THERMOPLASTIC, COLOR NATURAL
CONTACT: BERYLLIUM COPPER

FINISH 1

DWN	R. TALLEY	8-7-91
CHK	R. MILLER	8-7-91
APVD	D. HUFFMAN	8-9-91
PRODUCT SPEC	108-7514	
APPLICATION SPEC	114-7005	
WEIGHT	-	

CUSTOMER DRAWING

1-435174-1
PART NO

AMP Incorporated
Harrisburg, PA 17105-3608

NAME ROTARY SWITCH ASSY, 8 POSN, 6000 SERIES BCO

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C- 435174	-


SCALE	SHEET	REV
2:1	2 OF 3	H

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION ,19 .
© COPYRIGHT 19 BY AMP INCORPORATED. ALL RIGHTS RESERVED.


LOC	DIST
FT	69

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	H	SEE SHEET 1	-	-	-



1. FINISH: SOLDERTAILS TIN PLATE 0.0051 [.000200] MIN. THICK. CONTACT AREA 0.00076[.000030] MIN. HARD GOLD OVER 0.00127-0.00254 [.000050-.000100] LOW STRESS NICKEL.
2. POSITION MARKINGS ø7.62 [ø.030], COLOR BLACK.
3. BLANK HOLE FOR MECHANICAL STABILITY OF SWITCH.



P.C. BOARD HOLE LAYOUT
SWITCH SIDE

		SWITCH POSITION							
		0	1	2	3	4	5	6	7
COMMON TO	1		●		●		●		●
	2			●	●			●	●
	4					●	●	●	●

SUPERSEDED BY 1-435174-1

1-435174-3
PART NO

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ±-
1 PLC ±-
2 PLC ±0.5 [.02]
3 PLC ±-
4 PLC ±-
ANGLES ±0°30′

MATERIAL
CASE: THERMOPLASTIC, COLOR NATURAL
CONTACT: BERYLLIUM COPPER

FINISH 1

DWN	R. TALLEY 8-7-91
CHK	R. MILLER 8-7-91
APVD	D.HUFFMAN 8-9-91
PRODUCT SPEC	108-7514
APPLICATION SPEC	114-7005
WEIGHT	-

CUSTOMER DRAWING

AMP Incorporated
Harrisburg, PA 17105-3608

NAME ROTARY SWITCH ASSY, 8 POSN, 6000 SERIES BCO

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A3	00779	C- 435174	-

SCALE	SHEET	REV
2:1	3 OF 3	H

AMP 1470-19 REV 11JUN97

18-SEP-98 12:52:23 amp45354 /home/amp45354/98-173

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331