

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION –,– .
© COPYRIGHT – BY TYCO ELECTRONICS CORPORATION. ALL RIGHTS RESERVED.


LOC	DIST
AD	00


REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	N	ECR–05–000991, ECR–05–003293	01JUN05	MB	DLS











RECOMMENDED HOLE PATTERN



BASIC DIMENSIONS FOR EVEN NO OF SPACES (SEE TABLE)



BASIC DIMENSIONS FOR ODD NO OF SPACES (SEE TABLE)

DETAIL R

1. CONTACT AREA PLATED WITH .000030 MIN GOLD; SOLDER TAILS PLATED WITH .000150 MIN TIN–LEAD, ALL OVER .000050 MIN NICKEL
2. POINT OF MEASUREMENT FOR PLATING THICKNESS
3. CIRCUIT IDENTIFICATION FEATURE OMITTED ON 8,10,12 AND 14 POSN HEADER ASSEMBLIES
4. DIMENSION APPLIES AT BASE OF SHROUD
5. THE NOTED DIMENSIONS APPLY AT THE INTERSECTION OF THE POST AND HOUSING
6. Y 3 / Y 4 ARE LOCATED THE SAME AS Y 1 / Y 2 EXCEPT ON OPPOSITE SIDE OF HOUSING.
7. CONTACT AREA PLATED WITH .000030 MIN. GOLD; SOLDER TAILS PLATED WITH .000150 MIN TIN; ALL OVER .000050 MIN NICKEL

	A	B	C	NO OF POS	PART NUMBER
	.450	9	.630	20	104068–1
	.200	4	.380	10	104068–2
	.300	6	.480	14	104068–9
	.350	7	.530	16	1–104068–0
1 2	.550	11	.730	24	1–104068–1
	.600	12	.780	26	1–104068–2
	.800	16	.980	34	1–104068–3
	1.050	21	1.230	44	1–104068–4
	1.750	35	1.930	72	1–104068–5
	1.950	39	2.130	80	1–104068–6
	2.450	49	2.630	100	1–104068–7
	1.650	33	1.830	68	1–104068–8
	.450	9	.630	20	5–104068–1
	.200	4	.380	10	5–104068–2
	.700	14	.880	30	5–104068–3
7 2	.950	19	1.130	40	5–104068–4
	1.200	24	1.380	50	5–104068–5
	1.450	29	1.630	60	5–104068–6
	.250	5	.430	12	5–104068–8
PRELIMINARY	.150	3	.330	8	5–104068–7
	.300	6	.480	14	5–104068–9
	.350	7	.530	16	6–104068–0
	.550	11	.730	24	6–104068–1
	.600	12	.780	26	6–104068–2
	.800	16	.980	34	6–104068–3
	1.050	21	1.230	44	6–104068–4
	1.750	35	1.930	72	6–104068–5
	1.950	39	2.130	80	6–104068–6
	2.450	49	2.630	100	6–104068–7
7 2	1.650	33	1.830	68	6–104068–8

104068

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: INCHES

TOLERANCES UNLESS OTHERWISE SPECIFIED:
0 PLC ± –
1 PLC ± –
2 PLC ± –
3 PLC ± –
4 PLC ± –
ANGLES ± –

MATERIAL: HOUSING: THERMOPLASTIC COLOR–BLACK
POST: COPPER ALLOY

FINISH: SEE TABLE

DWN D. CLOUSER 10–3–88
CHK T. ZOLA 10–3–88
APVD T. ZOLA 10–3–88
PRODUCT SPEC 108–1093
APPLICATION SPEC 114–25031
WEIGHT –

CUSTOMER DRAWING

tyco Electronics — Tyco Electronics Corporation, Harrisburg, Pa 17105–3608

NAME: HEADER ASSEMBLY, VERTICAL SHROUDED, DOUBLE ROW W/SIDE & END LATCHES, AMPMODU System 50

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C–104068	–

SCALE	SHEET	REV
4:1	1 OF 1	N

Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург, Промышленная ул, дом № 19, литера Н, помещение 100-Н Офис 331