

## PRODUCT BRIEF

### KEY FEATURES

- ▶ Very low power consumption (uncooled pump)
- ▶ Micro 45x70x12 mm form factor
- ▶ Up to 16 dBm output power
- ▶ Fast power transient suppression for stable output power
- ▶ Can support G.657 low bend radius fiber pigtails
- ▶ Pre-amplifier or booster configuration

### APPLICATIONS

- ▶ Pre-amp or Booster for 40 Gb/s and 100 Gb/s transponder line cards
- ▶ Very long reach 10 Gb/s applications
- ▶ Submarine networks
- ▶ Military and industrial applications requiring small size and low power consumption
- ▶ Single channel networks

### OVERVIEW

Finisar's Single Channel Micro EDFA is a cost-effective micro processor-controlled module for amplifying single channels in the C-band. The amplifier is provided in a micro 45x70x12 mm package, and exhibits low power consumption allowing it to be easily integrated onto space and power constrained transponder line cards. The EDFA can be configured as either pre-amplifier or booster.

In order to support 40 Gb/s and 100 Gb/s applications, the amplifier provides excellent broadband noise performance. Fast transient suppression circuitry is also provided, allowing the amplifier output power to be kept constant when there are fast changes in input power.



## KEY OPTICAL SPECIFICATIONS

Parameter	Specifications			Remarks
	Min.	Max.	Units	
Wavelength Range	1528.77	1567.13	nm	
Input Power Range	-10	5	dBm	
Output Power Range	0	16	dBm	
Operational Gain	5	26	dB	
Noise Figure		6.5 11	dB dB	At -10 dBm input with 26dB signal gain At 5 dBm input with 5 dB signal gain
Transient Overshoot / Undershoot	-0.5	0.5	dB	Rise / fall time > 1msec, Input power change < 6 dB, Signal output power (APC) = +16dBm
Power consumption		2.5	W	Over case temp range to EOL
Power Supply	2.97	3.63	V	
Operating Case Temperature	0	70	°C	
Storage Temperature Range	-40	85	°C	
Dimensions (WxHxD)	45x70x12		mm	
Laser safety	Class 1M*			

\* Class 1M products are not hazardous under normal circumstances, but may pose an eye hazard when the laser output is viewed with certain optical instruments (for example eye loupes, magnifiers and microscopes) within a distance of 100 mm





## Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

### Наши контакты:

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331