



LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AA	00		A2	REV PER ECO-13-015117	16SEP2013	OL	SZ
			A3	ADD NEW PART 6--2	18NOV2013	OL	SZ
			A4	ECR-15-001425	19JAN2015	SZ	SZ



2-1926739-5 SHOWN

- HOUSING: GLASS FILLED LIQUID CRYSTAL POLYMER, COLOR: BLACK, UL 94 V-0 RATED
SIGNAL CONTACT: PHOSPHOR BRONZE
SIGNAL OVERMOLD: GLASS FILLED POLYESTER
POWER CONTACT: COPPER ALLOY
- SIGNAL CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00008mm MIN GOLD OVER
0.00076mm MIN PALLADIUM-NICKEL
TAIL AREA: 0.0005mm MIN MATTE TIN




POWER CONTACT: 0.00127mm MIN NICKEL ALL OVER,
MATING AREA: 0.00008mm MIN GOLD OVER
0.00076mm MIN PALLADIUM-NICKEL,
TAIL AREA: 0.0005mm MIN MATTE TIN
- CONTACT MATING AREA LUBRICATED WITH BELLCORE APPROVED LUBRICANT,
TECHNICAL REFERENCE: GR-1217-CORE, ISSUE 1, NOVEMBER 1995
- THIS CONNECTOR EMPLOYS UL RECOGNIZED Z-PACK 2mm HM SIGNAL CONTACTS

- DATUMS AND BASIC DIMENSIONS TO BE ESTABLISHED BY CUSTOMER
- PC BOARD THICKNESS 1.4mm MIN, FOR WAVE SOLDER PC BOARD THICKNESS 2.62 MAX
- SEE APPLICATION SPEC 114-13215 FOR PLATED THROUGH HOLE INFORMATION
8. SEE CUSTOMER DRAWING 1926730 OR 1926732 FOR MATING CONNECTOR
- UNPLATED HOLES
- #4-40 UNC PAN HEAD SCREW WITH HEX NUT, NOT SHOWN, SUPPLIED BY CUSTOMER

12	15	1	2	21.94	25.74	15S X 2P	8-1926739-0
144	40	23	7	92.44	96.24	40S X 24P	7-1926739-7
120	35	19	6	79.44	83.24	35S X 20P	6-1926739-2
108	35	17	6	73.94	77.74	35S X 18P	5-1926739-5
96	25	15	4	64.44	68.24	25S X 16P	4-1926739-6
72	15	11	2	49.44	53.24	15S X 12P	3-1926739-0
48	20	7	3	40.44	44.24	20S X 8P	1-1926739-1
72	25	11	4	51.44	57.24	25S X 12P	1926739-9
48	25	7	4	42.44	46.24	25S X 8P	1-1926739-8
36	20	5	3	36.74	40.54	20S X 6P	1-1926739-0
60	25	9	4	47.94	51.74	25S X 10P	2-1926739-5
F PLC	E PLC	D SPACES	C SPACES	DIM B	DIM A	NO OF POSITIONS	PART NUMBER


THIS DRAWING IS UNPUBLISHED. IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND WITHOUT LIABILITY. THE USER OF THIS DRAWING SHOULD BE CONTACTED FOR THE LATEST EDITION.				DWN ORLANDO LI 28OCT2011	Tyco Electronics Shanghai, PR 200233		
DIMENSIONS: mm				CHK SUNY ZHAO 28OCT2011			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ±0.13 3 PLC ± 4 PLC ± ANGLES ±				APVD SUNY ZHAO 28OCT2011	NAME RECEPTACLE ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER, WITH SCREW MOUNT, MINIPAK HDL		
MATERIAL SEE NOTE 1				PRODUCT SPEC 108-2325			
FINISH SEE NOTE 2				APPLICATION SPEC 114-13215	SIZE A100779C=1926739		
Customer Drawing				WEIGHT -			
				SCALE 3:1	SHEET 1	OF 3	REV A4

LOC		DIST		REVISIONS					
AA		00		P	LTR	DESCRIPTION	DATE	DWN	APVD
				-	-	SEE SHEET 1	-	-	-



THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION. IT IS SUBJECT TO CHANGE AND SHOULD BE CONTROLLED BY THE ISSUING ORGANIZATION. SHOULD BE CONTACTED FOR THE LATEST VERSION.		DWN	ORANDO LI	28OCT2011	Tyco Electronics Shanghai, PR 200233	
		CHK	SUNY ZHAO	28OCT2011		
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME	
mm		0 PLC ±.1		SUNY ZHAO	RECEPTACLE ASSEMBLY, RIGHT ANGLE,	
		1 PLC ±.13		28OCT2011	PASSIVE GUIDE, SIGNAL/POWER,	
		2 PLC ±.1		PRODUCT SPEC	WITH SCREW MOUNT, MINIPAK HDL	
		3 PLC ±.1		108-2325	SIZE	
		4 PLC ±.1		APPLICATION SPEC	CAGE CODE	
ANGLES		±.1		114-13215	DRAWING NO	
FINISH		SEE NOTE 2		114-13215	RESTRICTED TO	
MATERIAL		SEE NOTE 1		114-13215	A100779	
Customer Drawing		SCALE		3:1	SHEET 2 OF 3	
					REV A4	

LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
AA	00	-	-	SEE SHEET 1	-	-	-



2-1926739-5 SHOWN
RECOMMENDED PRINTED CIRCUIT BOARD LAYOUT
(AS VIEWED FROM COMPONENT SIDE)

THIS DRAWING IS A CONTROLLED DOCUMENT FOR TYCO ELECTRONICS CORPORATION. IT IS SUBJECT TO CHANGE WITHOUT NOTICE AND EXISTING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST EDITION.		DWN	ORANDO LI	28OCT2011	Tyco Electronics Shanghai, PR 200233	
		CHK	SUNY ZHAO	28OCT2011		
DIMENSIONS:		TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	NAME	
mm		0 PLC ± 1 PLC ± 2 PLC ±0.13 3 PLC ± 4 PLC ± ANGLES ± FINISH		SUNY ZHAO	RECEPTACLE ASSEMBLY, RIGHT ANGLE, PASSIVE GUIDE, SIGNAL/POWER, WITH SCREW MOUNT, MINIPAK HDL	
MATERIAL		SEE NOTE 1		PRODUCT SPEC	SIZE	
SEE NOTE 2		SEE NOTE 2		108-2325	CAGE CODE	
Customer Drawing		Customer Drawing		114-13215	DRAWING NO	
				WEIGHT	RESTRICTED TO	
				-	A100779C=1926739	
					SCALE	
					3:1	
					SHEET	
					3 OF 3	
					REV	
					A4	



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331