

## 3A, 60V Trench Schottky Rectifier

### FEATURES

- Patented Trench Schottky technology
- Ideal for automated placement
- High surge current capability
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

### APPLICATIONS

- Trench Schottky barrier rectifier is designed for high frequency miniature switched mode power supplies such as adapters, lighting.

### MECHANICAL DATA

- Case: DO-214AC (SMA)
- Molding compound meets UL 94V-0 flammability rating
- Moisture sensitivity level: level 1, per J-STD-020
- Packing code with suffix "G" means green compound (halogen-free)
- Part no. with suffix "H" means AEC-Q101 qualified
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: As marked
- Weight: 0.06 g (approximately)

| KEY PARAMETERS |                |      |
|----------------|----------------|------|
| PARAMETER      | VALUE          | UNIT |
| $I_{F(AV)}$    | 3              | A    |
| $V_{RRM}$      | 60             | V    |
| $I_{FSM}$      | 60             | A    |
| $T_{J\ MAX}$   | 150            | °C   |
| Package        | DO-214AC (SMA) |      |
| Configuration  | Single dice    |      |



**DO-214AC (SMA)**

### ABSOLUTE MAXIMUM RATINGS ( $T_A = 25^\circ\text{C}$ unless otherwise noted)

| PARAMETER                                                                                     | SYMBOL      | TSSA3U60     | UNIT |
|-----------------------------------------------------------------------------------------------|-------------|--------------|------|
| Marking code on the device                                                                    |             | 3U60         |      |
| Repetitive peak reverse voltage                                                               | $V_{RRM}$   | 60           | V    |
| Reverse voltage, total rms value                                                              | $V_{RMS}$   | 42           | V    |
| Maximum DC blocking voltage                                                                   | $V_{DC}$    | 60           | V    |
| Forward current                                                                               | $I_{F(AV)}$ | 3            | A    |
| Surge peak forward current, 8.3 ms single half sine-wave superimposed on rated load per diode | $I_{FSM}$   | 60           | A    |
| Junction temperature                                                                          | $T_J$       | - 55 to +150 | °C   |
| Storage temperature                                                                           | $T_{STG}$   | - 55 to +150 | °C   |

**THERMAL PERFORMANCE**

| PARAMETER                              | SYMBOL          | LIMIT | UNIT |
|----------------------------------------|-----------------|-------|------|
| Junction to Lead Thermal Resistance    | $R_{\theta JL}$ | 27    | °C/W |
| Junction to Ambient Thermal Resistance | $R_{\theta JA}$ | 70    | °C/W |
| Junction to Case Thermal Resistance    | $R_{\theta JC}$ | 20    | °C/W |

**Thermal Performance Note:** Units mounted on recommended PCB (5mm x 5mm Cu pad test board)

**ELECTRICAL SPECIFICATIONS** ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

| PARAMETER                                              | CONDITIONS                                                        | SYMBOL   | TYP  | MAX  | UNIT          |
|--------------------------------------------------------|-------------------------------------------------------------------|----------|------|------|---------------|
| Forward voltage per diode <sup>(1)</sup>               | $I_F = 3\text{A}, T_J = 25^\circ\text{C}$                         | $V_F$    | 0.48 | 0.54 | V             |
|                                                        | $I_F = 3\text{A}, T_J = 125^\circ\text{C}$                        |          | 0.41 | 0.50 |               |
| Reverse current @ rated $V_R$ per diode <sup>(2)</sup> | $T_J = 25^\circ\text{C}$                                          | $I_R$    | -    | 500  | $\mu\text{A}$ |
|                                                        | $T_J = 125^\circ\text{C}$                                         |          | 12   | 30   | mA            |
| Junction capacitance                                   | 1 MHz, $V_R = 4.0\text{V}$                                        | $C_T$    | 450  | 610  | pF            |
| Reverse recovery time                                  | $I_F = 0.5\text{A}, I_R = 1.0\text{A}$<br>$I_{RR} = 0.25\text{A}$ | $t_{rr}$ | 20   | 25   | ns            |

**Notes:**

1. Pulse test with  $PW = 0.3\text{ ms}$
2. Pulse test with  $PW = 30\text{ ms}$

**ORDERING INFORMATION**

| PART NO.             | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX | PACKAGE  | PACKING                  |
|----------------------|-----------------|--------------|---------------------|----------|--------------------------|
| TSSA3U60<br>(Note 1) | H               | E3           | G                   | Clip SMA | 1,800 / 7" Plastic reel  |
|                      |                 | E2           |                     | Clip SMA | 7,500 / 13" Plastic reel |
|                      |                 | M2           |                     | SMA      | 7,500 / 13" Plastic reel |
|                      |                 | R3           |                     | SMA      | 1,800 / 7" Plastic reel  |

**Note:**

1. Whole series with green compound (halogen-free)


**EXAMPLE**

| EXAMPLE P/N  | PART NO. | PART NO. SUFFIX | PACKING CODE | PACKING CODE SUFFIX | DESCRIPTION                          |
|--------------|----------|-----------------|--------------|---------------------|--------------------------------------|
| TSSA3U60HR3G | TSSA3U60 | H               | R3           | G                   | Green compound<br>AEC-Q101 qualified |


## CHARACTERISTICS CURVES

( $T_A = 25^\circ\text{C}$  unless otherwise noted)


**Forward Current Derating Curve**




**Total Capacitance Characteristics**



**Typical Reverse Characteristics**




**Typical Forward Characteristics**




## PACKAGE OUTLINE DIMENSIONS

DO-214AC (SMA)




| DIM | Unit (mm) |      | Unit (inch) |       |
|-----|-----------|------|-------------|-------|
|     | Min       | Max  | Min         | Max   |
| A   | 1.27      | 1.58 | 0.050       | 0.062 |
| B   | 4.06      | 4.60 | 0.160       | 0.181 |
| C   | 2.29      | 2.83 | 0.090       | 0.111 |
| D   | 1.99      | 2.50 | 0.078       | 0.098 |
| E   | 0.90      | 1.41 | 0.035       | 0.056 |
| F   | 4.95      | 5.33 | 0.195       | 0.210 |
| G   | 0.10      | 0.20 | 0.004       | 0.008 |
| H   | 0.15      | 0.31 | 0.006       | 0.012 |

## SUGGESTED PAD LAYOUT



| Symbol | Unit (mm) | Unit (inch) |
|--------|-----------|-------------|
| A      | 1.68      | 0.066       |
| B      | 1.52      | 0.060       |
| C      | 3.93      | 0.155       |
| D      | 2.41      | 0.095       |
| E      | 5.45      | 0.215       |

## MARKING DIAGRAM



P/N = Marking Code  
G = Green Compound  
YW = Date Code  
F = Factory Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331