

5000UE Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

 	For more information please call 1-800-Belden1 <u>See Put-ups and Colors</u>
--	---

Description:

12 AWG bare copper conductors, PVC insulation, PVC jacket with ripcord, sequential footage marking every two feet.

SUITABLE APPLICATIONS:

Suitable Applications	Intercom/PA Systems, Sound/Audio Systems, Fire Alarm (For color Red only)(Dual Rated)
-----------------------	---

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	12
Stranding	19x25
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.014 in.

OVERALL CABLING:

Overall Cabling Lay Length	4.5 in.
Overall Cabling Twists/ft.	2.7

Overall Cabling Color Code Chart :

Number	Color	Number	Color
1	Black	2	White

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.015 in.
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.268 in.
--------------------------	----------

5000UE Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	53.6 lbs/1000 ft.
Max. Recommended Pulling Tension	152 lbs.
Min. Bend Radius (Install)	2.6 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CL3R, FPLR
NEC Articles	725 or 760
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	UL1666 Vertical Riser
CSA Flame Test	FT4

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
Plenum Number	6000UE

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	0.15 µH/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	33.5 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	1.6 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	12 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
5000UE 0021000	2 #12 SR PVC FRPVC	1000	57	RED	C
5000UE 0081000	2 #12 SR PVC FRPVC	1000	57	GRAY	C
5000UE 008500	2 #12 SR PVC FRPVC	500	29	GRAY	C
5000UE 0101000	2 #12 SR PVC FRPVC	1000	57	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 05-08-2006

5000UE Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs. (San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003); Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331