



Western Digital® PC SN720 NVMe™ SSD

Performance Reimagined

Cutting-edge NVMe Architecture

With future-ready, scalable NVMe architecture, the Western Digital PC SN720 NVMe SSD is breaking through performance limits of commercial and embedded applications, and supporting higher storage uses in today's IoT market, while providing a compact storage device with high capacity points from 256GB to 2TB.

Powerful Construction Suited for IoT

The Western Digital PC SN720 NVMe SSD, supporting PCIe Gen3 x4, is designed for applications that require both high performance and low power. Partners that could benefit from NVMe technology include:

- **Edge Equipment and IoT Gateway:** Such as network equipment, industrial machinery, medical equipment, or embedded PC that need the high capacities to capture the floor's and sensors' data and the high IOPS to support the system's data analytics
- **Media Content Delivery and Streaming:** In-flight entertainment systems, train control and monitoring systems, data recorder and video surveillance that require high capacity and reliability
- **Commercial:** Interactive kiosks, ATMs and Point-of-Sales (POS), Multi-Functional Printers (MFP) and industries that require high-volume transaction processing

Pushing the Performance for IoT

Equipped with a fully integrated solution which includes in-house controller, 64-layer 3D NAND, firmware, and testing, Western Digital provides longevity of supply in a robust and reliable design.

Designed with Western Digital's in-house tiered-caching NVMe architecture, the Western Digital PC SN720 NVMe SSD delivers extreme performance with sequential read and write speeds up to 3,400MB/s and 2,800MB/s respectively and high endurance up to 500 TBW, all of which is available in a M.2 2280 form factor.

Summary

The Western Digital PC SN720 NVMe SSD packs a powerful punch in a compact design, which enables outstanding performance for the most demanding IoT and embedded applications that seek a reliable storage device with capacity points from 256GB to 2TB.



WESTERN DIGITAL PC SN720 NVMe SSD KEY BENEFITS & FEATURES

**READ SPEEDS UP TO 3,400MB/S SATURATES THE
PCIe GEN3 x4 INTERFACE SUPPORTING NVMe
ARCHITECTURE**

**256GB-2TB CAPACITIES AVAILABLE IN M.2 2280
FORM FACTOR**

ENDURANCE OF UP TO 500 TBW

5 YEAR LIMITED WARRANTY

Western Digital PC SN720 NVMe SSD

Specifications are subject to change

| | | | | | |
|---|--------------------|-----------------|-------|-----|--|
| Form Factors | | | | | M.2 2280 |
| Interface | | | | | PCIe Gen3 x4 NVMe v1.3 |
| Formatted Capacities¹ | | | | | 256GB, 512GB, 1TB, (2TB version for later release) |
| Performance² | 256GB | 512GB | 1TB | 2TB | |
| Sequential Read up to (MB/s) | 3,000 | 3,400 | 3,400 | | |
| Sequential Write up to (MB/s) | 1,600 | 2,400 | 2,800 | | |
| Random Read up to (IOPS) | 225K | 400K | 500K | | Coming Soon |
| Random Write up to (IOPS) | 185K | 330K | 400K | | |
| Endurance ³ (TBW) | 200 | 300 | 400 | | |
| Power | 256GB | 512GB | 1TB | 2TB | |
| Peak Power (10µs) (A) | 2.8 | 2.8 | 2.8 | | |
| Avg. Active Power ^{4,5} (mW) | 110 | 110 | 140 | | |
| Low Power (PS3) ⁵ (mW) | 70 | 70 | 100 | | Coming Soon |
| Sleep (PS4) ⁵ (mW) | 2.5 | 2.5 | 2.5 | | |
| Supply Voltage (V / ±5%) | 3.3 | 3.3 | 3.3 | | |
| Reliability | | | | | |
| MTTF ⁶ | | | | | Up to 1.752M hours |
| Environmental | | | | | |
| Operating Temperature ⁷ | | | | | 32°F to 158°F (0°C to 70°C) |
| Non-operating Temperature ⁸ | | | | | -67°F to 185°F (-55°C to 85°C) |
| Operating Vibration | | | | | 5 gRMS, 10-2000 Hz, 3 axes |
| Non-operating Vibration | | | | | 4.9 gRMS, 7-800 Hz, 3 axes |
| Shock | | | | | 1,500G @0.5 ms half sine, 3 pulses per face |
| Certifications | | | | | FCC, UL, TUV, KCC, BSMI, VCCI, C-Tick |
| Limited Warranty ⁹ | | | | | 5 years |
| Physical Dimensions | | | | | |
| Width | | | | | 22mm ±0.15mm |
| Length | | | | | 2280: 80mm ±0.15mm |
| Thickness (max) | | | | | 2.38mm |
| Weight | | | | | 7.5g ±1g |
| SKU | Form Factor | Capacity | | | |
| SDAPNTW-256G | M.2 2280 S3-M | 256GB | | | |
| SDAPNTW-512G | M.2 2280 S3-M | 512GB | | | |
| SDAPNTW-1T00 | M.2 2280 S3-M | 1TB | | | |
| SDAPNTW-2T00 | M.2 2280 S3-M | 2TB | | | |



Western Digital

Western Digital
5601 Great Oaks Parkway
San Jose, CA 95119, USA
www.wdc.com

Western Digital and the Western Digital logo are the registered trademarks of Western Digital Corporation or its affiliates in the U.S. and/or other countries. All marks are the property of their respective owners. Pictures shown may vary from actual products. The NVMe™ word mark is a trademark of NVM Express, Inc.

¹ As used for storage capacity, one gigabyte (GB) = one billion bytes and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment.

² Test Conditions: Performance is based on the CrystalDiskMark 5.2.2 benchmark using a 1000MB LBA range ASUS Z170A desktop with Intel® i7-6700K 4.0GHz, 8GB 2133MHz DDR4. Windows 10 Pro 64-bit using Microsoft StorNVMe driver, secondary drive. Performance may vary based on host device. 1 MB = 1,000,000 bytes. IOPS = input/output operations per second.

³ TBW (terabytes written) values calculated using JEDEC client workload (JESD219) and vary by product capacity.

⁴ Measured using MobileMark™ 2014 on HP EliteBook X360 1030 G2 with i7-7600U, 8GB RAM. Windows 10 Pro, 64-bit RS3 using Microsoft StorNVMe driver, primary drive.

⁵ Power measurements at 25°C.

⁶ MTTF = Mean Time To Failure based on internal testing using Telcordia stress part testing. MTTF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTTF does not predict an individual drive's reliability and does not constitute a warranty. (Telecordia SR-332, GB, 40°C)

⁷ Operational temperature as reported by device (composite temperature.)

⁸ Non-operational storage temperature does not guarantee data retention.

⁹ 5 years or Max Endurance (TBW) limit, whichever occurs first. 5 year warranty in regions not recognizing "limited." See <http://support.wdc.com> for more details.

Product specifications subject to change without notice. Not all products are available in all regions of the world.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331