

## 6100FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information  
please call

1-800-Belden1

**General Description:**

Security & Commercial Audio Cable, Plenum-CL2P, 2-14 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

**Usage (Overall)**

**Suitable Applications:** Intercom/PA Systems, Sound/Audio Systems

**Physical Characteristics (Overall)****Conductor**

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
2	14	19x27	BC - Bare Copper

**Total Number of Conductors:** 2

**Insulation**

**Insulation Material:**

Insulation Trade Name	Insulation Material	Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.279

**Outer Shield**

**Outer Shield Material:**

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
22	Solid	TC - Tinned Copper

**Outer Jacket**

**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (mm)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.381

**Outer Jacket Ripcord:** Yes

**Overall Cable**

**Overall Cabling Lay Length & Direction:**

Length (mm)	Twists (twist/m)
69.849725	14.4364

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	White

**Overall Nominal Diameter:** 5.588 mm

**Mechanical Characteristics (Overall)**

**UL Temperature Rating:** 75°C

**Bulk Cable Weight:** 68.904 Kg/Km

**Max. Recommended Pulling Tension:** 557.804 N

## 6100FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

Min. Bend Radius/Minor Axis:	58.420 mm
------------------------------	-----------

## Applicable Specifications and Agency Compliance (Overall)

## Applicable Standards &amp; Environmental Programs

NEC/(UL) Specification:	CL2P
-------------------------	------

NEC Articles:	725
---------------	-----

EU Directive 2011/65/EU (ROHS II):	Yes
------------------------------------	-----

EU CE Mark:	Yes
-------------	-----

EU Directive 2000/53/EC (ELV):	Yes
--------------------------------	-----

EU Directive 2002/95/EC (RoHS):	Yes
---------------------------------	-----

EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
---------------------------------------	------------

EU Directive 2002/96/EC (WEEE):	Yes
---------------------------------	-----

EU Directive 2003/11/EC (BFR):	Yes
--------------------------------	-----

CA Prop 65 (CJ for Wire & Cable):	Yes
-----------------------------------	-----

MII Order #39 (China RoHS):	Yes
-----------------------------	-----

## Flame Test

UL Flame Test:	NFPA 262
----------------	----------

## Suitability

Suitability - Indoor:	Yes
-----------------------	-----

## Plenum/Non-Plenum

Plenum (Y/N):	Yes
---------------	-----

Non-Plenum Number:	5100FE
--------------------	--------

## Electrical Characteristics (Overall)

## Nom. Inductance:

Inductance (μH/m)
-------------------

0.475745
----------

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
--------------------

278.885
---------

## Nom. Capacitance Cond. to Other Conductor &amp; Shield:

Capacitance (pF/m)
--------------------

501.993
---------

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
---------------------

8.33374
---------

## Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)
---------------------

32.810
--------

## Max. Operating Voltage - UL:

Voltage
---------

150 V RMS
-----------

## Max. Recommended Current:

Description	Current
10C Temperature Rise	8 Amps per conductor @ 25°C ambient

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
--------	-------	-------------	-------	-------	-----------

## METRIC MEASUREMENT VERSION

**6100FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled**

6100FE 877U1000	305 MT	22.226 KG	NATURAL		2 #14 FLRST FS FLRST
6100FE 8771000	305 MT	23.133 KG	NATURAL	C	2 #14 FLRST FS FLRST
6100FE 877500	152 MT	11.340 KG	NATURAL		2 #14 FLRST FS FLRST

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 08-16-2013

© 2013 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331