

R30A – AC Operated, Light Weight RVDT



- AC operation
- ± 60 degree angular sensing range
- Light weight
- Non-contact electrical design
- Wide operating temperature range
- Size 11 servo mount
- Anodized aluminum housing

DESCRIPTION

The **R30A RVDT** (Rotary Variable Differential Transformer) is an angular position sensor that incorporates a proprietary non-contact design which dramatically improves long term reliability when compared to other traditional rotary devices such as synchros, resolvers and potentiometers. This unique design eliminates assemblies that degrade over time such as slip rings, rotor windings, contact brushes and wipers, without sacrificing accuracy.

High reliability and performance are achieved through the use of a specially shaped rotor and wound coil that together simulates the linear displacement of a Linear Variable Differential Transformer (LVDT). Rotational movement of the rotor shaft results in a linear change in the amplitude of the output signal, directly proportional to the shaft angle change, while the phase of this output signal indicates the direction of displacement from the null point. Non-contact electromagnetic coupling of the rotor provides infinite resolution thus enabling absolute measurements to a fraction of a degree.

AC operation eliminates the need for integrated signal conditioning components, thereby offering the user an extremely wide operating temperature range of -55°C to $+150^{\circ}\text{C}$. Factory calibrated to operate over a ± 30 degree range, the R30A offers a non-linearity of less than $\pm 0.25\%$ of full range. Extended range operation up to a maximum of ± 60 degrees is possible with increased non-linearity. Packaged in a small, size 11 servo mount, aluminum housing with flying lead termination, the R30A is ideal for space restrictive applications.

Also see our other angular position sensor models, **R36AS** (stainless steel housing, MS style connector), **RSYN** (high output, shock and vibration tolerant), **R30D** and **R60D** (bipolar DC operation), and the **RVIT-15 Series** (single ended DC operation, voltage or current output).

Measurement Specialties, Inc. (NASDAQ MEAS) offers many other types of sensors and signal conditioners. Data sheets can be downloaded from our web site at: <http://www.meas-spec.com/datasheets.aspx>

MEAS acquired Schaevitz Sensors and the **Schaevitz™** trademark in 2000.

FEATURES

- High accuracy
- Infinite resolution
- Long term reliability
- Wide -55° to $+150^{\circ}\text{C}$ operating temp range
- Rugged anodized aluminum housing
- Shielded ABEC 3 precision bearings

APPLICATIONS

- Valve position
- Machine tool equipment
- Rotary actuator feedback
- Dancer arm position
- Process control

R30A – AC Operated, Light Weight RVDT

PERFORMANCE SPECIFICATIONS

ELECTRICAL SPECIFICATIONS						
Parameter	@10kHz Input Frequency <i>(recommended)</i>			@2.5kHz Input Frequency		
Angular range, degrees	±30°	±40°	±60°	±30°	±40°	±60°
Non-linearity, % of FR, max.	±0.25%	±0.5%	±2%	±0.25%	±0.5%	±2%
Output at range ends (*)	87mV/V	116mV/V	174mV/V	69 mV/V	92 mV/V	138 mV/V
Sensitivity	2.9 mV/V/degree			2.3 mV/V/degree		
Temp coefficient of sensitivity	0.02%/°F [0.036%/°C], 20 to +160°F [-7 to +71°C]			Not specified		
Input / Output impedances	370Ω / 1300Ω			135Ω / 600Ω		
Phase shift	+3°			+35°		
Input voltage and frequency	3 VRMS @ 2.5 to 10 kHz (10kHz recommended)					
Null voltage	0.5% of FRO, maximum					
ENVIRONMENTAL AND MECHANICAL SPECIFICATIONS						
Operating temperature	-67°F to +300°F [-55°C to 150°C]					
Mechanical angular range	360 degrees (no stops)					
Bearings	Shielded ABEC 3 precision					
Shaft diameter	3/16 inch [4.76 mm]					
Housing material	Aluminum, anodized					
Mounting	Size 11 servo mount per BU-ORD					
Moment of inertia	0.53 x 10 ⁻⁶ inch.lb-force.second ² [0.61 x 10 ⁻⁶ Kg-force.cm.second ²]					
Maximum torque, unbalance	0.004 inch.ounce-force [0.3 gram-force.cm]					
Maximum torque, friction	0.015 inch.ounce-force [1.1 gram-force.cm]					
Shaft load capability	10 lb [4.5Kg] Axial; 8 lb [3.6 Kg] Radial					
Electrical connection	6 lead wires, AWG 28, PTFE insulation, 12 inches [30cm] long					
Weight	1.3 oz [36 Grams]					
IEC 60529 rating	IP60					

Notes:


All values are nominal unless otherwise noted

(*): Unit for output at range ends is millivolt per volt of excitation (input voltage)

FR (Full Range) is the angular range, end to end; 2xA° for ±A° angular range

FRO (Full Range Output): Algebraic difference in outputs measured at the ends of the range


DIMENSIONS



Dimensions are in inch (mm)

R30A – AC Operated, Light Weight RVDT

WIRING INFORMATION



Connect Green to Blue for differential output

ORDERING INFORMATION

Description	Model	Part Number
RVDT $\pm 30^\circ$, 10KHz calibration (standard)	R30A	02560231-000
OPTIONS		
RVDT $\pm 40^\circ$, 10KHz calibration		02560231-140
RVDT $\pm 60^\circ$, 10KHz calibration		02560231-160
RVDT with 2.5KHz calibration		02560231-2XX
ACCESSORIES		
R-FLEX multipurpose coupling kit		66530072-000

Refer to our ["RVDT and RVIT Accessories"](#) data sheet for other accessories.

TECHNICAL CONTACT INFORMATION

NORTH AMERICA	EUROPE	ASIA
Measurement Specialties, Inc. 1000 Lucas Way Hampton, VA 23666 United States Phone: +1-800-745-8008 Fax: +1-757-766-4297 Email: sales@meas-spec.com Web: www.meas-spec.com	MEAS Deutschland GmbH Hauert 13 D-44227 Dortmund Germany Phone: +49-(0)231-9740-0 Fax: +49-(0)231-9740-20 Email: info.de@meas-spec.com Web: www.meas-spec.com	Measurement Specialties China Ltd. No. 26, Langshan Road High-tech Park (North) Nanshan District, Shenzhen 518057 China Phone: +86-755-33305088 Fax: +86-755-33305099 Email: info.cn@meas-spec.com Web: www.meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331