

## 512K x 8 HIGH-SPEED ASYNCHRONOUS CMOS STATIC RAM

AUGUST 2009

### FEATURES

#### HIGH SPEED: (IS61/64WV5128ALL/BLL)

- High-speed access time: 8, 10, 20 ns
- Low Active Power: 85 mW (typical)
- Low stand-by power: 7 mW (typical)  
CMOS standby

#### LOW POWER: (IS61/64WV5128ALS/BLS)

- High-speed access time: 25, 35 ns
- Low Active Power: 35 mW (typical)
- Low stand-by power: 0.6 mW (typical)  
CMOS standby
- Single power supply
  - V<sub>DD</sub> 1.65V to 2.2V (IS61WV5128Axx)
  - V<sub>DD</sub> 2.4V to 3.6V (IS61/64WV5128Bxx)
- Fully static operation: no clock or refresh required
- Three state outputs
- Industrial and Automotive temperature support
- Lead-free available

### DESCRIPTION

The *ISSI* IS61WV5128Axx and IS61/64WV5128Bxx are very high-speed, low power, 524,288-word by 8-bit CMOS static RAMs. The IS61WV5128Axx and IS61/64WV5128Bxx are fabricated using *ISSI*'s high-performance CMOS technology. This highly reliable process coupled with innovative circuit design techniques, yields higher performance and low power consumption devices.


When  $\overline{CE}$  is HIGH (deselected), the device assumes a standby mode at which the power dissipation can be reduced down with CMOS input levels.

The IS61WV5128Axx and IS61/64WV5128Bxx operate from a single power supply.

The IS61WV5128ALL and IS61/64WV5128BLL are available in 36-pin 400-mil SOJ, 36-pin mini BGA, and 44-pin TSOP (Type II) packages.

The IS61WV5128ALS and IS61/64WV5128BLS are available in 32-pin TSOP (Type I), 32-pin sTSP (Type I), 32-pin SOP and 32-pin TSOP (Type II) packages.


### FUNCTIONAL BLOCK DIAGRAM




Copyright © 2006 Integrated Silicon Solution, Inc. All rights reserved. ISSI reserves the right to make changes to this specification and its products at any time without notice. ISSI assumes no liability arising out of the application or use of any information, products or services described herein. Customers are advised to obtain the latest version of this device specification before relying on any published information and before placing orders for products.

## PIN CONFIGURATION (HIGH SPEED) (61/64WV5128ALL/BLL)

### 36 mini BGA




### 44-Pin TSOP (Type II)



## PIN DESCRIPTIONS


|                 |                     |
|-----------------|---------------------|
| A0-A18          | Address Inputs      |
| $\overline{CE}$ | Chip Enable Input   |
| $\overline{OE}$ | Output Enable Input |
| $\overline{WE}$ | Write Enable Input  |
| I/O0-I/O7       | Bidirectional Ports |
| VDD             | Power               |
| GND             | Ground              |
| NC              | No Connection       |

### 36-Pin SOJ




## PIN CONFIGURATION (LOW POWER) (61/64WV5128ALS/BLS)

32-pin TSOP (TYPE I), (Package Code T)  
32-pin sTSOP (TYPE I) (Package Code H)



32-pin SOP  
32-pin TSOP (TYPE II)  
(Package Code T2)



## PIN DESCRIPTIONS

|                 |                     |
|-----------------|---------------------|
| A0-A18          | Address Inputs      |
| $\overline{CE}$ | Chip Enable 1 Input |
| $\overline{OE}$ | Output Enable Input |
| $\overline{WE}$ | Write Enable Input  |
| I/O0-I/O7       | Input/Output        |
| VDD             | Power               |
| GND             | Ground              |

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

$V_{DD} = 3.3V \pm 5\%$

| Symbol   | Parameter                        | Test Conditions                                   | Min. | Max.           | Unit    |
|----------|----------------------------------|---------------------------------------------------|------|----------------|---------|
| $V_{OH}$ | Output HIGH Voltage              | $V_{DD} = \text{Min.}, I_{OH} = -4.0 \text{ mA}$  | 2.4  | —              | V       |
| $V_{OL}$ | Output LOW Voltage               | $V_{DD} = \text{Min.}, I_{OL} = 8.0 \text{ mA}$   | —    | 0.4            | V       |
| $V_{IH}$ | Input HIGH Voltage               |                                                   | 2    | $V_{DD} + 0.3$ | V       |
| $V_{IL}$ | Input LOW Voltage <sup>(1)</sup> |                                                   | -0.3 | 0.8            | V       |
| $I_{LI}$ | Input Leakage                    | $GND \leq V_{IN} \leq V_{DD}$                     | -1   | 1              | $\mu A$ |
| $I_{LO}$ | Output Leakage                   | $GND \leq V_{OUT} \leq V_{DD}$ , Outputs Disabled | -1   | 1              | $\mu A$ |

**Note:**

1.  $V_{IL} (\text{min.}) = -0.3V \text{ DC}$ ;  $V_{IL} (\text{min.}) = -2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.  
 $V_{IH} (\text{max.}) = V_{DD} + 0.3V \text{ DC}$ ;  $V_{IH} (\text{max.}) = V_{DD} + 2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

$V_{DD} = 2.4V-3.6V$

| Symbol   | Parameter                        | Test Conditions                                   | Min. | Max.           | Unit    |
|----------|----------------------------------|---------------------------------------------------|------|----------------|---------|
| $V_{OH}$ | Output HIGH Voltage              | $V_{DD} = \text{Min.}, I_{OH} = -1.0 \text{ mA}$  | 1.8  | —              | V       |
| $V_{OL}$ | Output LOW Voltage               | $V_{DD} = \text{Min.}, I_{OL} = 1.0 \text{ mA}$   | —    | 0.4            | V       |
| $V_{IH}$ | Input HIGH Voltage               |                                                   | 2.0  | $V_{DD} + 0.3$ | V       |
| $V_{IL}$ | Input LOW Voltage <sup>(1)</sup> |                                                   | -0.3 | 0.8            | V       |
| $I_{LI}$ | Input Leakage                    | $GND \leq V_{IN} \leq V_{DD}$                     | -1   | 1              | $\mu A$ |
| $I_{LO}$ | Output Leakage                   | $GND \leq V_{OUT} \leq V_{DD}$ , Outputs Disabled | -1   | 1              | $\mu A$ |

**Note:**

1.  $V_{IL} (\text{min.}) = -0.3V \text{ DC}$ ;  $V_{IL} (\text{min.}) = -2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.  
 $V_{IH} (\text{max.}) = V_{DD} + 0.3V \text{ DC}$ ;  $V_{IH} (\text{max.}) = V_{DD} + 2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.

## DC ELECTRICAL CHARACTERISTICS (Over Operating Range)

$V_{DD} = 1.65V-2.2V$

| Symbol         | Parameter           | Test Conditions                                   | Min. | Max.           | Unit    |
|----------------|---------------------|---------------------------------------------------|------|----------------|---------|
| $V_{OH}$       | Output HIGH Voltage | $V_{DD} = \text{Min.}, I_{OH} = -0.1 \text{ mA}$  | 1.4  | —              | V       |
| $V_{OL}$       | Output LOW Voltage  | $V_{DD} = \text{Min.}, I_{OL} = 0.1 \text{ mA}$   | —    | 0.2            | V       |
| $V_{IH}$       | Input HIGH Voltage  |                                                   | 1.4  | $V_{DD} + 0.2$ | V       |
| $V_{IL}^{(1)}$ | Input LOW Voltage   |                                                   | -0.2 | 0.4            | V       |
| $I_{LI}$       | Input Leakage       | $GND \leq V_{IN} \leq V_{DD}$                     | -1   | 1              | $\mu A$ |
| $I_{LO}$       | Output Leakage      | $GND \leq V_{OUT} \leq V_{DD}$ , Outputs Disabled | -1   | 1              | $\mu A$ |

**Note:**

1.  $V_{IL} (\text{min.}) = -0.3V \text{ DC}$ ;  $V_{IL} (\text{min.}) = -2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.  
 $V_{IH} (\text{max.}) = V_{DD} + 0.3V \text{ DC}$ ;  $V_{IH} (\text{max.}) = V_{DD} + 2.0V \text{ AC}$  (pulse width <10 ns). Not 100% tested.

## TRUTH TABLE

| Mode                         | $\overline{WE}$ | $\overline{CE}$ | $\overline{OE}$ | I/O Operation    | V <sub>DD</sub> Current |
|------------------------------|-----------------|-----------------|-----------------|------------------|-------------------------|
| Not Selected<br>(Power-down) | X               | H               | X               | High-Z           | ISB1, ISB2              |
| Output Disabled              | H               | L               | H               | High-Z           | I <sub>CC</sub>         |
| Read                         | H               | L               | L               | D <sub>OUT</sub> | I <sub>CC</sub>         |
| Write                        | L               | L               | X               | D <sub>IN</sub>  | I <sub>CC</sub>         |

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

| Symbol            | Parameter                            | Value                         | Unit |
|-------------------|--------------------------------------|-------------------------------|------|
| V <sub>TERM</sub> | Terminal Voltage with Respect to GND | −0.5 to V <sub>DD</sub> + 0.5 | V    |
| V <sub>DD</sub>   | V <sub>DD</sub> Relates to GND       | −0.3 to 4.0                   | V    |
| T <sub>STG</sub>  | Storage Temperature                  | −65 to +150                   | °C   |
| P <sub>T</sub>    | Power Dissipation                    | 1.0                           | W    |

### Notes:

1. Stress greater than those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

## CAPACITANCE<sup>(1,2)</sup>

| Symbol           | Parameter                | Conditions            | Max. | Unit |
|------------------|--------------------------|-----------------------|------|------|
| C <sub>IN</sub>  | Input Capacitance        | V <sub>IN</sub> = 0V  | 6    | pF   |
| C <sub>I/O</sub> | Input/Output Capacitance | V <sub>OUT</sub> = 0V | 8    | pF   |

### Notes:

1. Tested initially and after any design or process changes that may affect these parameters.
2. Test conditions: T<sub>A</sub> = 25°C, f = 1 MHz, V<sub>DD</sub> = 3.3V.

## HIGH SPEED (IS61WV5128ALL/BLL)

### OPERATING RANGE (V<sub>DD</sub>) (IS61WV5128ALL)

| Range      | Ambient Temperature | V <sub>DD</sub> | Speed |
|------------|---------------------|-----------------|-------|
| Commercial | 0°C to +70°C        | 1.65V-2.2V      | 20ns  |
| Industrial | -40°C to +85°C      | 1.65V-2.2V      | 20ns  |
| Automotive | -40°C to +125°C     | 1.65V-2.2V      | 20ns  |

### OPERATING RANGE (V<sub>DD</sub>) (IS61WV5128BLL)<sup>(1)</sup>

| Range      | Ambient Temperature | V <sub>DD</sub> (8 ns) <sup>1</sup> | V <sub>DD</sub> (10 ns) <sup>1</sup> |
|------------|---------------------|-------------------------------------|--------------------------------------|
| Commercial | 0°C to +70°C        | 3.3V ± 5%                           | 2.4V-3.6V                            |
| Industrial | -40°C to +85°C      | 3.3V ± 5%                           | 2.4V-3.6V                            |

**Note:**

1. When operated in the range of 2.4V-3.6V, the device meets 10ns. When operated in the range of 3.3V ± 5%, the device meets 8ns.

### OPERATING RANGE (V<sub>DD</sub>) (IS64WV5128BLL)

| Range      | Ambient Temperature | V <sub>DD</sub> (10 ns) |
|------------|---------------------|-------------------------|
| Automotive | -40°C to +125°C     | 2.4V-3.6V               |

### POWER SUPPLY CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)

| Symbol           | Parameter                                        | Test Conditions                                                                                                                          |                     | -8   |      | -10  |      | -20  |      | Unit |
|------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------|------|------|------|------|------|------|
|                  |                                                  |                                                                                                                                          |                     | Min. | Max. | Min. | Max. | Min. | Max. |      |
| I <sub>CC</sub>  | V <sub>DD</sub> Dynamic Operating Supply Current | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0 mA, f = f <sub>MAX</sub>                                                                 | Com.                | —    | 50   | —    | 40   | —    | 40   | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 55   | —    | 45   | —    | 45   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | —    | —    | 65   | —    | 65   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —    | —    | 25   |      | —    | —    |      |
| I <sub>CC1</sub> | Operating Supply Current                         | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0 mA, f = 0                                                                                | Com.                | —    | 35   | —    | 35   | —    | 30   | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 40   | —    | 40   | —    | 40   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | —    | —    | 60   | —    | 60   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —    | —    | 25   |      | —    | —    |      |
| I <sub>SB1</sub> | TTL Standby Current (TTL Inputs)                 | V <sub>DD</sub> = Max.,<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> ,<br>CE ≥ V <sub>IH</sub> , f = 0                        | Com.                | —    | 10   | —    | 10   | —    | 10   | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 15   | —    | 15   | —    | 15   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | —    | —    | 30   | —    | 30   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —    | —    | 25   |      | —    | —    |      |
| I <sub>SB2</sub> | CMOS Standby Current (CMOS Inputs)               | V <sub>DD</sub> = Max.,<br>CE ≥ V <sub>DD</sub> - 0.2V,<br>V <sub>IN</sub> ≥ V <sub>DD</sub> - 0.2V, or<br>V <sub>IN</sub> ≤ 0.2V, f = 0 | Com.                | —    | 7    | —    | 7    | —    | 7    | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 10   | —    | 10   | —    | 10   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | —    | —    | 20   | —    | 20   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | —    | —    | 2    |      | —    | —    |      |

**Note:**

- At f = f<sub>MAX</sub>, address and data inputs are cycling at the maximum frequency, f = 0 means no input lines change.
- Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

## LOW POWER (IS61WV5128ALS/BLS)

### OPERATING RANGE ( $V_{DD}$ ) (IS61WV5128ALS)

| Range      | Ambient Temperature | $V_{DD}$   | Speed |
|------------|---------------------|------------|-------|
| Commercial | 0°C to +70°C        | 1.65V-2.2V | 35ns  |
| Industrial | -40°C to +85°C      | 1.65V-2.2V | 35ns  |
| Automotive | -40°C to +125°C     | 1.65V-2.2V | 35ns  |

### OPERATING RANGE ( $V_{DD}$ ) (IS61WV5128BLS)<sup>(1)</sup>

| Range      | Ambient Temperature | $V_{DD}$  | Speed |
|------------|---------------------|-----------|-------|
| Commercial | 0°C to +70°C        | 2.4V-3.6V | 25 ns |
| Industrial | -40°C to +85°C      | 2.4V-3.6V | 25 ns |

### OPERATING RANGE ( $V_{DD}$ ) (IS64WV5128BLS)

| Range      | Ambient Temperature | $V_{DD}$  | Speed |
|------------|---------------------|-----------|-------|
| Automotive | -40°C to +125°C     | 2.4V-3.6V | 35 ns |

### POWER SUPPLY CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)

| Symbol           | Parameter                                        | Test Conditions                                                                                                                          |                     | -25  |      | -35  |      | Unit |
|------------------|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------------|------|------|------|------|------|
|                  |                                                  |                                                                                                                                          |                     | Min. | Max. | Min. | Max. |      |
| I <sub>CC</sub>  | V <sub>DD</sub> Dynamic Operating Supply Current | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0 mA, f = f <sub>MAX</sub>                                                                 | Com.                | —    | 20   | —    | 20   | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 25   | —    | 25   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | 50   | —    | 50   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | 11   |      |      |      |      |
| I <sub>CC1</sub> | Operating Supply Current                         | V <sub>DD</sub> = Max.,<br>I <sub>OUT</sub> = 0 mA, f = 0                                                                                | Com.                | —    | 10   | —    | 10   | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 12   | —    | 12   |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | 20   | —    | 20   |      |
| I <sub>SB1</sub> | TTL Standby Current (TTL Inputs)                 | V <sub>DD</sub> = Max.,<br>V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>CE ≥ V <sub>IH</sub> , f = 0                          | Com.                | —    | 5    | —    | 5    | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 7    | —    | 7    |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | 10   | —    | 10   |      |
| I <sub>SB2</sub> | CMOS Standby Current (CMOS Inputs)               | V <sub>DD</sub> = Max.,<br>CE ≥ V <sub>DD</sub> – 0.2V,<br>V <sub>IN</sub> ≥ V <sub>DD</sub> – 0.2V, or<br>V <sub>IN</sub> ≤ 0.2V, f = 0 | Com.                | —    | 1    | —    | 1    | mA   |
|                  |                                                  |                                                                                                                                          | Ind.                | —    | 2    | —    | 2    |      |
|                  |                                                  |                                                                                                                                          | Auto.               | —    | 10   | —    | 10   |      |
|                  |                                                  |                                                                                                                                          | typ. <sup>(2)</sup> | 0.2  |      |      |      |      |

**Note:**

- At f = f<sub>MAX</sub>, address and data inputs are cycling at the maximum frequency, f = 0 means no input lines change.
- Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

## AC TEST CONDITIONS

| Parameter                                                    | Unit<br>(2.4V-3.6V) | Unit<br>(3.3V $\pm$ 10%) | Unit<br>(1.65V-2.2V) |
|--------------------------------------------------------------|---------------------|--------------------------|----------------------|
| Input Pulse Level                                            | 0V to 3V            | 0V to 3V                 | 0V to 1.8V           |
| Input Rise and Fall Times                                    | 1V/ ns              | 1V/ ns                   | 1V/ ns               |
| Input and Output Timing<br>and Reference Level ( $V_{Ref}$ ) | 1.5V                | 1.5V                     | 0.9V                 |
| Output Load                                                  | See Figures 1 and 2 | See Figures 1 and 2      | See Figures 1 and 2  |

## AC TEST LOADS




Figure 1.




Figure 2.

## READ CYCLE SWITCHING CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)

| Symbol                           | Parameter                               | -8   |      | -10  |      | Unit |
|----------------------------------|-----------------------------------------|------|------|------|------|------|
|                                  |                                         | Min. | Max. | Min. | Max. |      |
| t <sub>RC</sub>                  | Read Cycle Time                         | 8    | —    | 10   | —    | ns   |
| t <sub>AA</sub>                  | Address Access Time                     | —    | 8    | —    | 10   | ns   |
| t <sub>OHA</sub>                 | Output Hold Time                        | 2.0  | —    | 2.0  | —    | ns   |
| t <sub>ACE</sub>                 | $\overline{\text{CE}}$ Access Time      | —    | 8    | —    | 10   | ns   |
| t <sub>DOE</sub>                 | $\overline{\text{OE}}$ Access Time      | —    | 4.5  | —    | 4.5  | ns   |
| t <sub>HZOE</sub> <sup>(2)</sup> | $\overline{\text{OE}}$ to High-Z Output | —    | 3    | —    | 4    | ns   |
| t <sub>LZOE</sub> <sup>(2)</sup> | $\overline{\text{OE}}$ to Low-Z Output  | 0    | —    | 0    | —    | ns   |
| t <sub>HZCE</sub> <sup>(2)</sup> | $\overline{\text{CE}}$ to High-Z Output | 0    | 3    | 0    | 4    | ns   |
| t <sub>LZCE</sub> <sup>(2)</sup> | $\overline{\text{CE}}$ to Low-Z Output  | 3    | —    | 3    | —    | ns   |
| t <sub>PU</sub>                  | Power Up Time                           | 0    | —    | 0    | —    | ns   |
| t <sub>PD</sub>                  | Power Down Time                         | —    | 8    | —    | 10   | ns   |

### Notes:

1. Test conditions assume signal transition times of 3 ns or less, timing reference levels of 1.5V, input pulse levels of 0V to 3.0V and output loading specified in Figure 1.
2. Tested with the load in Figure 2. Transition is measured  $\pm 500$  mV from steady-state voltage.

## READ CYCLE SWITCHING CHARACTERISTICS<sup>(1)</sup> (Over Operating Range)


| Symbol                           | Parameter           | -20 ns |      | -25 ns |      | -35 ns |      | Unit |
|----------------------------------|---------------------|--------|------|--------|------|--------|------|------|
|                                  |                     | Min.   | Max. | Min.   | Max. | Min.   | Max. |      |
| t <sub>RC</sub>                  | Read Cycle Time     | 20     | —    | 25     | —    | 35     | —    | ns   |
| t <sub>AA</sub>                  | Address Access Time | —      | 20   | —      | 25   | —      | 35   | ns   |
| t <sub>OHA</sub>                 | Output Hold Time    | 2.5    | —    | 4      | —    | 4      | —    | ns   |
| t <sub>ACE</sub>                 | CE Access Time      | —      | 20   | —      | 25   | —      | 35   | ns   |
| t <sub>DOE</sub>                 | OE Access Time      | —      | 8    | —      | 12   | —      | 15   | ns   |
| t <sub>HZOE</sub> <sup>(2)</sup> | OE to High-Z Output | 0      | 8    | 0      | 8    | 0      | 10   | ns   |
| t <sub>LZOE</sub> <sup>(2)</sup> | OE to Low-Z Output  | 0      | —    | 0      | —    | 0      | —    | ns   |
| t <sub>HZCE</sub> <sup>(2)</sup> | CE to High-Z Output | 0      | 8    | 0      | 8    | 0      | 10   | ns   |
| t <sub>LZCE</sub> <sup>(2)</sup> | CE to Low-Z Output  | 3      | —    | 10     | —    | 10     | —    | ns   |
| t <sub>PU</sub>                  | Power Up Time       | 0      | —    | 0      | —    | 0      | —    | ns   |
| t <sub>PD</sub>                  | Power Down Time     | —      | 20   | —      | 25   | —      | 35   | ns   |

### Notes:


1. Test conditions assume signal transition times of 1.5 ns or less, timing reference levels of 1.25V, input pulse levels of 0.4V to V<sub>DD</sub>-0.3V and output loading specified in Figure 1a.
2. Tested with the load in Figure 1b. Transition is measured ±500 mV from steady-state voltage. Not 100% tested.
3. Not 100% tested.

## AC WAVEFORMS

### READ CYCLE NO. 1<sup>(1,2)</sup> (Address Controlled) ( $\overline{CE} = \overline{OE} = V_{IL}$ )



### READ CYCLE NO. 2<sup>(1,3)</sup> ( $\overline{CE}$ and $\overline{OE}$ Controlled)



#### Notes:

1.  $\overline{WE}$  is HIGH for a Read Cycle.
2. The device is continuously selected.  $\overline{OE}$ ,  $\overline{CE} = V_{IL}$ .
3. Address is valid prior to or coincident with  $\overline{CE}$  LOW transitions.

**WRITE CYCLE SWITCHING CHARACTERISTICS<sup>(1,3)</sup>** (Over Operating Range)

| Symbol                          | Parameter                                             | -8   |      | -10  |      | Unit |
|---------------------------------|-------------------------------------------------------|------|------|------|------|------|
|                                 |                                                       | Min. | Max. | Min. | Max. |      |
| t <sub>WC</sub>                 | Write Cycle Time                                      | 8    | —    | 10   | —    | ns   |
| t <sub>SCE</sub>                | $\overline{CE}$ to Write End                          | 6.5  | —    | 8    | —    | ns   |
| t <sub>AW</sub>                 | Address Setup Time to Write End                       | 6.5  | —    | 8    | —    | ns   |
| t <sub>HA</sub>                 | Address Hold from Write End                           | 0    | —    | 0    | —    | ns   |
| t <sub>SA</sub>                 | Address Setup Time                                    | 0    | —    | 0    | —    | ns   |
| t <sub>PWE1</sub>               | $\overline{WE}$ Pulse Width ( $\overline{OE}$ = HIGH) | 6.5  | —    | 8    | —    | ns   |
| t <sub>PWE2</sub>               | $\overline{WE}$ Pulse Width ( $\overline{OE}$ = LOW)  | 8.0  | —    | 10   | —    | ns   |
| t <sub>SD</sub>                 | Data Setup to Write End                               | 5    | —    | 6    | —    | ns   |
| t <sub>HD</sub>                 | Data Hold from Write End                              | 0    | —    | 0    | —    | ns   |
| t <sub>HZWE<sup>(2)</sup></sub> | $\overline{WE}$ LOW to High-Z Output                  | —    | 3.5  | —    | 5    | ns   |
| t <sub>LZWE<sup>(2)</sup></sub> | $\overline{WE}$ HIGH to Low-Z Output                  | 2    | —    | 2    | —    | ns   |

**Notes:**

1. Test conditions assume signal transition times of 3 ns or less, timing reference levels of 1.5V, input pulse levels of 0V to 3.0V and output loading specified in Figure 1.
2. Tested with the load in Figure 2. Transition is measured  $\pm 500$  mV from steady-state voltage. Not 100% tested.
3. The internal write time is defined by the overlap of  $\overline{CE}$  LOW and  $\overline{WE}$  LOW. All signals must be in valid states to initiate a Write, but any one can go inactive to terminate the Write. The Data Input Setup and Hold timing are referenced to the rising or falling edge of the signal that terminates the write. Shaded area product in development

**WRITE CYCLE SWITCHING CHARACTERISTICS<sup>(1,2)</sup>** (Over Operating Range)


| Symbol                           | Parameter                                | -20 ns |      | -25 ns |      | -35 ns |      | Unit |
|----------------------------------|------------------------------------------|--------|------|--------|------|--------|------|------|
|                                  |                                          | Min.   | Max. | Min.   | Max. | Min.   | Max. |      |
| t <sub>WC</sub>                  | Write Cycle Time                         | 20     | —    | 25     | —    | 35     | —    | ns   |
| t <sub>SCE</sub>                 | CE to Write End                          | 12     | —    | 18     | —    | 25     | —    | ns   |
| t <sub>AW</sub>                  | Address Setup Time to Write End          | 12     | —    | 15     | —    | 25     | —    | ns   |
| t <sub>HA</sub>                  | Address Hold from Write End              | 0      | —    | 0      | —    | 0      | —    | ns   |
| t <sub>SA</sub>                  | Address Setup Time                       | 0      | —    | 0      | —    | 0      | —    | ns   |
| t <sub>PWE1</sub>                | WE Pulse Width ( $\overline{OE}$ = HIGH) | 12     | —    | 18     | —    | 30     | —    | ns   |
| t <sub>PWE2</sub>                | WE Pulse Width ( $\overline{OE}$ = LOW)  | 17     | —    | 20     | —    | 30     | —    | ns   |
| t <sub>SD</sub>                  | Data Setup to Write End                  | 9      | —    | 12     | —    | 15     | —    | ns   |
| t <sub>HD</sub>                  | Data Hold from Write End                 | 0      | —    | 0      | —    | 0      | —    | ns   |
| t <sub>HZWE</sub> <sup>(3)</sup> | WE LOW to High-Z Output                  | —      | 9    | —      | 12   | —      | 20   | ns   |
| t <sub>LZWE</sub> <sup>(3)</sup> | WE HIGH to Low-Z Output                  | 3      | —    | 5      | —    | 5      | —    | ns   |

**Notes:**


1. Test conditions for IS61WV6416LL assume signal transition times of 1.5ns or less, timing reference levels of 1.25V, input pulse levels of 0.4V to V<sub>DD</sub>-0.3V and output loading specified in Figure 1a.
2. Tested with the load in Figure 1b. Transition is measured  $\pm 500$  mV from steady-state voltage. Not 100% tested.
3. The internal write time is defined by the overlap of  $\overline{CE}$  LOW and  $\overline{WE}$  LOW. All signals must be in valid states to initiate a Write, but any one can go inactive to terminate the Write. The Data Input Setup and Hold timing are referenced to the rising or falling edge of the signal that terminates the write.

## AC WAVEFORMS

### WRITE CYCLE NO. 1<sup>(1,2)</sup> ( $\overline{CE}$ Controlled, $\overline{OE}$ = HIGH or LOW)




**WRITE CYCLE NO. 2**<sup>(1,2)</sup> ( $\overline{WE}$  Controlled:  $\overline{OE}$  is HIGH During Write Cycle)



**Notes:**

1. The internal write time is defined by the overlap of  $\overline{CE}$  LOW and  $\overline{WE}$  LOW. All signals must be in valid states to initiate a Write, but any one can go inactive to terminate the Write. The Data Input Setup and Hold timing are referenced to the rising or falling edge of the signal that terminates the Write.
2. I/O will assume the High-Z state if  $\overline{OE} > V_{IH}$ .

**WRITE CYCLE NO. 3** ( $\overline{WE}$  Controlled:  $\overline{OE}$  is LOW During Write Cycle)



## HIGH SPEED (IS61WV5128ALL/BLL)

### DATA RETENTION SWITCHING CHARACTERISTICS (2.4V-3.6V)

| Symbol           | Parameter                          | Test Condition                                             | Options               | Min.            | Typ. <sup>(1)</sup> | Max.         | Unit |
|------------------|------------------------------------|------------------------------------------------------------|-----------------------|-----------------|---------------------|--------------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                                |                       | 2.0             | —                   | 3.6          | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 2.0V, $\overline{CE} \geq V_{DD} - 0.2V$ | Com.<br>Ind.<br>Auto. | —<br>—<br>—     | 2<br>—<br>—         | 6<br>8<br>15 | mA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                                |                       | 0               | —                   | —            | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                                |                       | t <sub>RC</sub> | —                   | —            | ns   |


**Note 1:** Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

### DATA RETENTION SWITCHING CHARACTERISTICS (1.65V-2.2V)

| Symbol           | Parameter                          | Test Condition                                             | Options      | Min.            | Typ. <sup>(1)</sup> | Max.   | Unit |
|------------------|------------------------------------|------------------------------------------------------------|--------------|-----------------|---------------------|--------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                                |              | 1.2             | —                   | 3.6    | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 1.2V, $\overline{CE} \geq V_{DD} - 0.2V$ | Com.<br>Ind. | —<br>—          | 2<br>—              | 6<br>8 | mA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                                |              | 0               | —                   | —      | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                                |              | t <sub>RC</sub> | —                   | —      | ns   |

**Note 1:** Typical values are measured at V<sub>DD</sub> = 1.8V, T<sub>A</sub> = 25°C and not 100% tested.

### DATA RETENTION WAVEFORM ( $\overline{CE}$ Controlled)



## LOW POWER (IS61WV5128ALS/BLS)

### DATA RETENTION SWITCHING CHARACTERISTICS (2.4V-3.6V)

| Symbol           | Parameter                          | Test Condition                                      | Options               | Min.            | Typ. <sup>(1)</sup> | Max.         | Unit |
|------------------|------------------------------------|-----------------------------------------------------|-----------------------|-----------------|---------------------|--------------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                         |                       | 2.0             | —                   | 3.6          | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 2.0V, CE ≥ V <sub>DD</sub> - 0.2V | Com.<br>Ind.<br>Auto. | —<br>—<br>—     | 0.2<br>—<br>—       | 1<br>2<br>10 | mA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                         |                       | 0               | —                   | —            | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                         |                       | t <sub>RC</sub> | —                   | —            | ns   |


**Note 1:** Typical values are measured at V<sub>DD</sub> = 3.0V, T<sub>A</sub> = 25°C and not 100% tested.

### DATA RETENTION SWITCHING CHARACTERISTICS (1.65V-2.2V)

| Symbol           | Parameter                          | Test Condition                                      | Options      | Min.            | Typ. <sup>(1)</sup> | Max.   | Unit |
|------------------|------------------------------------|-----------------------------------------------------|--------------|-----------------|---------------------|--------|------|
| V <sub>DR</sub>  | V <sub>DD</sub> for Data Retention | See Data Retention Waveform                         |              | 1.2             | —                   | 3.6    | V    |
| I <sub>DR</sub>  | Data Retention Current             | V <sub>DD</sub> = 1.2V, CE ≥ V <sub>DD</sub> - 0.2V | Com.<br>Ind. | —<br>—          | 0.2<br>—            | 1<br>2 | mA   |
| t <sub>SDR</sub> | Data Retention Setup Time          | See Data Retention Waveform                         |              | 0               | —                   | —      | ns   |
| t <sub>RDR</sub> | Recovery Time                      | See Data Retention Waveform                         |              | t <sub>RC</sub> | —                   | —      | ns   |

**Note 1:** Typical values are measured at V<sub>DD</sub> = 1.8V, T<sub>A</sub> = 25°C and not 100% tested.

### DATA RETENTION WAVEFORM ( $\overline{\text{CE}}$ Controlled)



## ORDERING INFORMATION (HIGH SPEED)

**Commercial Range: 0°C to +70°C**

**Voltage Range: 2.4V to 3.6V**

| Speed (ns)           | Order Part No.     | Package                   |
|----------------------|--------------------|---------------------------|
| 10 (8 <sup>1</sup> ) | IS61WV5128BLL-10TL | TSOP (Type II), Lead-free |

**Note:**

1. Speed = 8ns for  $V_{DD} = 3.3V \pm 5\%$ . Speed = 10ns for  $V_{DD} = 2.4V$  to 3.6V.

**Industrial Range: -40°C to +85°C**

**Voltage Range: 2.4V to 3.6V**

| Speed (ns)           | Order Part No.      | Package                                 |
|----------------------|---------------------|-----------------------------------------|
| 10 (8 <sup>1</sup> ) | IS61WV5128BLL-10BI  | 36-ball mini BGA (6mm x 8mm)            |
|                      | IS61WV5128BLL-10BLI | 36-ball mini BGA (6mm x 8mm), Lead-free |
|                      | IS61WV5128BLL-10TI  | TSOP (Type II)                          |
|                      | IS61WV5128BLL-10TLI | TSOP (Type II), Lead-free               |
|                      | IS61WV5128BLL-10KLI | 400-mil Plastic SOJ, Lead-free          |

**Note:**

1. Speed = 8ns for  $V_{DD} = 3.3V \pm 5\%$ . Speed = 10ns for  $V_{DD} = 2.4V$  to 3.6V.

**Industrial Range: -40°C to +85°C**

**Voltage Range: 1.65V to 2.2V**

| Speed (ns) | Order Part No.     | Package                      |
|------------|--------------------|------------------------------|
| 20         | IS61WV5128ALL-20BI | 36-ball mini BGA (6mm x 8mm) |
|            | IS61WV5128ALL-20TI | TSOP (Type II)               |

**Automotive Range: -40°C to +125°C**

**Voltage Range: 2.4V to 3.6V**




| Speed (ns) | Order Part No.        | Package                                    |
|------------|-----------------------|--------------------------------------------|
| 10         | IS64WV5128BLL-10BA3   | 36-ball mini BGA (6mm x 8mm)               |
|            | IS64WV5128BLL-10BLA3  | 36-ball mini BGA (6mm x 8mm), Lead-free    |
|            | IS64WV5128BLL-10CTA3  | TSOP (Type II), Copper Leadframe           |
|            | IS64WV5128BLL-10CTLA3 | TSOP (Type II), Copper Leadframe Lead-free |

**ORDERING INFORMATION (LOW POWER)**

**Industrial Range: -40°C to +85°C**

**Voltage Range: 2.4V to 3.6V**

| Speed (ns) | Order Part No.      | Package                   |
|------------|---------------------|---------------------------|
| 25         | IS61WV5128BLS-25TLI | TSOP (Type II), Lead-free |



| SYMBOL | DIMENSION IN MM |       | DIMENSION IN INCH |       |
|--------|-----------------|-------|-------------------|-------|
|        | MIN.            | MAX.  | MIN.              | MAX.  |
| A      | 3.25            | 3.76  | 0.128             | 0.148 |
| A1     | 2.08            |       | 0.082             |       |
| A3     | 0.635           |       | 0.025             |       |
| b      | 0.38            | 0.51  | 0.015             | 0.020 |
| b2     | 0.66            | 0.71  | 0.026             | 0.028 |
| D      | 23.36           | 23.49 | 0.920             | 0.930 |
| E      | 11.05           | 11.18 | 0.435             | 0.445 |
| E1     | 10.03           | 10.16 | 0.395             | 0.405 |
| E2     | 9.40            | BSC.  | 0.370             | BSC.  |
| e      | 1.27            | BSC.  | 0.050             | BSC.  |
| ZD     | 0.95            | REF.  | 0.037             | REF.  |

NOTE :

- 1. Controlling dimension : mm
- 2. Dimension D and E1 do not include mold protrusion .
- 3. Dimension b2 does not include dambar protrusion/intrusion.
- 4. Formed leads shall be planar with respect to one another within 0.1mm at the seating plane after final test.
- 5. Reference document : JEDEC SPEC MS-027.



36L 400mil SOJ  
Package Outline


REV.

F

DATE

12/20/2007


TOP VIEW






| SYMBOL   | DIMENSION IN MM |      |      | DIMENSION IN INCH |       |       |
|----------|-----------------|------|------|-------------------|-------|-------|
|          | MIN.            | NOM. | MAX. | MIN.              | NOM.  | MAX.  |
| A        |                 |      | 1.20 |                   |       | 0.047 |
| A1       | 0.20            |      | 0.30 | 0.008             |       | 0.012 |
| $\phi b$ | 0.30            | 0.35 | 0.40 | 0.012             | 0.014 | 0.016 |
| D        | 7.90            | 8.00 | 8.10 | 0.311             | 0.315 | 0.319 |
| D1       | 5.25 BSC.       |      |      | 0.207 BSC.        |       |       |
| E        | 5.90            | 6.00 | 6.10 | 0.232             | 0.236 | 0.240 |
| E1       | 3.75 BSC.       |      |      | 0.148 BSC.        |       |       |
| e        | 0.75 BSC.       |      |      | 0.030 BSC.        |       |       |
| ZD       | 1.375 REF.      |      |      | 0.054 REF.        |       |       |
| ZE       | 1.125 REF.      |      |      | 0.044 REF.        |       |       |

NOTE :

1. CONTROLLING DIMENSION : MM .
2. Reference document : JEDEC MO-207



|      |       |                                        |      |   |      |            |
|------|-------|----------------------------------------|------|---|------|------------|
| ISSI | TITLE | 36/48L 6x8mm TF-BGA<br>Package Outline | REV. | E | DATE | 08/12/2008 |
|------|-------|----------------------------------------|------|---|------|------------|



NOTE :



- 1. CONTROLLING DIMENSION : MM
- 2. DIMENSION D AND E1 DO NOT INCLUDE MOLD PROTRUSION.
- 3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION/INTRUSION.

| SYMBOL | DIMENSION IN MM |       |       | DIMENSION IN INCH |       |       |
|--------|-----------------|-------|-------|-------------------|-------|-------|
|        | MIN.            | NOM.  | MAX.  | MIN.              | NOM.  | MAX.  |
| A      | 1.00            |       | 1.20  | 0.039             |       | 0.047 |
| A1     | 0.05            |       | 0.15  | 0.002             |       | 0.006 |
| A2     | 0.95            | 1.00  | 1.05  | 0.037             | 0.039 | 0.041 |
| b      | 0.30            |       | 0.45  | 0.012             |       | 0.018 |
| D      | 18.28           | 18.41 | 18.54 | 0.720             | 0.725 | 0.730 |
| E      | 11.56           | 11.76 | 11.96 | 0.455             | 0.463 | 0.471 |
| E1     | 10.03           | 10.16 | 10.29 | 0.395             | 0.400 | 0.405 |
| e      | 0.80 BSC.       |       |       | 0.031 BSC.        |       |       |
| L      | 0.40            |       | 0.69  | 0.016             |       | 0.027 |
| L1     | 0.25 BSC.       |       |       | 0.010 BSC.        |       |       |
| ZD     | 0.805 REF.      |       |       | 0.032 REF.        |       |       |
| Θ      | 0               |       | 8°    | 0                 |       | 8°    |




44L 400mil TSOP-2  
Package Outline

REV. F  
DATE 06/04/2008






DETAIL A



**NOTE:**

1. CONTROLLING DIMENSION : MM
2. DIMENSION D1 AND E DO NOT INCLUDE MOLD PROTRUSION.
3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION/INTRUSION.
4. Reference Document : JEDEC MO-183

| SYMBOL | DIMENSION IN MM |           |       | DIMENSION IN INCH |            |       |
|--------|-----------------|-----------|-------|-------------------|------------|-------|
|        | MIN             | NDM       | MAX   | MIN               | NDM        | MAX   |
| A      | 0.95            |           | 1.25  | 0.037             |            | 0.049 |
| A1     | 0.05            |           | 0.15  | 0.002             |            | 0.008 |
| A2     | 0.90            |           | 1.05  | 0.035             |            | 0.041 |
| b      | 0.16            |           | 0.27  | 0.006             |            | 0.011 |
| D      | 13.10           | 13.40     | 13.70 | 0.516             | 0.528      | 0.539 |
| D1     | 11.70           | 11.80     | 11.90 | 0.461             | 0.465      | 0.469 |
| E      | 7.90            | 8.00      | 8.10  | 0.311             | 0.315      | 0.319 |
| e      |                 | 0.50 BSC. |       |                   | 0.020 BSC. |       |
| L      | 0.30            | 0.50      | 0.70  | 0.012             | 0.020      | 0.028 |
| L1     |                 | 0.25 BSC. |       |                   | 0.010 BSC. |       |
| ZD     |                 | 0.25 REF. |       |                   | 0.010 REF. |       |
| Θ      | 0               | 3°        | 5°    | 0                 | 3°         | 5°    |




NOTE :

- 1. CONTROLLING DIMENSION : MM
- 2. DIMENSION D AND E1 DO NOT INCLUDE MOLD PROTRUSION.
- 3. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION/INTRUSION.

| SYMBOL | DIMENSION IN MM |      |       | DIMENSION IN INCH |      |       |
|--------|-----------------|------|-------|-------------------|------|-------|
|        | MIN.            | NOM. | MAX.  | MIN.              | NOM. | MAX.  |
| A      | 2.62            |      | 3.12  | 0.103             |      | 0.123 |
| A1     | 0.05            |      | 0.30  | 0.002             |      | 0.012 |
| b      | 0.33            |      | 0.51  | 0.013             |      | 0.020 |
| D      | 20.24           |      | 20.75 | 0.797             |      | 0.817 |
| E      | 13.79           |      | 14.45 | 0.543             |      | 0.569 |
| E1     | 11.18           |      | 11.43 | 0.440             |      | 0.450 |
| e      | 1.27 BSC.       |      |       | 0.050 BSC.        |      |       |
| L      | 0.38            |      | 1.27  | 0.015             |      | 0.050 |
| L1     | 0.25 BSC.       |      |       | 0.010 BSC.        |      |       |
| ZD     | 0.725 REF.      |      |       | 0.029 REF.        |      |       |
| θ      | 0               |      | 8°    | 0                 |      | 8°    |

|      |       |                                   |      |   |      |            |
|------|-------|-----------------------------------|------|---|------|------------|
| ISSI | TITLE | 32L 450mil SOP<br>Package Outline | REV. | D | DATE | 04/20/2009 |
|------|-------|-----------------------------------|------|---|------|------------|





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331