

## Flexible and Durable Activations for Multiple Systems

525 Series Service Fittings provide an expanded range of services to include audio/video devices. 525 Series Service Fittings' four-piece design delivers the flexibility of interchangeable faceplates and the durability to withstand multiple moves, adds and changes. These fittings can be applied to Walkerdut® Pro Series, Walkerdut® Underfloor Duct, Flushduct® and Walker 800 Series Floor Boxes.

525 Series Service Fittings are made from die-cast aluminum with a brushed satin finish. Each pedestal provides a single service, with multiple fittings required for two or more services. This line of fittings is ideal for use in schools, commercial office spaces and in labs.














525 Series Fittings provide single service wiring solutions.

### FEATURES & BENEFITS




- **All 525 Series Fittings are UL Listed to U.S. and Canadian underfloor duct safety standards.**
- **Enlarged baseplate openings.** Two openings in the baseplate have been enlarged to accept 11/4" [32mm] locking nipple. Third opening accepts 1" [25mm] locking nipple. Provides greater wiring capacity.
- **Unique 3-position baseplate.** Allows fitting to be centered or adjusted 3/4" [19.1mm] to one side of center. This integral flexibility permits the fitting to be placed clear of furniture, equipment or adjacent fittings.
- **Interchangeable faceplates.** The 525 Series uses the same faceplates as the previous 505 Series four-piece fittings. Functional changes are now as simple as changing faceplates instead of entire activations.
- **A/V compatibility.** Accepts Extron® Electronics and Ortronics® audio/video devices.
- **Die-cast aluminum with satin finish.** Durable construction provides a fitting that performs and maintains a good appearance after years of service.
- **Flexible four-piece design.** Accommodates two removable faceplates. Choices include blank, power and communication styles. Reduces labor cost for making moves and changes.
- **New housing design.** Reduces the amount of visible lines and angles, improving aesthetic impact.
- **Datacom connectivity options.** Accepts industry standard and proprietary devices from a wide range of manufacturers to provide a seamless and aesthetically pleasing interface for voice, data, audio, and video applications at the point of use.





## Four-Piece Service Fittings

| Catalog No./Item                                                                        | Description/Specifications                                      |
|-----------------------------------------------------------------------------------------|-----------------------------------------------------------------|
| 525A   | <b>Service Fitting</b> – 1" [25mm] I.D. grommet one side.       |
| 525B   | <b>Service Fitting</b> – 1" [25mm] I.D. grommet both sides.     |
| 525C   | <b>Service Fitting</b> – 1 1/4" [32mm] I.D. grommet one side.   |
| 525D   | <b>Service Fitting</b> – 1 1/4" [32mm] I.D. grommet both sides. |
| 525F   | <b>Service Fitting</b> – Duplex receptacle opening, one side.   |
| 525G  | <b>Service Fitting</b> – Duplex receptacle opening, both sides  |









| Catalog No./Item                                                                          | Description/Specifications                                                                                              |
|-------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| 525H    | <b>Service Fitting</b> – 20A, 125V duplex receptacle, one side.                                                         |
| 525I    | <b>Service Fitting</b> – 20A, 125V duplex receptacle, both sides.                                                       |
| 525J    | <b>Service Fitting</b> – Decora or GFI receptacle opening, one side.                                                    |
| 525RT   | <b>Service Fitting</b> – Includes faceplate with opening, one side. Ortronics Series II and TracJack adapters included. |
| 525ACT  | <b>Service Fitting</b> – Includes faceplate with opening, one side. Activate CM-MAB adapter included.                   |

## 525 Series Accessories

| Catalog No./Item                                                                                                               | Description/Specifications                                                             |
|--------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| 500RT                                       | <b>Faceplate</b> – Single opening. Ortronics Series II and TracJack adapters included. |
| 500ACT <br>2 5/8" [67mm]<br>4 7/16" [113mm] | <b>Faceplate</b> – Single opening. Activate CM-MAB adapter included.                   |
| 500B                                        | <b>Faceplate</b> – Blank.                                                              |
| 500-MAAP                                    | <b>Faceplate</b> – Accepts Extron® Electronics MAAP device plates.                     |
| 500T                                        | <b>Faceplate</b> – 1" [25mm] I.D. grommeted hole.                                      |

| Catalog No./Item                                                                             | Description/Specifications                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
|----------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|---------------|-----|---------------|-----|---------------|--------|----------------|-------|---------------|------|--------------|--------|----------------|-------|---------------|--------|----------------|-------|---------------|---|-----------|
| 500SP-   | <b>Faceplate</b> – Single opening. Suffix indicates hole diameter. <table border="1"> <thead> <tr> <th>SUFFIX</th><th>HOLE DIAMETER</th></tr> </thead> <tbody> <tr> <td>1/2</td><td>1/2" [12.7mm]</td></tr> <tr> <td>7/8</td><td>7/8" [22.2mm]</td></tr> <tr> <td>1.0625</td><td>1.0625" [27mm]</td></tr> <tr> <td>1 1/8</td><td>1 1/8" [29mm]</td></tr> <tr> <td>1.39</td><td>1.39" [35mm]</td></tr> <tr> <td>1 7/16</td><td>1 7/16" [37mm]</td></tr> <tr> <td>1 1/2</td><td>1 1/2" [38mm]</td></tr> <tr> <td>1 9/16</td><td>1 9/16" [40mm]</td></tr> <tr> <td>1 5/8</td><td>1 5/8" [41mm]</td></tr> <tr> <td>2</td><td>2" [51mm]</td></tr> </tbody> </table> | SUFFIX | HOLE DIAMETER | 1/2 | 1/2" [12.7mm] | 7/8 | 7/8" [22.2mm] | 1.0625 | 1.0625" [27mm] | 1 1/8 | 1 1/8" [29mm] | 1.39 | 1.39" [35mm] | 1 7/16 | 1 7/16" [37mm] | 1 1/2 | 1 1/2" [38mm] | 1 9/16 | 1 9/16" [40mm] | 1 5/8 | 1 5/8" [41mm] | 2 | 2" [51mm] |
| SUFFIX                                                                                       | HOLE DIAMETER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1/2                                                                                          | 1/2" [12.7mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 7/8                                                                                          | 7/8" [22.2mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1.0625                                                                                       | 1.0625" [27mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1 1/8                                                                                        | 1 1/8" [29mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1.39                                                                                         | 1.39" [35mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1 7/16                                                                                       | 1 7/16" [37mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1 1/2                                                                                        | 1 1/2" [38mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1 9/16                                                                                       | 1 9/16" [40mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 1 5/8                                                                                        | 1 5/8" [41mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 2                                                                                            | 2" [51mm]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 500DR    | <b>Faceplate</b> – For single duplex receptacle.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 500-GFI  | <b>Faceplate</b> – For Decora or GFI device.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |
| 525HB    | <b>Housing and Base Plate</b> – Only.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |        |               |     |               |     |               |        |                |       |               |      |              |        |                |       |               |        |                |       |               |   |           |

## Activation Accessories

| Catalog No./Item                                                                                                                                                                                        | Description/Specifications                                                                                                                                                                               | Catalog No./Item                                                                                     | Description/Specifications                                                                                                                   |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| <b>436-2 -7/8 [22.2mm]</b><br><b>-11/2 [38mm]</b><br><b>-2 [51mm]</b><br><b>-23/8 [60mm]</b><br><b>-3 [76mm]</b><br>   | <b>Afterset Inserts for Duct</b> – 2" [51mm] IPS. 2 1/2" [64mm] core drill size; 2 1/4" [57mm] hole saw size. Suffix denotes height.                                                                     | <b>825SFCK</b><br> | <b>Conversion Kit</b> – To attach service fitting to 800 Series floor boxes. Includes 825C Ring, 1124L-1 Locking Nipple, and 825P-1 Adapter. |
| <b>424 -3/4 [19.1mm]</b><br><b>-1 [25mm]</b><br>                                                                       | <b>Extensions</b> – For 2" [51mm] IPS preset or afterset inserts. Suffix denotes height of extension.                                                                                                    | <b>430S505</b><br> | <b>Single Trim Plate</b> – To attach fitting to Walkerdut Pro Series Preset. Base of 525 fitting not needed.                                 |
| <b>1126A-1/4 [6.4mm]</b><br><b>-3/4 [19.1mm]</b><br><b>-1 [25mm]</b><br><b>-11/4 [32mm]</b><br><b>-11/2 [38mm]</b><br> | <b>Adapter</b> – To change 2" [51mm] IPS preset or afterset to reduced opening size. Suffix denotes opening size.                                                                                        | <b>431D505</b><br> | <b>Double Trim Plate</b> – To attach two fittings to Walkerdut Pro Series Presets. Base of 525 fitting not needed.                           |
| <b>1124 -1 [25mm]</b><br><b>1124L -1 [25mm]</b><br>                                                                    | <b>Locking Nipple</b> – For 1" [25mm] IPS opening; 1" [25mm] long.<br><b>Locking Nipple</b> – For 1" [38mm] IPS opening; 1 1/2" [38mm] long.                                                             | <b>428B525</b><br> | <b>Flush Carpet Plate</b> – To attach to Walkerdut Pro Series Plate. Includes hardware.                                                      |
| <b>1124-11/4 [38mm]</b><br><b>1124L -11/4 [38mm]</b><br>                                                             | <b>Locking Nipple</b> – For 1 1/4" [32mm] IPS opening; 1" [25mm] long.<br><b>Locking Nipple</b> – For 1 1/4" [32mm] IPS opening; 1 1/2" [38mm] long.                                                     |                                                                                                      |                                                                                                                                              |
| <b>1124F-1 [25mm]</b><br>                                                                                            | <b>Locking Nipple</b> – For 1" [25mm] IPS opening; 5/8" [16mm] long. For use on Flushduct Infloor Raceway.                                                                                               |                                                                                                      |                                                                                                                                              |
| <b>455F-1</b><br>                                                                                                    | <b>Outlet Flange</b> – For 1 5/8" [241mm] diameter opening on Flushduct Infloor Raceway. Accepts 1" [25mm] locking nipple.                                                                               |                                                                                                      |                                                                                                                                              |
| <b>1044B</b><br><b>1044S</b> For 3/4" IPS                                                                                                                                                               | <b>Blanking Plates</b> – 3 1/2" [89mm] diameter top plate<br><br><b>NOTE: B - Brass</b><br><b>S - Stainless Steel</b> |                                                                                                      |                                                                                                                                              |
| <b>1045B</b><br><b>1045S</b> For 1" IPS                                                                                                                                                                 |                                                                                                                                                                                                          |                                                                                                      |                                                                                                                                              |
| <b>1046B</b><br><b>1046S</b> For 1 1/4" IPS                                                                                                                                                             |                                                                                                                                                                                                          |                                                                                                      |                                                                                                                                              |
| <b>1043B</b><br><b>1043S</b> For 2" IPS                                                                                                                                                                 |                                                                                                                                                                                                          |                                                                                                      |                                                                                                                                              |
|                                                                                                                                                                                                         |                                                                                                                                                                                                          |                                                                                                      |                                                                                                                                              |

### Cross Reference

| OLD CATALOG NUMBER | NEW CATALOG NUMBER |
|--------------------|--------------------|
| 505A, 501E         | 525A               |
| 505ACT             | 525ACT             |
| 505B, 502E         | 525B               |
| 505C, 503E         | 525C               |
| 505F               | 525F               |
| 505G               | 525G               |
| 505H, 523E         | 525H               |
| 505HB              | 525HB              |
| 505I               | 525I               |
| 505J               | 525J               |
| 505RT              | 525RT              |



**Electrical Wiring Systems**

60 Woodlawn Street  
West Hartford, CT 06110  
Phone: 1.877.BY.LEGRAND (295-3472)  
[www.legrand.us](http://www.legrand.us)

570 Applewood Crescent  
Vaughan, Ontario L4K 4B4  
Phone: 905.738.9195  
[www.legrand.ca](http://www.legrand.ca)





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331