

Solid Tantalum Chip Capacitors TANTAMOUNT® Conformal Coated, Maximum CV



FEATURES

- Large capacitance rating range
- Terminations: Tin (2) standard
- 8 mm, 12 mm tape and reel packaging available per EIA 481-1 and reeling per IEC 286-3. 7" [178 mm] standard. 13" [330 mm] available.
- Case code compatibility with EIA 535BAAC and CECC30801 molded chips



RoHS*
COMPLIANT

PERFORMANCE CHARACTERISTICS

Operating Temperature: - 55 °C to + 85 °C
(To + 125 °C with voltage derating)

Note: Refer to Doc. 40088

Capacitance Range: 0.1 µF to 1500 µF

Capacitance Tolerance: ± 10 %, ± 20 % standard

Voltage Rating: 4 WVDC to 50 WVDC

| ORDERING INFORMATION | | | | | | |
|--|--|-----------------------------|--|----------------------------------|--|---|
| 595D TYPE | 106 CAPACITANCE | X0 CAPACITANCE TOLERANCE | 010 DC VOLTAGE RATING AT + 85 °C | A CASE CODE | 2 TERMINATION | T PACKAGING |
| | This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow. | X0 = ± 20 % X9 = ± 10 % | This is expressed in volts. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an "R" (6R3 = 6.3 volts). | See Ratings and Case Codes Table | 2 = 100 % Tin 4 = Gold Plated 8 = Solder Plated (60/40) Special Order | T = Tape and Reel 7" [178 mm] Reel W = 13" [330 mm] Reel See Tape and Reel Specifications. |
| <p>Note: Preferred Tolerance and reel sizes are in bold. We reserve the right to supply higher voltage ratings and tighter capacitance tolerance capacitors in the same case size. Voltage substitutions will be marked with the higher voltage rating.</p> | | | | | | |

DIMENSIONS in inches [millimeters]



| CASE CODE | L (Max.) | W | H | A | B | D (REF.) | J (MAX.) |
|-----------|------------------------------|--|--|--------------------------------|--------------------------------|----------------|----------------|
| T | 0.087 [2.2] | 0.045 ± 0.012 [1.1 ± 0.3] | 0.045 ± 0.012 [1.1 ± 0.3] | 0.016 ± 0.008 [0.4 ± 0.2] | 0.042 ± 0.010 [1.07 ± 0.25] | 0.063 [1.6] | 0.004 [0.1] |
| S | 0.126 ± 0.008 [3.2 ± 0.2] | 0.067 ± 0.008 [1.7 ± 0.2] | 0.051 ± 0.008 [1.3 ± 0.2] | 0.031 ± 0.012 [0.80 ± 0.30] | 0.078 ± 0.012 [2.0 ± 0.3] | 0.086 [2.2] | 0.004 [0.1] |
| A | 0.146 [3.7] | 0.072 ± 0.012 [1.8 ± 0.3] | 0.056 ± 0.012 [1.4 ± 0.3] | 0.031 ± 0.012 [0.80 ± 0.30] | 0.085 ± 0.016 [2.2 ± 0.4] | 0.115 [2.9] | 0.004 [0.1] |
| B | 0.158 [4.0] | 0.110 + 0.012 - 0.016 [2.8 + 0.3 - 0.4] | 0.075 + 0.012 - 0.024 [1.9 + 0.3 - 0.6] | 0.031 ± 0.012 [0.80 ± 0.30] | 0.097 ± 0.016 [2.5 ± 0.4] | 0.138 [3.5] | 0.004 [0.1] |
| C | 0.281 [7.1] | 0.126 ± 0.012 [3.2 ± 0.3] | 0.098 ± 0.012 [2.5 ± 0.3] | 0.051 ± 0.012 [1.3 ± 0.30] | 0.180 ± 0.024 [4.6 ± 0.6] | 0.236 [6.0] | 0.004 [0.1] |
| G | 0.205 ± 0.016 [5.2 ± 0.4] | 0.144 ± 0.016 [3.65 ± 0.4] | 0.087 [2.2] Max. | 0.051 ± 0.012 [1.3 ± 0.3] | 0.133 ± 0.016 [3.4 ± 0.4] | 0.173 [4.4] | 0.004 [0.1] |
| H | 0.205 ± 0.016 [5.2 ± 0.4] | 0.181 ± 0.016 [4.6 ± 0.4] | 0.078 [2.0] Max. | 0.051 ± 0.012 [1.3 ± 0.30] | 0.133 ± 0.016 [3.4 ± 0.4] | 0.173 [4.4] | 0.004 [0.1] |
| D | 0.293 [7.5] | 0.170 ± 0.012/- 0.024 [4.3 ± 0.3/- 0.6] | 0.110 ± 0.012 [2.8 ± 0.3] | 0.051 ± 0.012 [1.3 ± 0.30] | 0.180 ± 0.024 [4.6 ± 0.6] | 0.253 [6.4] | 0.004 [0.1] |
| M | 0.129 ± 0.012 [3.3 ± 0.3] | 0.106 ± 0.012 [2.7 ± 0.3] | 0.067 ± 0.012 [1.7 ± 0.3] | 0.031 ± 0.012 [0.80 ± 0.3] | 0.078 ± 0.012 [2.0 ± 0.3] | 0.095 [2.5] | 0.004 [0.1] |
| R | 0.283 [7.2] | 0.235 ± 0.012/- 0.024 [6.0 ± 0.3/- 0.6] | 0.136 ± 0.012 [3.5 ± 0.3] | 0.051 ± 0.012 [1.3 ± 0.30] | 0.180 ± 0.024 [4.6 ± 0.6] | 0.243 [6.2] | 0.004 [0.1] |

Note: The anode termination (D less B) will be a minimum of 0.010" (0.3 mm). T Case = 0.005" (0.13 mm) minimum.

* Pb containing terminations are not RoHS compliant, exemptions may apply



Solid Tantalum Chip Capacitors
TANTAMOUNT® Conformal Coated,
Maximum CV

Vishay Sprague

| RATINGS AND CASE CODES | | | | | | | | |
|------------------------|-----|---------|-------|------|------|------|------|------|
| µF | 4 V | 6.3 V | 10 V | 16 V | 20 V | 25 V | 35 V | 50 V |
| 0.10 | | | | | | | | T |
| 0.15 | | | | | | | | T |
| 0.22 | | | | | | | | T |
| 0.33 | | | | | | | T | A |
| 0.47 | | | | | | T | A | A |
| 0.68 | | | | | T | | A | A/B |
| 1.0 | | | | | T | A | A | A/B |
| 1.5 | | | | T | | A | A/B | C |
| 2.2 | | | T | T/A | A | A | B | B/C |
| 3.3 | | T | | T | A | B/C | C | C |
| 4.7 | T | | T | A | A/B | | B/C | C |
| 6.8 | | T | | A | A/B | B | C | C/D |
| 10 | T | | A | A/B | B | B/C | D | D/R |
| 15 | A | A | A/B | A/B | B | C | C/D | R |
| 22 | | A/B | A | B/M | B/C | C/D | D/R | R |
| 33 | A/B | S/A/B | A/B | B/C | | C/D | R | |
| 47 | A | A/B | B | B/C | C/D | D/R | R | |
| 68 | A | A/B | B/C | C/D | D | D/R | | |
| 100 | A/B | B/C/M | B/D | C/D | D/R | R | | |
| 120 | C | C | D | R | R | | | |
| 150 | B/C | | C/D | D/R | R | | | |
| 180 | D | D | D/R | R | | | | |
| 220 | C/D | C/D/G/H | C/D/R | R | | | | |
| 270 | C/D | | R | | | | | |
| 330 | C* | C/D/R | D/R | R | | | | |
| 390 | D | R | R | | | | | |
| 470 | C/R | D/R | R | | | | | |
| 560 | | R | | | | | | |
| 680 | D | R | R | | | | | |
| 1000 | R | R | | | | | | |
| 1500 | R | | | | | | | |

Note: * Preliminary values, contact factory for availability

| STANDARD/EXTENDED RATINGS | | | | | | | |
|---|-----------|-----------------|--------------------------|-------------------------------|---------------------------------|------------------------------|--|
| CAPACITANCE (µF) | CASE CODE | PART NUMBER | MAX. DCL AT + 25 °C (µA) | MAX. DF AT + 25 °C 120 Hz (%) | MAX. ESR AT + 25 °C 100 kHz (Ω) | MAX. RIPPLE 100 kHz Irms (A) | |
| 4 WVDC AT+ 85 °C, SURGE = 5.2 V . . . 2.7 WVDC AT + 125 °C, SURGE = 3.4 V | | | | | | | |
| 4.7 | T | 595D475X_004T2T | 0.5 | 6 | 7.8 | 0.06 | |
| 10 | T | 595D106X_004T2T | 0.5 | 6 | 7.8 | 0.06 | |
| 15 | A | 595D156X_004A2T | 0.6 | 6 | 1.4 | 0.23 | |
| 33 | A | 595D336X_004A2T | 1.3 | 6 | 1.4 | 0.23 | |
| 33 | B | 595D336X_004B2T | 1.3 | 6 | 0.47 | 0.43 | |
| 47 | A | 595D476X_004A2T | 1.9 | 6 | 1.40 | 0.23 | |
| 68 | A | 595D686X_004A2T | 2.7 | 6 | 1.30 | 0.24 | |
| 100 | A | 595D107X_004A2T | 4.0 | 12 | 0.60 | 0.35 | |
| 100 | B | 595D107X_004B2T | 4.0 | 8 | 0.45 | 0.44 | |
| 120 | C | 595D127X_004C2T | 4.8 | 8 | 0.19 | 0.76 | |

Note: * Preliminary values, contact factory for availability. For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".



| STANDARD/EXTENDED RATINGS | | | | | | |
|---|-----------|------------------|--------------------------------------|--|--|---|
| CAPACITANCE (μ F) | CASE CODE | PART NUMBER | MAX. DCL AT + 25 °C (μ A) | MAX. DF AT + 25 °C 120 Hz (%) | MAX. ESR AT + 25 °C 100 kHz (Ω) | MAX. RIPPLE 100 kHz I _{rms} (A) |
| 4 WVDC AT + 85 °C, SURGE = 5.2 V . . . 2.7 WVDC AT + 125 °C, SURGE = 3.4 V | | | | | | |
| 150 | B | 595D157X_004B2T | 6.0 | 8 | 0.45 | 0.44 |
| 150 | C | 595D157X_004C2T | 6.0 | 8 | 0.18 | 0.78 |
| 180 | D | 595D187X_004D2T | 7.2 | 8 | 0.14 | 1.04 |
| 220 | C | 595D227X_004C2T | 8.8 | 8 | 0.18 | 0.78 |
| 220 | D | 595D227X_004D2T | 8.8 | 8 | 0.14 | 1.04 |
| 270 | C | 595D277X_004C2T | 10.8 | 8 | 0.17 | 0.80 |
| 270 | D | 595D277X_004D2T | 10.8 | 8 | 0.13 | 1.07 |
| 330* | C* | 595D337X_004C2T* | 13.2* | 8* | 0.17* | 0.80* |
| 390 | D | 595D397X_004D2T | 15.6 | 8 | 0.13 | 1.07 |
| 470 | C | 595D477X_004C2T | 18.8 | 10 | 0.16 | 0.83 |
| 470 | R | 595D477X_004R2T | 18.8 | 10 | 0.13 | 1.39 |
| 680 | D | 595D687X_004D2T | 27.2 | 12 | 0.13 | 1.07 |
| 1000 | R | 595D108X_004R2T | 40.0 | 16 | 0.07 | 1.88 |
| 1500 | R | 595D158X_004R2T | 60.0 | 20 | 0.07 | 1.88 |
| 6.3 WVDC AT + 85 °C, SURGE = 8 V . . . 4 WVDC AT + 125 °C, SURGE = 5 V | | | | | | |
| 3.3 | T | 595D335X_6R3T2T | 0.5 | 6 | 8.5 | 0.06 |
| 6.8 | T | 595D685X_6R3T2T | 0.5 | 6 | 8.5 | 0.06 |
| 15 | A | 595D156X_6R3A2T | 0.9 | 6 | 1.7 | 0.20 |
| 22 | A | 595D226X_6R3A2T | 1.4 | 6 | 1.7 | 0.20 |
| 22 | B | 595D226X_6R3B2T | 1.4 | 6 | 0.57 | 0.37 |
| 33 | A | 595D336X_6R3A2T | 2.1 | 6 | 1.70 | 0.20 |
| 33 | B | 595D336X_6R3B2T | 1.7 | 5 | 0.57 | 0.39 |
| 33 | S | 595D336X_6R3S2T | 2.1 | 8 | 1.30 | 0.20 |
| 47 | A | 595D476X_6R3A2T | 2.8 | 6 | 1.50 | 0.22 |
| 47 | B | 595D336X_6R3B2T | 2.4 | 5 | 0.57 | 0.39 |
| 68 | A | 595D686X_6R3A2T | 4.3 | 12 | 0.5 | 0.19 |
| 68 | B | 595D686X_6R3B2T | 4.3 | 6 | 0.55 | 0.38 |
| 100 | B | 595D107X_6R3B2T | 6.3 | 8 | 0.55 | 0.39 |
| 100 | C | 595D107X_6R3C2T | 6.3 | 8 | 0.20 | 0.74 |
| 100 | M | 595D107X_6R3M2T | 6.3 | 14 | 0.40 | 0.49 |
| 120 | C | 595D127X_6R3C2T | 7.6 | 8 | 0.19 | 0.76 |
| 180 | D | 595D187X_6R3D2T | 11.3 | 8 | 0.14 | 1.04 |
| 220 | C | 595D227X_6R3C2T | 13.9 | 8 | 0.18 | 0.78 |
| 220 | D | 595D227X_6R3D2T | 13.9 | 8 | 0.14 | 1.04 |
| 220 | G | 595D227X_6R3G2T | 13.9 | 8 | 0.18 | 0.75 |
| 220 | H | 595D227X_6R3H2T | 13.9 | 8 | 0.18 | 0.75 |
| 330 | C | 595D337X_6R3C2T | 20.8 | 8 | 0.17 | 0.80 |
| 330 | C | 595D337X_6W3C2T | 20.8 | 8 | 0.17 | 0.80 |
| 330 | D | 595D337X_6R3D2T | 20.8 | 8 | 0.14 | 1.04 |
| 330 | R | 595D337X_6R3R2T | 20.8 | 8 | 0.13 | 1.39 |
| 390 | R | 595D397X_6R3R2T | 24.6 | 8 | 0.13 | 1.39 |
| 470 | D | 595D477X_6R3D2T | 29.6 | 8 | 0.13 | 1.07 |
| 470 | D | 595D477X_6W3D2T | 29.6 | 10 | 0.12 | 1.44 |
| 470 | R | 595D477X_6R3R2T | 29.6 | 10 | 0.12 | 1.44 |
| 560 | R | 595D567X_6R3R2T | 35.3 | 10 | 0.11 | 1.51 |
| 680 | R | 595D687X_6R3R2T | 42.8 | 10 | 0.09 | 1.66 |
| 680 | R | 595D687X_6W3R2T | 42.8 | 10 | 0.09 | 1.66 |
| 1000 | R | 595D108X_6R3R2T | 63.0 | 16 | 0.07 | 1.88 |
| 1000 | R | 595D108X_6W3R2T | 63.0 | 16 | 0.07 | 1.88 |

Note: * Preliminary values, contact factory for availability. For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".



Solid Tantalum Chip Capacitors
TANTAMOUNT® Conformal Coated,
Maximum CV

Vishay Sprague

| STANDARD/EXTENDED RATINGS | | | | | | | |
|---|-----------|-----------------|--------------------------------------|--|--|---|--|
| CAPACITANCE (μ F) | CASE CODE | PART NUMBER | MAX. DCL AT + 25 °C (μ A) | MAX. DF AT + 25 °C 120 Hz (%) | MAX. ESR AT + 25 °C 100 kHz (Ω) | MAX. RIPPLE 100 kHz I _{rms} (A) | |
| 10 WVDC AT + 85 °C, SURGE = 13 V . . . 7 WVDC AT + 125 °C, SURGE = 8 V | | | | | | | |
| 2.2 | T | 595D225X_010T2T | 0.5 | 6 | 8.6 | 0.06 | |
| 4.7 | T | 595D475X_010T2T | 0.5 | 6 | 8.6 | 0.06 | |
| 10 | A | 595D106X_010A2T | 1.0 | 6 | 1.9 | 0.19 | |
| 15 | A | 595D156X_010A2T | 1.5 | 6 | 1.8 | 0.20 | |
| 15 | B | 595D156X_010B2T | 1.5 | 6 | 0.67 | 0.35 | |
| 22 | A | 595D226X_010A2T | 2.2 | 6 | 1.80 | 0.20 | |
| 33 | A | 595D336X_010A2T | 3.3 | 8 | 3.0 | 0.16 | |
| 33 | B | 595D336X_010B2T | 3.3 | 6 | 1.90 | 0.21 | |
| 47 | B | 595D476X_010B2T | 4.7 | 6 | 0.65 | 0.35 | |
| 68 | B | 595D686X_010B2T | 6.8 | 6 | 0.65 | 0.36 | |
| 68 | C | 595D686X_010C2T | 6.8 | 6 | 0.24 | 0.68 | |
| 100 | B | 595D107X_010B2T | 10.0 | 12 | 0.4 | 0.46 | |
| 100 | D | 595D107X_010D2T | 8.0 | 7 | 0.15 | 1.00 | |
| 120 | D | 595D127X_010D2T | 12.0 | 8 | 0.14 | 1.04 | |
| 150 | C | 595D157X_010C2T | 15.0 | 8 | 0.22 | 0.71 | |
| 150 | D | 595D157X_010D2T | 15.0 | 8 | 0.14 | 1.04 | |
| 180 | D | 595D187X_010D2T | 18.0 | 8 | 0.38 | 0.63 | |
| 180 | R | 595D187X_010R2T | 18.0 | 8 | 0.13 | 1.39 | |
| 220 | C | 595D227X_010C2T | 22.0 | 8 | 0.20 | 0.74 | |
| 220 | D | 595D227X_010D2T | 22.0 | 8 | 0.14 | 1.04 | |
| 220 | R | 595D227X_010R2T | 22.0 | 8 | 0.13 | 1.39 | |
| 270 | R | 595D277X_010R2T | 27.0 | 8 | 0.13 | 1.39 | |
| 330 | D | 595D337X_010D2T | 33.0 | 8 | 0.14 | 1.04 | |
| 330 | R | 595D337X_010R2T | 33.0 | 8 | 0.13 | 1.39 | |
| 390 | R | 595D397X_010R2T | 39.0 | 8 | 0.12 | 1.44 | |
| 470 | R | 595D477X_010R2T | 47.0 | 8 | 0.12 | 1.44 | |
| 680 | R | 595D687X_010R2T | 68.0 | 14 | 0.09 | 1.66 | |
| 16 WVDC AT + 85 °C, SURGE = 20 V . . . 10 WVDC AT + 125 °C, SURGE = 12 V | | | | | | | |
| 1.5 | T | 595D155X_016T2T | 0.5 | 6 | 8.7 | 0.06 | |
| 2.2 | T | 595D225X_016T2T | 0.5 | 6 | 8.7 | 0.06 | |
| 2.2 | A | 595D225X_010D2T | 0.4 | 5 | 3.9 | 0.14 | |
| 3.3 | T | 595D335X_016T2T | 0.5 | 6 | 8.6 | 0.06 | |
| 4.7 | A | 595D475X_016A2T | 0.8 | 6 | 2.9 | 0.16 | |
| 6.8 | A | 595D685X_016A2T | 1.1 | 6 | 2.8 | 0.16 | |
| 10 | A | 595D106X_016A2T | 1.6 | 6 | 2.5 | 0.17 | |
| 10 | B | 595D106X_016B2T | 1.6 | 6 | 0.76 | 0.32 | |
| 15 | A | 595D156X_016A2T | 2.4 | 6 | 2.40 | 0.17 | |
| 15 | B | 595D156X_016B2T | 2.4 | 6 | 0.75 | 0.33 | |
| 22 | B | 595D226X_016B2T | 3.5 | 6 | 0.75 | 0.32 | |
| 22 | M | 595D226X_016M2T | 3.5 | 6 | 0.50 | 0.44 | |
| 33 | B | 595D336X_016B2T | 5.3 | 6 | 0.72 | 0.33 | |
| 33 | C | 595D336X_016C2T | 5.3 | 6 | 0.29 | 0.62 | |
| 47 | B | 595D476X_016B2T | 7.5 | 6 | 0.72 | 0.33 | |
| 47 | C | 595D476X_016C2T | 7.5 | 6 | 0.28 | 0.63 | |
| 68 | C | 595D686X_016C2T | 10.9 | 6 | 0.26 | 0.64 | |
| 68 | D | 595D686X_016D2T | 10.9 | 6 | 0.14 | 1.04 | |
| 100 | C | 595D107X_016C2T | 16.0 | 8 | 0.27 | 0.64 | |

Note: * Preliminary values, contact factory for availability. For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".



| STANDARD/EXTENDED RATINGS | | | | | | | |
|---|-----------|-----------------|---|--|--|---|--|
| CAPACITANCE (μF) | CASE CODE | PART NUMBER | MAX. DCL AT + 25 °C (μA) | MAX. DF AT + 25 °C 120 Hz (%) | MAX. ESR AT + 25 °C 100 kHz (Ω) | MAX. RIPPLE 100 kHz I _{rms} (A) | |
| 16 WVDC AT + 85 °C, SURGE = 20 V . . . 10 WVDC AT + 125 °C, SURGE = 12 V | | | | | | | |
| 100 | D | 595D107X_016D2T | 16.0 | 8 | 0.14 | 1.04 | |
| 120 | R | 595D127X_016R2T | 19.2 | 8 | 0.14 | 1.34 | |
| 150 | D | 595D157X_016D2T | 24.0 | 8 | 0.14 | 1.04 | |
| 150 | R | 595D157X_016R2T | 24.0 | 8 | 0.13 | 1.39 | |
| 180 | R | 595D187X_016R2T | 28.8 | 8 | 0.13 | 1.39 | |
| 220 | R | 595D227X_016R2T | 35.2 | 8 | 0.12 | 1.44 | |
| 330 | R | 595D337X_016R2T | 52.8 | 14 | 0.11 | 1.51 | |
| 20 WVDC AT + 85 °C, SURGE = 26 V . . . 13 WVDC AT + 125 °C, SURGE = 16 V | | | | | | | |
| 0.68 | T | 595D684X_020T2T | 0.5 | 4 | 10.8 | 0.05 | |
| 1.0 | T | 595D105X_020T2T | 0.5 | 4 | 9.0 | 0.06 | |
| 2.2 | A | 595D225X_020A2T | 0.5 | 6 | 3.8 | 0.14 | |
| 3.3 | A | 595D335X_020A2T | 0.7 | 6 | 3.8 | 0.14 | |
| 4.7 | A | 595D475X_020A2T | 0.9 | 6 | 3.1 | 0.15 | |
| 4.7 | B | 595D475X_020B2T | 0.9 | 6 | 0.95 | 0.29 | |
| 6.8 | A | 595D685X_020A2T | 1.4 | 6 | 3.0 | 0.15 | |
| 6.8 | B | 595D685X_020B2T | 1.4 | 6 | 0.95 | 0.29 | |
| 10 | B | 595D106X_020B2T | 2.0 | 6 | 1.0 | 0.28 | |
| 15 | B | 595D156X_020B2T | 3.0 | 6 | 1.0 | 0.28 | |
| 22 | B | 595D226X_020B2T | 4.4 | 6 | 0.90 | 0.31 | |
| 22 | C | 595D226X_020C2T | 4.4 | 6 | 0.38 | 0.54 | |
| 47 | C | 595D476X_020C2T | 9.4 | 6 | 0.35 | 0.56 | |
| 47 | D | 595D476X_020D2T | 9.4 | 6 | 0.19 | 0.89 | |
| 68 | D | 595D686X_020D2T | 12.2 | 6 | 0.19 | 0.89 | |
| 100 | D | 595D107X_020D2T | 20.0 | 8 | 0.18 | 0.91 | |
| 100 | R | 595D107X_020R2T | 20.0 | 8 | 0.14 | 1.34 | |
| 120 | R | 595D127X_020R2T | 24.0 | 8 | 0.14 | 1.34 | |
| 150 | R | 595D157X_020R2T | 30.0 | 8 | 0.14 | 1.34 | |
| 25 WVDC AT + 85 °C, SURGE = 32 V . . . 17 WVDC AT + 125 °C, SURGE = 20 V | | | | | | | |
| 0.47 | T | 595D474X_025T2T | 0.5 | 4 | 13.5 | 0.05 | |
| 1 | A | 595D105X_025A2T | 0.4 | 4 | 4.2 | 0.13 | |
| 1.5 | A | 595D155X_025A2T | 0.5 | 6 | 3.8 | 0.14 | |
| 2.2 | A | 595D225X_025A2T | 0.6 | 6 | 3.8 | 0.14 | |
| 3.3 | B | 595D335X_025B2T | 0.8 | 6 | 1.9 | 0.21 | |
| 4.7 | C | 595D475X_025C2T | 1.3 | 5 | 0.68 | 0.40 | |
| 6.8 | B | 595D685X_025B2T | 1.7 | 6 | 1.5 | 0.23 | |
| 10 | B | 595D106X_025B2T | 2.5 | 6 | 1.5 | 0.23 | |
| 10 | C | 595D106X_025C2T | 2.5 | 6 | 0.57 | 0.44 | |
| 15 | C | 595D156X_025C2T | 3.8 | 6 | 0.56 | 0.44 | |
| 22 | C | 595D226X_025C2T | 5.5 | 6 | 0.50 | 0.47 | |
| 22 | D | 595D226X_025D2T | 5.5 | 6 | 0.28 | 0.73 | |
| 33 | C | 595D336X_025C2T | 8.3 | 6 | 0.45 | 0.49 | |
| 33 | D | 595D336X_025D2T | 8.3 | 6 | 0.27 | 0.75 | |
| 47 | D | 595D476X_025D2T | 11.8 | 6 | 0.26 | 0.76 | |
| 47 | R | 595D476X_025R2T | 11.8 | 6 | 0.20 | 1.12 | |
| 68 | D | 595D686X_025D2T | 17.0 | 8 | 0.26 | 0.76 | |
| 68 | R | 595D686X_025R2T | 17.0 | 6 | 0.20 | 1.12 | |
| 100 | R | 595D107X_025R2T | 25.0 | 8 | 0.20 | 1.12 | |

Note: * Preliminary values, contact factory for availability. For 10 % tolerance, specify "9"; for 20 % tolerance, change to "0".



Solid Tantalum Chip Capacitors
TANTAMOUNT® Conformal Coated,
Maximum CV

Vishay Sprague

| STANDARD/EXTENDED RATINGS | | | | | | |
|---|------------------|--------------------|--|--|--|--|
| CAPACITANCE (μF) | CASE CODE | PART NUMBER | MAX. DCL AT + 25 °C (μA) | MAX. DF AT + 25 °C 120 Hz (%) | MAX. ESR AT + 25 °C 100 kHz (Ω) | MAX. RIPPLE 100 kHz I_{rms} (A) |
| 35 WVDC AT + 85 °C, SURGE = 46 V . . . 23 WVDC AT + 125 °C, SURGE = 28 V | | | | | | |
| 0.33 | T | 595D334X_035T2T | 0.5 | 4 | 14.4 | 0.05 |
| 0.47 | A | 595D474X_035A2T | 0.5 | 4 | 4.3 | 0.13 |
| 0.68 | A | 595D684X_035A2T | 0.5 | 4 | 4.2 | 0.13 |
| 1.0 | A | 595D105X_035A2T | 0.5 | 4 | 4.1 | 0.13 |
| 1.5 | A | 595D155X_035A2T | 0.5 | 6 | 3.8 | 0.14 |
| 1.5 | B | 595D155X_035B2T | 0.5 | 6 | 2.8 | 0.17 |
| 2.2 | B | 595D225X_035B2T | 0.8 | 6 | 2.3 | 0.19 |
| 3.3 | C | 595D335X_035C2T | 1.2 | 6 | 0.75 | 0.38 |
| 4.7 | B | 595D475X_035B2T | 1.6 | 6 | 2.2 | 0.19 |
| 4.7 | C | 595D475X_035C2T | 1.6 | 6 | 0.66 | 0.41 |
| 6.8 | C | 595D685X_035C2T | 2.4 | 6 | 0.63 | 0.42 |
| 10 | D | 595D106X_035D2T | 3.5 | 6 | 0.43 | 0.59 |
| 15 | C | 595D156X_035C2T | 5.3 | 6 | 0.60 | 0.43 |
| 15 | D | 595D156X_035D2T | 5.3 | 6 | 0.41 | 0.60 |
| 22 | D | 595D226X_035D2T | 7.7 | 6 | 0.32 | 0.68 |
| 22 | R | 595D226X_035R2T | 7.7 | 6 | 0.28 | 0.94 |
| 33 | R | 595D336X_035R2T | 11.6 | 6 | 0.28 | 0.94 |
| 47 | R | 595D476X_035R2T | 16.5 | 6 | 0.28 | 0.94 |
| 50 WVDC AT + 85 °C, SURGE = 65 V . . . 33 WVDC AT + 125 °C, SURGE = 38 V | | | | | | |
| 0.10 | T | 595D104X_050T2T | 0.5 | 4 | 22.5 | 0.04 |
| 0.15 | T | 595D154X_050T2T | 0.5 | 4 | 18.0 | 0.04 |
| 0.22 | T | 595D224X_050T2T | 0.5 | 4 | 15.3 | 0.04 |
| 0.33 | A | 595D334X_050A2T | 0.5 | 4 | 8.1 | 0.09 |
| 0.47 | A | 595D474X_050A2T | 0.5 | 4 | 7.2 | 0.10 |
| 0.68 | A | 595D684X_050A2T | 0.5 | 4 | 6.1 | 0.11 |
| 0.68 | B | 595D684X_050B2T | 0.5 | 4 | 5.4 | 0.12 |
| 1.0 | A | 595D105X_050A2T | 0.5 | 4 | 6.0 | 0.11 |
| 1.0 | B | 595D105X_050B2T | 0.5 | 4 | 5.0 | 0.13 |
| 1.5 | C | 595D155X_050C2T | 0.8 | 6 | 1.8 | 0.25 |
| 2.2 | B | 595D225X_050B2T | 1.1 | 6 | 3.2 | 0.16 |
| 2.2 | C | 595D225X_050C2T | 1.1 | 6 | 1.7 | 0.25 |
| 3.3 | C | 595D335X_050C2T | 1.7 | 6 | 1.6 | 0.26 |
| 4.7 | C | 595D475X_050C2T | 2.4 | 6 | 1.4 | 0.28 |
| 6.8 | C | 595D685X_050C2T | 3.4 | 6 | 1.3 | 0.29 |
| 6.8 | D | 595D685X_050D2T | 3.4 | 6 | 0.82 | 0.43 |
| 10 | D | 595D106X_050D2T | 5.0 | 6 | 0.80 | 0.43 |
| 10 | R | 595D106X_050R2T | 5.0 | 6 | 0.65 | 0.62 |
| 15 | R | 595D156X_050R2T | 7.5 | 6 | 0.40 | 0.79 |
| 22 | R | 595D226X_050R2T | 11.0 | 6 | 0.39 | 0.80 |



TYPICAL CURVES AT + 25 °C, IMPEDANCE AND ESR VS. FREQUENCY





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.



Стандарт Электрон Связь

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331