

## 6300UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information  
please call

1-800-Belden1



### Description:

18 AWG bare copper conductors, Flamarrest® insulation, conductors cabled, Flamarrest® jacket with ripcord, sequential footage marking every two feet.

### Usage (Overall)

**Suitable Applications:** Intercom/PA Systems, Sound/Audio Systems

### Physical Characteristics (Overall)

#### Conductor

**AWG:**

# Conductors	AWG	Stranding	Conductor Material
2	18	7x26	BC - Bare Copper

**Total Number of Conductors:** 2

#### Insulation

**Insulation Material:**

Insulation Trade Name	Insulation Material	Wall Thickness (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.008

#### Outer Shield

**Outer Shield Material:**

Outer Shield Material
Unshielded

#### Outer Jacket

**Outer Jacket Material:**

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	.015

**Outer Jacket Ripcord:** Yes

#### Overall Cable

**Overall Cabling Lay Length & Direction:**

Length (in.)	Twists (twist/ft)
3.5	3.4

**Overall Cabling Color Code Chart:**

Number	Color
1	Black
2	Red

**Overall Nominal Diameter:** 0.154 in.

### Mechanical Characteristics (Overall)

**Operating Temperature Range:** 0°C To +75°C

**UL Temperature Rating:** 75°C

**Bulk Cable Weight:** 16 lbs/1000 ft.

**Max. Recommended Pulling Tension:** 45 lbs.

**Min. Bend Radius/Minor Axis:** 1.550 in.

## 6300UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CMP
NEC Articles:	800
CEC/C(UL) Specification:	CMP
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

#### Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

#### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	5300UE

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance (µH/ft)

.15

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)

34.000

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)

6.5

#### Max. Operating Voltage - UL:

Voltage

300 V RMS

#### Max. Recommended Current:

Current

5 Amps per conductor @ 25°C

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6300UE 004U1000	1,000 FT	18.000 LB	YELLOW		2 #18 FLRST FLRST
6300UE 004I1000	1,000 FT	18.000 LB	YELLOW	C	2 #18 FLRST FLRST
6300UE 007I1000	1,000 FT	18.000 LB	VIOLET	C	2 #18 FLRST FLRST
6300UE 008U1000	1,000 FT	18.000 LB	GRAY		2 #18 FLRST FLRST
6300UE 008U500	500 FT	9.500 LB	GRAY		2 #18 FLRST FLRST
6300UE 008I1000	1,000 FT	18.000 LB	GRAY	C	2 #18 FLRST FLRST
6300UE 009U1000	1,000 FT	18.000 LB	WHITE		2 #18 FLRST FLRST
6300UE 010U1000	1,000 FT	18.000 LB	BLACK		2 #18 FLRST FLRST
6300UE 010U500	500 FT	9.500 LB	BLACK		2 #18 FLRST FLRST
6300UE 010I1000	1,000 FT	18.000 LB	BLACK	C	2 #18 FLRST FLRST

## 6300UE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

6300UE 0105000	5,000 FT	90.000 LB	BLACK		2 #18 FLRST FLRST
6300UE 012U1000	1,000 FT	18.000 LB	PINK		2 #18 FLRST FLRST
6300UE 3371000	1,000 FT	18.000 LB	GREEN, LIGHT	C	2 #18 FLRST FLRST
6300UE 877U1000	1,000 FT	18.000 LB	NATURAL		2 #18 FLRST FLRST
6300UE 877U500	500 FT	9.500 LB	NATURAL		2 #18 FLRST FLRST
6300UE 8771000	1,000 FT	18.000 LB	NATURAL	C	2 #18 FLRST FLRST
6300UE 877500	500 FT	9.500 LB	NATURAL		2 #18 FLRST FLRST

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 2    Revision Date: 03-26-2010

© 2012 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331