

10BASE-T Isolation Modules

Dual Port SMD or DIL Package



US Patent Numbers

5,656,985 6,297,721 B1
6,297,720 B1 6,320,489 B1
6,344,785 B1 6,662,431 B1

Product Features:


- Standard series of Dual Port Isolation Modules to meet the isolation requirements of IEEE 802.3
- Designed specifically for use with the “filterless” repeater / switch chips and “stacked” RJ45 connectors.
- Non-standard turns ratios are also available
- SMD parts include patented open frame construction
- 1500Vrms hi-pot

Part Number	Pckg	Turns Ratio $\pm 3\%$	PRI OCL (μ H)	PRI DCR (Ω max)	PRI LL (μ H max)	Cw/w (pF max)	Temp Range
		PRI 1-2, 3-4, 5-6, 7-8					
TD01-1006L1RL	DIL	1:1, 1:1, 1:1, 1:1	100 Typ.	0.3	0.3	12	0 to +70°C
TG01-1006N2LF	SMD	1:1, 1:1, 1:1, 1:1	100 Typ.	0.3	0.3	12	0 to +70°C
TD54-1006L1RL	DIL	1:1.41, 1:1.41, 1:1.41, 1:1.41	140 Typ.	0.4	0.4	15	0 to +70°C
TG54-1006N2LF	SMD	1:1.41, 1:1.41, 1:1.41, 1:1.41	140 Typ.	0.4	0.4	15	0 to +70°C
TD55-1406L1RL	DIL	1:1, 1:1.41, 1:1.41, 1:1	140/140 Typ.	0.4/0.4	0.4	12	0 to +70°C
TG55-1406N2LF	SMD	1:1, 1:1.41, 1:1.41, 1:1	140/140 Typ.	0.4/0.4	0.4	12	0 to +70°C
TD83-2006L1RL	DIL	1:1, 1:2, 1:2, 1:1	200/50 Min.	0.5/0.35	0.15	11	-40 to +85°C
TG83-2006N2LF	SMD	1:1, 1:2, 1:2, 1:1	200/50 Min.	0.5/0.35	0.15	11	-40 to +85°C

Notes:




1. Please contact the factory or local representative for individual datasheets or additional information
2. DIL (Through-Hole) packages not recommended for new designs
3. Part numbers with LF suffix are RoHS compliant and PB-Free. Part numbers with RL suffix are RoHS compliant using exemption 7a.

Schematic




Reinforced 10BASE-T Isolation Modules

Package N2






Dimensions: inches [mm]
Co-Planarity: 0.004 [0.10]



Recommended
Solder Pad Layout

Package L1



Dimensions: inches [mm]



2880 Lakeside Drive #116
Santa Clara, CA 95054
(650) 903-3800
www.haloelectronics.com

HALO® Electronics is a leading supplier of high quality communication magnetics including signal transformers, filters, CMR chokes, PoE power transformers, DC/DC converters, and integrated Ethernet connectors. HALO's leading edge technology solutions are manufactured in ISO9001 and ISO14001 factories offering high quality products at a competitive price.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331