

## Telpower® Compact Fused Disconnect Switch

## TPC &amp; TPCDS

## TPC &amp; TPCDS

TPCDS - Telpower® Compact Fused Disconnect Switch

TPC - Telpower® Compact Fuse - Current Limiting

Ampere Ratings: 3-125A

Available Ratings: 3, 4, 5, 6, 7, 8, 10, 12, 15, 20, 25, 30,  
40, 50, 60, 75, 90, 100, 125A

Voltage Rating: 80Vdc

Interrupting Rating: 100,000A

Agency Information: CE

UL Recognized (investigated to UL 1801) as a  
disconnect switch for the interruption of load current  
by means of withdrawing the fuse pullout.Recognized to U.S. and Canadian requirements under the  
component recognition program of Underwriters  
Laboratories Inc.

Files E219046 and E56412.

## General Information:

- Fusible solution for replacement of existing dc Telecom circuit breakers.
- Compact size fused disconnect switch.
- AmpColor ID™ System for easy fuse replacement.
- Available in two disconnect switch profiles in addition to a variety of terminal styles.
- Local and remote open fuse indication.  
Local alarm indication provided by LED on TPC fuse.
- Remote alarm terminal available in three positions commonly found in dc circuit protection devices.
- Recommended .75 inch center-to-center product spacing.
- Current-limiting capability
- Complete system coordination capability.
- Highest interrupting rating (100,000A) available for dc circuit protection of this footprint.
- No venting of arc or molten metals and gases during fuse opening.
- Fuse material: Black thermoplastic, UL rated 94 V-O, 170° C RTI.
- Housing material: Black thermoplastic, UL rated 94 V-O, 120° C RTI.

**CE** CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering for more information.



| Catalog Number | Description        | Ampere Rating |
|----------------|--------------------|---------------|
| TPC-3          | Compact Fuse       | 3A            |
| TPC-4          | Compact Fuse       | 4A            |
| TPC-5          | Compact Fuse       | 5A            |
| TPC-6          | Compact Fuse       | 6A            |
| TPC-7          | Compact Fuse       | 7A            |
| TPC-8          | Compact Fuse       | 8A            |
| TPC-10         | Compact Fuse       | 10A           |
| TPC-12         | Compact Fuse       | 12A           |
| TPC-15         | Compact Fuse       | 15A           |
| TPC-20         | Compact Fuse       | 20A           |
| TPC-25         | Compact Fuse       | 25A           |
| TPC-30         | Compact Fuse       | 30A           |
| TPC-40         | Compact Fuse       | 40A           |
| TPC-50         | Compact Fuse       | 50A           |
| TPC-60         | Compact Fuse       | 60A           |
| TPC-75         | Compact Fuse       | 75A           |
| TPC-90         | Compact Fuse       | 90A           |
| TPC-100        | Compact Fuse       | 100A          |
| TPC-125        | Compact Fuse       | 125A          |
| TPCDS-BBE-1    | Compact Disconnect | 3-125A        |
| TPCDS-BBE-2    | Compact Disconnect | 3-125A        |
| TPCDS-BBE-3    | Compact Disconnect | 3-125A        |
| TPCDS-BBM-1    | Compact Disconnect | 3-125A        |
| TPCDS-BBM-2    | Compact Disconnect | 3-125A        |
| TPCDS-BBM-3    | Compact Disconnect | 3-125A        |
| TPCDS-BSE-1    | Compact Disconnect | 3-125A        |
| TPCDS-BSE-2    | Compact Disconnect | 3-125A        |
| TPCDS-BSE-3    | Compact Disconnect | 3-125A        |
| TPCDS-BSM-1    | Compact Disconnect | 3-125A        |
| TPCDS-BSM-2    | Compact Disconnect | 3-125A        |
| TPCDS-BSM-3    | Compact Disconnect | 3-125A        |
| TPCDS-SSE-1    | Compact Disconnect | 3-125A        |
| TPCDS-SSE-2    | Compact Disconnect | 3-125A        |
| TPCDS-SSE-3    | Compact Disconnect | 3-125A        |
| TPCDS-SSM-1    | Compact Disconnect | 3-125A        |
| TPCDS-SSM-2    | Compact Disconnect | 3-125A        |
| TPCDS-SSM-3    | Compact Disconnect | 3-125A        |
| TPCDS-D-BC1*   | Compact Disconnect | 3-125A        |
| TPCDS-D-BC2*   | Compact Disconnect | 3-125A        |
| TPCDS-D-CC1*   | Compact Disconnect | 3-125A        |
| TPCDS-D-SEC1*  | Compact Disconnect | 3-125A        |
| TPCDS-D-SEC2*  | Compact Disconnect | 3-125A        |
| TPCDS-D-SMC1*  | Compact Disconnect | 3-125A        |
| TPCDS-D-SMC2*  | Compact Disconnect | 3-125A        |

\*Not investigated to Canadian Requirements.

## Telpower® Compact Fused Disconnect Switch

## TPC &amp; TPCDS

## Compact Fused Disconnect Switch

- Bullet and / or stud terminals for line and load connections (1.940 inch / 49.3 mm spacing).
- Front access with bullet terminals.  
Rear access with stud terminals.
- Three terminal style configurations available (see below).
- Remote alarm terminal available in three positions common to dc circuit protection devices.

## Part Number System --

## Compact Fused Disconnect Switch

To identify part number, replace block with appropriate suffix to identify line and load terminals, thread type, and alarm terminal distance.

## TPCDS - TELPOWER® Compact Fused Disconnect Switch

TPCDS -    - 

## Terminal Style (select one)

- BB - Bullet contact on the line  
Bullet contact on the load
- BS - Bullet contact on the line  
Stud terminal on the load
- SS - Stud terminal on the line  
Stud terminal on the load

## Thread (select one)

- M - Metric threads for panel mount  
fasteners (M3) and stud (M5)
- E - English threads for panel mount  
fasteners (6-32) and stud (10-32)

Remote Alarm Terminal Distance  
(select one)

- 1 - .645 inch from line terminal
- 2 - .970 inch from line terminal
- 3 - 1.285 inch from line terminal

## DIN Rail Fused Disconnect Switch

- 35mm DIN rail mountable
- Front access.
- Three terminal style configurations available (see below).
- Screw clamp accepts 10 to 1 AWG (6mm<sup>2</sup> - 50mm<sup>2</sup>) wire.
- Two remote alarm terminal positions available.

## Part Number System --

## DIN Rail Fused Disconnect Switch

To identify part number, replace block with appropriate suffix to identify line and load terminals, thread type if applicable, and alarm terminal option.

TPCDS - TELPOWER® Compact Fused Disconnect  
Switch D - DIN-Rail style productTPCDS - D -    

## Terminal Style (select one)

- CC - Screw Clamp terminal on the line  
Screw Clamp terminal on the load
- BC - Bullet contact on the line  
Screw Clamp terminal on the load
- SEC - Stud terminal on the line  
English threads for stud (10-32)  
Screw Clamp terminal on the load
- SMC - Stud terminal on the line  
Metric threads for stud (M5)  
Screw Clamp terminal on the load

Remote Alarm Terminal Location  
(select one)

- 1 - Side output  
(available on CC and BC terminal styles)
- 2 - Bottom output, .970 inch  
from line terminal  
(available on BC terminal style only)



The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

## Telpower® Compact Fused Disconnect Switch

## TPC &amp; TPCDS



# TPCDS Terminal Styles

## Compact Fused Disconnect Switch




## Telpower® Compact Fused Disconnect Switch

## TPC &amp; TPCDS

TPCDS-D Terminal Styles  
DIN Rail Fused Disconnect Switch


## Alarm Schematic



## NOTES:

1. The Electronic Monitoring Circuit (EMC) is a high input impedance device that will provide alarming for an open-fuse condition.
2. Typical leakage current through the load when the EMC is operational  $\leq 2$  mA.
3. The resistance, R, must be provided by the end-user to limit the alarm output current to a maximum of 20 mA. The value, R, should be calculated using the system voltage value.
  - If remote alarm functionality is not required, the *END-USER CIRCUITRY* must still be supplied to provide a resistive path to the return for the local alarm to properly function.
4. The fuse is polarized to maintain proper orientation with the switch housing. The line and load terminals are identified on the switch housing.
5. Electrical integrity of the load must be maintained after fuse has opened in order for the local and remote alarm to properly function.

## AmpColor ID™ System




AmpColor ID™ Chart included with each box of ten TPC fuses.

**TPC Fuses: 3-125A**  
**TPM Fuses: 3-30A**


Reference Data Sheet: 5022 for TPM fuse specifications.

Twelve AmpColor ID™ tags included with each box of ten TPC fuses.



Telpower® Compact Fused Disconnect Switch


TPC & TPCDS



Time-Current Characteristic Curve—Average Melt - 3-20 Amp

## Telpower® Compact Fused Disconnect Switch

## TPC &amp; TPCDS



Time-Current Characteristic Curve—Average Melt - 25-125 Amp

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331