


more than you expect



Figure 1 is a mechanical drawing of a component, showing top, side, and detail views. The top view shows a rectangular component with pins 1-10 and a central square area. The side view shows the component's profile with dimensions .100 MIN. [2.54] and .512 MAX. [13.00]. The detail view shows the component's top surface with dimensions .740 MAX. [18.80] and .665 MAX. [16.90]. The detail view also shows the component's bottom surface with dimensions .020 SQ.(10) [.50] and .126(8) [3.20]. The detail view includes a 'TRUE POSITION GRID' and a 'P.C. PATTERN, COMPONENT SIDE'.

Figure 1: Mechanical drawing of the component showing top, side, and detail views. The top view shows a rectangular component with pins 1-10 and a central square area. The side view shows the component's profile with dimensions .100 MIN. [2.54] and .512 MAX. [13.00]. The detail view shows the component's top surface with dimensions .740 MAX. [18.80] and .665 MAX. [16.90]. The detail view also shows the component's bottom surface with dimensions .020 SQ.(10) [.50] and .126(8) [3.20]. The detail view includes a 'TRUE POSITION GRID' and a 'P.C. PATTERN, COMPONENT SIDE'.

PARAMETER	TEST CONDITIONS	VALUE
D.C. RESISTANCE 1-4	@20°C	2.15 ohms max.
D.C. RESISTANCE 2-3	@20°C	0.050 ohms max.
D.C. RESISTANCE 6-10	@20°C	0.14 ohms max.
INDUCTANCE 1-4	66kHz, 100mVAC, Ls	1.55mH ±10%
LEAKAGE INDUCTANCE 1-4	tie(2+3, 6+10), 100kHz, 100mVAC, Ls	25.0uH typ., 50.0uH max.
DIELECTRIC RATING 4-10	tie(1+3), 3750VAC, 1 second	3000VAC, 1 minute
URNS RATIO	(4-1):(10-6)	7.142:1, ±1%
URNS RATIO	(4-1):(3-2)	7.692:1, ±1%
RESONANT FREQUENCY	-	500kHz min.

REV.	DATE	Packaging Specifications Method: Tray PKG-0887 www.wg-online.com/midcom	 CONVENTION PLACEMENT
6B	12/12		
6A	2/09		

SEE REVISION SHEET FOR REVISION LEVEL

Tolerances unless otherwise specified:
Angles: $\pm 1^\circ$ Decimals: ± 0.005 [.13]
Fractions: $\pm 1/64$ Footprint: ± 0.005 [.13]

This drawing is dual dimensioned. Dimensions in brackets are in millimeters.

TRANSFORMER

eiSos p/n: 750871032

PART NO.

750871032

SPECIFICATION SHEET 1 OF 1



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331