

## **Aluminum electrolytic capacitors**

Axial-lead and soldering star capacitors

Series/Type: B43693, B43793

Date: February 2011

© EPCOS AG 2011. Reproduction, publication and dissemination of this publication, enclosures hereto and the information contained therein without EPCOS' prior express consent is prohibited.



#### Axial-lead and soldering star capacitors

B43693, B43793

High voltage - 125 °C

#### **Applications**

■ For high-voltage applications in automotive

#### Features

- High ripple current capability
- Long useful life
- High vibration resistance

#### Construction


- Charge/discharge-proof, polar
- Aluminum case with insulating sleeve
- Negative pole connected to case

#### **Terminals**

- Axial leads, welded to ensure perfect electrical contact
- Also available with soldering stars

#### Taping and packing

- Axial-lead capacitors will be delivered in pallet package. Capacitors with d × I ≤ 16 × 30 mm are also available taped on reel.
- Soldering star capacitors are packed in cardboard.







## High voltage - 125 °C



## Specifications and characteristics in brief

Rated voltage V <sub>R</sub>	250 V DC					
Surge voltage V <sub>S</sub>	1.15 · V <sub>R</sub>					
Rated capacitance C <sub>R</sub>	22 130 μF					
Capacitance tolerance	-10/+30% ≙ Q	!				
Leakage current I <sub>leak</sub> (5 min, 20 °C)	$I_{leak} \le 0.3 \ \mu A \cdot \left(\frac{C_R}{\mu F} \cdot \frac{V_R}{V}\right)^{0.7} + 4 \ \mu A$					
Self-inductance ESL <sup>1)</sup>	Diameter d (mn	n)	14	18	21	
	Terminals	Length I (mm)	Approx	Approx. ESL (nH)		
	axial	30	24	34	_	
		39	_	38	45	
		49	-	_	50	
	soldering star	30	7	10	_	
		39	_	11	13	
		49	_	_	14	
Useful life			Requirements:			
125 °C; V <sub>R</sub> ; I <sub>AC,R</sub>	> 2500 h		ΔC/C	≤ ±30% of initial value		
105 °C; V <sub>R</sub> ; I <sub>AC,R</sub>	> 10000 h		ESR	$\leq$ 3 times initial specified limit		
85 °C; $V_R$ ; $I_{AC,max}$	> 4000 h > 250000 h		I <sub>leak</sub>	$\leq$ initial specified limit		
40 °C; $V_R$ ; 2 · $I_{AC,R}$						
Voltage endurance test			Post te	Post test requirements:		
105 °C; V <sub>R</sub>	5000 h		ΔC/C	$\pm 10\%$ of initial value		
			ESR	≤ 1.3%	of initia	I specified limit
			I <sub>leak</sub>	≤ initia	l specifie	ed limit
Vibration resistance test	To IEC 60068-2	2-6, test Fc:				
	' '	je 10 Hz 2 kHz			•	le max.
	-	ration max. 20 g,				
	Capacitor mounted by its wire leads at a distance of $(6 \pm 1)$ mm from the case and additionally clamped by the case.					1) mm from
IFO elimentia antonomia			ea by the	e case.		
IEC climatic category	To IEC 60068-1: 40/125/56 (-40 °C/+125 °C/56 days damp heat test)					
Detail specification	Similar to CECC 30301-802					
Sectional specification	IEC 60384-4					

<sup>1)</sup> If optimum circuit design is used, the values are lower by 30%.






## High voltage - 125 °C

#### B43693, Axial-lead capacitors


#### **Dimensional drawing**



## Dimensions, weights and packing units

$d \times I$	$d_{max} \times I_{max}$	Approx. weight	Packing units (pcs	s.)
mm	mm	g	Pallet	Reel
14 × 30	14.5 × 30.5	6.8	200	350
$18 \times 30$	$18.5 \times 30.5$	11.1	160	_
18 × 39	$18.5 \times 40$	14.7	160	_
21 × 39	21.5 × 40	20.0	140	_
21 × 49	21.5 × 50	25.0	110	_








## B43793, Soldering star capacitors Dimensional drawings

Mounting holes d = 14 mm

## Mounting holes d = 16 mm ... 21 mm



## Dimensions, weights and packing units

$d \times I$	$d_{max} \times I_{max}$	c ±0.1	Approx. weight	Packing units
mm	mm	mm	g	pcs.
14 × 30	15.5 × 32	14.5	7.2	480
18 × 30	19.5 × 32	18.5	11.8	300
18 × 39	19.5 × 41.5	18.5	15.4	200
21 × 39	22.5 × 41.5	21.5	21.0	324
21 × 49	22.5 × 51.5	21.5	26.0	264





High voltage − 125 °C

## Case dimensions and ordering codes


$V_R$	C <sub>R</sub>	Case	Ordering code	Ordering code	Ordering code
	100 Hz	dimensions	Axial pallet	Axial reel	Soldering star
	20 °C	$d \times I$			
V DC	μF	mm			
250	22	14 × 30	B43693A2226Q007	B43693A2226Q009	B43793A2226Q000
	47	18 × 30	B43693A2476Q007		B43793A2476Q000
	68	18 × 39	B43693A2686Q007		B43793A2686Q000
	100	21 × 39	B43693A2107Q007		B43793A2107Q000
	130	21 × 49	B43693A2137Q007		B43793A2137Q000

#### **Technical data**

C <sub>R</sub>	ESR <sub>typ</sub>	ESR <sub>max</sub>	ESR <sub>max</sub>	ESR <sub>max</sub>	Z <sub>max</sub>	$I_{AC,max}$	$I_{AC,max}$	$I_{AC,max}$	$I_{AC,R}$	I <sub>AC,max</sub>
100 Hz	100 Hz	100 Hz	100 Hz	10 kHz	100 kHz	10 kHz	10 kHz	10 kHz	10 kHz	10 kHz
20 °C	20 °C	20 °C	-40 °C	20 °C	20 °C	40 °C	85 °C	105 °C	105 °C	125 °C
μF	$m\Omega$	mΩ	Ω	$m\Omega$	$m\Omega$	Α	Α	Α	Α	Α
$V_{R} = 250$	V DC									
22	1400	2300	34.0	454	510	3.65	3.32	2.90	1.20	2.27
47	650	1100	16.0	222	246	5.43	4.95	4.35	1.78	3.38
68	450	750	11.0	154	171	7.36	6.71	5.90	2.41	4.58
100	300	520	7.5	102	114	10.16	9.26	8.15	3.33	6.33
130	240	400	6.0	79	88	12.89	11.75	10.35	4.23	8.03











#### Useful life

depending on ambient temperature  $T_A$  under ripple current operating conditions at  $V_{R^{1)}}$ 



#### **Useful life**

depending on case temperature  $T_{\text{C}}$  under ripple current operating conditions at  $V_{\text{R}}^{1)}$ 




Refer to chapter "General technical information, 5.3 Calculation of useful life" for an explanation on how to interpret the useful life graphs.






#### High voltage - 125 °C

# Frequency factor of permissible ripple current I<sub>AC</sub> versus frequency f




## Frequency characteristics of ESR

Typical behavior




## Equivalent series resistance ESR versus frequency f

Typical behavior for 47 µF/250 V




# Impedance Z versus frequency f

Typical behavior for 47  $\mu$ F/250 V









#### Cautions and warnings

#### Personal safety

The electrolytes used by EPCOS have not only been optimized with a view to the intended application, but also with regard to health and environmental compatibility. They do not contain any solvents that are detrimental to health, e.g. dimethyl formamide (DMF) or dimethyl acetamide (DMAC).

Furthermore, part of the high-voltage electrolytes used by EPCOS are self-extinguishing. They contain flame-retarding substances which will quickly extinguish any flame that may have been ignited.

As far as possible, EPCOS does not use any dangerous chemicals or compounds to produce operating electrolytes. However, in exceptional cases, such materials must be used in order to achieve specific physical and electrical properties because no safe substitute materials are currently known. However, the amount of dangerous materials used in our products has been limited to an absolute minimum. Nevertheless, the following rules should be observed when handling aluminum electrolytic capacitors:

- Any escaping electrolyte should not come into contact with eyes or skin.
- If electrolyte does come into contact with the skin, wash the affected parts immediately with running water. If the eyes are affected, rinse them for 10 minutes with plenty of water. If symptoms persist, seek medical treatment.
- Avoid breathing in electrolyte vapor or mists. Workplaces and other affected areas should be well ventilated. Clothing that has been contaminated by electrolyte must be changed and rinsed in water.





## High voltage - 125 °C

## **Product safety**

The table below summarizes the safety instructions that must be observed without fail. A detailed description can be found in the relevant sections of chapter "General technical information".

Topic	Safety information	Reference chapter "General technical information"
Polarity	Make sure that polar capacitors are connected with the right polarity.	1 "Basic construction of aluminum electrolytic capacitors"
Reverse voltage	Voltages polarity classes should be prevented by connecting a diode.	3.1.6 "Reverse voltage"
Upper category temperature	Do not exceed the upper category temperature.	7.2 "Maximum permissible operating temperature"
Maintenance	Make periodic inspections of the capacitors.  Before the inspection, make sure that the power supply is turned off and carefully discharge the electricity of the capacitors.  Do not apply any mechanical stress to the capacitor terminals.	10 "Maintenance"
Mounting position of screw-terminal capacitors	Do not mount the capacitor with the terminals (safety vent) upside down.	11.1. "Mounting positions of capacitors with screw terminals"
Mounting of single-ended capacitors	The internal structure of single-ended capacitors might be damaged if excessive force is applied to the lead wires.  Avoid any compressive, tensile or flexural stress.  Do not move the capacitor after soldering to PC board.  Do not pick up the PC board by the soldered capacitor.  Do not insert the capacitor on the PC board with a hole space different to the lead space specified.	11.4 "Mounting considerations for single-ended capacitors"
Robustness of terminals	The following maximum tightening torques must not be exceeded when connecting screw terminals: M5: 2 Nm M6: 2.5 Nm	11.3 "Mounting torques"
Soldering	Do not exceed the specified time or temperature limits during soldering.	11.5 "Soldering"





## High voltage − 125 °C

Topic	Safety information	Reference chapter "General technical information"
Soldering, cleaning agents	Do not allow halogenated hydrocarbons to come into contact with aluminum electrolytic capacitors.	11.6 "Cleaning agents"
Passive flammability	Avoid external energy, such as fire or electricity.	8.1 "Passive flammability"
Active flammability	Avoid overload of the capacitors.	8.2 "Active flammability"
		Reference chapter "Capacitors with screw terminals"
Breakdown strength of insulating sleeves	Do not damage the insulating sleeve, especially when ring clips are used for mounting.	"Screw terminals – accessories"





## High voltage − 125 °C

## Symbols and terms

Symbol	English	German
С	Capacitance	Kapazität
$C_R$	Rated capacitance	Nennkapazität
Cs	Series capacitance	Serienkapazität
$C_{S,T}$	Series capacitance at temperature T	Serienkapazität bei Temperatur T
$C_{f}$	Capacitance at frequency f	Kapazität bei Frequenz f
d	Case diameter, nominal dimension	Gehäusedurchmesser, Nennmaß
$d_{\text{max}}$	Maximum case diameter	Maximaler Gehäusedurchmesser
ESL	Self-inductance	Eigeninduktivität
ESR	Equivalent series resistance	Ersatzserienwiderstand
ESR <sub>f</sub>	Equivalent series resistance at frequency f	Ersatzserienwiderstand bei Frequenz f
ESR <sub>T</sub>	Equivalent series resistance at temperature T	Ersatzserienwiderstand bei Temperatur T
f	Frequency	Frequenz
1	Current	Strom
$I_{AC}$	Alternating current (ripple current)	Wechselstrom
$I_{\text{AC,rms}}$	Root-mean-square value of alternating current	Wechselstrom, Effektivwert
$I_{AC,f}$	Ripple current at frequency f	Wechselstrom bei Frequenz f
$I_{AC,max}$	Maximum permissible ripple current	Maximal zulässiger Wechselstrom
$I_{AC,R}$	Rated ripple current	Nennwechselstrom
I <sub>AC,R</sub> (B)	Rated ripple current for base cooling	Nennwechselstromstrom für Bodenkühlung
l <sub>leak</sub>	Leakage current	Reststrom
I <sub>leak,op</sub>	Operating leakage current	Betriebsreststrom
1	Case length, nominal dimension	Gehäuselänge, Nennmaß
I <sub>max</sub>	Maximum case length (without	Maximale Gehäuselänge (ohne Anschlüsse
	terminals and mounting stud)	und Gewindebolzen)
R	Resistance	Widerstand
$R_{ins}$	Insulation resistance	Isolationswiderstand
$R_{\text{symm}}$	Balancing resistance	Symmetrierwiderstand
Т	Temperature	Temperatur
$\DeltaT$	Temperature difference	Temperaturdifferenz
$T_A$	Ambient temperature	Umgebungstemperatur
$T_C$	Case temperature	Gehäusetemperatur
T <sub>B</sub>	Capacitor base temperature	Temperatur des Becherbodens
t	Time	Zeit
$\Delta t$	Period	Zeitraum
t <sub>b</sub>	Service life (operating hours)	Brauchbarkeitsdauer (Betriebszeit)







Symbol	English	German
V	Voltage	Spannung
$V_{F}$	Forming voltage	Formierspannung
$V_{op}$	Operating voltage	Betriebsspannung
$V_{R}$	Rated voltage, DC voltage	Nennspannung, Gleichspannung
$V_{S}$	Surge voltage	Spitzenspannung
$X_{C}$	Capacitive reactance	Kapazitiver Blindwiderstand
$X_{L}$	Inductive reactance	Induktiver Blindwiderstand
Z	Impedance	Scheinwiderstand
$Z_T$	Impedance at temperature T	Scheinwiderstand bei Temperatur T
$tan \ \delta$	Dissipation factor	Verlustfaktor
λ	Failure rate	Ausfallrate
$\epsilon_{0}$	Absolute permittivity	Elektrische Feldkonstante
$\epsilon_{\text{r}}$	Relative permittivity	Dielektrizitätszahl
ω	Angular velocity; $2 \cdot \pi \cdot f$	Kreisfrequenz; $2 \cdot \pi \cdot f$

#### Note

All dimensions are given in mm.



#### Important notes

The following applies to all products named in this publication:

- 1. Some parts of this publication contain statements about the suitability of our products for certain areas of application. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
- 2. We also point out that in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or lifesaving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
- 3. The warnings, cautions and product-specific notes must be observed.
- 4. In order to satisfy certain technical requirements, some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous). Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
- 5. We constantly strive to improve our products. Consequently, the products described in this publication may change from time to time. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also reserve the right to discontinue production and delivery of products. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
- Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI).
- 7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKK, MKD, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are trademarks registered or pending in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

#### Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331