


# H Series

## 4 & 6 Tumbler Power Switchlocks



Models Available

### Features/Benefits

- Positive detent
- Multi-pole and multi-position
- Snap-together assembly
- Power switching

### Typical Applications

- Machine controls
- Elevators

### Specifications

CONTACT RATING: Q contact material: 12 AMPS @ 125 V AC; 6 AMPS @ 250 V AC; 1 AMP @ 125 V DC (UL/CSA). See page L-37 for additional ratings.

ELECTRICAL LIFE: 10,000 make-and-break cycles at full load.

CONTACT RESISTANCE: Below 10 m  $\Omega$  typ. initial @ 2-4 V DC, 100 mA, for both silver and gold plated contacts.

INSULATION RESISTANCE: 10<sup>9</sup>  $\Omega$  min.

DIELECTRIC STRENGTH: 1,000 Vrms min. @ sea level.

OPERATING TEMPERATURE: -30°C to 85°C.

INDEXING: 45° or 90°, 2-4 Positions.

**NOTE:** Any models supplied with Q or B contact material are RoHS compliant.

**NOTE:** Specifications and materials listed above are for switchlocks with standard options. For information on specific and custom switchlocks, consult Customer Service Center.

### Materials

LOCK: Zinc alloy with stainless steel facing (4 tumbler locks and 6 tumbler tubular lock).

KEYS: Two nickel plated brass keys with code number (4 tumbler). Two die cast chrome plated zinc alloy keys (6 tumbler).

SWITCH HOUSING: 6/6 nylon (UL 94V-2).

CONTACTS & TERMINALS: Q contact material: Copper, silver plated. See page L-37 for additional contact materials.

CONTACT SPRING: Music wire or stainless steel.

MOUNTING NUT: Zinc alloy.

MOUNTING CLIP: Steel, zinc plated.

DRESS NUT: Brass, nickel plated.

TERMINAL SEAL: Epoxy.

### Build-A-Switch

To order, simply select desired option from each category and place in the appropriate box. Available options are shown and described on pages L-35 through L-38. For additional options not shown in catalog, consult Customer Service Center.



#### Switch and Lock Function

**H10113** SP, 90° Index, keypull pos.1

**H2011U** DP, 90° Index, keypull pos. 1 & 2

**H100AA** SP, 45° Index, keypull pos. 1,2 & 3

**H200AA** DP, 45° Index, keypull pos. 1, 2 & 3

**H20113** DP, 90° Index, keypull pos. 1

**H1011U** SP, 90° Index, keypull pos.1 & 2

**H1417U** SP, 90° Index, keypull pos. 1,2 & 3

#### Keying

- 2** Two nickel plated brass keys (4 tumbler) or two die cast zinc alloy keys with chrome plating (6 tumbler)
- T** One nickel plated brass key with plastic insert molded square head and one nickel plated brass key

#### Lock Type

- F** 4 Tumbler lock with detent
- V** 6 Tumbler tubular lock

#### Lock Finish

- 2** Stainless steel facing
- 8** Gloss black facing

#### Terminations

- 05** Quick connect
- WC** Wire lead

#### Mounting/Lock Style

- N** With nut
- D** With clip

#### Contact Material

- Q** Silver
- B** Gold

#### Key Color

- NONE** Nickel plated brass (4 tumbler) or chrome plated zinc alloy (6 tumbler)
- 2** Black



Switchlock



# H Series 4 & 6 Tumbler Power Switchlocks

## SWITCH AND LOCK FUNCTION




| NO. TUMBLERS | NO. POLES | MODEL NO.                      | CONNECTED TERMINALS |                 |                 |        | KEY PULL POSITIONS | LOCK CONFIGURATION | INDEXING |
|--------------|-----------|--------------------------------|---------------------|-----------------|-----------------|--------|--------------------|--------------------|----------|
|              |           |                                | POS. 1              | POS. 2          | POS. 3          | POS. 4 |                    |                    |          |
| 4            | SP DP     | <b>H100AA</b><br><b>H200AA</b> | 7-8<br>7-8, 3-4     | 8-1<br>8-1, 4-5 | 6-7<br>6-7, 2-3 |        | Positions 1, 2 & 3 |                    | 45°      |
| 4 & 6        | SP DP     | <b>H10113</b><br><b>H20113</b> | 7-8<br>7-8, 3-4     | 8-2<br>8-2, 4-6 |                 |        | Position 1         |                    | 90°      |
| 4 & 6        | SP DP     | <b>H1011U</b><br><b>H2011U</b> | 7-8<br>7-8, 3-4     | 8-2<br>8-2, 4-6 |                 |        | Positions 1 & 2    |                    |          |
| 4            | SP        | <b>H1417U</b>                  | 6-8                 | 8-2             | 5-6             |        | Positions 1, 2 & 3 |                    |          |

All models  with all options when ordered with 'G' or 'Q' contact material.

### TERMINAL NUMBERS


### LEGEND

- = Detent Positions (45° or 90°)
- ⊙ = Key pull possible in these positions.
- = Stop Positions




Terminal numbers molded on housing.

### 4 Tumbler



Part number shown: H101132F205NQ

### 6 Tumbler



Part number shown: H1011U2V205NQ



Third Angle  
Projection

Dimensions are shown: Inch (mm)  
Specifications and dimensions subject to change

# H Series

## 4 & 6 Tumbler Power Switchlocks

### KEYING



KEYING


KEY COLOR

| OPTION CODE | KEY OPTIONS                                                                                  | CODE NO. ON KEY | CODE NO. ON LOCK |
|-------------|----------------------------------------------------------------------------------------------|-----------------|------------------|
| <b>2</b>    | 2 NICKEL PLATED BRASS KEYS (4 TUMBLER) OR 2 CHROME PLATED ZINC ALLOY KEYS (6 TUMBLER)        | YES             | NO               |
| <b>T</b>    | 1 NICKEL PLATED BRASS KEY WITH PLASTIC INSERT MOLDED SQUARE HEAD & 1 NICKEL PLATED BRASS KEY | YES             | NO               |

| OPTION CODE | KEY COLOR                                                               |
|-------------|-------------------------------------------------------------------------|
| <b>NONE</b> | NICKEL PLATED BRASS (4 TUMBLER) OR CHROME PLATED ZINC ALLOY (6 TUMBLER) |
| <b>2</b>    | BLACK                                                                   |


**NOTE:** All orders keyed alike, standard. For more than one key code, replacement keys, or other special features, consult Customer Service Center.

#### NICKEL PLATED BRASS KEY




Key part number: 115140126

#### NICKEL PLATED BRASS KEY WITH PLASTIC INSERT MOLDED SQUARE HEAD



Key part number: 11599112602

#### CHROME PLATED ZINC ALLOY KEY




Key part number: 363C1AAAA

**NOTE:** Key head shape subject to change without notice.


### LOCK TYPE



#### F 4 TUMBLER LOCK WITH ADDED DETENT



#### V 6 TUMBLER TUBULAR LOCK



### LOCK FINISH



#### 2 STAINLESS STEEL FACING



Available with V lock type only.


#### 8 GLOSS BLACK FACING




### TERMINATIONS



#### 05 .110" QUICK CONNECT



#### WC WIRE LEAD



Black wire standard, other colors, gages and lengths available, consult Customer Service Center. UL style 1015.



Third Angle Projection

Dimensions are shown: Inch (mm)  
Specifications and dimensions subject to change




Switchlock

# H Series 4 & 6 Tumbler Power Switchlocks

## MOUNTING/LOCK STYLE




**N** WITH NUT




Nut part number: 937C00000

**D** WITH CLIP




Clip part number: 906B00000

PANEL MOUNTING



| MOUNTING STYLES | PANEL THICKNESS       |
|-----------------|-----------------------|
| D               | .065-.085 (1,65-2,16) |
| N               | .195 (4,95) max.      |

## Switch and Lock Assembly Instructions



1. Place lock assembly in mounting hole on panel, secure with mounting nut.
2. Align keying tab on switch assembly with keying slot on lock assembly.
3. Snap assemblies together.
4. Switch installation is permanent. Switch cannot be removed from lock after assembly. Attempting to separate switch and lock may cause damage to switchlock.

## CONTACT MATERIAL



| OPTION CODE | RoHS COMPLIANT* | RoHS COMPATIBLE* | CONTACT AND TERMINAL MATERIAL | RATING                |                                                                   |
|-------------|-----------------|------------------|-------------------------------|-----------------------|-------------------------------------------------------------------|
| <b>Q</b>    | YES             | YES              | SILVER <sup>2</sup>           | POWER                 | 12 AMPS @ 125 V AC; 6 AMPS @ 250 V AC; 1 AMP @ 125 V DC (UL/CSA). |
| <b>B</b>    | YES             | YES              | GOLD <sup>1</sup>             | LOW LEVEL/DRY CIRCUIT | 0.4 VA MAX. @ 20 V AC or DC MAX.                                  |

<sup>1</sup> CONTACTS & TERMINALS: Copper, with gold plate over nickel plate.

<sup>2</sup> CONTACTS & TERMINALS: Copper, silver plated.

\* Note: See Technical Data section of this catalog for RoHS compliant and compatible definition and specifications.

All models  with all options when ordered with 'Q' contact material.



Third Angle  
Projection

Dimensions are shown: Inch (mm)  
Specifications and dimensions subject to change

# H Series

## 4 & 6 Tumbler Power Switchlocks

### AVAILABLE HARDWARE



Key Code: A126  
4 TUMBLER  
**PART NO. (ONE KEY)**  
**115140126**  
**Material:** Brass  
Finish: Nickel plate



Key Code: AAAA  
**PART NO. (ONE KEY)**  
**363C1AAAA**  
**Material:** Zinc Alloy  
Finish: Chrome plate



Key Code: A126  
4 TUMBLER  
**PART NO. (ONE KEY)**  
**1159112602** BLACK  
**Material:** Brass  
Finish: Nickel plate  
6/6 Nylon insert molded head



Switchlock



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331