



Product: [3105A](#)

RS485, 1 Pr #22 Str TC, PO Ins, OS+TC Brd, PVC Jkt, CM

Request Sample

Product Description

RS-485, 1 Pair 22AWG (7x30) Tinned Copper, PO Insulation, Overall Beldfoil®+Tinned Copper Braid(65%) Shield, PVC Outer Jacket, CM

Technical Specifications

Product Overview

Suitable Applications:	harsh environment, IIoT, factory or process automation, video, audio, data communication, etc.
------------------------	--

Physical Characteristics (Overall)

Conductor				
AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	1
Conductor Count:			2	

Insulation		
Material	Material Trade Name	Nominal Diameter
PE - Polyethylene (Foam)	Datalene®	0.087 in

Color Chart	
Number	Color
1	White/Blue Ringband Stripe and Blue/White Ringband Stripe

Outer Shield Material							
Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Alum / Poly	Beldfoil®	100 %	TC - Tinned Copper	22	7x30
Braid	2	TC - Tinned Copper		65 %			

Outer Jacket Material	
Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.281 in

Electrical Characteristics

Conductor DCR	
Nominal Conductor DCR	Nominal Outer Shield DCR
14.7 Ohm/1000ft	2.8 Ohm/1000ft

Capacitance	
Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
11 pF/ft	20.9 pF/ft

Impedance	
Nominal Characteristic Impedance	
120 Ohm	

High Frequency (Nominal/Typical)

Nom. Insertion Loss
0.5 dB/100ft

Delay

Nominal Velocity of Propagation (VP) [%]
78 %

Current

Max. Recommended Current [A]
2.7 Amps per conductor @ 25°C

Voltage

UL Voltage Rating
300 V RMS (NEC Type PLTC)
300 V RMS (NEC Type CM)

Electrical Characteristics Notes:	Input Impedance/Unfitted Impedance .5 - 10 MHZ, 120 +/-12 Ohms
-----------------------------------	--

Temperature Range

Non-UL Temp Rating:	60°C
UL Temp Rating:	60°C
Operating Temp Range:	-20°C To +60°C

Mechanical Characteristics

Bulk Cable Weight:	43 lbs/1000ft
Max Recommended Pulling Tension:	200 lbs
Min Bend Radius/Minor Axis:	6.0 in

Standards

NEC/(UL) Specification:	CM, PLTC
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2005-10-01
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Hazardous Locations:	Yes
Suitability - Indoor:	Yes
Suitability - Oil Resistance:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (NEC Type PLTC)

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

--

Variants

Item #	Color	Putup Type	Length	UPC/EAN
3105A 01010000	Black			612825386551
3105A.00152	Black	Reel	152 m	8719605005816
3105A.00305	Black	Reel	305 m	8719605005830
3105A 010500	Black	Reel	500 ft	612825141600
3105A.00610	Black	Reel	610 m	8719605005854
3105A 0101000	Black	Reel	1,000 ft	612825141594
3105A.001000	Black	Reel	1,000 m	8719605005809
3105A.001525	Black	Reel	1,525 m	8719605005823
3105A.003050	Black	Reel	3,050 m	8719605005847
3105A 0105000	Black	Reel	5,000 ft	612825141617

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	N - FINAL PUT-UP LENGTH MAY VARY -0% TO +10% FROM LENGTH SHOWN.

Product Notes

Notes:	Oil Resistance: Passes Oil Res II Per UL1277, Table 10.17. For CPE jacketed version order Part No. YR44345.
--------	---

History

Update and Revision:	Revision Number: 0.329 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331