CHEMTRONICS Technical Data Sheet

TDS # DEL1681

Pow-R-Wash[™] **Delta Electronics Contact Cleaner**

PRODUCT DESCRIPTION

Pow-R-Wash™ Delta electronics contact cleaner is a highly efficient and effective solvent cleaner for electrical and electronic components and assemblies. This cleaning agent is both nonflammable, and engineered to be compatible with most metals and plastics found in electronic assemblies. This material can be used on energized equipment, is fast drying and has excellent solvency for oil, grease, dirt.

- Rapidly cleans dirt, oils, carbon, grease and other contaminants
- Nonflammable
- Excellent material compatibility
- Displaces moisture
- Evaporates fast
- Leaves no residues
- Enhances electrical signal
- Low toxicity
- Available with All-Way Spray valve

TYPICAL APPLICATIONS

Pow-R-Wash™ Delta effectively cleans and degreases:

- Printed Circuit Boards
- Circuit Breakers
- Electrical Motors
- Potentiometers
- Contacts and Relays
- Motors and Generators
- Selector Switches
- Solenoids

TYPICAL PRODUCT DATA AND PHYSICAL PROPERTIES

| Boiling Point | 99°F (Initial) | | | | |
|--|-----------------------------------|--|--|--|--|
| Evaporation Rate (butyl acetate=1) >1 | | | | | |
| Flash Point (TCC) | None | | | | |
| Appearance | Clear, Colorless | | | | |
| | Liquid | | | | |
| Odor | Ethereal | | | | |
| Specific Gravity | 1.30 | | | | |
| Vapor Pressure @68°F | 51 mmHg | | | | |
| Solubility in Water | Negligible | | | | |
| Dielectric Breakdown | 30 kV | | | | |
| (ASTM D-877) | | | | | |
| Surface Tension | 15 | | | | |
| (dynes/cm @ 73°F) | | | | | |
| Kauri Butanol Number | 60 | | | | |
| VOC* Content: | Aerosol | | | | |
| CARB | 73% | | | | |
| SCAQMD | 695 g/L | | | | |
| Federal | 56% | | | | |
| RoHS Compliant | ROHS WEEE Complant | | | | |
| Shelflife | 5 years | | | | |
| *Volatila Organia Compound (VO | C) information is solaulated an a | | | | |

^{*}Volatile Organic Compound (VOC) information is calculated on a weight basis using the VOC definition of California Air Resources Board (CARB) Consumer Product Regulations, South Coast Air Quality Management District (SCAQMD) Rule 102 and the Federal definition published in 40 CFR 51.100(s).

COMPATIBILITY

Pow-R-WashTM Delta has excellent compatibility with most materials used in the electronics industry. With any cleaning agent, compatibility with substrate should be determined on a non-critical area prior to use.

| Material | Compatibility | |
|------------------------|-----------------|--|
| ABS | Not Recommended | |
| Buna-N | Not recommended | |
| EPDM | Good | |
| Graphite | Excellent | |
| HDPE | Good | |
| Kynar TM | Good | |
| LDPE | Good | |
| Lexan TM | Good | |
| Neoprene | Good | |
| Noryl [®] | Good | |
| Nylon TM 66 | Excellent | |
| Cross-Linked PE | Good | |
| Polypropylene | Good | |
| Polystyrene | Not Recommended | |
| PVC | Excellent | |
| Silicone Rubber | Good | |
| Teflon TM | Good | |
| Viton™ | Not Recommended | |

| Performance | | | | |
|---------------------------------------|------------------|--|--|--|
| Grease & Lubricating Oil solvent (mg) | Removal per gram | | | |
| Pow-R-Wash Delta | 12.4 | | | |
| AK225-based Cleaner | 8.4 | | | |

USAGE INSTRUCTIONS

For commercial use only.

Read MSDS carefully prior to use.

Spray 4-6 inches from surface to clean. Wash parts from top to bottom, allowing the liquid to flush away dirt and dissolved oil and grease. For precise application use attached extension tube.

AVAILABILITY

DEL1681 12 oz. Aerosol

TECHNICAL & APPLICATION ASSISTANCE

Chemtronics provides a technical hotline to answer your technical and application related questions. The toll free number is: **1-800-TECH-401.**

| ENVIRONMENTAL IMPACT DATA | | | | | | |
|---------------------------|------|-----|------|--|--|--|
| HCFC-141b | 0.0% | HFC | 49% | | | |
| HCFC-225 | 0.0% | nPB | 0.0% | | | |

HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. HCFC-225, HCFC-141b, HFC, and nPB percentages shown are the content by weight. Hydrochlorofluorocarbons (HCFCs) are regulated under the Montreal Protocol as Class II ozone depleting substances. HCFC-141b is no longer produced in the US under this legislation. HCFC-225 is phased out for production as of 2015. Hydrofluorocarbons (HFCs) are not currently regulated.

NOTE:

This information is believed to be accurate. It is intended for professional end users having the skills to evaluate and use the data properly. CHEMTRONICS does not guarantee the accuracy of the data and assumes no liability in connection with damages incurred while using it.

Chemtronics® is a registered trademark of Chemtronics. All rights reserved. Pow-R-Wash™ is a trademark of Chemtronics. All rights reserved.

All other trademarks herein are trademarks or registered trademarks of their respective owners.

CHEMTRONICS 8125 COBB CENTER DRIVE KENNESAW, GA 30152

1-770-424-4888 REV. A (01/15)

| DISTRIBUT | ED BY: | |
|-----------|--------|--|
| | | |
| | | |
| | | |
| | | |



Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию.

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России, а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научноисследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,

Промышленная ул, дом № 19, литера Н,

помещение 100-Н Офис 331