


SPECIFICATION CONTROL DRAWING		SCD		55A0134																																																					
Title THREE CONDUCTOR CABLE, UNSHIELDED, UNJACKETED, GENERAL PURPOSE, 600 VOLT		Date 2-12-16		Revision D																																																					
This specification sheet forms a part of the latest issue of Raychem Specification 55A.																																																									
COMPONENT WIRES - 55A0114  <table border="1" style="margin: auto; border-collapse: collapse; font-size: 0.8em;"> <thead> <tr> <th colspan="5" style="padding: 5px;">CABLE CONSTRUCTION DETAILS</th> </tr> <tr> <th rowspan="2" style="padding: 5px;">PART NUMBER <u>1/</u></th> <th rowspan="2" style="padding: 5px;">CONDUCTOR SIZE (AWG)</th> <th colspan="2" style="padding: 5px;">OUTSIDE DIAMETER (inch)</th> <th rowspan="2" style="padding: 5px;">MAXIMUM WEIGHT (lbs/1000 ft.)</th> </tr> <tr> <th style="padding: 5px;">NOMINAL</th> <th style="padding: 5px;">MAXIMUM</th> </tr> </thead> <tbody> <tr><td style="padding: 5px;">55A0134-30-*</td><td style="padding: 5px;">30</td><td style="padding: 5px;">.052</td><td style="padding: 5px;">.056</td><td style="padding: 5px;">2.0</td></tr> <tr><td style="padding: 5px;">55A0134-28-*</td><td style="padding: 5px;">28</td><td style="padding: 5px;">.058</td><td style="padding: 5px;">.063</td><td style="padding: 5px;">2.8</td></tr> <tr><td style="padding: 5px;">55A0134-26-*</td><td style="padding: 5px;">26</td><td style="padding: 5px;">.069</td><td style="padding: 5px;">.073</td><td style="padding: 5px;">4.3</td></tr> <tr><td style="padding: 5px;">55A0134-24-*</td><td style="padding: 5px;">24</td><td style="padding: 5px;">.080</td><td style="padding: 5px;">.084</td><td style="padding: 5px;">6.1</td></tr> <tr><td style="padding: 5px;">55A0134-22-*</td><td style="padding: 5px;">22</td><td style="padding: 5px;">.093</td><td style="padding: 5px;">.097</td><td style="padding: 5px;">8.9</td></tr> <tr><td style="padding: 5px;">55A0134-20-*</td><td style="padding: 5px;">20</td><td style="padding: 5px;">.108</td><td style="padding: 5px;">.112</td><td style="padding: 5px;">13.5</td></tr> <tr><td style="padding: 5px;">55A0134-18-*</td><td style="padding: 5px;">18</td><td style="padding: 5px;">.130</td><td style="padding: 5px;">.134</td><td style="padding: 5px;">19.9</td></tr> <tr><td style="padding: 5px;">55A0134-16-*</td><td style="padding: 5px;">16</td><td style="padding: 5px;">.147</td><td style="padding: 5px;">.151</td><td style="padding: 5px;">25.4</td></tr> </tbody> </table> CABLE RATINGS AND ADDITIONAL REQUIREMENTS TEMPERATURE RATING: 200°C Maximum continuous conductor temperature VOLTAGE RATING: 600 volts (rms) at sea level DIELECTRIC WITHSTAND: 1500 volts (rms), 60 Hz INSULATION FLAWS: Spark Test, 5.7 kV (rms) at 3 kHz Impulse Dielectric Test, 8.0 kV (peak) <u>1/</u> PART NUMBER: The "*" in the part numbers above shall be replaced by color code designators with a slash separating the component wire colors. Colors shown do not necessarily reflect the sequence of manufacturing. Example: AWG 22, black, brown, and red component wires: 55A0134-22-0/1/2						CABLE CONSTRUCTION DETAILS					PART NUMBER <u>1/</u>	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)	NOMINAL	MAXIMUM	55A0134-30-*	30	.052	.056	2.0	55A0134-28-*	28	.058	.063	2.8	55A0134-26-*	26	.069	.073	4.3	55A0134-24-*	24	.080	.084	6.1	55A0134-22-*	22	.093	.097	8.9	55A0134-20-*	20	.108	.112	13.5	55A0134-18-*	18	.130	.134	19.9	55A0134-16-*	16	.147	.151	25.4
CABLE CONSTRUCTION DETAILS																																																									
PART NUMBER <u>1/</u>	CONDUCTOR SIZE (AWG)	OUTSIDE DIAMETER (inch)		MAXIMUM WEIGHT (lbs/1000 ft.)																																																					
		NOMINAL	MAXIMUM																																																						
55A0134-30-*	30	.052	.056	2.0																																																					
55A0134-28-*	28	.058	.063	2.8																																																					
55A0134-26-*	26	.069	.073	4.3																																																					
55A0134-24-*	24	.080	.084	6.1																																																					
55A0134-22-*	22	.093	.097	8.9																																																					
55A0134-20-*	20	.108	.112	13.5																																																					
55A0134-18-*	18	.130	.134	19.9																																																					
55A0134-16-*	16	.147	.151	25.4																																																					
NOTE: Nominal values are for information only. Nominal values are not requirements.																																																									
Users should evaluate the suitability of this product for their application. Specifications are subject to change without notice. Tyco Electronics Corporation also reserves the right to make changes in materials or processing, which do not affect compliance with any specification, without notification to Buyer.																																																									
<u>1/</u> COLORS AND COLOR CODE DESIGNATORS SHALL BE IN ACCORDANCE WITH MIL-STD-681. HOWEVER, DUE TO LENGTH LIMITATIONS OF THE RAYCHEM PART NUMBER, AN ALTERNATIVE COLOR CODE MAY REPLACE MIL-STD-681 COLOR CODE DESIGNATORS. (EXAMPLE: "901/902..." MAY BE REPLACED BY "Axxx".) OTHER CODES AND SUFFIXES MAY BE ADDED TO THE PART NUMBER, AS NECESSARY, TO CAPTURE ANY ADDITIONAL REQUIREMENTS IMPOSED BY THE PURCHASE ORDER.																																																									
Page 1 of 1	Raychem, TE Connectivity, TE connectivity (logo), and TE (logo) are trademarks.		 Raychem Wire & Cable 501 Oakside Avenue Redwood City, CA 94063-3800 Phone: 1-800-227-8816 Fax: 1-650-361-6297																																																						
	DIMENSIONS ARE IN INCHES AND, UNLESS OTHERWISE DESIGNATED, ARE NOMINAL																																																								
	THIS SPECIFICATION SHEET TAKES PRECEDENCE OVER DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.																																																								



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331