


Thyristor/Thyristor, 150 A (New INT-A-PAK Power Module)



New INT-A-PAK

FEATURES

- Electrically isolated by DBC ceramic (Al_2O_3)
- 3500 V_{RMS} isolating voltage
- Industrial standard package
- High surge capability
- Glass passivated chips
- Simple mounting
- UL approved file E78996 
- Designed and qualified for multiple level
- Material categorization: For definitions of compliance please see www.vishay.com/doc?99912



RoHS
COMPLIANT

PRODUCT SUMMARY

$I_{\text{T(AV)}}$	150 A
Type	Modules - Thyristor, Standard
Package	INT-A-PAK
Circuit	Two SCRs doubler circuit

APPLICATIONS

- Battery charges
- Welders
- Power converters

MAJOR RATINGS AND CHARACTERISTICS

SYMBOL	CHARACTERISTICS	VALUES	UNITS
$I_{\text{T(AV)}}$	85 °C	150	A
$I_{\text{T(RMS)}}$		330	A
I_{TSM}	50 Hz	4000	
	60 Hz	4200	
I^2t	50 Hz	80	kA^2s
	60 Hz	73	
$I^2\sqrt{t}$		800	$\text{kA}^2\sqrt{\text{s}}$
V_{RRM}		400	V
T_{Stg}	Range	-40 to 150	°C
T_{J}	Range	-40 to 125	

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

TYPE NUMBER	$V_{\text{RRM}}/V_{\text{DRM}}$, MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	$V_{\text{RSM}}/V_{\text{DSM}}$, MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	$I_{\text{RRM}}/I_{\text{DRM}}$ AT 125 °C mA
VS-VSKT152/04PbF	400	500	50



ON-STATE CONDUCTION						
PARAMETER	SYMBOL	TEST CONDITIONS			VALUES	UNITS
Maximum average on-state current at case temperature	$I_{T(AV)}$	180° conduction half sine wave			150	A
					85	°C
Maximum RMS on-state current	$I_{T(RMS)}$	As AC switch			330	A
Maximum peak, one-cycle on-state, non-repetitive surge current	I_{TSM}	t = 10 ms	No voltage reapplied	Sine half wave, initial T_J = T_J maximum	4000	
		t = 8.3 ms			4200	
		t = 10 ms	100 % V_{RRM} reapplied		3350	
		t = 8.3 ms			3500	
Maximum I^2t for fusing	I^2t	t = 10 ms	No voltage reapplied		80	kA ² s
		t = 8.3 ms			73	
		t = 10 ms	100 % V_{RRM} reapplied		56	
		t = 8.3 ms			51	
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	t = 0.1 ms to 10 ms, no voltage reapplied			800	kA ² √s
Value of threshold voltage	$V_{T(TO)}$	T_J maximum			0.82	V
On-state slope resistance	r_t				1.44	mΩ
Maximum on-state voltage drop	V_{TM}	$I_{pk} = \pi \times I_{T(AV)}$, $T_J = 25\text{ °C}$			1.48	V
Maximum holding current	I_H	$T_J = 25\text{ °C}$, anode supply = 6 V, resistive load, gate open circuit			200	mA
Maximum latching current	I_L	$T_J = 25\text{ °C}$, anode supply = 6 V, resistive load			400	

SWITCHING					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Typical delay time	t_{gd}	$T_J = 25\text{ }^{\circ}\text{C}$	Gate current = 1 A, $di_g/dt = 1\text{ A}/\mu\text{s}$ $V_d = 0.67\text{ \% }V_{\text{DRM}}$	1	μs
Typical rise time	t_{gr}			2	
Typical turn-off time	t_q	$I_{\text{TM}} = 300\text{ A}$, - $di/dt = 15\text{ A}/\mu\text{s}$; $T_J = T_J$ maximum $V_R = 50\text{ V}$; $dV/dt = 20\text{ V}/\mu\text{s}$; gate 0 V, 100 Ω		50 to 200	

BLOCKING				
PARAMETER	SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum peak reverse and off-state leakage current	I_{RRM} , I_{DRM}	$T_J = 125\text{ }^{\circ}\text{C}$	50	mA
RMS insulation voltage	V_{INS}	50 Hz, circuit to base, all terminals shorted, t = 1 s	3500	V
Critical rate of rise of off-state voltage	dV/dt	$T_J = T_J$ maximum, exponential to 67 % rated V_{DRM}	1000	V/μs



TRIGGERING						
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS	
Maximum peak gate power	P _{GM}	t _p ≤ 5 ms, T _J = T _J maximum		12	W	
Maximum average gate power	P _{G(AV)}	f = 50 Hz, T _J = T _J maximum		3		
Maximum peak gate current	I _{GM}	t _p ≤ 5 ms, T _J = T _J maximum		3	A	
Maximum peak negative gate voltage	- V _{GT}			10	V	
Maximum required DC gate voltage to trigger	V _{GT}	T _J = - 40 °C	Anode supply = 6 V, resistive load; R _a = 1 Ω	4		
		T _J = 25 °C		2.5		
		T _J = T _J maximum		1.7		
Maximum required DC gate current to trigger	I _{GT}	T _J = - 40 °C		270	mA	
		T _J = 25 °C		150		
		T _J = T _J maximum		80		
Maximum gate voltage that will not trigger	V _{GD}	T _J = T _J maximum, rated V _{DRM} applied		0.3	V	
Maximum gate current that will not trigger	I _{GD}			10	mA	
Maximum rate of rise of turned-on current	di/dt	T _J = T _J maximum, I _{TM} = 400 A rated V _{DRM} applied		300	A/μs	

THERMAL AND MECHANICAL SPECIFICATIONS					
PARAMETER		SYMBOL	TEST CONDITIONS	VALUES	UNITS
Maximum junction operating temperature range		T _J		- 40 to 125	°C
Maximum storage temperature range		T _{Stg}		- 40 to 150	
Maximum thermal resistance, junction to case per junction		R _{thJC}	DC operation	0.18	K/W
Maximum thermal resistance, case to heatsink per module		R _{thCS}	Mounting surface smooth, flat and greased	0.05	
Mounting torque ± 10 %	IAP to heatsink		A mounting compound is recommended and the torque should be rechecked after a period of 3 hours to allow for the spread of the compound. Lubricated threads.	4 to 6	Nm
	busbar to IAP				
Approximate weight				200	g
				7.1	oz.
Case style				INT-A-PAK	

ΔR CONDUCTION PER JUNCTION											
DEVICES	SINUSOIDAL CONDUCTION AT T _J MAXIMUM					RECTANGULAR CONDUCTION AT T _J MAXIMUM					UNITS
	180°	120°	90°	60°	30°	180°	120°	90°	60°	30°	
VSKT152/04PbF	0.007	0.010	0.013	0.016	0.017	0.009	0.012	0.014	0.016	0.017	K/W

Note

- Table shows the increment of thermal resistance R_{thJC} when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - On-State Power Loss Characteristics




Fig. 8 - On-State Power Loss Characteristics




Fig. 9 - On-State Power Loss Characteristics




Fig. 10 - On-State Voltage Drop Characteristics




Fig. 11 - Thermal Impedance Z_{thJC} Characteristics


Fig. 12 - Gate Characteristics



ORDERING INFORMATION TABLE

Device code	VS-VS	KT	152	04	PbF
	1	2	3	4	5
1	- Vishay Semiconductors product				
2	- Circuit configuration				
3	- Current rating				
4	- Voltage rating (04 = 400 V)				
5	- PbF = Lead (Pb)-free				

Note


- To order the optional hardware go to www.vishay.com/doc?95172

CIRCUIT CONFIGURATION		
CIRCUIT DESCRIPTION	CIRCUIT CONFIGURATION CODE	CIRCUIT DRAWING
Two SCRs doubler circuit	T	

LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95067

INT-A-PAK IGBT/Thyristor

DIMENSIONS in millimeters (inches)





Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.



**Стандарт
Электрон
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

Наши контакты:

Телефон: +7 812 627 14 35

Электронная почта: sales@st-electron.ru

Адрес: 198099, Санкт-Петербург,
Промышленная ул, дом № 19, литера Н,
помещение 100-Н Офис 331