



Data Sheet

# HD110C

## Heavy-Duty Digital Multimeter

### Key features:

- Measures 1500 VDC
- CAT IV 1000 V
- IP67 Rated
- Magne-Grip™ holster with magnetic hanging strap

- Highest voltage capability, measuring to 1500 V dc and 1000 V ac
- CAT IV 1000 V rated
- Special sealing for environment and water resistance. IP67 rated
- Constructed with drop-resistant housing and PCB mounting
- Magne-Grip™ holster, frees both hands for work
- Includes high voltage test leads with threaded alligator clips

The HD110C is designed for professional use in harsh environments. The meter is unusually rugged and reliable in everyday heavy use applications. The meter is made using waterproof construction to prevent dirt, grime and moisture from entering the case and causing inaccurate readings or damaging shorts.

Built of tough, fire-retardant thermoplastic resistant to grease and chemical spills, with all sensitive components shock-mounted for a drop resistant to at least eight feet.

HD110C has an extended voltage measurement capability of 1500 V dc and 1000 V ac, unmatched by any other line of digital multimeters. The extended voltage ranges can withstand transients up to 12 kV.



HD110C

## No hassle warranty

*No waiting.*

*No shipping charges.*



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.





## HD110C Technical Specifications

## Data Sheet

### General Specifications

|                                      |                                                                                                                                                                          |
|--------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display                              | 3-1/2 digit LCD, 1999 counts, with annunciators and menu features                                                                                                        |
| Polarity Indication                  | Automatic                                                                                                                                                                |
| Input overload indication            | 1                                                                                                                                                                        |
| Low Battery Indication               | ; < 50 hours battery life remain, accuracy is no longer guaranteed                                                                                                       |
| Display Update Rate                  | 2.5/sec, nominal                                                                                                                                                         |
| Oper. Temp.                          | 0 °C to +50 °C, (< 75 % R.H.)                                                                                                                                            |
| Storage Temp                         | -20 °C to 60 °C, 0 to 80 % RH, battery removed                                                                                                                           |
| Temperature coefficient              | 0.1 x (spec. accuracy)/°C (0 ° to 18 °C and 28° to 50 °C) all functions and ranges except for mVDC<br>0.3 x (spec. accuracy)/°C (0 ° to 18 °C and 28° to 50 °C) for mVDC |
| Altitude                             | Up to 2000 m — indoor use                                                                                                                                                |
| Fuse                                 | F 2 A/1500 V fuse (8 mm x 65 mm), I.R. 30 kA – Amprobe® p/n FP700                                                                                                        |
| Power                                | Standard 9 V battery, NEDA 1604, JIS 006P, IEC 6F22                                                                                                                      |
| Auto Power-Down                      | Meter powers down after approx. 30 min. of inactivity.                                                                                                                   |
| Battery Life                         | 250 hours typical with carbon-zinc, 500 hours typical with alkaline                                                                                                      |
| Dimensions, with holster (H x W x D) | 200 x 102 x 59 mm (7.9 in x 4.0 in x 2.3 in)                                                                                                                             |
| Weight (incl. battery)               | 642 g (20 oz)                                                                                                                                                            |
| Accessories                          | Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (in instrument), hex wrench in holster, Magne-Grip flex strap and User Manual        |
| Case material                        | Flame retardant, high-impact thermoplastic                                                                                                                               |
| Safety                               | Meets EN 61010-1 CAT IV 1000 V (1500 V DC max) Class II, EN 60529:IP67                                                                                                   |
| EMC                                  | Meets EN 61326-1                                                                                                                                                         |

### Electrical Specifications *(Accuracies at 23 °C ± 5 °C, <75 % RH non-condensing, guaranteed for one year.)*

| Function                         | Range                                                                                                                                                                                   | Accuracy            |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| <b>DC Volts</b>                  |                                                                                                                                                                                         |                     |
| Ranges                           | 200 mV, 2 V, 20 V, 200 V, 1500 V                                                                                                                                                        |                     |
| Resolution                       | 0.1 mV                                                                                                                                                                                  |                     |
| Accuracy                         | All ranges                                                                                                                                                                              | ±(0.1 % rdg+2 dgts) |
| Input Impedance                  | 10 MΩ                                                                                                                                                                                   |                     |
| OL Protection                    | 1500 V dc/1000 V ac rms                                                                                                                                                                 |                     |
| Transient Protection             | 12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V product. This product should not be used in installations where transients exceed 12 kV. |                     |
| <b>AC Volts (45 Hz to 2 kHz)</b> |                                                                                                                                                                                         |                     |
| Ranges                           | 200 mV, 2 V, 20 V, 200 V, 1000 V                                                                                                                                                        |                     |
| Resolution                       | 0.1 mV                                                                                                                                                                                  |                     |
| Accuracy                         | 200 mV to 200 V (45-500 Hz)                                                                                                                                                             | ±(0.8 % rdg+4 dgts) |
|                                  | 200 mV to 200 V (500 Hz-2 kHz)                                                                                                                                                          | ±(1.5 % rdg+5 dgts) |
|                                  | 1000 V (50-60 Hz)                                                                                                                                                                       | ±(0.8 % rdg+4 dgts) |
|                                  | 1000 V (60-500 Hz)                                                                                                                                                                      | ±(1.5 % rdg+5 dgts) |
| Input Impedance                  | 10 MΩ                                                                                                                                                                                   |                     |
| OL Protection                    | 1500 V dc/1000 V ac rms                                                                                                                                                                 |                     |
| Transient Protection             | 12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V product. This product should not be used in installations where transients exceed 12 kV. |                     |
| <b>DC Current</b>                |                                                                                                                                                                                         |                     |
| Ranges                           | 200 μA, 2 mA, 20 mA, 200 mA, 2 A                                                                                                                                                        |                     |
| Resolution                       | 0.1 μA                                                                                                                                                                                  |                     |
| Accuracy                         | 200 μA to 20 mA                                                                                                                                                                         | ±(0.5 % rdg+2 dgts) |
|                                  | 200 mA to 2 A                                                                                                                                                                           | ±(1.0 % rdg+2 dgts) |



## HD110C Technical Specifications (continued)

## Data Sheet

| Function                           | Range                                                                                                                                                                         | Accuracy                                                                                                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DC Current (cont.)</b>          |                                                                                                                                                                               |                                                                                                                                                                              |
| Voltage Burden                     | 250 mV max. (1 mV/1 $\mu$ A on 200 $\mu$ A Range)<br>(100 mV/1 mA on 2 mA Range)<br>(10 mV/1 mA on 20 mA Range)<br>(1.5 mV/1 mA on 200 mA Range)<br>(500 mV/1 A on 2 A Range) |                                                                                                                                                                              |
| OL Protection                      | A Input (F 2 A/1500 V, size 8 x 65 mm IR fast blow ceramic) (FP 700)                                                                                                          |                                                                                                                                                                              |
| <b>AC Current (45 Hz to 1 kHz)</b> |                                                                                                                                                                               |                                                                                                                                                                              |
| Ranges                             | 200 $\mu$ A, 2 mA, 20 mA, 200 mA, 2 A                                                                                                                                         |                                                                                                                                                                              |
| Resolution                         | 0.1 $\mu$ A                                                                                                                                                                   |                                                                                                                                                                              |
| Accuracy                           | 200 $\mu$ A to 20 mA<br>200 mA to 2 A                                                                                                                                         | $\pm(0.8 \% \text{ rdg}+4 \text{ dgts})$<br>$\pm(1.2 \% \text{ rdg}+4 \text{ dgts})$                                                                                         |
| Voltage Burden                     | 250 mV max. (1 V on 2 A range)                                                                                                                                                |                                                                                                                                                                              |
| OL Protection                      | same as DC Current                                                                                                                                                            |                                                                                                                                                                              |
| <b>Resistance</b>                  |                                                                                                                                                                               |                                                                                                                                                                              |
| Ranges                             | 200 $\Omega$ , 2 k $\Omega$ , 20 k $\Omega$ , 200 k $\Omega$ , 2 M $\Omega$ , 20 M $\Omega$                                                                                   |                                                                                                                                                                              |
| Resolution                         | 0.1 $\Omega$                                                                                                                                                                  |                                                                                                                                                                              |
| Accuracy                           | 200 $\Omega$<br>2 k $\Omega$ to 200 k $\Omega$<br>2 M $\Omega$<br>20 M $\Omega$                                                                                               | $\pm(0.5 \% \text{ rdg}+4 \text{ dgts})$<br>$\pm(0.3 \% \text{ rdg}+2 \text{ dgts})$<br>$\pm(1.0 \% \text{ rdg}+4 \text{ dgts})$<br>$\pm(2.0 \% \text{ rdg}+4 \text{ dgts})$ |
| OL Protection                      | 1500 V dc/1000 V ac rms                                                                                                                                                       |                                                                                                                                                                              |
| Open Circuit Voltage               | 200 $\Omega$ range<br>all other ranges                                                                                                                                        | 3.0 V dc typical<br>0.3 V dc typical.                                                                                                                                        |
| <b>Diode/Continuity Test</b>       |                                                                                                                                                                               |                                                                                                                                                                              |
| Test Current                       | 1m A dc typical                                                                                                                                                               |                                                                                                                                                                              |
| Test/Open Circuit Voltage          | 3.0 V dc Typical                                                                                                                                                              |                                                                                                                                                                              |
| Diode Accuracy                     | $\pm(1.5 \% \text{ rdg}+2 \text{ dgts})$                                                                                                                                      |                                                                                                                                                                              |
| Continuity Audible Threshold       | <50 $\Omega \pm 25 \Omega$                                                                                                                                                    |                                                                                                                                                                              |
| Response Time                      | <100 msec                                                                                                                                                                     |                                                                                                                                                                              |
| OL Protection                      | 1500 V dc/1000 V ac rms                                                                                                                                                       |                                                                                                                                                                              |



### Included Accessories

Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (in instrument), hex wrench in holster, Magne-Grip flex strap and User Manual

### Optional Accessories

- |           |                                                                     |
|-----------|---------------------------------------------------------------------|
| TL1500    | Cat IV 1000 V Test Leads with Alligator Clips                       |
| CT235A    | 1000 A ac/dc Clamp                                                  |
| CT237A    | 200 A ac/dc Current Clamp                                           |
| CT238A    | 20 A ac/dc Current Clamp                                            |
| VC221B    | Padded Vinyl Case. Fits meter & holster.                            |
| DC205C    | Deluxe Hard-Shell Carry Case                                        |
| DC207C    | Large Deluxe Hard-Shell Carry Case with extra space for accessories |
| HV231-10A | High Voltage Probe                                                  |
| FP700     | Replacement Fuse, 2 A/1500 V, pack of two                           |

### Amprobe® Test Tools

website: [www.Amprobe.com](http://www.Amprobe.com)  
email: [info@amprobe.com](mailto:info@amprobe.com)  
6920 Seaway Blvd.  
Everett, WA 98203  
tel: 877-AMPROBE

### Amprobe® Test Tools Europe

P.O. Box 1186  
5602 BD Eindhoven  
The Netherlands



**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331