

## Class CC/CD and Midget Fuse Blocks

### 600 Volt



Space saving 600 volt, 30 amp molded case fuse blocks with side barriers for isolation. Class CC blocks and Midget blocks are identical except Class CC blocks incorporate a rejection feature to assure proper fusing.

### Safety

- Rejection feature — Class CC fuse blocks have a rejection feature which prevents the insertion of fuses with lower interrupting rating or voltage ratings. Class CC fuses are rated 600 volts and have an

interrupting rating of 200,000 amperes. Midget fuse voltage ratings vary and their interrupting rating may be as low as 10,000 amperes.

*Note that Class CC fuses may be used in Midget fuse blocks, but Midget fuses cannot be used in Class CC blocks.*

### Long life

- High-strength materials — Class CC and Midget fuse blocks are molded of high-strength, high-temperature material to minimize block breakage during handling and installation, as well as damage caused by overheating.
- Reduced resistance, less heat — High conductivity, one-piece copper alloy fuse clips have lower resistance than traditional two-piece brass or phosphor bronze fuse clips, which minimizes heat rise and watts loss within the fuse block.

### Reduced inventory

- Gangable — Interlocking fuse blocks allow ganging to produce a fuse block with any number of poles.
- Flexible terminal arrangements — 30A Class CC and Midget fuse blocks are available with type C box lug, type SQ screw, or type PQ pressure plate terminals. Type SQ terminals have binding-head screws, while type PQ terminals have captive pressure plates. Both terminal types can accommodate side or top mounted quick-connect terminals. This flexibility allows the accommodation of most needs and reduces part inventory requirements.
- 60A CD fuse blocks are available with type C box lug terminals.
- DIN rail mountable — FBDIN1 adapters permit snap-mounting Littelfuse Class CC and Midget 30 amp fuse blocks directly to standard or low profile 35mm symmetrical “hat” and 32mm asymmetrical DIN rails. Patented DIN rail adapters snap securely to Littelfuse fuse blocks and to DIN rails without tools. They can be readily removed from rails by lifting the disconnect tab.
- L60060C 60A fuse blocks have patented integral DIN rail adapters which allow direct mounting to 35mm “hat” type DIN rails.

### Specifications

|                                          |                                             |                                 |  |
|------------------------------------------|---------------------------------------------|---------------------------------|--|
| <b>Voltage Rating:</b>                   | 600 Volts AC/600 Volts DC                   |                                 |  |
| <b>Ampere ratings:</b>                   | L60030C:                                    | 30 amps                         |  |
|                                          | L60030M:                                    | 30 amps                         |  |
|                                          | L60060C:                                    | 60 amps                         |  |
| <b>Dielectric strength:</b>              | 1200 volts minimum                          |                                 |  |
| <b>Clip/terminals:</b>                   | Tin-plated copper alloy                     |                                 |  |
| <b>Box lug:</b>                          | Copper                                      |                                 |  |
| <b>Screw and captive pressure plate:</b> | Zinc-plated steel                           |                                 |  |
| <b>Base:</b>                             | Thermoplastic. UL 94V0 flammability rating. |                                 |  |
| <b>Approvals:</b>                        | Class CC:                                   | UL Listed (File No. E14721)     |  |
|                                          | Midget:                                     | UL Recognized (File No. E14721) |  |
|                                          | Class CC/Midget:                            | CSA Certified (File No. LR7316) |  |

### Recommended Fuses

#### Class CC Blocks:

CCMR | KLDR | KLKR

#### Midget Blocks:

BLF | BLS | FLM | FLU | KLKD | LA60Q-2  
BLN | FLA | FLQ | KLK | KLO

#### Class CD Blocks:

CCMR

*Note: L60030M can be used up to 40A.*

## Class CC/CD and Midget Fuse Blocks

### 600 Volt

#### Class CC 30A Fuse Blocks

| Amp Rating | No. of Poles | Catalog Number | Connector Type (Add Suffix Shown) | Maximum Wire Size |
|------------|--------------|----------------|-----------------------------------|-------------------|
| 30         | 1            | L60030C-1C     | Box Lug                           | #6 CU             |
|            | 2            | L60030C-2C     |                                   |                   |
|            | 3            | L60030C-3C     |                                   |                   |
| 30         | 1            | L60030C-1PQ    | Pressure Plate/<br>Q. C. Terminal | #10 CU            |
|            | 2            | L60030C-2PQ    |                                   |                   |
|            | 3            | L60030C-3PQ    |                                   |                   |
| 30         | 1            | L60030C-1SQ    | Screw/ Q. C. Terminal             | #10 CU            |
|            | 2            | L60030C-2SQ    |                                   |                   |
|            | 3            | L60030C-3SQ    |                                   |                   |

Note: Quick Connect Terminals are rated at 20 amperes.


#### Class CD 60A Fuse Blocks

| Amp Rating | No. of Poles | Catalog Number | Connector Type (Add Suffix Shown) | Maximum Wire Size |
|------------|--------------|----------------|-----------------------------------|-------------------|
| 60         | 1            | L60060C-1C     | Box Lug                           | #6 CU             |
|            | 2            | L60060C-2C     |                                   |                   |
|            | 3            | L60060C-3C     |                                   |                   |
| 60         | Adder Block  | L60060C-AC     | Box Lug                           | #6 CU             |

#### Midget Fuse Blocks

| Amp Rating | No. of Poles | Catalog Number | Connector Type (Add Suffix Shown) | Maximum Wire Size |
|------------|--------------|----------------|-----------------------------------|-------------------|
| 30         | 1            | L60030M-1C     | Box Lug                           | #6 CU             |
|            | 2            | L60030M-2C     |                                   |                   |
|            | 3            | L60030M-3C     |                                   |                   |
| 30         | 1            | L60030M-1PQ    | Pressure Plate/<br>Q. C. Terminal | #10 CU            |
|            | 2            | L60030M-2PQ    |                                   |                   |
|            | 3            | L60030M-3PQ    |                                   |                   |
| 30         | 1            | L60030M-1SQ    | Screw/ Q. C. Terminal             | #10 CU            |
|            | 2            | L60030M-2SQ    |                                   |                   |
|            | 3            | L60030M-3SQ    |                                   |                   |

Note: Quick Connect Terminals are rated at 20 amperes.





**Стандарт  
Электрон  
Связь**

Мы молодая и активно развивающаяся компания в области поставок электронных компонентов. Мы поставляем электронные компоненты отечественного и импортного производства напрямую от производителей и с крупнейших складов мира.

Благодаря сотрудничеству с мировыми поставщиками мы осуществляем комплексные и плановые поставки широчайшего спектра электронных компонентов.

Собственная эффективная логистика и склад в обеспечивает надежную поставку продукции в точно указанные сроки по всей России.

Мы осуществляем техническую поддержку нашим клиентам и предпродажную проверку качества продукции. На все поставляемые продукты мы предоставляем гарантию .

Осуществляем поставки продукции под контролем ВП МО РФ на предприятия военно-промышленного комплекса России , а также работаем в рамках 275 ФЗ с открытием отдельных счетов в уполномоченном банке. Система менеджмента качества компании соответствует требованиям ГОСТ ISO 9001.

Минимальные сроки поставки, гибкие цены, неограниченный ассортимент и индивидуальный подход к клиентам являются основой для выстраивания долгосрочного и эффективного сотрудничества с предприятиями радиоэлектронной промышленности, предприятиями ВПК и научно-исследовательскими институтами России.

С нами вы становитесь еще успешнее!

**Наши контакты:**

**Телефон:** +7 812 627 14 35

**Электронная почта:** [sales@st-electron.ru](mailto:sales@st-electron.ru)

**Адрес:** 198099, Санкт-Петербург,  
Промышленная ул, дом № 19, литера Н,  
помещение 100-Н Офис 331